


OCCUPATIONAL SAFETY AND HEALTH GUIDELINE FOR 2-ACETYLAMINOFLUORENE POTENTIAL HUMAN CARCINOGEN

INTRODUCTION

This guideline summarizes pertinent information about 2-acetylaminofluorene for workers, employers, and occupational safety and health professionals who may need such information to conduct effective occupational safety and health programs. Recommendations may be superseded by new developments in these fields; therefore, readers are advised to regard these recommendations as general guidelines.

SUBSTANCE IDENTIFICATION

- **Formula:** C₁₅H₁₃NO
- **Structure:** 
- **Synonyms:** 2-AAF; 2-acetamidofluorene; 2-acetylaminofluorene; N-acetyl-2-aminofluorene; 2-(acetylamino)fluorene; N-FAA; 2-FAA
- **Identifiers:** CAS 53-96-3; RTECS AB9450000; DOT not assigned
- **Appearance:** Tan, crystalline solid

CHEMICAL AND PHYSICAL PROPERTIES

- **Physical data**
 1. Molecular weight: 223.29
 2. Melting point: 194°C (381.2°F)
 3. Insoluble in water
- **Flammability**

Extinguishant: Dry chemical, carbon dioxide
- **Warning properties**

Evaluation of warning properties for respirator selection: Warning properties are not considered in recommending respirators for use with carcinogens.

EXPOSURE LIMITS

The Occupational Safety and Health Administration (OSHA) does not have a specific permissible exposure limit (PEL) for 2-acetylaminofluorene; however, the OSHA standard requires implementation of stringent controls wherever 2-acetylaminofluorene or solid or liquid mixtures containing at least 0.1% by weight or volume of 2-acetylaminofluorene are manufactured, processed, repackaged, released, handled, or stored (see "General Control Procedures"). Details of this standard can be found in the Code of Federal Regulations, 29 CFR 1910.1014, 2-Acetylaminofluorene. The National Institute for Occupational Safety and Health (NIOSH) concurs with the OSHA standard. The American Conference of Governmental Industrial Hygienists (ACGIH) does not have an assigned threshold limit value (TLV®) for 2-acetylaminofluorene.

HEALTH HAZARD INFORMATION

- **Routes of exposure**

2-Acetylaminofluorene may cause adverse health effects following exposure via inhalation, ingestion, or dermal or eye contact.
- **Summary of toxicology**
 1. *Effects on animals:* Subchronic or chronic oral administration of 2-acetylaminofluorene in dogs, rats, or hamsters produced cancers of the bladder or liver. In rats, cancers of the kidneys, pancreas, pelvis, salivary glands, eyes, ear ducts, and auditory and sebaceous glands were also found. In all animals that developed cancer from exposure to 2-acetylaminofluorene, the potent carcinogenic metabolite N-hydroxy-2-acetylaminofluorene was produced. Single oral doses of 2-acetylaminofluorene to pregnant rats on days 8-12 of gestation induced fetal malformations (hydrocephaly).
 2. *Effects on humans:* Five cancer patients treated with single oral doses of 2-acetylaminofluorene produced the N-hydroxy-2-acetylaminofluorene metabolite, indicating that 2-acetylaminofluorene may be metabolized in humans as it was in animals that developed cancer from exposure to 2-acetylaminofluorene.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES
Public Health Service Centers for Disease Control
National Institute for Occupational Safety and Health
Division of Standards Development and Technology Transfer

RECOMMENDED MEDICAL PRACTICES

• Medical surveillance program

Workers with potential exposures to chemical hazards should be monitored in a systematic program of medical surveillance intended to prevent or control occupational injury and disease. The program should include education of employers and workers about work-related hazards, placement of workers in jobs that do not jeopardize their safety and health, earliest possible detection of adverse health effects, and referral of workers for diagnostic confirmation and treatment. The occurrence of disease (a "sentinel health event," SHE) or other work-related adverse health effects should prompt immediate evaluation of primary preventive measures (e.g., industrial hygiene monitoring, engineering controls, and personal protective equipment). A medical surveillance program is intended to supplement, not replace, such measures.

A medical surveillance program should include systematic collection and epidemiologic analysis of relevant environmental and biologic monitoring, medical screening, morbidity, and mortality data. This analysis may provide information about the relatedness of adverse health effects and occupational exposure that cannot be discerned from results in individual workers. Sensitivity, specificity, and predictive values of biologic monitoring and medical screening tests should be evaluated on an industry-wide basis prior to application in any given worker group. Intrinsic to a surveillance program is the dissemination of summary data to those who need to know, including employers, occupational health professionals, potentially exposed workers, and regulatory and public health agencies.

• Preplacement medical evaluation

Prior to placing a worker in a job with a potential for exposure to 2-acetylaminofluorene, the physician should evaluate and document the worker's baseline health status with thorough medical, environmental, and occupational histories, a physical examination, and physiologic and laboratory tests appropriate for the anticipated occupational risks. These should concentrate on the function and integrity of the skin, liver, urinary tract, and reproductive system.

A preplacement medical evaluation is recommended in order to detect and assess preexisting or concurrent conditions which may be aggravated or result in increased risk when a worker is exposed to 2-acetylaminofluorene. The examining physician should consider the probable frequency, intensity, and duration of exposure, as well as the nature and degree of the condition, in placing such a worker. Such conditions, which should not be regarded as absolute contraindications to job placement, include a history of chronic skin disease or concurrent dermatitis and a history of reproductive dysfunction. In addition to the medical interview and physical examination, the means to identify these conditions may include an evaluation of fertility.

• Periodic medical screening and/or biologic monitoring

Occupational health interviews and physical examinations should be performed at regular intervals. Additional exami-

nations may be necessary should a worker develop symptoms that may be attributed to exposure to 2-acetylaminofluorene. Because the metabolite N-hydroxy-2-acetylaminofluorene has been identified in both animals and humans administered 2-acetylaminofluorene, consideration should be given to monitoring for this metabolite in workers who may be exposed to 2-acetylaminofluorene.

• Medical practices recommended at the time of job transfer or termination

The medical, environmental, and occupational history interviews, the physical examination, and selected physiologic and laboratory tests which were conducted at the time of placement should be repeated at the time of job transfer or termination. Any changes in the worker's health status should be compared to those expected for a suitable reference population. Because occupational exposure to 2-acetylaminofluorene may cause adverse reproductive effects and diseases of prolonged induction-latency, the need for medical surveillance may extend well beyond termination of employment.

• Sentinel health events

Acute SHE's include: Contact and/or allergic dermatitis.

MONITORING AND MEASUREMENT PROCEDURES

• Method

There is no NIOSH-validated sampling or analytical method for 2-acetylaminofluorene.

PERSONAL PROTECTIVE EQUIPMENT

Chemical protective clothing (CPC) should be selected after utilizing available performance data, consulting with the manufacturer, and then evaluating the clothing under actual use conditions.

In operations involving "laboratory type hoods" or in locations where 2-acetylaminofluorene is contained in an otherwise "closed system" but is transferred, charged, or discharged into other normally closed containers, OSHA requires that workers: (1) be provided with and required to use clean, full-body CPC (smocks, coveralls, or long-sleeved shirts and long pants), shoe covers, and gloves prior to entering a regulated area; (2) be provided with and required to use approved respirators (a respirator affording higher levels of protection may be substituted); and (3) remove the protective clothing and equipment prior to exiting a regulated area, and at the last exit of the day, place used clothing and equipment in impervious containers for decontamination or disposal.

SANITATION

For closed system operations or in locations where 2-acetylaminofluorene is contained in an otherwise "closed system" but is transferred, charged, or discharged into other normally closed containers, OSHA requires that workers: (1) wash their hands, forearms, faces, and necks prior to exiting

the regulated area and before engaging in other activities, and (2) shower after the last exit of the day in designated facilities.

In isolated systems, such as a "glove box," OSHA requires that workers wash their hands and arms with soap and water upon completion of the assigned task and before engaging in other activities not associated with the isolated system. If it is necessary for workers to wear protective clothing, OSHA requires that a clean change room be provided and equipped with showers and washing facilities. NIOSH recommends that lockers that permit separation of street and work clothes be provided for the worker.

Clothing which is contaminated with 2-acetylaminofluorene should be removed immediately and placed in sealed containers for storage until it can be discarded or until provision is made for the removal of 2-acetylaminofluorene from the clothing. If the clothing is to be laundered or cleaned, the person performing the operation should be informed of 2-acetylaminofluorene's hazardous properties. Reusable clothing and equipment should be checked for residual contamination before reuse or storage.

Decontamination and disposal procedures should be established and implemented to remove 2-acetylaminofluorene from materials and equipment. Contaminated materials should be removed from regulated areas without further contamination of the facility.

OSHA requires that workers wash their faces, necks, hands, and forearms thoroughly with soap and water before eating, smoking, or using toilet facilities.

In regulated areas, OSHA prohibits the storage or consumption of food or beverages, the storage or application of cosmetics, the storage or smoking of tobacco or other smoking materials, and the storage or use of products for chewing.

OSHA prohibits the location of drinking fountains in regulated areas.

GENERAL CONTROL PROCEDURES

The following control procedures are derived from OSHA requirements as stated in 29 CFR 1910.1014:

Areas where 2-acetylaminofluorene is manufactured, processed, used, repackaged, released, handled, or stored shall be designated as regulated areas, and entry into and exit from these areas shall be restricted and controlled. Only authorized workers shall be permitted access to regulated areas.

Workers authorized to enter regulated areas shall receive a training and indoctrination program including but not limited to the nature of the carcinogenic hazards of 2-acetylaminofluorene, including local and systemic toxicity, the specific nature of the operation which could result in exposure, and the purpose for the significance of decontamination and emergency practices and procedures.

Entrances to regulated areas shall be posted with signs indicating that a cancer-suspect agent is present and that only

authorized workers wearing appropriate protective clothing and equipment shall be admitted.

Appropriate signs and instructions shall be posted at the entrance to and exit from regulated areas to inform workers of the procedures that must be followed when entering or leaving a regulated area.

Open vessel system operations involving 2-acetylaminofluorene which are not in an isolated system, laboratory type hood, or other system affording equivalent protection against the entry of 2-acetylaminofluorene into regulated areas, non-regulated areas, or the external environment are prohibited.

In operations involving "laboratory type hoods" or in locations where 2-acetylaminofluorene is contained in an otherwise "closed system" but is transferred, charged, or discharged into other normally closed containers, each operation shall be provided with continuous local exhaust ventilation so that air movement is always from ordinary work areas to the operation. Exhaust air shall not be discharged to regulated areas, nonregulated areas, or the external environment unless decontaminated. Clean makeup air shall be introduced in sufficient volume to maintain the correct operation of the local exhaust system.

Containers of 2-acetylaminofluorene shall be identified as to contents and shall contain a hazard warning.

Regulated areas (with the exception of outdoor operations) shall be operated under negative pressure with respect to non-regulated areas. Local exhaust ventilation may be used to satisfy this requirement. Clean makeup air in equal volume shall replace air that is removed.

The introduction or removal of any equipment, materials, or other items to or from a regulated area shall be done in a manner that does not cause contamination of nonregulated areas or the external environment.

Decontamination procedures shall be established and implemented to remove 2-acetylaminofluorene from materials, equipment, and decontamination facility.

COMMON OPERATIONS AND CONTROLS

Common operations in which exposure to 2-acetylaminofluorene may occur and control methods which may be effective in each case are listed in Table 1.

Table 1.—Operations and methods of control for 2-acetylaminofluorene

Operation	Controls
During use in research and laboratory facilities	Process enclosure, restricted access, local exhaust ventilation, personal protective equipment, good housekeeping and personal hygiene practices, substitution with less toxic substances

EMERGENCY FIRST AID PROCEDURES

In the event of an emergency, remove the victim from further exposure, send for medical assistance, and initiate emergency procedures. If a worker has contact with 2-acetylaminofluorene, OSHA requires that the worker shower as soon as possible, unless contraindicated by physical injuries.

• Eye exposure

Where there is any possibility of a worker's eyes being exposed to 2-acetylaminofluorene, an eye-wash fountain should be provided within the immediate work area for emergency use.

If 2-acetylaminofluorene gets into the eyes, flush them immediately with large amounts of water for 15 minutes, lifting the lower and upper lids occasionally. Get medical attention as soon as possible. Contact lenses should not be worn when working with this chemical.

• Skin exposure

Where there is any possibility of a worker's body being exposed to 2-acetylaminofluorene, facilities for quick drenching of the body should be provided within the immediate work area for emergency use. If 2-acetylaminofluorene gets on the skin, wash it immediately with soap and water. If 2-acetylaminofluorene penetrates the clothing, remove the clothing immediately and wash the skin with soap and water. Get medical attention promptly.

• Rescue

If a worker has been incapacitated, move the affected worker from the hazardous exposure. Put into effect the established emergency rescue procedures. Do not become a casualty. Understand the facility's emergency rescue procedures and know the locations of rescue equipment before the need arises.

SPILLS AND LEAKS

OSHA requires that hazardous conditions created by spills or leaks be eliminated and that potentially affected areas be decontaminated prior to the resumption of normal operations.

OSHA requires that affected areas of spills or leaks be evacuated as soon as an emergency has been determined.

OSHA requires that only authorized workers provided with and wearing clean, impervious garments (including gloves, boots, and continuous air-supplied hoods) enter areas of spills or leaks.

OSHA requires that workers authorized to enter areas of spills or leaks be decontaminated before removing the protective garments and hoods and showering.

If 2-acetylaminofluorene is spilled or leaked, the following steps should be taken:

1. Ventilate area of spill or leak.
2. If in solid form, 2-acetylaminofluorene may be collected and placed in an appropriate container.
3. For small quantities of liquids containing 2-acetylaminofluorene, absorb on paper towels and place in an appropriate container.
4. Large quantities of liquids containing 2-acetylaminofluorene may be absorbed in vermiculite, dry sand, earth, or a similar material and placed in an appropriate container.
5. 2-acetylaminofluorene dust may be collected by vacuuming with an appropriate high-efficiency filtration system or by using wet methods and placed in an appropriate container. Dry sweeping and dry mopping of 2-acetylaminofluorene are prohibited by OSHA.

WASTE REMOVAL AND DISPOSAL

U.S. Environmental Protection Agency, Department of Transportation, and/or state and local regulations shall be followed to assure that removal, transport, and disposal are in accordance with existing regulations.

RESPIRATORY PROTECTION

It must be stressed that the use of respirators is the least preferred method of controlling worker exposure and should not normally be used as the only means of preventing or minimizing exposure during routine operations. However, there are some exceptions for which respirators may be used to control exposure: when engineering and work practice controls are not technically feasible, when engineering controls are in the process of being installed, or during emergencies and certain maintenance operations including those requiring confined-space entry (Table 2).

In addition to respirator selection, a complete respiratory protection program should be instituted which as a minimum complies with the requirements found in the OSHA Safety and Health Standards 29 CFR 1910.134. A respiratory protection program should include as a minimum an evaluation of the worker's ability to perform the work while wearing a respirator, the regular training of personnel, fit testing, periodic environmental monitoring, maintenance, inspection, and cleaning. The implementation of an adequate respiratory protection program, including selection of the correct respirators, requires that a knowledgeable person be in charge of the program and that the program be evaluated regularly.

Only respirators that have been approved by the Mine Safety and Health Administration (MSHA, formerly Mining Enforcement and Safety Administration) and by NIOSH should be used. **Remember! Air-purifying respirators will not protect from oxygen-deficient atmospheres.**

BIBLIOGRAPHY

- Alexandrov, V.A.: "Embryotoxic and Teratogenic Effects of Chemical Carcinogens," *Transplacental Carcinogens*, IARC Scientific Publication, No. 4, Lyon, France, 1973.
- American Conference of Governmental Industrial Hygienists: *TLVs® Threshold Limit Values and Biological Exposure Indices for 1987-88*, Cincinnati, 1987.
- American Lung Association of San Diego and Imperial Counties: "Taking the Occupational History," *Annals of Internal Medicine*, 99:641-651, November 1983.
- *Code of Federal Regulations*, U.S. Department of Labor, Occupational Safety and Health Administration, 29 CFR 1910.134, 1910.1014, OSHA 2206, revised July 1, 1986.
- Goldman, R.H., and Peters, J.M.: "The Occupational and Environmental Health History," *Journal of the American Medical Association*, 246:2831-2836, 1981.
- Halperin, W.E., Ratcliffe, J., Frazier, T.M., Wilson, L., Becker, S.P., and Shulte, P.A.: "Medical Screening in the Workplace: Proposed Principles," *Journal of Occupational Medicine*, 28(8):547-552, 1986.
- Hankinson, J.L.: "Pulmonary Function Testing in the Screening of Workers: Guidelines for Instrumentation, Performance, and Interpretation," *Journal of Occupational Medicine*, 28(10):1081-1092, 1986.
- Leidel, N.A., Busch, K.A., and Lynch, J.R.: *Occupational Exposure Sampling Strategy Manual*, U.S. Department of Health, Education, and Welfare, Public Health Service, Center for Disease Control, National Institute for Occupational Safety and Health, DHEW (NIOSH) Publication No. 77-173, Cincinnati, 1977.
- Levy, B.S., and Wegman, D.H. (eds.): *Occupational Health: Recognizing and Preventing Work-Related Disease*, Little, Brown and Company, Boston, 1983.
- Mark, H.F., Othmer, D.F., Overberger, C.G., Seaborg, G.T., Grayson, M., and Eckroth, D. (eds.): *Kirk-Othmer Encyclopedia of Chemical Technology* (3rd ed.), John Wiley & Sons, Inc., New York, 1981.
- National Institute for Occupational Safety and Health, U.S. Department of Health and Human Services, Public Health Service, Centers for Disease Control, *Registry of Toxic Effects of Chemical Substances* (Microfiche Edition), Sweet, D.V., and Lewis, R.J., (eds.), Cincinnati, April 1985.
- National Institute for Occupational Safety and Health, U.S. Department of Health, Education, and Welfare, Public Health Service, Centers for Disease Control: *Occupational Diseases—A Guide to Their Recognition* (rev. ed., 2nd printing), DHEW (NIOSH) Publication No. 77-181, 1978.
- Parmeggiani, L. (ed.): *Encyclopedia of Occupational Health and Safety* (3rd ed.), International Labour Office, Geneva, Switzerland, 1983.
- Proctor, N.H., and Hughes, J.P.: *Chemical Hazards of the Workplace*, J.B. Lippincott Company, Philadelphia, 1978.
- Rom, W.N. (ed.): *Environmental and Occupational Medicine*, Little, Brown and Company, Boston, 1983.
- Rothstein, M.A.: *Medical Screening of Workers*, Bureau of National Affairs, Washington, DC, 1984.
- Rutstein, D.D., Mullan, R.J., Frazier, T., Halperin, W., Melius, J.M., and Sestito, J.P.: "Sentinel Health Events (Occupational): A Basis for Physician Recognition and Public Health Surveillance," *American Journal of Public Health*, 73:1054-1062, 1983.
- Scientific Assembly on Environmental and Occupational Health: "Evaluation of Impairment/Disability Secondary to Respiratory Disease," *American Review of Respiratory Diseases*, 126:945-951, 1982.
- Scientific Assembly on Environmental and Occupational Health: "Surveillance for Respiratory Hazards in the Occupational Setting," *American Review of Respiratory Diseases*, 126:952-956, 1982.
- Weast, R.C. (ed.): *CRC Handbook of Chemistry and Physics* (64th ed.), CRC Press, Inc., Boca Raton, Florida, 1983.
- Windholz, M. (ed.): *The Merck Index* (10th ed.), Merck & Co., Inc., Rahway, New Jersey, 1983.

Table 2.—Respiratory protection for 2-acetylaminofluorene

Condition	Minimum respiratory protection*
Any detectable concentration	Any self-contained breathing apparatus with a full facepiece and operated in a pressure-demand or other positive pressure mode Any supplied-air respirator with a full facepiece and operated in a pressure-demand or other positive pressure mode in combination with an auxiliary self-contained breathing apparatus operated in a pressure-demand or other positive pressure mode
Planned or emergency entry into environments containing unknown or any detectable concentration	Any self-contained breathing apparatus with a full facepiece and operated in a pressure-demand or other positive pressure mode Any supplied-air respirator with a full facepiece and operated in a pressure-demand or other positive pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode
Firefighting	Any self-contained breathing apparatus with a full facepiece and operated in a pressure-demand or other positive pressure mode
Escape only	Any air-purifying full facepiece respirator with a high-efficiency particulate filter Any appropriate escape-type self-contained breathing apparatus

* Only NIOSH/MSHA-approved equipment should be used.