

DATA FIELD	COLUMNS	CONTENTS OF DATA FIELDS
0	1-2	AS
1	3-8	Stationing at end point in feet of area above 1-percent-annual-chance SWEL
2	9-16	Ground elevation in feet at end point
3	17-24	A blank or zero indicates no change to the 10-percent-annual-chance SWEL; otherwise new 10-percent-annual-chance SWEL
4	25-32	A blank or zero indicates no change to the 1-percent-annual-chance SWEL; otherwise new 1-percent-annual-chance SWEL
5-10	33-80	Not used

BU Line (Buildings)

This line enters information needed to compute wave dissipation at each group of buildings.

DATA FIELD	COLUMNS	CONTENTS OF DATA FIELDS
0	1-2	BU
1	3-8	Stationing of end point in feet of group of buildings
2	9-16	Ground elevation at end point in feet
3	17-24	Ratio of open space between buildings to total transverse width of developed area
4	25-32	Number of rows of buildings
5	33-40	A blank or zero indicates no change to 10-percent-annual-chance SWEL; otherwise new 10-percent-annual-chance SWEL
6	41-48	A blank or zero indicates no change to 1-percent-annual-chance SWEL; otherwise new 1-percent-annual-chance SWEL
7-10	49-80	Not used

DU Line (Dune)

This line enters information necessary to compute wave dissipation at substantial sand dunes and other natural or manmade elongated barriers (e.g., levees, seawalls).

DATA FIELD	COLUMNS	CONTENTS OF DATA FIELDS
0	1-2	DU
1	3-8	Stationing at top of dune or barrier in feet
2	9-16	Elevation at top of dune or barrier in feet
3	17-24	A blank or zero indicates a dune or other natural barrier; any other number indicates a seawall or other manmade barrier
4	25-32	A blank or zero indicates no change to 10-percent-annual-chance SWEL; otherwise new 10-percent-annual-chance SWEL
5	33-40	A blank or zero indicates no change to 1-percent-annual-chance SWEL;

Guidelines and Specifications for Flood Hazard Mapping Partners

DATA FIELD	COLUMNS	CONTENTS OF DATA FIELDS
		otherwise new 1-percent-annual-chance SWEL
6-10	41-80	Not used

IF Line (Inland Fetch)

This line enters the parameters necessary to compute wave regeneration through inland fetches and over shallow inland waterbodies. The IF regeneration is computed using overland wind speed of 30 mph for Great Lakes floods.

DATA FIELD	COLUMNS	CONTENTS OF DATA FIELDS
0	1-2	IF
1	3-8	Stationing at end point of fetch in feet
2	9-16	Ground elevation at end point in feet
3	17-24	A blank or zero indicates no change to 10-percent-annual-chance SWEL; otherwise new 10-percent-annual-chance SWEL
4	25-32	A blank or zero indicates no change to 1-percent-annual-chance SWEL; otherwise new 1-percent-annual-chance SWEL
5-10	33-80	Not used

OF Line (Overwater Fetch)

This line enters the parameters necessary to compute wave regeneration over large bodies of water (i.e., large lakes, bays) using overwater wind speed of 40 mph for Great Lakes floods. If an inland waterbody is sheltered and has a depth of ten feet or less, the IF line calling for overland wind speeds should be used.

DATA FIELD	COLUMNS	CONTENTS OF DATA FIELDS
0	1-2	OF
1	3-8	Stationing at end point of fetch in feet
2	9-16	Ground elevation at end point in feet
3	17-24	A blank or zero indicates no change to the 10-percent-annual-chance SWEL; otherwise new 10-percent-annual-chance SWEL
4	25-32	A blank or zero indicates no change to 1-percent-annual-chance SWEL; otherwise new 1-percent-annual-chance SWEL
5-10	33-80	Not used

VE Line (Vegetation)

This line enters parameters necessary to compute wave dissipation due to rigid vegetation stands.

Guidelines and Specifications for Flood Hazard Mapping Partners

DATA FIELD	COLUMNS	CONTENTS OF DATA FIELDS
0	1-2	VE
1	3-8	Stationing at end point of vegetation in feet
2	9-16	Ground elevation at end point in feet
3	17-24	Mean effective diameter of equivalent circular cylinder in feet
4	25-32	Average actual height of vegetation in feet
5	33-40	Average horizontal spacing between plants in feet
6	41-48	Drag coefficient; a blank or zero causes a default to 1.0
7	49-56	A blank or zero indicates no change to 10-percent-annual-chance SWEL; otherwise new 10-percent-annual-chance SWEL
8	57-64	A blank or zero indicates no change to 1-percent-annual-chance SWEL; otherwise new 1-percent-annual-chance SWEL
9-10	65-80	Not used

VH Line (Vegetation Header for Marsh Grass)

Marsh grass is often part of a plant community that may consist of several plant types. The VH line is used to enter data that apply to all plant types modeled in the transect segment. To enter data for each plant type, MG lines for each plant type must follow the VH line.

DATA FIELD	COLUMNS	CONTENTS OF DATA FIELDS
0	1-2	VH
1	3-8	Stationing at end point of marsh vegetation segment in feet
2	9-16	Ground elevation at end point in feet
3	17-24	Reg _p , number of the primary seacoast region for default plant parameters. Leave blank for Great Lakes computations.
4	25-32	Wt _p , weighting factor for the primary seacoast region. Not applicable for Great Lakes analyses.
5	33-40	Reg _s , number of secondary seacoast region. Not applicable for Great Lakes analyses.
6	41-48	N _{p1} , number of plant types; range is 1 to 10, inclusive. One MG line is required for each plant type.
7	49-56	A blank or zero indicates no change to the 10-percent-annual-chance SWEL; otherwise new 10-percent-annual-chance SWEL
8	57-64	A blank or zero indicates no change to the 1-percent-annual-chance SWEL; otherwise new 1-percent-annual-chance SWEL
9	65-72	Not used
10	73-80	This field is for overriding the default method of averaging flood hazard factors in A Zones; if 1 in column 80, averaging process begins or ends at end of vegetation segment; otherwise, default averaging method is used

MG Line (Marsh Grass)

This line is used to enter data for a particular plant type. The first MG line must be preceded by a VH line. For the common seacoast marsh grasses listed in Table D-21, potentially useful default values are supplied in Table D-22. If a plant type not listed in the table is used, then appropriate data must be developed for Fields 2-9.

DATA FIELD	COLUMNS	CONTENTS OF DATA FIELDS
0	1-2	MG
1	5-8	Marsh plant type abbreviation (see Table 10)
2	9-16	C_D , effective drag Coefficient; default value is 0.1
3	17-24	F_{cov} , decimal fraction of vegetated area to be covered by this plant type; a blank or zero causes a default to be calculated so that each plant type is represented equally
4	25-32	h, mean unflexed height of stem (feet); for marsh plants, the inflorescence is not included
5	33-40	N, number of plants per square foot
6	41-48	D_1 , base stem diameter (inches)
7	49-56	D_2 , mid stem diameter (inches)
8	57-64	D_3 , top stem diameter (inches)
9	65-72	CA_b , ratio of the total frontal area of cylindrical part of leaves to frontal area of main stem
10	73-80	Not used

ET Line (End of Transect)

This line is required and must be the last input card because it identifies the end of input for the transect.

DATA FIELD	COLUMNS	CONTENTS OF DATA FIELDS
0	1-2	ET
3-10	3-80	Not used

Table D-12. Significant Marsh Plant Types in Each Seacoast Region and WHAFIS Default Regional Plant Parameter Data

REGION NO.	1	2	3	4	5	6	7	8
REGION NAME:	NORTH ATLANTIC	MID-ATLANTIC	SOUTH ATLANTIC	SOUTH FLORIDA	NORTHEASTERN GULF	DELTA PLAIN	CHENIER PLAIN	SOUTH TEXAS
CLAD	---	---	---	7.50(+) 0.0656 6	6.00(2) 0.0260 6	---	---	---
DIST	---	0.78(1) 0.0039 211	1.00(1) 0.038 243	1.00(+) 0.0038 248	---	1.08(4) 0.0035 102	1.08(+) 0.0035 102	---
JUNM	1.23(1) 0.0042 300	1.23(+) 0.0042 300	---	---	---	---	---	---
JUNR	---	2.95(+) 0.0095 147	2.95(+) 0.0095 147	---	2.95(3) 0.0095 147	3.00(4) 0.0106 83	2.95(+) 0.0095 147	---
SALM	1.39(1) 0.0184 45	1.06(1) 0.0103 36	1.63(1) 0.0141 12	1.63(+) 0.0141 12	---	1.67(4) 0.0141 21	2.62(5) 0.0211 16	---
SALT	1.86(1) 0.0175 37	2.21(1) 0.0169 18	3.20(1) 0.0183 10	3.20(+) 0.0183 10	---	3.20(4) 0.0183 10	3.20(+) 0.0183 10	---
SCYN	---	---	8.29(+) 0.0492 6	---	---	4.00(4) 0.0267 7	---	---
SPAT	1.03(1) 0.0025 409	0.85(1) 0.0019 327	1.65(1) 0.0019 236	---	2.58(2) 0.0026 236	1.88(4) 0.0016 333	1.88(+) 0.0019 333	---

Guidelines and Specifications for Flood Hazard Mapping Partners

Data arranged in vertical triplets:

h, stem height below inflorescence, in feet
D, base diameter, in feet
N, number density, in inverse square feet

Parenthetical references indicate data source:

1 = Hardisky and Reimold, 1977
2 = Monte, August 1983
3 = Kruczynski, Subrahmanyam, Drake, 1978
4 = Hopkinson, Gosselink, Parrondo, 1980, Diameters extrapolated

5 = Turner and Gosselink, 1975, Diameters extrapolated
+ = Extrapolated Data
--- = Insignificant amounts of this plant type in the region

[February 2002]

D.3.6.4 Error Messages

While using the WHAFIS program, the Mapping Partner may encounter the error messages listed below.

- "AS card ground elevation less than SWEL, should use other type card, job dumped."

Only use AS (above surge) line when the ground elevation is above the SWEL. Can otherwise use IF, OF, BU, DU, VE, or VH.

- "Ground elevation greater than surge elevation encountered, job dumped."

If ground elevation is above surge elevation, AS card should be used.

- "Average depth less than or equal to zero, job dumped."

The water depth must be greater than zero or a wave height cannot be computed. Check the SWEL and the ground elevation if point of job dump is not the last point along the transect profile.

- "The above card contains illegal data in the first 2 columns."

Check input data for incorrect values or input within wrong columns. Aside from the title line, the first two columns in each line should contain the card identifiers.

- "Transmitted wave height at last fetch or obstruction = _____ which exceeds 0.5."

Code the transect profile up to the inland limit where ground elevation intersects the SWEL so that wave height should decrease to zero. If the scope of work ends at the corporate limits before the ground elevation meets the SWEL, this message can be ignored.

- "Array dimensions exceeded. Job dumped."

Size of the array is limited and the number of input parameters has exceeded the array. Check the number of input parameters at the location where the job dumped.

- "Invalid data in field 1 of IF card," etc.

Check input data to make sure that data are in correct columns.

- "Wave period less than or equal to zero in subroutine fetch. Abort run."

Either a fetch length or a wave period must be input for the program to run properly. Check input data.

- "Invalid data in field 3 or field 5 of VH card."

Check input data.

- "Invalid data in field 4 of VH card."

Check input data.

- "Invalid data in field 3 of MG card."

Guidelines and Specifications for Flood Hazard Mapping Partners

Check input data. The fraction of vegetated area covered by the stated plant type should be a decimal number between 0.0 and 1.0.

- "Missing MG card or incorrect data in field 6 of VH card."

A MG card must always follow the VH card. Field 6 of the VH card pertains to the number of plant types, and one MG card is required for each plant type.

- "Invalid input data."

Check input data for invalid characters, such as an O instead of a zero. Check to be sure that all data are in their correct columns.

- "Fcov was found to be negative for plant type = _____."

Check input data to be sure that the decimal fraction of the vegetated area covered by the plant type is not negative.

- "Ncov is .LE. zero in Sub.Lookup when it should be .GT. zero. Abort run."

Check input for number of plants covering the area.

- "The first card is not an IE card, this transect is aborted. Continued to next transect."

The first card after the title line must always be an IE card. Check input data.

- "***** The surge elevation at this station (stationing ____), which is ____ card, is less than the ground elevation. The interpolation process is continued. *** Please double check the surge and ground elevations in the vicinity of this station!!!!!"

The surge elevation should not be below the ground elevation. If the interpolated surge elevation is interpolated below the ground elevation, insert additional cards to specify surge and ground elevations and use an AS card if necessary.

- "Interpolation line cuts off more than two portions of high ground ridge. This transect is aborted, re-assign 1-percent-annual-chance elevations at high ground stations."

When the interpolated value falls below the ground elevation, insert additional cards to better model the area and set the SWEL equal to the ground elevation where appropriate. Insert AS cards as necessary.

- "***** Unreasonable high ground elevation at station ____ which is ____ card. This transect is aborted, continued to next transect. ***** Double check the surge and ground elevations in the vicinity of this station. If the ground elevations are correct, either assign a higher surge elevation or use AS cards."

Add additional input data as necessary to better define the ground elevation and surge elevation in this area.

[February 2002]

D.3.6.5 Output Description

The output of the program provides all the data necessary for plotting the BFEs and flood insurance risk zones along the transect. The output is in six parts:

Part 1 - Input

This is a printout showing all input data lines and the parameters assigned to each line, both manually and by default. This is followed by a more detailed printout with column headings for each input data line. When VH and MG Lines are used, a separate insert will be printed directly beneath the MG Line showing any default values supplied by the computer.

Part 2 - Controlling Wave Heights, Spectral Peak Wave Period, and Wave Crest Elevations

This is a list of the calculated controlling wave heights, spectral wave peak periods, and wave crest elevations at the end point of each fetch and obstruction of the input, and at calculation points generated between the input stations.

Part 3 - Location of Areas Above 1-Percent-Annual-Chance Surge

This is a list of the locations of areas where the ground elevation is greater than the 1-percent-annual-chance stillwater (surge) elevation. Only areas identified by AS lines are listed.

Part 4 - Location of Surge Elevations

This is a list of the 10- and 1-percent-annual-chance stillwater (surge) elevations and the stationing of the points where each set of SWELs first becomes fully effective.

Part 5 - Location of V Zones

This is a list of the locations of the V/A Zone boundary and locations of the V Zone areas relative to these boundaries. The stationing is given for each V/A Zone boundary. The locations of the V Zone areas in relation to these boundaries are given as windward or leeward of the boundary.

Part 6 - Numbered A Zones and V Zones

This is a list of the zone data needed to delineate the flood hazard boundaries on the FIRM. The location of a flood zone boundary and the wave crest elevation at that boundary are given on the left. Between the boundary listings are the zone designations and FHF's. Under FEMA's Map Initiatives Procedure guidelines, all numbered V and A Zones should be changed to VE and AE Zones, respectively (elevations will not change), and the FHF's can be ignored (FEMA, 1991). When the same zone and elevation are repeated in the list, they should be treated as a single zone.

[February 2002]

D.3.7 Mapping of Flood Elevations and Zones

This subsection discusses procedures for reviewing the initial model results and identifying flood insurance risk zones, and provides guidance for depicting the analysis on the FIRM.

[February 2002]

D.3.7.1 Review and Evaluation of Basic Results

The results of the technical analyses performed for the FIS or map revision determine the special flood hazards shown on the FIRM. The coastal hazards mapped on the FIRM depict the effects of erosion on overland wave propagation, the impact of steep beach slopes and bluffs on wave runup elevation, and the areas subject to high velocity wave hazards (V Zones). Because the FIRM is used for floodplain management and flood insurance determination, the Mapping Partner shall ensure the SFHAs are mapped with as much accuracy as possible.

With the results of the various analyses at hand, the Mapping Partner shall place flood elevations and zones on the work map or up-to-date topographic survey map, after first reviewed them for their consistency with the terrain and conditions they represent and with historical data. In using the models, it is possible to forget that the transects represent real shorelines of sandy beaches, rocky or cohesive bluffs, wetlands, etc., being subjected to extremely high water, waves, and winds. The Mapping Partner shall review the results of the analyses to determine if they are a reasonable representation of the coastal areas being modeled.

Although historical data from a storm closely approximating the base (1-percent-annual-chance) flood are seldom available, flood data for less intense storms will still indicate, at a minimum, what areas should be in flood zones. For instance, if a storm produced an extreme flood that caused structural damage to houses 100 feet from the shoreline, yet the flood was below the 1-percent-annual-chance flood SWEL, a reasonable Zone VE width would be at least 100 feet. Similarly, houses more than 100 feet from the shoreline that are flooded but not structurally damaged by the same storm must be at least in a Zone AE, AH, or AO. If the analyses of the 1-percent-annual-chance flood produce flood zones and elevations indicating lesser hazards than those recorded for a more common storm, the Mapping Partner shall reevaluate the analyses. There may be an explanation for the inconsistency (other than an error in the input data); for instance, a new coastal structure may act to reduce flood hazards locally or a big storm may have significantly altered the terrain. A field check should be undertaken to determine whether such an explanation exists.

If no explanation for the inconsistency is apparent, the Mapping Partner shall examine the data input to the models including checking that the SWELs, wave heights, wave periods, and fetch lengths were input correctly and are consistent with the historical data. A further field check could examine whether buildings or structures modeled would be destroyed by the storm or whether the buildings are on pilings above the flooding.

The Mapping Partner also shall evaluate the results of the erosion assessment by comparing the eroded profile to past effects, whether in the form of profiles, photographs, or simply

descriptions. A general idea of what happened previously can be sufficient. Judgment and experience must be used to project previous storm effects to the 1-percent-annual-chance flood conditions and to ensure that the eroded profile is consistent with previous events.

The main point emphasized here is that the results are not to be blindly accepted. Many uncertainties and variables in coastal processes may occur during an extreme flood, and many possible adjustments to methodologies for treating such an event may be appropriate. The validity of any model is demonstrated by its success in reproducing recorded events. Therefore, the model results must be in basic agreement with past flooding patterns and results, and historical data must be used to evaluate these results.

[February 2002]

D.3.7.2 Identification of Flood Insurance Risk Zones

Interpretation and accurate delineations of the hazards on the maps are the final critical elements in a coastal flood hazard study. The transect used in the wave elevation determination and the resulting wave analyses, whether for wave height or wave runup, is the tool by which the results can be mapped. Mapping Partner shall identify the flood zones and BFEs should be identified on each of the transect plots before transferring the information and delineating the hazard zones and BFEs on the work maps. It should be noted that because of changes in the NFIP in 1988 that redefined the Coastal High Hazard Area and incorporated wave runup hazards, Part 6 of the WHAFIS output, discussed in Section D.3.6, is no longer used to plot zones on the work maps.

It is important to understand the interrelationship of the three key elements in determining the flood hazard zone and BFE. These elements are the existing transect ground profile, the eroded transect ground profile, and the wave envelope. The existing transect ground profile may be modified by the presence of erosion forces along the shoreline, if appropriate, in which case the flood hazard zone depicted by the transect and wave analyses results may not appear to reflect the topography shown for existing conditions with ground elevations higher than the BFE. The eroded transect ground profile, developed using treatment described in Subsection D.3.4, must be used in the wave analyses described in Subsections D.3.5 and D.3.6. The BFEs and the topography shown on the work maps may differ from those produced by the erosion treatments for a shoreline reach and the wave analyses. This is because the topography of the work maps does not reflect the erosion of the shoreline determined as part of the coastal FIS or map revision request. To clarify areas where these discrepancies exist, the Mapping Partner shall provide a description of the areas subject to erosion treatments either in the coastal FIS Report or in the supporting engineering report for a map revision request.

The wave envelope is the most important of the three elements for identifying the flood hazard zone. The wave envelope is a combination of representative wave runup elevation and the wave crest profile determined by the wave results computed using the WHAFIS program. The wave crest profile is plotted on the final transect ground profile (with or without the effects of erosion) based on the results computed and shown in Part 2 of the WHAFIS output. For wave runup elevation results, a horizontal line is extended seaward from the computed runup elevation to its intersection with the wave crest profile. This determines the wave envelope profile for the

Guidelines and Specifications for Flood Hazard Mapping Partners

results combined from the WHAFIS wave height analysis and the RUNUP 2.0 wave runup analysis, as shown in Figure D-46. If the runup elevation is greater than the maximum wave crest elevation, the wave envelope will be a horizontal line at the runup elevation. Conversely, if the wave runup is negligible or was not modeled because of coastal processes and shoreline conditions that prevent significant runup from occurring, the wave crest profile alone will become the wave envelope.

Before transferring the established wave envelope information from each transect onto the work maps, it is important to understand the NFIP coastal flood zones and how to determine their location along the transect plot. The descriptions are as follows:

Zone VE - Coastal High Hazard Areas where wave action and/or high velocity water can cause structural damage in the base (1-percent-annual-chance) flood. The three criteria for determining a Zone VE area are: (1) the area where 3 foot or greater wave height could occur (this is the area where the WHAFIS wave crest profile is 2.1 feet or more above the SWEL), (2) the area where the eroded ground profile is 3 feet or more below the representative runup elevation, and (3) the primary frontal dune, by definition. Subdivided into elevation zones with BFEs assigned.

Zone AE - Areas of inundation by the base (1-percent-annual-chance) flood, including wave heights less than 3 feet and runup elevations less than 3 feet above the ground. Also subdivided into elevation zones with BFEs assigned.

Zone AH - Areas of shallow flooding or ponding, with water depth equal to 3 feet or less. Usually not subdivided, but a BFE is assigned.

Zone AO - Areas of "sheet-flow" shallow flooding where overtopping water flows into another flooding source. Assigned with 1-, 2-, or 3-foot depth of flooding.

Zone X - Areas above base (1-percent-annual-chance) flood inundation. On the FIRM, shaded Zone X is inundated by the 0.2-percent annual chance flood, unshaded Zone X is above 0.2-percent annual chance flood.




Figure D-46. Wave Envelope Resulting from Combination of Nearshore Crest Elevations and Shore Runup Elevation.

Guidelines and Specifications for Flood Hazard Mapping Partners

The first step in identifying the flood insurance risk zones on the transect is locating the inland extent of the VE Zone, also known as the VE/AE boundary. Once the Mapping Partner has identified the VE Zone limits for each of the three criteria described above, the Mapping Partner shall place the VE/AE boundary at the location that is furthest landward. The AE Zone will extend from the VE Zone limit to the inland limit of the 1-percent-annual-chance flood inundation, which is a ground elevation equal to the representative runup elevation, or the 1-percent-annual-chance SWEL if runup is negligible or not included in the wave analyses. Additional areas of shallow flooding or ponding for the 1-percent-annual-chance flood event can be designated as Zone AH or Zone AO. All areas above the 1-percent-annual-chance flood inundation are Zone X.

The Mapping Partner shall then subdivide the AE and VE Zones into elevation zones with whole-foot BFEs assigned. Ideally, to help in floodplain management and insurance determinations for buildings and property, the Mapping Partner shall establish an elevation zone for every BFE in the wave envelope. However, the FIRM scale may limit the number of zones that can be mapped. For the FIRM to be legible, there must be a minimum width for the zones. For coastal areas, the minimum zone width is 0.2 inch. For identifying elevation zones on the transect, the minimum width is 0.2 times the final FIRM scale; for example, 80 feet for a FIRM at a scale of 1 inch equals 400 feet, 100 feet for a FIRM at a scale of 1 inch equals 500 feet.

The Mapping Partner shall not subdivide the horizontal runup portion of the wave envelope, if any; the runup elevation, rounded to the nearest whole foot, is the BFE. However, the Mapping Partner shall subdivide the WHAFIS wave crest profile. Generally, the VE Zone is subdivided first. Initially, the Mapping Partner shall mark the location of all the elevation zone boundaries on the transect. Because whole-foot BFEs are being used, these must always be at the location of the half-foot elevation on the envelope.

The Mapping Partner shall combine elevation zones that do not meet the minimum width criterion with an adjacent zone or zones to yield an elevation zone that is wider than the minimum. The BFE for this combined zone is a weighted average of the combined zones. Often in subdividing VE Zones, the maximum BFE is located just inside the mapped shoreline, and the remainder of the VE Zone is then subdivided into minimum width elevation zones.

The Mapping Partner shall subdivide the AE Zone, if it is wide enough, in the same manner. If the total AE Zone is less than the minimum width, the lowest elevation VE Zone is usually assigned to that area. This situation typically occurs for steep or rapidly rising ground profiles, and it is not unreasonable to designate the entire inundated area as a VE Zone.

Relatively low areas inland of the AE Zone may be subject to shallow flooding or ponding of flood water and designated as AH or AO Zone. Such designations can be relatively common landward of coastal structures and dunes, where wave overtopping occurs.

Identifying appropriate zones and elevations may require particular care for dunes, given that the entire primary frontal dune is defined as Coastal High Hazard Area. Although the analyses may have determined a dune will not completely erode and wave action should stop at the retreated

duneface with only overtopping possibly propagating inland, the entire dune is still designated as a VE Zone. The BFE at the duneface is assigned for the remainder of the dune.

It may seem unusual to use a BFE that is lower than the ground elevation, although this is actually fairly common. Most of the BFEs for areas where the dune was assumed to be eroded are also below existing ground elevations. In these cases, it is the VE Zone designation that is most important to the NFIP; current regulations require structures to be built on pilings and prohibit alterations to the dune.

[February 2002]

D.3.7.3 Mapping Procedures

The final work maps prepared from the results of the coastal FIS or map revision request will be used to produce a new or revised FIRM for the affected community. The work map is essentially the base map selected for the study area, as described in Subsection D.3.2, and the depiction and delineation of the coastal flood hazards that reflect the results of the wave elevation determinations and flood zones established for each respective area. The Mapping Partner shall set the work map up with contour lines, buildings, structures, vegetation, and transects used in the wave analyses clearly and accurately located.

The Mapping Partner shall transfer the flood zones and wave elevations identified on the transects to the work maps and interpolate the boundaries between the transects. The interpolation of the results at the transects and between the transects for the results of the wave height and wave runup analyses involves judgment and skill in reading the topographic and land cover information shown on the work maps. The time and effort put forth to determine the wave elevations will be negated if the results cannot be properly delineated on the work maps and shown on the FIRM. Because roads are the only fixed physical features shown on the FIRM, it is very important that other features and the flood zone boundaries are properly located on the work maps in relation to the centerline of the roads as they will appear on the FIRM. Other important considerations for mapping the results of the coastal FIS or map revision request discussed below include shoreline fluctuations, flood zone widths, interpolation of the transitions between zones for the represented transects, and the depiction and delineation of the Zone X shaded special flood hazard areas in areas subject to wave runup hazard.

An important but potentially ambiguous map feature is the depicted shoreline in the study area. Great Lakes shorelines are subject to large position changes, given shore erosion or accretion along with the considerable range in mean lake levels. The shoreline location may vary among the transects analyzed because of historical erosion or accretion not shown or accounted for on existing maps, but some clearly designated shoreline should be used for the work maps. For Great Lakes studies, the Mapping Partner shall ensure the depicted shoreline corresponds to the land intercept of Low Water Datum, as given in Table D-12 and usually shown on USGS maps. (It is customary to delineate flood zones only landward of the shoreline.)

The Mapping Partner shall transfer the identified elevation zones for each transect to the work maps, locating the boundaries along the transect line so that boundary lines can be interpolated

Guidelines and Specifications for Flood Hazard Mapping Partners

between transects, assuring that the boundaries are marked at the correct location. Because of the erosion assumptions, the location of the elevation 0.0 NGVD shoreline changes on the transect but not the work maps. The transect profile is used to determine the location of the zone change in relation to a physical feature, such as a ground contour, road, the back side of a row of houses, 50 feet into a vegetated area, etc. The boundary line along this feature for the area represented by that transect is then delineated.

The Mapping Partner shall check the widths of the zones being delineated carefully; if they narrow to less than 0.2 inch, they should be tapered to an end. Likewise, if an averaged elevation zone becomes much wider, it may be possible to break it into two elevation zones, both wider than 0.2 inch. Consideration of the final map scale of the FIRM to be produced from the work maps will help in determining how the zones should be combined and averaged.

One of the more difficult steps in delineating coastal flood zones and elevations is the interpolation and transition between transect results. Good judgment and an understanding of typical flooding patterns are the best tools for this job. The first step is to locate on the work maps any area of transition that is not exactly represented by either transect. The next step is to delineate the flood boundaries for each transect up to this area. Then consideration should be given to how a transition can be made across this area to connect matching zones, and still have the boundaries follow logical physical features. If there are other transects that are similar to this area, they could give an indication of flooding. Sometimes the elevation zones for the two contiguous transects are not the same; thus, some zones may have to be tapered to an end, or enlarged and divided in the transition area.

Communities with significant flooding hazards from wave runup may have one transect representing more than one area because the areas have similar shore slopes. In this case, the different areas are identified, and the results of the typical transect delineated in each area. Transition zones may be necessary between areas with high runup elevations to avoid large differences in BFEs and to smooth the change in flood boundaries. These zones, which should be fairly short, should cover the shore segment with a slope not exactly typical of either area. The transition elevation is determined by examining runup transects with similar slopes and using good judgment. Transition zones should not be used if there is a very abrupt change in topography, such as is found at the end of a structure.

Lastly, Mapping Partner shall map the Zone X (shaded) areas. Areas below the 0.2-percent annual chance SWEL and not covered by any other flood zone are designated Zone X shaded and shown on the FIRM. Often the maximum runup elevation is higher than the 0.2-percent annual chance elevation; thus, there will be no shaded Zone X in that area. The Mapping Partner shall designate all other areas as Zone X without any shading.

These *Guidelines* were compiled to give guidance in the preparation of coastal FISs and map revision requests. The collection of accurate and representative data, the correct application of the models, the evaluation and comparison of the results to historical data, and the proper delineation of flood elevations and zones will produce a FIRM that is both technically correct and directly usable for the intended purposes.

During all steps of the study, especially the mapping, the final product and its purposes should be remembered: the FIRM is used to determine flood insurance premiums and regulate building standards.

Because flood elevations are rounded to the nearest whole foot, there is no reason for spending hours to resolve a minor elevation difference. Also, because structures or proposed structures must be located on the FIRM, an attempt should be made whenever possible to smooth the boundary lines and to follow a fixed feature such as a road. In preparing the FIS, not only must the mapped results be technically correct, but the FIRM must be easy for the local insurance agent, building inspector, or permit officer to use.

Additional criteria and submittal requirements are documented in the Certification forms for Study Contractors (SC-1) and Application/Certification form 5 (MT-2) for map revision requests.

[February 2002]

D.3.8 Required Documentation

The Mapping Partner shall fully document the coastal flood hazard determination for each affected community. Because FIS Reports and FIRMs form the basis of Federal, State, and local regulatory and statutory enforcement mechanisms and are subject to administrative appeal and litigation, Mapping Partners shall ensure that all technical processes and decisions are recorded and documented. The FIS Report may not contain all the documentation that would be needed for a response in the event that the study results are questioned. Therefore, the Mapping Partner shall prepare an engineering report for each study. This report will provide detailed data needed by FEMA or the community to reconstruct or defend on technical grounds the study results. The minimum information required for the engineering report are summarized below.

Basic Data.

In this section, the Mapping Partner shall include all contacts made to obtain data for the study. All basic data used must be fully referenced and, if possible, reproduced in the report. All historical flood information must be documented in this section, even if the Mapping Partner did not use the information in quantitative analyses.

Transects

Each transect must be plotted separately and show the erosion assessment, input data for wave models, wave envelope, and zone determination.

Model Input and Output

The Mapping Partner shall provide computer printout listings for input and output data for both the Wave Runup and Wave Height Models for all the transects. These listings must be keyed to the transect location map and transect plots.

Study File

During the course of the study, the Mapping Partner shall maintain a file containing records of all coordination, activities, and decisions. This is especially important where nonstandard approaches were used and engineering judgment played a significant role. The Mapping Partner shall ensure this file meets the requirements for a Technical Support Data Notebook as documented in Appendix M of these Guidelines.

[February 2002]

D.3.9 Open Coast Flood Elevations and Wave Information

As discussed in Subsection D.3.2, the draft of "Basic Analyses of Wave Action and Erosion with Extreme Floods on Great Lakes Shores" (Dewberry & Davis, 1995) concluded from historical evidence that extreme floods were usually accompanied by the local 1/2-year wave condition on Lake Ontario, or by the 3-year wave condition on Lakes Erie, Huron, Michigan, and Superior. Examples of appropriate wave conditions derived for numerous sites on each of the Great Lakes are presented in Figures D-47 through D-56 and in Tables D-23 through D-27.




Figure D-47. Lake Superior Table and Map of Open Coast Flood Levels (USACE, 1988).




Figure D-48. Station Location Map for Lake Superior Wave Information Stations.

Table D-23. Three-Year Wave Conditions as Hindcast for Selected Nearshore Sites on Lake Superior

HINDCAST SITE ID	WAVE HEIGHT (METERS)	WAVE PERIOD (SECONDS)
SUPER-05	6.0	10.0
SUPER-13	5.8	10.0
SUPER-15	3.7	7.1
SUPER-23	4.3	--
SUPER-29	5.0	9.1
SUPER-35	5.9	--
SUPER-42	5.2	--
SUPER-47	7.7	11.1
SUPER-54	6.2	--
SUPER-60	4.5	7.7




PLATE 2

Figure D-49. Lake Michigan Table and Map of Open Coast Flood Levels (USACE, April 1988).




Figure D-50. Station Location Map for Lake Michigan Wave Information Stations.

Table D-24. Three-Year Wave Conditions as Hindcast for Selected Nearshore Sites on Lake Michigan

HINDCAST SITE ID	WAVE HEIGHT (METERS)	WAVE PERIOD (SECONDS)
MICH-01	4.4	9.1
MICH-03	4.6	9.1
MICH-09	4.7	8.3
MICH-14	3.9	--
MICH-19	4.0	8.3
MICH-22	3.7	7.7
MICH-26	3.3	8.3
MICH-30	3.4	8.0
MICH-34	3.7	--
MICH-41	4.1	--
MICH-46	4.7	9.1
MICH-48	5.2	9.1
MICH-54	5.2	9.1
MICH-60	4.5	8.3




Figure D-51. Lake Huron Table and Map of Open Coast Flood Levels (USACE, 1988).




Figure D-52. Station Location Map for Lake Huron Wave Information Stations.

Table D-25. Three-Year Wave Conditions as Hindcast for Selected Nearshore Sites on Lake Huron

HINDCAST SITE ID	WAVE HEIGHT (METERS)	WAVE PERIOD (SECONDS)
HURON-01	6.1	9.1
HURON-02	6.2	10.0
HURON-07	5.6	9.1
HURON-11	6.3	9.1
HURON-12	6.2	9.5
HURON-15	6.1	9.1
HURON-20	5.0	--
HURON-25	4.1	7.7
HURON-26	4.3	9.1




PLATE 4

Figure D-53. Lake Erie Table and Map of Open Coast Flood Levels (USACE, 1988).




Figure D-54. Station Location Map for Lake Erie Wave Information Stations.

Table D-26. Three-Year Wave Conditions as Hindcast for Selected Nearshore Sites on Lake Erie

HINDCAST SITE ID	WAVE HEIGHT (METERS)	WAVE PERIOD (SECONDS)
ERIE-01	2.0	6.2
ERIE-04	1.9	6.2
ERIE-07	3.3	--
ERIE-10	3.6	7.7
ERIE-12	4.0	8.3
ERIE-15	4.2	--
ERIE-18	4.6	9.1
ERIE-21	4.9	9.1
ERIE-24	4.2	9.1
ERIE-47	1.8	5.6




Figure D-55. Lake Ontario Table and Map of Open Coast Flood Levels (USACE, 1988).




Figure D-56. Station Location Map for Lake Ontario Wave Information Stations.

Table D-27. One-Half-Year Wave Conditions as Hindcast for Selected Nearshore Sites on Lake Ontario

HINDCAST SITE ID	WAVE HEIGHT (METERS)	WAVE PERIOD (SECONDS)
ONT-04	2.7	--
ONT-06	2.9	6.7
ONT-07	3.0	7.1
ONT-11	3.2	7.1
ONT-14	2.6	--
ONT-17	3.2	7.1
ONT-21	2.4	5.9

[February 2002]

D.4 Wave Elevation Determination and V Zone Mapping: Pacific Ocean

No FEMA guidance documents have been published for Pacific Ocean coastal flood studies. Guidance is to be developed based on existing methodologies recommended by FEMA and coastal states for coastal analyses in the Pacific Ocean. Mapping Partners that are undertaking a flood hazard analysis of a Pacific coast site should consult with the FEMA RPO for that area.

[February 2002]

D.5 Erosion Hazard Study, Identification, and Mapping

No FEMA guidance documents have been published for erosion hazard studies and mapping. Guidance is to be developed based on new or existing methodologies recommended by FEMA and coastal states for erosion hazard studies and mapping in all coastal areas.

[February 2002]

D.6 References

- Abel, C. E., Tracy, B. A., Vincent, C. L., & Jensen, R. E. (1989). Hurricane Hindcast Methodology and Wave Statistics for Atlantic and Gulf Hurricanes from 1956-1975. WIS Report 19. Coastal Engineering Research Center. Vicksburg, Mississippi.
- Birkemeier, W. A., Kraus, N. C., Scheffner, N., & Knowles, S. C. (1987). U.S. Army Corps of Engineers, Coastal Engineering Research Center, Technical Report CERC-87-8. Feasibility Study of Quantitative Erosion Models for Use by FEMA in the Prediction of Coastal Flooding. Vicksburg, Mississippi
- Cox, J. C. & Machemehl, J. (1986). "Overland Bore Propagation Due to an Overtopping Wave." Journal of Waterway, Port, Coastal and Ocean Engineering, Vol. 112, pp. 161-163.
- Dawdy, David & Maloney, M. David. (1980). Method of estimating on-shore propagation of storm waves. Geophysical Research Letters. Vol. 7. (pp. 845-847).
- de Waal, J. P. & van der Meer, J. W. (1992). Wave Runup and Overtopping on Coastal Structures. Proceedings 23rd Coastal Engineering Conference, pp. 1758-1771.
- Delft Hydraulics Laboratory. (1983). Wave Runup and Overtopping at Dunes During Extreme Storm Surge Report M1819, Part II. (in Dutch). Delft, The Netherlands.
- Dewberry & Davis. (1990). Investigation and Improvement of the Capabilities of the FEMA Wave Runup Model (Technical Documentation for RUNUP 2.0), Report and Computer Program. Fairfax, Virginia.
- Dewberry & Davis. (1991). Technical Documentation for RUNUP 2.0. Report and computer program, Fairfax, Virginia
- Dewberry & Davis. (1995). Basic Analyses of Wave Action and Erosion with Extreme Floods on Great Lakes Shores, draft prepared for Federal Emergency Management Agency. Fairfax, Virginia.
- Driver, D. B., Reinhard, R. D., & Hubertz, J. M. (1991). Hindcast Wave Information for the Great Lakes: Lake Erie, WIS Report 22, USACE, Coastal Engineering Research Center. Vicksburg, Mississippi.
- Driver, D. B., Reinhard, R. D., & Hubertz, J. M. (1992). Hindcast Wave Information for the Great Lakes: Lake Superior, WIS Report 23, USACE, Coastal Engineering Research Center. Vicksburg, Mississippi.
- Federal Emergency Management Agency. (January 1981). Computer Program for Determining Wave Height Elevations for Flood Insurance Studies, revised. Washington, D.C.

Guidelines and Specifications for Flood Hazard Mapping Partners

Federal Emergency Management Agency. (February 1981). Users Manual for Wave Height Analysis, revised. Washington, D.C.

Federal Emergency Management Agency. (1984). Procedures for Applying Marsh Grass Methodology. Washington, D.C.

Federal Emergency Management Agency. (1986). Assessment of Current Procedures Used for the Identification of Coastal High Hazard Areas (V Zones). Washington, D.C.

Federal Emergency Management Agency. (September 1988). Wave Height Analysis for Flood Insurance Studies (Technical Documentation for WHAFIS Program Version 3.0). Washington, D.C.

Federal Emergency Management Agency. (August 1988). Coastal Flooding Hurricane Storm Surge Model, Volumes 1, 2, and 3. Washington, D.C.

Federal Emergency Management Agency. (November 1988). Basis of Erosion Assessment Procedures for Coastal Flood Insurance Studies. Washington, D.C.

Federal Emergency Management Agency, Federal Insurance Administration. (1989). *Guidelines and Specifications for Wave Elevation Determination and V Zone Mapping*, Third draft report. Washington, D.C.

Federal Emergency Management Agency. (1990). "Memorandum on Criteria for Evaluating Coastal Flood Protection Structures for National Flood Insurance Program Purposes." Washington, DC, dated April 23, 1990.

Federal Emergency Management Agency, Federal Insurance Administration. (1991). *Guidelines for Great Lakes Wave Runup Computation and Mapping*. Washington, D.C.

Federal Emergency Management Agency, Federal Insurance Administration. (August 1994). Basic Analyses of Wave Action and Erosion with Extreme Floods on Great Lakes Shores, draft report. Washington, D.C.

Federal Emergency Management Agency. (1994). *Guidelines and Specifications for Flood Hazard Mapping at Coastal Sites on the Great Lakes*, draft. Washington, D.C.

Federal Emergency Management Agency, Federal Insurance Administration. (1995.) *Guidelines and Specifications for Wave Elevation Determination and V Zone Mapping*, final report. Washington, D.C.

French, J. (1982). Memorandum on Special Computation Procedure Developed for Wave Runup Analysis for Casco Bay, FIS - Maine, 9700-153. Camp Dresser & McKee.

Guidelines and Specifications for Flood Hazard Mapping Partners

- Gadd, P. E., Potter, R. E., Safaie, B. & Resio, D. (1984). Wave Runup and Overtopping: A Review and Recommendations. OTC 4674. Proceedings 1984 Offshore Technology Conference, pp. 239-248.
- Gilhousen, D. B., Meindl, E. A., Changery, M. J., Franks, P. L., Burgin, M. G., & McKittrick, D. A. (1990). Climatic Summaries for NDBC Buoys and Stations: Update 1. National Data Buoy Center, National Space Technology Laboratory. Mississippi.
- Goda, Yoshima. (1985). Random Seas and Design of Maritime Structures. University of Tokyo Press. Japan.
- Hardisky, M.A. & Reimold, R. J. (1977). Nondestructive Assessment of Salt Marsh Plant Biomass, unpublished report. University of Georgia: Athens, Georgia.
- Hopkinson, C. W., Gosselink, J. G., & Parrondo, R. T. (1980). Production of Coastal Louisiana Marsh Plants Calculated from Phenometric Techniques. Ecology, 61(5), 1091-1098.
- Ho, F. P., Su, J. C., Hanevich, K. L., Smith, R. J., & Richards, F. P. (1987). Hurricane Climatology for the Atlantic and Gulf Coasts of the United States. NOAA Technical Report NWS 38. National Weather Service. Silver Spring, Maryland.
- Hubertz, J. M., Driver, D. B., & Reinhard, R. D. (1991). Hindcast Wave Information for the Great Lakes: Lake Michigan, WIS Report 24, USACE, Coastal Engineering Research Center. Vicksburg, Mississippi.
- Hubertz, J. M., Brooks, R. M., Brandon, W. A., & Tracy, B. A. (1993). Hindcast Wave Information for the U.S. Atlantic Coast. WIS Report 30. Coastal Engineering Research Center. Vicksburg, Mississippi.
- Hydraulics Research Station. (1980). Design of Seawalls Allowing for Wave Overtopping. Report no. ex. 924. Wallingford, United Kingdom.
- Jensen, R. E., Hubertz, J. M., Thompson, E. F., Reinhard, R. D., Borup, B. J., Brandon, W. A., Payne, J. B., Brooks, R. M., & McAneny, D. S. (1992). Southern California Hindcast Wave Information. WIS Report 20. Coastal Engineering Research Center. Vicksburg, Mississippi.
- Knutson, P. L. & Woodhouse, W. W. Jr. (1983). Shore Stabilization with Salt Marsh Vegetation. Special Report 9. Coastal Engineering Research Center. Fort Belvoir, Virginia.
- Kruczynski, W. L., Subrahmanyam, C. B., & Drake, S. H. (1978). Studies on the Plant Community of a North Florida Salt Marsh: Part I: Primary Production. Bulletin of Marine Science. 28(2), 316-334.
- Leenknecht, D. A., Szuwalski, A., & Sherlock, A. R. (1992). Automated Coastal Engineering System, Version 1.07. Coastal Engineering Research Center. Vicksburg, Mississippi.

Guidelines and Specifications for Flood Hazard Mapping Partners

Levels Reference Study Board. (1993). Levels Reference Study: Great Lakes - St. Lawrence River Basin. Annex 2 to report submitted to International Joint Commission. Ottawa, Ontario/Washington, D.C.

Messmore, J. A., Vogel, T. C., & Pearson, A. R. (1979). U.S. Army Corps of Engineers, Engineer Topographic Laboratories. Terrain Analysis Procedural Guide for Vegetation. ETL-0178. Fort Belvoir, Virginia.

Monte, J. A. (1983). Field Data from the Florida Panhandle, unpublished report. Greenhorne & O'Mara, Inc. Greenbelt, Maryland.

Nagai, S. & Takada, A. (1972). Relations Between the Runup and Overtopping of Waves. Proceedings 13th Coastal Engineering Conference, pp. 1975-1992.

National Academy of Sciences. (1977). Methodology for Calculating Wave Action Effects Associated with Storm Surges. Washington, D.C.

Owen, M. W. (1980). Design of Seawalls Allowing for Wave Overtopping. Report Ex. 924. Hydraulics Research Station. Wallingford, United Kingdom.

Reinhard, R. D., Driver, D. B., Hubertz, J. M. (1991). Hindcast Wave Information for the Great Lakes: Lake Huron, WIS Report 26, USACE, Coastal Engineering Research Center. Vicksburg, Mississippi.

Saville, T., Jr. (1958). Wave Runup on Composite Slopes. Proceedings of the Sixth Conference on Coastal Engineering. ASCE. Council on Wave Research.

Stoa, P. N. (1978). Reanalysis of Wave Runup on Structures and Beaches. Technical Paper 78-2. Coastal Engineering Research Center. Fort Belvoir, Virginia.

Stone & Webster Engineering Corporation. (1978). Development and Verification of a Synthetic Northeaster Model for Coastal Flood Analysis. Boston, Massachusetts.

Stone & Webster Engineering Corporation. (1981). Manual for Wave Runup Analysis, Coastal Flood Insurance Studies. Boston, Massachusetts.

Suhayda, J. N. (1984). Attenuation of Storm Waves Over Muddy Bottom Sediments. Baton Rouge, Louisiana.

Thompson, E. F. (1977). Wave Climate at Selected Locations Along U.S. Coasts. Technical Report 77-1. Coastal Engineering Research Center. Fort Belvoir, Virginia.

Turner, R. E. & Gosselink, J. G. (1975). A Note on Standing Crops of *Spartina alterniflora* in Texas and Florida. Contributions in Marine Science, University of Texas.

Guidelines and Specifications for Flood Hazard Mapping Partners

U.S. Army Corps of Engineers, Galveston District. (1973). General Guidelines for Identifying Coastal High Hazard Zone, Flood Insurance Study - Texas Gulf Coast Case Study. Galveston, Texas.

U.S. Army Corps of Engineers, Galveston District. (1975). Guidelines for Identifying Coastal High Hazard Zones. Galveston, Texas.

U.S. Army Corps of Engineers, Coastal Engineering Research Center. (1984). Shore Protection Manual, Volumes I and II, 4th Edition, Washington, D.C.

U.S. Army Corps of Engineers, Detroit District. (1988). Revised Report on Great Lakes Open-Coast Flood Levels, Phase I/Phase II. Detroit, Michigan.

U.S. Army Corps of Engineers, Detroit District. (June 1989). Great Lakes Wave Runup Methodology Study. Detroit, Michigan.

U.S. Army Corps of Engineers, Detroit District. (September 1989). Saginaw Bay Flood Levels Report, Detroit, Michigan.

U.S. Army Corps of Engineers, Coastal Engineering Research Center. (1992). Automated Coastal Engineering System Version 1.07. Computer Programs and Documentation. Vicksburg, Mississippi.

Vellinga, P. (1986). Beach and Dune Erosion During Storm Surges. Communication No. 372. Delft Hydraulics Laboratory. Delft University of Technology. Delft, The Netherlands.

Walton, T. L., Jr., Ahrens, J. P., Truitt, C. L., & Dean, R. G. (1989). Criteria for Evaluating Coastal Flood-Protection Structures. Technical Report CERC-89-15. U.S. Army Corps of Engineers, Coastal Engineering Research Center. Vicksburg, Mississippi.

Williams, P. (1983). Interoffice Correspondence on Wave Runup Methodology, Massachusetts and Rhode Island Flood Insurance Studies. PRC Harris, Inc.

[February 2002]