

**Subject: ENERGY STAR® criteria revisions**

Thank you for allowing us the opportunity to provide input regarding the upcoming ENERGY STAR revisions. We would like to submit the following comments for your consideration concerning the proposed draft side-hinged door criteria and analysis published on August 6, 2008:

We support separate criteria for glazed and opaque doors. However, we believe that any differentiation based on the quantity of glazing is not in the best interest of the homeowner. These values could persuade a consumer to purchase a lesser performing product (3/4-lite) over a higher performing product (1/2-lite) simply because it is ENERGY STAR qualified. This would result in less energy savings, not more.

Door Type	Phase 1	Phase 2
Opaque	U = 0.18	U = 0.16
1/4 & 1/2 Lite	U = 0.27	U = 0.23
3/4 & Full Lite	U = 0.32	U = 0.28

If criteria are variable by percent of glazing, we request the 1/2-lite values be adjusted to reflect the same glazing required by the full lite values (see Table 1). Simulations have demonstrated that the glazing required attaining a 0.32 U-factor in a full lite door will result in a 0.27 U-factor in a 1/2-lite door of identical construction and glazing.




Figure 1




Figure 2

We acknowledge that there is great opportunity for improvements in efficiencies with opaque door units. Opaque entry doors constitute a large percentage of the market. Therefore, we believe a more aggressive value for Phase 1 would better differentiate energy efficient products. Of the 463 opaque door records ( $VT \leq 0.00001$ ) in the NFRC database, 237 of them already perform at 0.18 or better (Fig 1 and Fig 2). We believe this would be an appropriate value that is achievable with current technologies.

We discourage the implementation of maximum SHGC. Lower U-factor requirements and the elimination of climate zones greatly reduce the importance of SHGC limitations. By their nature, products with low U-factors will also have low SHGC. The attempted "balance" is unnecessary. We continue to request that the interval between program criteria changes be at least four (4) years and would support a Phase 2 effective date 4 years after the Phase 1 effective date.

As a member of the Association of Millwork Distributors, we appreciated the EnergyStar Program and look forward to partnering with you in future efforts to promote safe, affordable, energy efficient millwork products.

Name: John Miller Company: Millwork Distributors Inc  
 Address: 6361 Sterling Dr. N. Sterling Heights, MI 48012  
 Email: \_\_\_\_\_

**Subject: ENERGY STAR® criteria revisions**

Thank you for allowing us the opportunity to provide input regarding the upcoming ENERGY STAR revisions. We would like to submit the following comments for your consideration concerning the proposed draft side-hinged door criteria and analysis published on August 6, 2008:

We support separate criteria for glazed and opaque doors. However, we believe that any differentiation based on the quantity of glazing is not in the best interest of the homeowner. These values could persuade a consumer to purchase a lesser performing product (3/4-lite) over a higher performing product (1/2-lite) simply because it is ENERGY STAR qualified. This would result in less energy savings, not more.

Door Type	Phase 1	Phase 2
Opaque	U = 0.18	U = 0.16
¼ & ½ Lite	U = 0.27	U = 0.23
¾ & Full Lite	U = 0.32	U = 0.28

If criteria are variable by percent of glazing, we request the ½-lite values be adjusted to reflect the same glazing required by the full lite values (see Table 1). Simulations have demonstrated that the glazing required attaining a 0.32 U-factor in a full lite door will result in a 0.27 U-factor in a ½-lite door of identical construction and glazing.




Figure 1




Figure 2

We acknowledge that there is great opportunity for improvements in efficiencies with opaque door units. Opaque entry doors constitute a large percentage of the market. Therefore, we believe a more aggressive value for Phase 1 would better differentiate energy efficient products. Of the 463 opaque door records (VT ≤ 0.00001) in the NFRC database, 237 of them already perform at 0.18 or better (Fig 1 and Fig 2). We believe this would be an appropriate value that is achievable with current technologies.

We discourage the implementation of maximum SHGC. Lower U-factor requirements and the elimination of climate zones greatly reduce the importance of SHGC limitations. By their nature, products with low U-factors will also have low SHGC. The attempted “balance” is unnecessary. We continue to request that the interval between program criteria changes be at least four (4) years and would support a Phase 2 effective date 4 years after the Phase 1 effective date.

As a member of the Association of Millwork Distributors, we appreciated the EnergyStar Program and look forward to partnering with you in future efforts to promote safe, affordable, energy efficient millwork products.

Name: MARK FORTUN Company: ENDURA PRODUCTS, INC

Address: 8817 W MARKET ST COLFAX, NC 27235

Email: mfortun@enduraproducts.com

**Subject: ENERGY STAR® criteria revisions**

Thank you for allowing us the opportunity to provide input regarding the upcoming ENERGY STAR revisions. We would like to submit the following comments for your consideration concerning the proposed draft side-hinged door criteria and analysis published on August 6, 2008:

We support separate criteria for glazed and opaque doors. However, we believe that any differentiation based on the quantity of glazing is not in the best interest of the homeowner. These values could persuade a consumer to purchase a lesser performing product (3/4-lite) over a higher performing product (1/2-lite) simply because it is ENERGY STAR qualified. This would result in less energy savings, not more.

Door Type	Phase 1	Phase 2
Opaque	U = 0.18	U = 0.16
¼ & ½ Lite	U = 0.27	U = 0.23
¾ & Full Lite	U = 0.32	U = 0.28

If criteria are variable by percent of glazing, we request the ½-lite values be adjusted to reflect the same glazing required by the full lite values (see Table 1). Simulations have demonstrated that the glazing required attaining a 0.32 U-factor in a full lite door will result in a 0.27 U-factor in a ½-lite door of identical construction and glazing.




Figure 1




Figure 2

We acknowledge that there is great opportunity for improvements in efficiencies with opaque door units. Opaque entry doors constitute a large percentage of the market. Therefore, we believe a more aggressive value for Phase 1 would better differentiate energy efficient products. Of the 463 opaque door records (VT ≤ 0.00001) in the NFRC database, 237 of them already perform at 0.18 or better (Fig 1 and Fig 2). We believe this would be an appropriate value that is achievable with current technologies.

We discourage the implementation of maximum SHGC. Lower U-factor requirements and the elimination of climate zones greatly reduce the importance of SHGC limitations. By their nature, products with low U-factors will also have low SHGC. The attempted “balance” is unnecessary. We continue to request that the interval between program criteria changes be at least four (4) years and would support a Phase 2 effective date 4 years after the Phase 1 effective date.

As a member of the Association of Millwork Distributors, we appreciated the EnergyStar Program and look forward to partnering with you in future efforts to promote safe, affordable, energy efficient millwork products.

Name: Paul Weller Company: Bayer Built Woodworks

Address: 24614 Highway 71 Belgrade, Mn 56312

Email: PSW@BayerBuilt.com

**Subject: ENERGY STAR® criteria revisions**

Thank you for allowing us the opportunity to provide input regarding the upcoming ENERGY STAR revisions. We would like to submit the following comments for your consideration concerning the proposed draft side-hinged door criteria and analysis published on August 6, 2008:

We support separate criteria for glazed and opaque doors. However, we believe that any differentiation based on the quantity of glazing is not in the best interest of the homeowner. These values could persuade a consumer to purchase a lesser performing product (3/4-lite) over a higher performing product (1/2-lite) simply because it is ENERGY STAR qualified. This would result in less energy savings, not more.

Door Type	Phase 1	Phase 2
Opaque	U = 0.18	U = 0.16
¼ & ½ Lite	U = 0.27	U = 0.23
¾ & Full Lite	U = 0.32	U = 0.28

If criteria are variable by percent of glazing, we request the ½-lite values be adjusted to reflect the same glazing required by the full lite values (see Table 1). Simulations have demonstrated that the glazing required attaining a 0.32 U-factor in a full lite door will result in a 0.27 U-factor in a ½-lite door of identical construction and glazing.




Figure 1




Figure 2

We acknowledge that there is great opportunity for improvements in efficiencies with opaque door units. Opaque entry doors constitute a large percentage of the market. Therefore, we believe a more aggressive value for Phase 1 would better differentiate energy efficient products. Of the 463 opaque door records (VT ≤ 0.00001) in the NFRC database, 237 of them already perform at 0.18 or better (Fig 1 and Fig 2). We believe this would be an appropriate value that is achievable with current technologies.

We discourage the implementation of maximum SHGC. Lower U-factor requirements and the elimination of climate zones greatly reduce the importance of SHGC limitations. By their nature, products with low U-factors will also have low SHGC. The attempted "balance" is unnecessary. We continue to request that the interval between program criteria changes be at least four (4) years and would support a Phase 2 effective date 4 years after the Phase 1 effective date.

As a member of the Association of Millwork Distributors, we appreciated the EnergyStar Program and look forward to partnering with you in future efforts to promote safe, affordable, energy efficient millwork products.

Name: Joe Bayer Company: Bayer Built Woodworks  
 Address: 24614 Hwy 71, Belgrade, MN 56312  
 Email: jbba@bayerbuilt.com

# Subject: ENERGY STAR® criteria revisions

Thank you for allowing us the opportunity to provide input regarding the upcoming ENERGY STAR revisions. We would like to submit the following comments for your consideration concerning the proposed draft side-hinged door criteria and analysis published on August 6, 2008:

We support separate criteria for glazed and opaque doors. However, we believe that any differentiation based on the quantity of glazing is not in the best interest of the homeowner. These values could persuade a consumer to purchase a lesser performing product (3/4-lite) over a higher performing product (1/2-lite) simply because it is ENERGY STAR qualified. This would result in less energy savings, not more.

Door Type	Phase 1	Phase 2
Opaque	U = 0.18	U = 0.16
¼ & ½ Lite	U = 0.27	U = 0.23
¾ & Full Lite	U = 0.32	U = 0.28

If criteria are variable by percent of glazing, we request the ½-lite values be adjusted to reflect the same glazing required by the full lite value (see Table 1). Simulations have demonstrated that the glazing required to attain a 0.32 U-factor in a full lite door will result in a 0.27 U-factor in a ½-lite door of identical construction and glazing.

We acknowledge that there is great opportunity for improvements in efficiencies with opaque door units. Opaque entry doors constitute a large percentage of the market. Therefore, we believe a more aggressive value for Phase 1 would better differentiate energy efficient products. Of the 463 opaque door records ( $VT \leq 0.00001$ ) in the NFR database, 237 of them already perform at 0.18 or better (Fig 1 and Fig 2). We believe this would be an appropriate value that is achievable with current technologies.

We discourage the implementation of maximum SHGC. Lower U-factor requirements and the elimination of climate zones greatly reduce the importance of SHGC limitations. By their nature, products with low U-factors will also have low SHGC. The attempted "balance" is unnecessary. We continue to request that the interval between program criteria changes be at least four (4) years and would support a Phase 2 effective date 4 years after the Phase 1 effective date.

As a member of the Association of Millwork Distributors, we appreciated the EnergyStar Program and look forward to partnering with you in future efforts to promote safe, affordable, energy efficient millwork products.

Opaque Doors in NFR Database by Core




Figure 1

Opaque Doors in NFR Database U ≤ 0.18




Figure 2

Name: Jon Bayer

Company: Bayer Built Woodworks, Inc

Address: 24614 Hwy 71 Belgrade, MW 56312

Email: bayerjonathan@hotmail.com

**Subject: ENERGY STAR® criteria revisions**

Thank you for allowing us the opportunity to provide input regarding the upcoming ENERGY STAR revisions. We would like to submit the following comments for your consideration concerning the proposed draft side-hinged door criteria and analysis published on August 6, 2008:

We support separate criteria for glazed and opaque doors. However, we believe that any differentiation based on the quantity of glazing is not in the best interest of the homeowner. These values could persuade a consumer to purchase a lesser performing product (3/4-lite) over a higher performing product (1/2-lite) simply because it is ENERGY STAR qualified. This would result in less energy savings, not more.

Door Type	Phase 1	Phase 2
Opaque	U = 0.18	U = 0.16
¼ & ½ Lite	U = 0.27	U = 0.23
¾ & Full Lite	U = 0.32	U = 0.28

If criteria are variable by percent of glazing, we request the ½-lite values be adjusted to reflect the same glazing required by the full lite values (see Table 1). Simulations have demonstrated that the glazing required attaining a 0.32 U-factor in a full lite door will result in a 0.27 U-factor in a ½-lite door of identical construction and glazing.




Figure 1




Figure 2

We acknowledge that there is great opportunity for improvements in efficiencies with opaque door units. Opaque entry doors constitute a large percentage of the market. Therefore, we believe a more aggressive value for Phase 1 would better differentiate energy efficient products. Of the 463 opaque door records (VT ≤ 0.00001) in the NFRC database, 237 of them already perform at 0.18 or better (Fig 1 and Fig 2). We believe this would be an appropriate value that is achievable with current technologies.

We discourage the implementation of maximum SHGC. Lower U-factor requirements and the elimination of climate zones greatly reduce the importance of SHGC limitations. By their nature, products with low U-factors will also have low SHGC. The attempted "balance" is unnecessary. We continue to request that the interval between program criteria changes be at least four (4) years and would support a Phase 2 effective date 4 years after the Phase 1 effective date.

As a member of the Association of Millwork Distributors, we appreciated the EnergyStar Program and look forward to partnering with you in future efforts to promote safe, affordable, energy efficient millwork products.

Name: Bruce Proctor Company: ENDORA PRODUCTS

Address: 8817 W. MARKET ST COLFAX NC 27235

Email: bruce@endoraproducts.com

**Subject: ENERGY STAR® criteria revisions**

Thank you for allowing us the opportunity to provide input regarding the upcoming ENERGY STAR revisions. We would like to submit the following comments for your consideration concerning the proposed draft side-hinged door criteria and analysis published on August 6, 2008:

We support separate criteria for glazed and opaque doors. However, we believe that any differentiation based on the quantity of glazing is not in the best interest of the homeowner. These values could persuade a consumer to purchase a lesser performing product (3/4-lite) over a higher performing product (1/2-lite) simply because it is ENERGY STAR qualified. This would result in less energy savings, not more.

Door Type	Phase 1	Phase 2
Opaque	U = 0.18	U = 0.16
¼ & ½ Lite	U = 0.27	U = 0.23
¾ & Full Lite	U = 0.32	U = 0.28

If criteria are variable by percent of glazing, we request the ½-lite values be adjusted to reflect the same glazing required by the full lite values (see Table 1). Simulations have demonstrated that the glazing required attaining a 0.32 U-factor in a full lite door will result in a 0.27 U-factor in a ½-lite door of identical construction and glazing.




Figure 1




Figure 2

We acknowledge that there is great opportunity for improvements in efficiencies with opaque door units. Opaque entry doors constitute a large percentage of the market. Therefore, we believe a more aggressive value for Phase 1 would better differentiate energy efficient products. Of the 463 opaque door records (VT ≤ 0.00001) in the NFRC database, 237 of them already perform at 0.18 or better (Fig 1 and Fig 2). We believe this would be an appropriate value that is achievable with current technologies.

We discourage the implementation of maximum SHGC. Lower U-factor requirements and the elimination of climate zones greatly reduce the importance of SHGC limitations. By their nature, products with low U-factors will also have low SHGC. The attempted "balance" is unnecessary. We continue to request that the interval between program criteria changes be at least four (4) years and would support a Phase 2 effective date 4 years after the Phase 1 effective date.

As a member of the Association of Millwork Distributors, we appreciated the EnergyStar Program and look forward to partnering with you in future efforts to promote safe, affordable, energy efficient millwork products.

Name: JOAN EGGLETON Company: ENDURA PRODUCTS

Address: 8817 W MARKET ST COLFAX, NC 27235

Email: joane@enduraproducts.com

# Subject: ENERGY STAR® criteria revisions

Thank you for allowing us the opportunity to provide input regarding the upcoming ENERGY STAR revisions. We would like to submit the following comments for your consideration concerning the proposed draft side-hinged door criteria and analysis published on August 6, 2008:

We support separate criteria for glazed and opaque doors. However, we believe that any differentiation based on the quantity of glazing is not in the best interest of the homeowner. These values could persuade a consumer to purchase a lesser performing product (3/4-lite) over a higher performing product (1/2-lite) simply because it is ENERGY STAR qualified. This would result in less energy savings, not more.

If criteria are variable by percent of glazing, we request the 1/2-lite values be adjusted to reflect the same glazing required by the full lite values (see Table 1). Simulations have demonstrated that the glazing required to attain a 0.32 U-factor in a full lite door will result in a 0.27 U-factor in a 1/2-lite door of identical construction and glazing.

We acknowledge that there is great opportunity for improvements in efficiencies with opaque door units. Opaque entry doors constitute a large percentage of the market. Therefore, we believe a more aggressive value for Phase 1 would better differentiate energy efficient products. Of the 463 opaque door records ( $VT \leq 0.00001$ ) in the NFRC database, 237 of them already perform at 0.18 or better (Fig 1 and Fig 2). We believe this would be an appropriate value that is achievable with current technologies.

We discourage the implementation of maximum SHGC. Lower U-factor requirements and the elimination of climate zones greatly reduce the importance of SHGC limitations. By their nature, products with low U-factors will also have low SHGC. The attempted "balance" is unnecessary. We continue to request that the interval between program criteria changes be at least four (4) years and would support a Phase 2 effective date 4 years after the Phase 1 effective date.

As a member of the Association of Millwork Distributors, we appreciated the EnergyStar Program and look forward to partnering with you in future efforts to promote safe, affordable, energy efficient millwork products.

Door Type	Phase 1	Phase 2
Opaque	U = 0.18	U = 0.16
1/4 & 1/2 Lite	U = 0.27	U = 0.23
3/4 & Full Lite	U = 0.32	U = 0.28

Opaque Doors in NFRC Database by Core




Figure 1

Opaque Doors in NFRC Database U ≤ 0.18




Figure 2

Name: DANIEL WARREN

Company: WARREN WINDOW & SUPPLY

Address: 1051 CONCOURSE DR. Rapid City SD 57703

Email: dgw.wws@midconetwork.com



**Subject: ENERGY STAR® criteria revisions**

Thank you for allowing us the opportunity to provide input regarding the upcoming ENERGY STAR revisions. We would like to submit the following comments for your consideration concerning the proposed draft side-hinged door criteria and analysis published on August 6, 2008:

We support separate criteria for glazed and opaque doors. However, we believe that any differentiation based on the quantity of glazing is not in the best interest of the homeowner. These values could persuade a consumer to purchase a lesser performing product (3/4-lite) over a higher performing product (1/2-lite) simply because it is ENERGY STAR qualified. This would result in less energy savings, not more.

Door Type	Phase 1	Phase 2
Opaque	U = 0.18	U = 0.16
¼ & ½ Lite	U = 0.27	U = 0.23
¾ & Full Lite	U = 0.32	U = 0.28

If criteria are variable by percent of glazing, we request the ½-lite values be adjusted to reflect the same glazing required by the full lite values (see Table 1). Simulations have demonstrated that the glazing required attaining a 0.32 U-factor in a full lite door will result in a 0.27 U-factor in a ½-lite door of identical construction and glazing.




Figure 1




Figure 2

We acknowledge that there is great opportunity for improvements in efficiencies with opaque door units. Opaque entry doors constitute a large percentage of the market. Therefore, we believe a more aggressive value for Phase 1 would better differentiate energy efficient products. Of the 463 opaque door records ( $VT \leq 0.00001$ ) in the NFRC database, 237 of them already perform at 0.18 or better (Fig 1 and Fig 2). We believe this would be an appropriate value that is achievable with current technologies.

We discourage the implementation of maximum SHGC. Lower U-factor requirements and the elimination of climate zones greatly reduce the importance of SHGC limitations. By their nature, products with low U-factors will also have low SHGC. The attempted "balance" is unnecessary. We continue to request that the interval between program criteria changes be at least four (4) years and would support a Phase 2 effective date 4 years after the Phase 1 effective date.

As a member of the Association of Millwork Distributors, we appreciated the EnergyStar Program and look forward to partnering with you in future efforts to promote safe, affordable, energy efficient millwork products.

Name: *John* Company: *Millwork Distributors Inc*

Address: *6361 STERLING DR. N. STERLING HEIGHTS, MI 48012*

Email: \_\_\_\_\_

**Subject: ENERGY STAR® criteria revisions**

Thank you for allowing us the opportunity to provide input regarding the upcoming ENERGY STAR revisions. We would like to submit the following comments for your consideration concerning the proposed draft side-hinged door criteria and analysis published on August 6, 2008:

We support separate criteria for glazed and opaque doors. However, we believe that any differentiation based on the quantity of glazing is not in the best interest of the homeowner. These values could persuade a consumer to purchase a lesser performing product (3/4-lite) over a higher performing product (1/2-lite) simply because it is ENERGY STAR qualified. This would result in less energy savings, not more.

Door Type	Phase 1	Phase 2
Opaque	U = 0.18	U = 0.16
¼ & ½ Lite	U = 0.27	U = 0.23
¾ & Full Lite	U = 0.32	U = 0.28

If criteria are variable by percent of glazing, we request the ½-lite values be adjusted to reflect the same glazing required by the full lite values (see Table 1). Simulations have demonstrated that the glazing required attaining a 0.32 U-factor in a full lite door will result in a 0.27 U-factor in a ½-lite door of identical construction and glazing.




Figure 1




Figure 2

We acknowledge that there is great opportunity for improvements in efficiencies with opaque door units. Opaque entry doors constitute a large percentage of the market. Therefore, we believe a more aggressive value for Phase 1 would better differentiate energy efficient products. Of the 463 opaque door records (VT ≤ 0.00001) in the NFRC database, 237 of them already perform at 0.18 or better (Fig 1 and Fig 2). We believe this would be an appropriate value that is achievable with current technologies.

We discourage the implementation of maximum SHGC. Lower U-factor requirements and the elimination of climate zones greatly reduce the importance of SHGC limitations. By their nature, products with low U-factors will also have low SHGC. The attempted "balance" is unnecessary. We continue to request that the interval between program criteria changes be at least four (4) years and would support a Phase 2 effective date 4 years after the Phase 1 effective date.

As a member of the Association of Millwork Distributors, we appreciated the EnergyStar Program and look forward to partnering with you in future efforts to promote safe, affordable, energy efficient millwork products.

Name: FECHT, PETE Company: GENERATION 4

Address: 1604 Regan Road, Rock Falls, IL 61071

Email: PETE@GENERATION4SALES.COM

## Subject: ENERGY STAR® criteria revisions

Thank you for allowing us the opportunity to provide input regarding the upcoming ENERGY STAR revisions. We would like to submit the following comments for your consideration concerning the proposed draft side-hinged door criteria and analysis published on August 6, 2008:

We support separate criteria for glazed and opaque doors. However, we believe that any differentiation based on the quantity of glazing is not in the best interest of the homeowner. These values could persuade a consumer to purchase a lesser performing product (3/4-lite) over a higher performing product (1/2-lite) simply because it is ENERGY STAR qualified. This would result in less energy savings, not more.

Door Type	Phase 1	Phase 2
Opaque	U = 0.18	U = 0.16
¼ & ½ Lite	U = 0.27	U = 0.23
¾ & Full Lite	U = 0.32	U = 0.28

If criteria are variable by percent of glazing, we request the ½-lite values be adjusted to reflect the same glazing required by the full lite values (see Table 1). Simulations have demonstrated that the glazing required attaining a 0.32 U-factor in a full lite door will result in a 0.27 U-factor in a ½-lite door of identical construction and glazing.




Figure 1




Figure 2

We acknowledge that there is great opportunity for improvements in efficiencies with opaque door units. Opaque entry doors constitute a large percentage of the market. Therefore, we believe a more aggressive value for Phase 1 would better differentiate energy efficient products. Of the 463 opaque door records (VT ≤ 0.00001) in the NFRC database, 237 of them already perform at 0.18 or better (Fig 1 and Fig 2). We believe this would be an appropriate value that is achievable with current technologies.

We discourage the implementation of maximum SHGC. Lower U-factor requirements and the elimination of climate zones greatly reduce the importance of SHGC limitations. By their nature, products with low U-factors will also have low SHGC. The attempted "balance" is unnecessary. We continue to request that the interval between program criteria changes be at least four (4) years and would support a Phase 2 effective date 4 years after the Phase 1 effective date.

As a member of the Association of Millwork Distributors, we appreciated the EnergyStar Program and look forward to partnering with you in future efforts to promote safe, affordable, energy efficient millwork products.

Name: CHRIS JORDAN Company: JORDAN MARKETING

Address: 113 WEST END AVE SUMMIT NJ 07901

Email: JUICJORDAN@AOL.COM

**Subject: ENERGY STAR® criteria revisions**

Thank you for allowing us the opportunity to provide input regarding the upcoming ENERGY STAR revisions. We would like to submit the following comments for your consideration concerning the proposed draft side-hinged door criteria and analysis published on August 6, 2008:

We support separate criteria for glazed and opaque doors. However, we believe that any differentiation based on the quantity of glazing is not in the best interest of the homeowner. These values could persuade a consumer to purchase a lesser performing product (3/4-lite) over a higher performing product (1/2-lite) simply because it is ENERGY STAR qualified. This would result in less energy savings, not more.

Door Type	Phase 1	Phase 2
Opaque	U = 0.18	U = 0.16
¼ & ½ Lite	U = 0.27	U = 0.23
¾ & Full Lite	U = 0.32	U = 0.28

If criteria are variable by percent of glazing, we request the ½-lite values be adjusted to reflect the same glazing required by the full lite values (see Table 1). Simulations have demonstrated that the glazing required attaining a 0.32 U-factor in a full lite door will result in a 0.27 U-factor in a ½-lite door of identical construction and glazing.




Figure 1




Figure 2

We acknowledge that there is great opportunity for improvements in efficiencies with opaque door units. Opaque entry doors constitute a large percentage of the market. Therefore, we believe a more aggressive value for Phase 1 would better differentiate energy efficient products. Of the 463 opaque door records ( $VT \leq 0.00001$ ) in the NFRC database, 237 of them already perform at 0.18 or better (Fig 1 and Fig 2). We believe this would be an appropriate value that is achievable with current technologies.

We discourage the implementation of maximum SHGC. Lower U-factor requirements and the elimination of climate zones greatly reduce the importance of SHGC limitations. By their nature, products with low U-factors will also have low SHGC. The attempted "balance" is unnecessary. We continue to request that the interval between program criteria changes be at least four (4) years and would support a Phase 2 effective date 4 years after the Phase 1 effective date.

As a member of the Association of Millwork Distributors, we appreciated the EnergyStar Program and look forward to partnering with you in future efforts to promote safe, affordable, energy efficient millwork products.

Name: Rich Horvath Company: Carpenter Concepts

Address: 514 Northshore DRWE, Southport NC 28461

Email: \_\_\_\_\_

**Subject: ENERGY STAR® criteria revisions**

Thank you for allowing us the opportunity to provide input regarding the upcoming ENERGY STAR revisions. We would like to submit the following comments for your consideration concerning the proposed draft side-hinged door criteria and analysis published on August 6, 2008:

We support separate criteria for glazed and opaque doors. However, we believe that any differentiation based on the quantity of glazing is not in the best interest of the homeowner. These values could persuade a consumer to purchase a lesser performing product (3/4-lite) over a higher performing product (1/2-lite) simply because it is ENERGY STAR qualified. This would result in less energy savings, not more.

Door Type	Phase 1	Phase 2
Opaque	U = 0.18	U = 0.16
¼ & ½ Lite	U = 0.27	U = 0.23
¾ & Full Lite	U = 0.32	U = 0.28

If criteria are variable by percent of glazing, we request the ½-lite values be adjusted to reflect the same glazing required by the full lite values (see Table 1). Simulations have demonstrated that the glazing required attaining a 0.32 U-factor in a full lite door will result in a 0.27 U-factor in a ½-lite door of identical construction and glazing.




Figure 1




Figure 2

We acknowledge that there is great opportunity for improvements in efficiencies with opaque door units. Opaque entry doors constitute a large percentage of the market. Therefore, we believe a more aggressive value for Phase 1 would better differentiate energy efficient products. Of the 463 opaque door records (VT ≤ 0.00001) in the NFRC database, 237 of them already perform at 0.18 or better (Fig 1 and Fig 2). We believe this would be an appropriate value that is achievable with current technologies.

We discourage the implementation of maximum SHGC. Lower U-factor requirements and the elimination of climate zones greatly reduce the importance of SHGC limitations. By their nature, products with low U-factors will also have low SHGC. The attempted “balance” is unnecessary. We continue to request that the interval between program criteria changes be at least four (4) years and would support a Phase 2 effective date 4 years after the Phase 1 effective date.

As a member of the Association of Millwork Distributors, we appreciated the EnergyStar Program and look forward to partnering with you in future efforts to promote safe, affordable, energy efficient millwork products.

Name: Richard Shupe Sr Company: Carpentry Concepts  
 Address: 9317 Long Path Ct, Wilmington NC 28412  
 Email: [Signature]

## Subject: ENERGY STAR® criteria revisions

Thank you for allowing us the opportunity to provide input regarding the upcoming ENERGY STAR revisions. We would like to submit the following comments for your consideration concerning the proposed draft side-hinged door criteria and analysis published on August 6, 2008:

We support separate criteria for glazed and opaque doors. However, we believe that any differentiation based on the quantity of glazing is not in the best interest of the homeowner. These values could persuade a consumer to purchase a lesser performing product (3/4-lite) over a higher performing product (1/2-lite) simply because it is ENERGY STAR qualified. This would result in less energy savings, not more.

Door Type	Phase 1	Phase 2
Opaque	U = 0.18	U = 0.16
¼ & ½ Lite	U = 0.27	U = 0.23
¾ & Full Lite	U = 0.32	U = 0.28

If criteria are variable by percent of glazing, we request the ½-lite values be adjusted to reflect the same glazing required by the full lite values (see Table 1). Simulations have demonstrated that the glazing required attaining a 0.32 U-factor in a full lite door will result in a 0.27 U-factor in a ½-lite door of identical construction and glazing.




Figure 1




Figure 2

We acknowledge that there is great opportunity for improvements in efficiencies with opaque door units. Opaque entry doors constitute a large percentage of the market. Therefore, we believe a more aggressive value for Phase 1 would better differentiate energy efficient products. Of the 463 opaque door records (VT ≤ 0.00001) in the NFRC database, 237 of them already perform at 0.18 or better (Fig 1 and Fig 2). We believe this would be an appropriate value that is achievable with current technologies.

We discourage the implementation of maximum SHGC. Lower U-factor requirements and the elimination of climate zones greatly reduce the importance of SHGC limitations. By their nature, products with low U-factors will also have low SHGC. The attempted "balance" is unnecessary. We continue to request that the interval between program criteria changes be at least four (4) years and would support a Phase 2 effective date 4 years after the Phase 1 effective date.

As a member of the Association of Millwork Distributors, we appreciated the EnergyStar Program and look forward to partnering with you in future efforts to promote safe, affordable, energy efficient millwork products.

Name: John Brown Company: Krosswood Doors  
 Address: 2064 W. Alexander St STE E, SLC, UT 84119  
 Email: jbrown@krosswood.com

## Subject: ENERGY STAR® criteria revisions

Thank you for allowing us the opportunity to provide input regarding the upcoming ENERGY STAR revisions. We would like to submit the following comments for your consideration concerning the proposed draft side-hinged door criteria and analysis published on August 6, 2008:

We support separate criteria for glazed and opaque doors. However, we believe that any differentiation based on the quantity of glazing is not in the best interest of the homeowner. These values could persuade a consumer to purchase a lesser performing product (3/4-lite) over a higher performing product (1/2-lite) simply because it is ENERGY STAR qualified. This would result in less energy savings, not more.

Door Type	Phase 1	Phase 2
Opaque	U = 0.18	U = 0.16
¼ & ½ Lite	U = 0.27	U = 0.23
¾ & Full Lite	U = 0.32	U = 0.28

If criteria are variable by percent of glazing, we request the ½-lite values be adjusted to reflect the same glazing required by the full lite values (see Table 1). Simulations have demonstrated that the glazing required attaining a 0.32 U-factor in a full lite door will result in a 0.27 U-factor in a ½-lite door of identical construction and glazing.




Figure 1




Figure 2

We acknowledge that there is great opportunity for improvements in efficiencies with opaque door units. Opaque entry doors constitute a large percentage of the market. Therefore, we believe a more aggressive value for Phase 1 would better differentiate energy efficient products. Of the 463 opaque door records (VT ≤ 0.00001) in the NFRC database, 237 of them already perform at 0.18 or better (Fig 1 and Fig 2). We believe this would be an appropriate value that is achievable with current technologies.

We discourage the implementation of maximum SHGC. Lower U-factor requirements and the elimination of climate zones greatly reduce the importance of SHGC limitations. By their nature, products with low U-factors will also have low SHGC. The attempted "balance" is unnecessary. We continue to request that the interval between program criteria changes be at least four (4) years and would support a Phase 2 effective date 4 years after the Phase 1 effective date.

As a member of the Association of Millwork Distributors, we appreciated the EnergyStar Program and look forward to partnering with you in future efforts to promote safe, affordable, energy efficient millwork products.

Name: Jason Olding Company: Krosswood Doors  
 Address: 2064 W Alexander St Suite E  
 Email: jason@krosswood.com

## Subject: ENERGY STAR® criteria revisions

Thank you for allowing us the opportunity to provide input regarding the upcoming ENERGY STAR revisions. We would like to submit the following comments for your consideration concerning the proposed draft side-hinged door criteria and analysis published on August 6, 2008:

We support separate criteria for glazed and opaque doors. However, we believe that any differentiation based on the quantity of glazing is not in the best interest of the homeowner. These values could persuade a consumer to purchase a lesser performing product (3/4-lite) over a higher performing product (1/2-lite) simply because it is ENERGY STAR qualified. This would result in less energy savings, not more.

Door Type	Phase 1	Phase 2
Opaque	U = 0.18	U = 0.16
¼ & ½ Lite	U = 0.27	U = 0.23
¾ & Full Lite	U = 0.32	U = 0.28

If criteria are variable by percent of glazing, we request the ½-lite values be adjusted to reflect the same glazing required by the full lite values (see Table 1). Simulations have demonstrated that the glazing required attaining a 0.32 U-factor in a full lite door will result in a 0.27 U-factor in a ½-lite door of identical construction and glazing.




Figure 1




Figure 2

We acknowledge that there is great opportunity for improvements in efficiencies with opaque door units. Opaque entry doors constitute a large percentage of the market. Therefore, we believe a more aggressive value for Phase 1 would better differentiate energy efficient products. Of the 463 opaque door records (VT ≤ 0.0001) in the NFRC database, 237 of them already perform at 0.18 or better (Fig 1 and Fig 2). We believe this would be an appropriate value that is achievable with current technologies.

We discourage the implementation of maximum SHGC. Lower U-factor requirements and the elimination of climate zones greatly reduce the importance of SHGC limitations. By their nature, products with low U-factors will also have low SHGC. The attempted "balance" is unnecessary. We continue to request that the interval between program criteria changes be at least four (4) years and would support a Phase 2 effective date 4 years after the Phase 1 effective date.

As a member of the Association of Millwork Distributors, we appreciated the EnergyStar Program and look forward to partnering with you in future efforts to promote safe, affordable, energy efficient millwork products.

Name: Steve Branlund Company: Branlund Sales + Marketing  
 Address: 1658 East Cliff Lake Rd. Burnsville MN 55337  
 Email: branlundsales@aol.com