

**Appendix G**

Deramus Field Station Sampling Data

Master										10 mesh (%)	20 mesh (%)	40 mesh (%)	100 mesh (%)	140 mesh (%)	200 mesh (%)	Pan (%)										
Phase	Number of Passes	Percent Moisture	Soil	Vehicle	Type of Test	Distance From Access	Area sampled (ft <sup>2</sup> )	Tare Weight (g)	Final Weight (g)	Difference (g)	Empty Bag mass (g)	Nonrecoverable mass (g)	Total loading (g/m <sup>2</sup> )	f	s <sub>lower</sub>	s <sub>upper</sub>	silt content									
1	100	4.2	4.9	4.5 native	pickup	10	250	59.9	177.3	117.4	62.5	2.6	1.54	0.15	0.23	0.26	0.17	30.4	14.1	11.6	19.6	4.6	4.6	15.0		
2	100	4.2	4.9	4.5 native	pickup	50	250	99.01	62.5	61.8	61.8	0.3	0.20	0.14	0.03	0.03	0.16	12.9	19.4	23.0	18.7	8.6	2.9	14.4		
3	100	4.2	4.9	4.5 native	pickup	90	250	99.04	103.6	43.2	61.4	1.0	0.57	0.09	0.05	0.06	0.11	44.0	19.3	14.4	11.0	1.5	1.2	8.6		
4	100	4.2	4.9	4.5 native	pickup	130	250	99.04	62.0	77.8	61.4	0.7	0.21	0.08	0.02	0.02	0.12	20.0	28.6	25.0	12.9	3.6	2.1	7.9		
5	100	14.31	0.4	7.2	6.0	9.4 native	pickup	50	250	99.06	62.4	3.2	1.27	0.05	0.11	0.16	0.07	34.3	20.9	21.2	13.3	3.6	1.2	5.1		
6	100	14.31	0.4	7.2	6.0	9.4 native	pickup	50	250	99.06	61.9	1.7	1.32	0.08	0.11	0.13	0.10	22.3	19.6	21.2	13.3	2.8	2.7	8.1		
7	50	25	0.18	9.20	4	21.4 native	pickup	63.3	99.07	61.4	398.5	1.9	4.40	0.08	0.33	0.35	0.08	9.2	20.0	30.5	26.4	4.4	1.9	7.5		
8	50	25	0.18	9.20	4	21.4 native	pickup	63.3	99.07	61.4	398.5	1.9	4.40	0.08	0.33	0.35	0.08	9.2	20.0	30.5	26.4	4.4	1.9	7.5		
9	50	25	0.18	9.20	4	21.4 native	pickup	63.3	99.09	61.3	449.0	2.6	6.40	0.09	0.58	0.61	0.10	16.9	22.9	23.9	19.7	5.3	2.2	9.1		
10	50	25	0.18	9.20	4	21.4 native	pickup	63.3	99.10	61.2	487.7	3.1	7.88	0.05	0.39	0.40	0.05	17.5	27.4	25.2	21.4	1.9	1.6	4.9		
11	50	23	824.6	24.1 native	pickup	50	250	99.11	1103.9	1041.7	62.6	1.4	13.67	0.06	0.88	0.80	0.07	37.2	26.7	14.7	11.9	1.7	1.7	6.4		
12	50	23	824.6	24.1 native	pickup	50	250	99.12	975.2	917.0	68.9	3.6	12.03	0.08	0.93	0.97	0.08	50.6	17.6	11.7	7.6	3.4	1.3	7.7		
13	50	6.1	5.1	5.2	5.5 sandy	pickup	45	250	99.13	188.6	62.7	2.6	2.46	0.17	0.45	0.44	0.18	16.5	19.9	20.2	20.2	3.0	3.0	17.2		
14	50	8.8	8.3	6.6	12.1 sandy	pickup	5	250	99.14	60.9	580.0	519.1	2.6	6.81	0.10	0.69	0.72	0.11	20.0	24.2	27.6	12.6	4.0	1.4	10.1	
15	50	17	81.7	17.9 sandy	pickup	5	250	99.15	60.0	368.6	306.6	61.7	1.7	4.02	0.13	0.52	0.54	0.13	21.2	25.0	23.2	14.5	1.6	1.7	12.9	
16	50	17	81.7	17.9 sandy	pickup	5	250	99.16	61.1	620.7	589.6	64.2	3.1	7.34	0.12	0.90	0.93	0.13	25.0	22.5	23.1	12.1	3.6	1.6	12.2	
17	50	11	110.0	7.2	9.4 sandy	pickup	25	250	99.17	60.5	419.3	62.2	3.0	4.73	0.20	0.96	0.99	0.21	13.7	20.7	25.1	14.9	2.8	2.0	20.4	
18	50	17	4.12	11.4	14.5 native	pickup	25	250	99.18	60.5	197.9	137.4	1.1	1.80	0.25	0.44	0.45	0.25	13.9	21.6	20.9	15.2	1.7	2.1	24.5	
19	50	17	4.12	11.4	14.5 native	pickup	25	250	99.19	60.9	771.8	710.9	64.4	3.5	9.93	0.16	1.48	1.52	0.16	26.1	19.9	16.3	15.7	3.4	2.8	15.9
20	50	17	4.12	11.4	14.5 native	pickup	25	250	99.20	60.3	272.2	211.9	61.9	1.6	2.78	0.17	0.88	0.50	0.18	20.0	20.8	15.9	19.0	3.3	3.7	17.2
21	50	19	4.19	5.19	19.3 sandy	pickup	5	250	99.21	60.9	365.7	304.8	64.9	3.6	4.00	0.21	0.83	0.87	0.22	17.9	18.5	23.0	14.9	2.9	2.1	20.8
22	50	19	4.19	5.19	19.3 sandy	pickup	5	250	99.22	61.2	237.3	176.1	63.4	2.2	2.31	0.27	0.63	0.66	0.28	10.1	17.9	22.3	17.6	2.1	2.4	27.4
23	50	24	225.7	25.0 native	pickup	25	250	99.23	62.3	1321.1	1258.8	67.2	4.9	16.52	0.08	1.40	1.46	0.09	26.8	23.9	18.6	16.2	3.5	2.5	8.5	
24	50	24	225.7	25.0 native	pickup	25	250	99.24	62.2	936.6	874.4	66.7	4.5	11.48	0.06	0.71	0.76	0.07	48.8	20.4	10.8	10.0	2.0	1.8	6.2	
25	50	17	0.18	7.14	16.7 sandy	pickup	25	250	99.25	59.5	338.5	279.0	61.2	1.7	3.66	0.22	0.81	0.83	0.23	18.7	20.5	20.2	13.8	2.6	2.2	22.1
26	50	17	0.18	7.14	16.7 sandy	pickup	25	250	99.26	57.7	225.0	167.3	59.2	1.3	2.20	0.20	0.43	0.45	0.20	18.5	23.7	20.1	14.5	1.8	1.8	19.7
27	50	15	724.5	20.1 native	pickup	25	250	99.27	58.0	770.0	712.0	60.6	2.6	9.34	0.17	1.56	1.59	0.17	15.6	24.0	19.3	17.6	3.8	3.1	16.7	
28	50	15	724.5	20.1 native	pickup	25	250	99.28	57.9	560.1	502.2	61.2	3.3	6.59	0.15	0.97	1.01	0.15	24.2	24.6	16.2	15.2	2.5	2.6	14.7	
29	50	19	317.4	18.4 sandy	pickup	25	250	99.29	54.9	174.7	119.8	55.9	1.0	1.57	0.21	0.32	0.33	0.21	12.5	22.2	22.9	16.0	3.7	2.3	20.5	
30	50	19	317.4	18.4 sandy	pickup	25	250	99.30	55.0	153.7	98.7	55.6	0.6	1.30	0.18	0.24	0.24	0.19	14.9	22.1	23.1	17.7	2.0	2.0	18.3	
31	50	16	822.6	19.7 native	pickup	45	250	99.31	55.3	693.7	644.4	59.1	3.8	8.46	0.10	0.82	0.87	0.10	42.8	20.2	12.8	10.6	2.1	1.7	9.7	
32	50	16	822.6	19.7 native	pickup	45	250	99.32	55.6	693.9	638.1	58.4	2.8	8.37	0.11	0.91	0.94	0.11	39.4	22.5	12.1	11.2	1.9	2.0	10.8	
33	50	22	818.2	20.5 sandy	pickup	25	250	99.33	55.6	1068.4	1012.8	58.4	2.8	13.29	0.12	1.59	1.62	0.12	26.1	23.5	16.2	16.6	2.8	2.8	12.0	
34	50	22	818.2	20.5 sandy	pickup	25	250	99.34	55.7	221.2	165.5	58.3	2.6	2.17	0.22	0.47	0.50	0.23	18.3	20.5	20.4	13.6	3.2	2.1	21.8	
35	50	31	216.3	23.8 native	pickup	25	250	99.35	55.7	198.5	142.8	57.4	1.7	1.87	0.17	0.34	0.34	0.18	27.4	20.7	19.2	10.6	3.6	1.5	16.9	
36	50	31	216.3	23.8 native	pickup	25	250	99.36	55.6	578.6	523.0	60.3	4.7	6.86	0.22	1.53	1.57	0.23	19.1	20.2	16.4	15.6	3.4	3.0	22.2	
37	50	19	219.1	19.2 sandy	pickup	25	250	99.37	55.5	381.7	326.2	59.6	4.1	4.28	0.19	0.80	0.85	0.20	22.9	22.8	14.9	15.1	2.6	2.9	18.8	
38	50	19	219.1	19.2 sandy	pickup	25	250	99.38	59.9	439.8	380.9	63.9	4.1	5.00	0.09	0.44	0.49	0.10	27.5	26.9	20.0	15.5	0.0	1.3	8.8	
39	50	35	629.4	32.5 native	pickup	25	250	99.39	57.9	329.3	271.4	59.5	2.2	6.21	0.13	0.47	0.49	0.14	27.6	21.8	19.9	13.1	2.5	1.7	13.3	
40	50	35	629.4	32.5 native	pickup	25	250	99.40	57.9	530.4	473.1	59.5	2.2	6.21	0.15	0.62	0.65	0.15	32.5	22.2	12.9	13.8	2.3	2.4	14.9	
41	50	35	629.4	32.5 native	pickup	25	250	99.41	57.9	368.3	310.6	59.6	1.9	4.08	0.15	0.61	0.63	0.15	34.3	21.9	12.1	13.8	1.1	1.9	14.9	
42	50	19	812.8	11.5	14.7 native	dump truck	5	250	99.42	57.8	1511.0	1453.2	61	3.2	19.07	0.21	4.09	4.12	0.22	24.2	16.8	15.7	15.4	3.5	3.0	21.4
43	50	21	812.8	11.5	14.7 native	dump truck	5	250	99.43	57.8	692.8	638.0	60.8	3.0	8.37	0.27	2.26	2.29	0.22	10.7	16.0	21.0	19.0	2.9	3.2	27.0
44	50	21	812.8	11.5	14.7 native	dump truck	5	250	99.44	55.6	1081.2	1025.6	59.3	3.7	13.46	0.22	2.66	3.00	0.22	22.9	19.4	14.6	15.3	3.1	2.7	20.0
45	50	15	26	111.2	17.6 sandy	pickup	5	250	99.45	58.3	925.4	869.5	59.9	3.1	11.41	0.30	3.38	3.41	0.30	14.1	17.6	19.8	14.1	2.5	2.3	29.6
46	50	24	21	2	22.0 native	pickup	5	250	99.46	58.3	341.2	285.9	59.2	2.9	3.75	0.17	0.85	0.88	0.18	18.8	16.9	24.7	27.9	2.2	2.1	17.2
47	50	14	412.1	13.3 sandy	pickup	5	250	99.47	58.2	513.5	462.9	59.2	3.6	6.07	0.30	1.90	1.93	0.30	13.2	17.0	15.5	17.5	3.7	3.4	29.7	
48																										

<b>TECHNICAL REPORT DATA</b> <i>(Please read instructions on the reverse before completing)</i>		
1. REPORT NO. EPA-600/R-01-031	2.	3. RECIPIENT'S ACCESSION NO.
4. TITLE AND SUBTITLE Particulate Emission Measurements from Controlled Construction Activities	5. REPORT DATE April 2001	6. PERFORMING ORGANIZATION CODE
	8. PERFORMING ORGANIZATION REPORT NO.	
7. AUTHORS Gregory F. Muleski and Chatten Cowherd, Jr.	10. PROGRAM ELEMENT NO.	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Midwest Research Institute 425 Volker Boulevard Kansas City, Missouri 64110-2299	11. CONTRACT/GRANT NO. 68-D7-0002, Work Assignment 2-04	
	13. TYPE OF REPORT AND PERIOD COVERED Final; 4/99 - 2/00	
12. SPONSORING AGENCY NAME AND ADDRESS EPA, Office of Research and Development Air Pollution Prevention and Control Division Research Triangle Park, NC 27711	14. SPONSORING AGENCY CODE EPA/600/13	
	15. SUPPLEMENTARY NOTES APPCD project officer C. C. Masser is no longer with the Agency. For details, contact John Kinsey, Mail Drop 61, 919/ 541-4121.	
16. ABSTRACT The report summarizes the results of field testing of the effectiveness of control measures for sources of fugitive particulate emissions found at construction sites. The effectiveness of watering temporary, unpaved travel surfaces on emissions of particulate matter with aerodynamic diameters of < 10 micrometers (PM-10) was tested in Beloit, Kansas, during September 1999. The tested operation was scraper transit. The effectiveness of paved and graveled access aprons on mud/dirt trackout from unpaved truck exit routes was tested in Grandview, Missouri, during November 1999. In the later tests, moisture content and soil type were varied to determine if watering of exit routes, while reducing on-site emissions, might offset the effect of increasing emissions attributable to in-place mud/dirt trackout controls.		
17. KEY WORDS AND DOCUMENT ANALYSIS		
a. DESCRIPTORS	b. IDENTIFIERS/OPEN ENDED TERMS	c. COSATI Field/Group
Pollution Emissions Particles Dust Control Construction Equipment Scrapers	Pollution Control Stationary Sources Fugitive Emissions Particulate Construction Sites Dirt Roads	13B 14G 05E 13C
18. DISTRIBUTION STATEMENT  Release to Public	19. SECURITY CLASS ( <i>This Report</i> ) Unclassified	21. NO. OF PAGES 176
	20. SECURITY CLASS ( <i>This Page</i> ) Unclassified	22. PRICE