

APPENDIX C
Shallow and Deep Groundwater
Monitoring Well Data Sheets

**Monitoring Well Sampling Log
Shumaker Site**

**Waterra Valve
Horiba U-22**

Well Number: SW-6 Date: 1/10/08

Well Depth: 29.9' to c

Water Level (from top): 3.95' to c

Screen Interval: 16.5 - 26.5 bgs

Sample ID Number: GW-S06 Sample Time: 1520 1550

Pump Rate: 650

Settings on Control Box: NOT APPLICABLE

Weather and field conditions: PARTLY CLOUDY, SLIGHT BREEZE, 60°F

Sampling Team: OREAR GUYER

Time	Flow Rate (ml/min)/Hz	Water Level (ft)	pH	Conductivity (mS/cm)	Turbidity (NTU)	DO (mg/l)	Temp °C	TDS	ORP (mv)
1454	650	4.02	5.06	5	170	1.3	16.9	0.03	228
1459		4.04	4.96	5	290	0.8	17.4	0.03	208
1503		4.02	4.97	6	910	1.0	17.7	0.04	204
1507		4.02	4.91	10	-5	2.1	17.8	0.07	211
1512		4.05	4.88	12	-5	2.9	17.9	0.08	219
1516		4.03	4.88	12	-5	2.9	17.9	0.08	221
1520		4.03	4.87	12	620	3.0	17.7	0.08	223
1524		4.05	4.87	12	500	3.0	17.8	0.08	225
1528		4.03	4.87	12	430	3.0	17.9	0.08	229
1532		4.03	4.87	12	320	3.0	17.8	0.08	231
1536		4.03	4.87	12	300	3.0	17.8	0.08	234
1540		4.03	4.87	12	250	3.0	17.7	0.08	237
1544		4.03	4.87	12	230	3.0	17.9	0.08	233
1548	↓	4.03	4.87	12	230	3.0	17.9	0.08	233

7

