Coast Guard, DOT § 92.01–5

(1) Has met the applicable requirements of the Convention; and,

(2) Is currently classed by the Bureau and classification requirements have been dealt with to the satisfaction of the Bureau

(c) When the Bureau determines that a vessel to which it has issued a Cargo Ship Safety Construction Certificate no longer complies with the Bureau's applicable requirements for classification, the Bureau shall immediately furnish to the Coast Guard all relevant information, which will be used by the Coast Guard to determine whether or not to withdraw, revoke or suspend the Cargo Ship Safety Construction Certificate.

[CGFR 65-50, 30 FR 16974, Dec. 30, 1965, as amended by CGD 90-008, 55 FR 30661, July 26, 1990; CGD 96-041, 61 FR 50729, Sept. 27, 1996; USCG-2000-7790, 65 FR 58461, Sept. 29, 2000]

PART 92—CONSTRUCTION AND ARRANGEMENT

Subpart 92.01—Hull Structure

Sec.

92.01-1 Application.

92.01-5 Vessels subject to load line.

92.01–10 Structural standards.

92.01-15 Special consideration.

92.01–90 Vessels contracted for prior to November 19, 1952.

Subpart 92.03—Navigation Bridge Visibility

92.03-1 Navigation bridge visibility.

Subpart 92.05—General Fire Protection

92.05–1 Fire hazards to be minimized.

92.05-5 Woodwork insulated from heated surfaces.

92.05-10 Lamp room construction.

92.05–15 Segregation of spaces containing the emergency source of electric power.

Subpart 92.07—Structural Fire Protection

92.07-1 Application.

92.07–5 Definitions.

92.07-10 Construction.

92.07-90 Vessels contracted for prior to July 1, 1968.

Subpart 92.10—Means of Escape

92.10-1 Application.

92.10–5 Two means required.

92.10-10 Location.

92.10-15 Vertical ladders not accepted.

92.10-20 No means for locking doors.

92.10-25 Stairway size.

92.10-30 Dead end corridors.

92.10-35 Public spaces.

92.10-40 Access to lifeboats.

92.10-45 Weather deck communications.

92.10–90 Vessels contracted for prior to November 19, 1952.

Subpart 92.15—Ventilation

92.15-1 Application.

92.15-5 Vessels using fuel having a flashpoint of 110 degrees or lower.

92.15-10 Ventilation for closed spaces.

92.15–15 Ventilation for crew quarters and, where provided, passenger spaces.

92.15-90 Vessels contracted for prior to November 19, 1952.

Subpart 92.20—Accommodations for Officers and Crew

92.20-1 Application.

92.20-5 Intent. 92.20-10 Location of crew spaces

92.20-15 Construction.

92.20-20 Sleeping accommodations.

92.20-25 Washrooms and toilet rooms.

92.20-30 Messrooms.

92.20–35 Hospital space. 92.20–40 Other spaces.

92.20-45 Lighting.

92.20-50 Heating and cooling.

92.20-55 Insect screens.

92.20–90 Vessels contracted for prior to November 19, 1952

Subpart 92.25—Rails and Guards

92.25-1 Application.

92.25-5 Where rails required.

92.25-10 Storm rails.

92.25–15 Guards in dangerous places.

92.25–90 Vessels contracted for prior to July 1, 1969.

AUTHORITY: 46 U.S.C. 3306; E.O. 12234, 45 FR 58801, 3 CFR, 1980 Comp., p. 277; 49 CFR 1.46.

SOURCE: CGFR 65-50, 30 FR 16983, Dec. 30, 1965, unless otherwise noted.

Subpart 92.01—Hull Structure

§92.01-1 Application.

(a) The provisions of this subpart, with the exception of §92.01–90, shall apply to all vessels contracted for on or after November 19, 1952. Vessels contracted for prior to November 19, 1952, shall meet the requirements of §92.01–90.

$\S 92.01-5$ Vessels subject to load line.

(a) For vessels assigned a load line, see subchapter E (Load Lines) of this