

## § 92.10-35

## 46 CFR Ch. I (10-1-02 Edition)

### § 92.10-35 Public spaces.

(a) In all cases, public spaces having a deck area of over 300 square feet shall have at least two exits. Where practicable, these exits shall give egress to different corridors, rooms, or spaces to minimize the possibility of one incident blocking both exits.

### § 92.10-40 Access to lifeboats.

(a) The stairways, corridors, and doors shall be so arranged as to permit a ready and direct access to the various lifeboat embarkation areas.

### § 92.10-45 Weather deck communications.

(a) Vertical communication shall be provided between the various weather decks by means of permanent inclined ladders.

### § 92.10-90 Vessels contracted for prior to November 19, 1952.

(a) Existing arrangements previously approved will be considered satisfactory so long as they are maintained in good condition to the satisfaction of the Officer in Charge, Marine Inspection. Minor repairs and alterations may be made to the same standards as the original design: *Provided*, That in no case will a greater departure from the standards of §§ 92.10-5 through 92.10-45 be permitted than presently exists. Nothing in this paragraph shall be construed as exempting any vessel from having 2 means of escape from all main compartments which are accessible to the passengers, if carried, or where the crew are normally quartered or employed.

## Subpart 92.15—Ventilation

### § 92.15-1 Application.

The provisions of this subpart, with the exception of § 92.15-90, shall apply to all vessels contracted for on or after November 19, 1952. Vessels contracted for prior to November 19, 1952, shall meet the requirements of § 92.15-90.

### § 92.15-5 Vessels using fuel having a flashpoint of 110 degrees or lower.

(a) Where liquid fuel having a flashpoint of 110 degrees F. or lower is used for main or auxiliary machinery

or for starting purposes, the spaces containing such machinery or fuel tanks shall have ventilation as required by this section.

(1) At least 2 ventilators fitted with cowls or their equivalent for the purpose of properly and effectively ventilating the bilges of every engine and fuel-tank compartment in order to remove any flammable or explosive gases.

(2) Vessels constructed so that the greater portions of the bilges under the engine and fuel tanks are open or exposed to the natural atmosphere at all times are not required to be fitted with ventilators.

### § 92.15-10 Ventilation for closed spaces.

(a) Except as noted in paragraph (c) of this section, all enclosed spaces within the vessel shall be properly vented or ventilated. Means shall be provided to close off all vents and ventilators.

(b) Means shall be provided for stopping all fans in ventilation systems serving machinery and cargo spaces and for closing all doorways, ventilators and annular spaces around funnels and other openings to such spaces, from outside these spaces, in case of fire.

(c) On unmanned cargo barges not fitted with a fixed bilge system, vents and ventilators may be omitted from void spaces.

(d) The ventilation of spaces which are "specially suitable for vehicles" shall be in accordance with the provisions of this paragraph. In addition, if vehicles are operated inside of enclosed spaces, the ventilation shall be in accordance with subpart 97.80 of this subchapter.

(1) Areas below the weather deck shall be provided with continuous pressure-positive ventilation at each level on which vehicles are transported.

(2) The quantity of ventilating air shall be not less than 1 cubic foot per minute per square foot of deck area.

(3) The ventilation system shall be such as to prevent air stratification as well as to prevent the accumulation of air pockets.

(4) An alarm system shall be provided which will indicate the loss of required