

## § 108.147

### § 108.147 Certain paints prohibited.

No nitrocellulose or other highly flammable or noxious fume-producing paint or lacquer may be used on a unit.

#### MEANS OF ESCAPE

### § 108.151 Two means required.

(a) Each of the following must have at least 2 means of escape:

(1) Each accommodation space with a deck area of at least 27 sq. meters (300 sq. ft.).

(2) Each space, other than an accommodation space, that is continuously manned or used on a regular working basis except for routine security checks.

(3) Weather deck areas where personnel may be normally employed.

(b) When two means of escape are required from a space below the main deck, one the means of escape must provide for a rapid escape through openings that are not required to be watertight by damage stability considerations.

(c) When two means of escape are required from a space above the main deck, one of the means of escape must provide for a rapid escape to a weather deck.

### § 108.153 Location of means of escape.

The required two means of escape must be through exits that minimize the possibility of having both exits blocked if a fire or other casualty occurs in the area.

### § 108.155 Restrictions on means of escape utilized.

A required means of escape may not be a vertical ladder or deck scuttle, except that one of the means of escape may be a vertical ladder or deck scuttle if a stairway would be impracticable.

### § 108.157 Locked doors.

No door to the required means of escape may be designed to lock except—

(a) A crash door or a door that has a locking device that can be easily forced, if on both sides of the door a permanent and easily seen instruction is placed; or

(b) An outside door to a deckhouse if the door can be locked by key only and

## 46 CFR Ch. I (10–1–02 Edition)

if the master or person in charge has control of the key to the door's lock.

### § 108.159 Stairways and exterior inclined ladders.

Each stairway, except a stairway in a machinery or storage space, and each exterior inclined ladder must be at least 70 centimeters (28 inches) wide with an angle of inclination from the horizontal of not more than 50 degrees, except that special consideration may be given to the installation if a 70 centimeters (28 inch) width is impracticable.

### § 108.160 Vertical ladders.

(a) Each vertical ladder must have rungs that are—

(1) At least 41 centimeters (16 inches) in length;

(2) Not more than 30 centimeters (12 inches) apart, uniform for the length of the ladder; and

(3) At least 18 centimeters (7 inches) from the nearest permanent object in back of the ladder.

(b) Except when unavoidable obstructions are encountered, there must be at least 11.5 centimeters (4½ inches) clearance above each rung.

(c) Except as provided in § 108.540(h)(3)(ii), each exterior vertical ladder more than 6 meters (20 ft.) in length must be fitted with a cage or ladder safety device meeting ANSI Standard 14.3 (1974) for fixed ladders.

(d) No vertical fixed ladders may be made of wood.

[CGD 73-251, 43 FR 56808, Dec. 4, 1978, as amended by USCG-2002-13058, 67 FR 61279, Sept. 30, 2002]

### § 108.161 Dead end corridors.

No dead end corridor may be more than 13 meters (43 feet) long.

### § 108.165 Access to lifeboats and liferafts.

Each unit must be designed to provide direct access to the lifeboat and liferaft embarkation areas.

### § 108.167 Weather deck ladders.

Each unit must have at least one permanent, inclined ladder between each weather deck.