

accesses and sounding tubes may open into corridors.

**§ 108.195 Location of accommodation spaces.**

(a) On surface type units, accommodation spaces must not be located forward of a vertical plane located at 5 percent of the unit's length aft of the stem, at the designed summer load line.

(b) On all units, the deckhead of each accommodation space must be above the deepest load line.

**§ 108.197 Construction of accommodation spaces.**

(a) Each sleeping, mess, recreational, or hospital space that is adjacent to or immediately above a stowage or machinery space, paint locker, drying room, washroom, toilet space, or other odor source must be made odorproof.

(b) Each accommodation space that is adjacent to or immediately above a galley, machinery space, machinery casing, boiler room, or other noise or heat source, must be protected from the heat and noise.

(c) Where the shell or an unsheathed weather deck forms a boundary of an accommodation space, the shell of deck must have a covering that prevents the formation of moisture.

(d) The deckheads of each accommodation space must be a light color.

(e) Each accommodation space in which water may accumulate must have a drain scupper located in the lowest part of the space, considering the average trim of the unit.

(f) Each public toilet space must be constructed and located so that its odors do not readily enter any sleeping, mess, recreational, or hospital space.

**§ 108.199 Arrangement of sleeping spaces.**

To the extent practicable, each occupation group must be berthed together in sleeping spaces arranged to minimize disturbance created by personnel leaving for or arriving from a working period.

**§ 108.201 Size of sleeping spaces.**

(a) No sleeping space may berth more than four persons, except that a sleeping space for personnel not regularly

employed on a unit may berth up to six persons if the space meets § 108.199 and berthing of six persons in that space is authorized by the Commandant (G-MSO).

(b) Without deducting any equipment used by the occupants, each sleeping space must have for each occupant—

(1) 2.8 square meters (approximately 30 square feet) of deck area; and

(2) 6 cubic meters (approximately 210 cubic feet) of volume.

(c) Each sleeping space must have at least 191 centimeters (approximately 6 feet 3 inches) of headroom over clear deck areas.

[CGD 73-251, 43 FR 56808, Dec. 4, 1978, as amended by CGD 82-063b, 48 FR 4781, Feb. 3, 1983; CGD 95-072, 60 FR 50465, Sept. 29, 1995; CGD 96-041, 61 FR 50730, Sept. 27, 1996]

**§ 108.203 Berths and lockers.**

(a) Each sleeping space must have a separate berth for each occupant.

(b) No more than one berth may be placed over another.

(c) Each berth must have a framework of hard, smooth material that is not likely to corrode or harbor vermin.

(d) Each berth must be arranged to provide ample room for easy occupancy.

(e) Each berth must be at least 76 centimeters (approximately 30 inches) wide by 193 centimeters (approximately 76 inches) long.

(f) Adjacent berths must be separated by a partition that extends at least 46 centimeters (approximately 18 inches) above the sleeping surface.

(g) The bottom of a lower berth must be at least 30 centimeters (approximately 12 inches) above the deck.

(h) The bottom of an upper berth must be at least 76 centimeters (approximately 2 feet 6 inches) from the bottom of the berth below it and from the deck or any pipe, ventilating duct, or other overhead installation.

(i) Each berth must have a berth light.

(j) Each occupant of a sleeping space must have a readily accessible locker of hard, smooth material.

(k) Each locker must be at least .194 square meters (approximately 300 square inches) in cross section and 1.53 meters (approximately 60 inches) high.