

(2) A single berth or examination table that is accessible from both sides; and

(3) A washbasin in or immediately adjacent to it.

§ 108.211 Miscellaneous accommodation spaces.

(a) Each unit must have enough facilities for personnel to wash their own clothes, including at least one tub or sink that has hot and cold running water.

(b) Each unit must have enough equipment or space for the personnel to dry their own clothes.

(c) Each unit must have an accommodation space that can be used for recreation.

§ 108.213 Heating requirements.

(a) Each accommodation space must be heated by a heating system that can maintain at least 20°C. (68°F.).

(b) Radiators and other heating apparatuses must be constructed, located or shielded so as to avoid risk of—

- (1) Fire;
- (2) Danger; and
- (3) Discomfort

to the occupants of each accommodation space.

(c) Each exposed pipe in an accommodation space, leading to a radiator or other heating apparatus must be insulated.

§ 108.215 Insect screens.

(a) Accommodation spaces must be protected against the admission of insects.

(b) Insect screens must be installed when natural ventilation is provided.

RAILS

§ 108.217 Guardrails and bulwarks.

(a) Each unit must have guardrails or bulwarks along the edge of the bridge, of each deck, and of each deck opening.

(b) Each guardrail and bulwark must extend at least one meter (39.37 inches) above the deck except where this height may interfere with the normal operation of the unit, a lesser height may be approved.

(c) Removable guardrails may be installed where operating conditions warrant their use.

§ 108.219 Guardrails.

(a) Except for exposed peripheries of a freeboard or superstructure deck, each guardrail must have at least two evenly spaced courses.

(b) At exposed peripheries of a freeboard or superstructure deck, each guardrail must have at least three courses not more than 38 centimeters (15 in.) apart with the lowest course not more than 23 centimeters (9 in.) above the deck.

(c) For a rounded gunwale, the guardrail must be at the edge of the flat of the deck.

§ 108.221 Storm rails.

Each unit must have a storm rail in the following locations:

(a) On each deckhouse side that is normally accessible.

(b) On each side of each passageway that is wider than 1.83 meters (6 feet).

(c) On at least one side of each passageway that is less than 1.83 meters (6 feet) wide.

§ 108.223 Guards on exposed equipment.

Each unit must have hand covers, guards, or rails installed on all belts, gears, shafts, pulleys, sprockets, spindles, flywheels or other reciprocating, rotating or moving parts of machinery or equipment normally exposed to contact by personnel.

HELICOPTER FACILITIES

§ 108.231 Application.

Sections 108.231 through 108.241 apply to each unit with a helicopter landing facility.

§ 108.233 Location and size.

(a) Each helicopter deck must be—

(1) At least the size of the rotor diameter of the largest single main rotor helicopter that will be used on the facility; or

(2) If tandem main rotor helicopters use the facility, at least of a size to provide a longitudinal axis of $\frac{3}{10}$ the overall length of the helicopter, and a