

§ 98.01-1

SOURCE: CGFR 65-50, 30 FR 17022, Dec. 30, 1965, unless otherwise noted.

Subpart 98.01—General

§ 98.01-1 Applicability.

(a) The provisions of this part shall apply to all self-propelled cargo vessels which carry in bulk any of the dangerous cargoes specifically noted in this part.

(b) [Reserved]

(c) The regulations for barges carrying any of the bulk chemical cargoes listed in subparts 98.01 through 98.25 are found in subchapter O of this chapter.

(d) [Reserved]

(e) Manned barges carrying any of the cargoes listed in Table 151.05 of this chapter will be considered individually by the Commandant and may be required to meet the applicable requirements of subchapter O of this chapter, as well as the requirements of this subchapter.

[CGFR 65-50, 30 FR 17022, Dec. 30, 1965, as amended by CGFR 70-10, 35 FR 3711, Feb. 25, 1970; CGD 84-043, 55 FR 37411, Sept. 11, 1990; 59 FR 17011, Apr. 11, 1994]

§ 98.01-3 Incorporation by reference.

(a) Certain standards and specifications are incorporated by reference into this part with the approval of the Director of the Federal Register in accordance with 5 U.S.C. 552(a). To enforce any edition other than the ones listed in paragraph (b) of this section, notice of change must be published in the FEDERAL REGISTER and the material made available to the public. All approved material is at the Office of the Federal Register, 800 North Capitol Street, NW., suite 700, Washington, DC, and is available from the sources indicated in paragraph (b) of this section.

(b) The standards and specifications approved for incorporation by reference in this part and the sections affected, are:

American Society for Nondestructive Testing (ASNT)

4153 Arlington Road, Caller # 28518, Columbus, OH, 43228-0518
ASNT "Recommended Practice No. SNT-TC-1A (1988), Personnel Qualification and Certification in Non-destructive Testing"98.25-97(c)(2)

46 CFR Ch. I (10-1-02 Edition)

American Society of Mechanical Engineers (ASME) International

Three Park Avenue, New York, N.Y. 10016-5990

ASME Boiler and Pressure Vessel Code, section V, Nondestructive Examination (1986)98.25-97(a)(1)

[CGD 85-061, 54 FR 50965, Dec. 11, 1989 as amended by USCG-1999-6216, 64 FR 53226, Oct. 1, 1999]

Subpart 98.25—Anhydrous Ammonia in Bulk

§ 98.25-1 Applicability.

(a) The regulations in this subpart apply to each self-propelled vessel that has anhydrous ammonia on board as a cargo, cargo residue, or vapor and that is not regulated under part 154 of this chapter.

(b) Any self-propelled vessel to which this subpart applies shall be inspected and certificated under this subchapter and subchapter D of this chapter.

[CGD 74-289, 44 FR 26008, May 3, 1979]

§ 98.25-5 How anhydrous ammonia may be carried.

(a) Anhydrous ammonia shall be carried in unfired pressure vessel type tanks independent of the structure as detailed in this part, except as otherwise provided in paragraph (b) of this section.

(b) When anhydrous ammonia is to be transported at its boiling temperature at or near atmospheric pressure, the Commandant may permit the use of alternate methods of storage if it is shown to his satisfaction that a degree of safety is obtained consistent with the minimum requirements of this subpart.

§ 98.25-10 Design and construction of cargo tanks.

(a) The cargo tanks shall meet the requirements for Class I, I-L, II, or II-L welded pressure vessels and shall be fabricated, inspected, and tested in accordance with the applicable requirements of part 54 of subchapter F (Marine Engineering) of this chapter.

(b) Unlagged cargo tanks subject to atmospheric temperatures shall be designed for a pressure of not less than 250 pounds per square inch gage.