

passed by a No. 54 drill size opening, need not be equipped with excess flow valves.

(f) Pressure gage connections need not be equipped with excess flow valves if the openings are not larger than No. 54 drill size.

(g) Excess flow valves may be designed with a bypass, not to exceed a No. 60 drill size opening, to allow equalization of pressure.

(h) Prior to disconnecting shore lines, the pressure in the liquid and vapor lines shall be relieved through suitable valves installed at the loading header.

(i) Relief valves shall be fitted in liquid lines which may be subject to excessive pressure caused by liquid full condition, and the escape from the relief valves shall be piped to the venting system.

(j) The pressure gage shall be located at the highest practical point. The thermometer well shall terminate in the liquid space and be attached to the shell by welding with the end of the fitting being provided with a gas-tight screwed plug or bolted cover.

[CGFR 65-50, 30 FR 17022, Dec. 30, 1965, as amended by CGFR 68-82, 33 FR 18902, Dec. 18, 1968; CGFR 70-10, 35 FR 3712, Feb. 25, 1970]

#### § 98.25-45 Liquid level gaging device.

(a) Each tank shall be fitted with a liquid level gaging device of suitable design to indicate the maximum level to which the tank may be filled with liquid at temperatures between 20° F. and 130° F.

(b) Liquid level gaging devices shall be of the following types: magnetic, rotary tube, slip tube, fixed tube, automatic float, or other types acceptable to the Commandant.

(c) Gaging devices that require bleeding of the product to the atmosphere, such as rotary tube, fixed tube, and slip tube, shall be so designed that the bleed valve maximum opening is not larger than a No. 54 drill size, unless provided with an excess flow valve.

(d) Gaging devices shall have a design pressure of at least 250 pounds per square inch.

(e) Gage glasses of the columnar type are prohibited.

#### § 98.25-50 Filling and discharge pipes.

(a) Filling connections shall be provided with one of the following:

(1) Combination back pressure check valve and excess flow valve;

(2) One double or two single back pressure check valves; or

(3) A positive shut-off valve in conjunction with either an internal back pressure check valve or an internal excess flow valve.

(b) All other liquid and vapor connections to tanks, except filling connections, safety relief valves, and liquid level gaging devices and pressure gages described in § 98.25-40(e) and (f) shall be equipped with automatic excess flow valves; or in lieu thereof, may be fitted with quick closing internal stop valves, which, except during filling and discharge operations, shall remain closed. The control mechanism for such valves shall be provided with a secondary remote control of a type acceptable to the Commandant.

(c) The excess flow, internal stop or back pressure check valves shall be located on the inside of the tank or outside where the piping enters the tank. In the latter case, installation shall be made in such a manner that any undue strain will not cause breakage between the tank and the excess flow or internal stop valve.

(d) Where the filling and discharge are made through a common nozzle at the tank, and the connection is fitted with a quick-closing internal stop valve as permitted in paragraph (b) of this section, the back pressure check valve or excess flow valve is not required, provided, however, a positive shut-off valve is installed in conjunction with the internal stop valve.

[CGFR 65-50, 30 FR 17022, Dec. 30, 1965, as amended by CGFR 70-10, 35 FR 3712, Feb. 25, 1970]

#### § 98.25-55 Cargo piping.

(a) Piping shall be of seamless steel meeting the requirements of § 56.60-1 of subchapter F (Marine Engineering) of this chapter. The piping shall be of not less than Schedule 40 thickness. In case of piping on the discharge side of the liquid pumps or vapor compressors, the design shall be for a pressure of not less than the pump or compressor relief