

(1) In the vicinity of another tank that contains a chemically incompatible product; and

(2) Unless all electrical equipment is explosion-proof or intrinsically safe, as defined in §§ 111.105-9 and 111.105-11 of this chapter, in the area of the tank and its associated equipment that is—

(i) Within 10 feet in any horizontal direction; and

(ii) Within 8 feet above the deck.

[CGD 73-172, 39 FR 22954, June 25, 1974, as amended by CGD 84-043, 55 FR 37412, Sept. 11, 1990; 55 FR 47477, Nov. 14, 1990]

§ 98.30-10 Pipe connections, and filling and discharge openings.

No person may transfer a hazardous material to or from a portable tank on board a vessel, unless each filling and discharge opening in the tank bottom is equipped with the following:

(a) For an IM 101 or IM 102 portable tank, the closures specified in 49 CFR 173.32c(g)(2); and

(b) For an MPT, the valves and closures specified in §§ 64.33 through 64.41 of this chapter.

[CGD 84-043, 55 FR 37412, Sept. 11, 1990]

§ 98.30-11 Cargo pumps.

No person may operate a cargo pump to transfer a product to or from a portable tank unless the pump is installed—

(a) Above deck; or

(b) Below deck, in conformance with subpart 32.60 of this chapter.

§ 98.30-13 Ground connection.

No person may transfer an inflammable or combustible product to or from a vessel unless—

(a) The portable tank and its pumping equipment is electrically grounded to the hull of the vessel; and

(b) The vessel is electrically grounded to an offshore platform, shore piping, or another vessel by a—

(1) Cargo hose constructed with an integral grounding wire if the end connections are used for electrical continuity; or

(2) Separate grounding that is maintained until the cargo hose is disconnected and drained.

§ 98.30-14 Requirements for ships carrying NLSs in portable tanks.

(a) The person in charge of a ship, except a ship under subpart 98.31 of this chapter, that carries an NLS in a portable tank shall ensure that—

(1) The ship's Certificate of Inspection is endorsed with the name of the NLS;

(2) Any letters issued by the Commandant (G-MSO) prescribing additional conditions for endorsement are attached; and

(3) Each operating requirement specified in writing by Commandant (G-MSO) as a condition for endorsement is met.

(b) To have a ship's Certificate of Inspection endorsed to allow the carriage of NLSs in portable tanks, the—

(1) Owner of the ship must make a request to the Commandant (G-MSO) following the procedures for requesting alternatives in § 153.10(a) of this chapter; and

(2) The ship must meet any design and equipment requirements specified in writing as a condition for the endorsement by the Commandant (G-MSO).

[CGD 81-101, 53 FR 28974, Aug. 1, 1988. Redesignated at CGD 84-043, 55 FR 37411, Sept. 11, 1990, and amended by CGD 84-043, 55 FR 37412, Sept. 11, 1990; CGD 95-072, 60 FR 50464, Sept. 29, 1995; CGD 96-041, 61 FR 50730, Sept. 27, 1996]

§ 98.30-15 Leakage containment.

(a) No person may transfer a product to or from a vessel unless there is a container or enclosed deck area that meets the requirements of this section under or around each transfer connection area.

(b) Each container or enclosed deck area must hold, in all conditions of vessel list or trim to be encountered during the transferring operation, 5 gallons or more and must have a means of draining or removing any leakage without mixing incompatible products or discharging into the water.

§ 98.30-17 Qualifications of person in charge.

(a) The operator or agent of each vessel shall designate the person in charge of a transfer of liquid cargo in bulk to or from a portable tank.