

§ 98.30-39

(3) Capable of covering the deck area without being moved;

(d) In a deck area of 500 square feet or less, there are 2 or more dry chemical fire extinguishers of 300 pounds or more total capacity of extinguishing agent; and

(e) In a deck area of more than 500 square feet, there are 3 or more dry chemical fire extinguishers of 450 pounds or more total capacity of extinguishing agent.

§ 98.30-39 Alternate fire extinguishing system.

An alternative to the fire extinguishing system required in § 98.30-37(c) may be approved in accordance with procedures contained in subpart 90.15 of this chapter.

Subpart 98.31—Control of Pollution From NLS Cargoes on Ocean-going Offshore Supply Vessels

SOURCE: CGD 82-004 and CGD 86-074, 62 FR 49321, Sept. 19, 1997, unless otherwise noted.

§ 98.31-5 Applicability.

This subpart applies to each offshore supply vessel contracted for, or the keel of which was laid, before March 15, 1996, that is oceangoing as defined in 33 CFR 151.05(j) and that carries noxious liquid substances (NLSs) as defined in § 153.2 of this chapter in bulk, including carriage in portable tanks.

§ 98.31-10 Certificate of inspection and NLS certificate endorsements.

(a) The Coast Guard issues the endorsed Certificate of Inspection or NLS Certificate required by § 98.31-15 for every vessel under this subpart to carry NLSs if the vessel—

(1) Has the Cargo Record Book prescribed in § 153.490(a)(1) of this chapter; and

(2) Unless it discharges no NLS residues as defined in § 153.2 of this chapter to the sea, meets the requirements in §§ 153.470 through 153.491 of this chapter.

(b) Each vessel under this subpart that does not meet the requirements in §§ 153.470 through 153.491 of this chapter must have a statement on its Certificate of Inspection or NLS Certificate stating that the vessel is prohibited

46 CFR Ch. I (10-1-02 Edition)

from discharging NLS residues to the sea.

§ 98.31-15 Operating requirements.

No person may operate a vessel that carries a bulk liquid cargo of NLS unless the vessel—

(a) Has on board a Certificate of Inspection and, if it is a vessel making a foreign voyage, an NLS Certificate endorsed under § 98.31-10 with the name of the NLS cargo;

(b) Discharges no NLS residues to the sea unless the vessel meets—

(1) The equipment requirements in § 98.31-10(a)(2); and

(2) The operating requirements prescribed for oceangoing ships carrying NLSs in §§ 153.901, 153.903, 153.909, and 153.1100 through 153.1132 of this chapter.

Subpart 98.33—Portable Tanks for Certain Grade E Combustible Liquids and Other Regulated Materials

SOURCE: CGD 84-043, 55 FR 37412, Sept. 11, 1990, unless otherwise noted.

§ 98.33-1 Applicability.

(a) This subpart contains regulations concerning transfer of certain low-hazard materials to and from portable tanks on vessels

(b) This subpart applies to the following portable tanks:

(1) A DOT-specification 57 portable tank (see 49 CFR 173.24, 173.32, 178.251, and 178.253);

NOTE TO PARAGRAPH (b)(1): Copies of Specifications 178.251 and 178.253 may be obtained from the Commandant (G-MSO-3).

(2) A portable tank authorized under 49 CFR 176.340(b); and

(3) A portable tank approved by the Commandant under subpart 50.20 of this chapter.

[CGD 84-043, 55 FR 37412, Sept. 11, 1990; 56 FR 13598, Apr. 3, 1991, as amended by CGD 97-057, 62 FR 51046, Sept. 30, 1997]

§ 98.33-3 Cargoes authorized.

The following cargoes are authorized for transfer to and from portable tanks authorized by § 98.33-5:

(a) Grade E combustible liquids that have a closed-cup flashpoint of 300 °F or higher and that meet the definition