

§ 130.420 Controls.

Each piece of machinery under automatic control must have an alternative manual means of control.

§ 130.430 Pilothouse control.

Each OSV must have, at the pilothouse, controls to start a fire pump, charge the fire main, and monitor the pressure in the fire main.

§ 130.440 Communications system.

(a) Each OSV must have a communications system to immediately summon a crew member to the machinery space wherever one of the alarms required by §130.460 of this subpart is activated.

(b) The communications system must be either—

- (1) An alarm that—
 - (i) Is dedicated for this purpose;
 - (ii) Sounds in the crew accommodations and the normally manned spaces; and
 - (iii) Is operable from the pilothouse; or
- (2) A telephone operated from the pilothouse that reaches the master's stateroom, engineer's stateroom, engine room, and crew accommodations that either—
 - (i) Is a sound-powered telephone; or
 - (ii) Gets its power from the emergency switchboard or from an independent battery continuously charged by its own charger.

§ 130.450 Machinery alarms.

(a) Each alarm required by §130.460 of this subpart must be of the self-monitoring type that will both show visibly and sound audibly upon an opening or break in the sensing circuit.

(b) The visible alarm must show until it is manually acknowledged and the condition is corrected.

(c) The audible alarm must sound until it is manually silenced.

(d) No silenced alarm may prevent any other audible alarm from sounding.

(e) Each OSV must be provided with means for testing each visible and audible alarm.

(f) Each OSV must provide battery power for the alarm required by §130.460(a)(8) of this subpart.

§ 130.460 Placement of machinery alarms.

(a) Visible and audible alarms must be installed at the pilothouse to indicate the following:

- (1) Loss of power for propulsion control.
- (2) Loss of power to the steering motor or for control of the main steering gear.
- (3) Engine-room fire.
- (4) High bilge-level.
- (5) Low lube-oil pressure for each main propulsion engine and each prime mover of a generator.
- (6) For each main propulsion engine and each prime mover of a generator—
 - (i) High lube-oil temperature; and
 - (ii) High jacket-water temperature.
- (7) For each reduction gear and each turbocharger with a pressurized oil system—
 - (i) Low lube-oil pressure; and
 - (ii) High lube-oil temperature.

(8) Loss of normal power for the alarms listed in paragraphs (a)(1) through (a)(7) of this section.

(b) Sensors for the high-bilge-level alarm required by paragraph (a)(4) of this section must be installed in—

- (1) Each space below the deepest load waterline that contains pumps, motors, or electrical equipment; and
- (2) The compartment that contains the rudder post.

(c) Centralized displays must be installed in the machinery spaces to allow rapid evaluation of each problem detected by the alarms required by paragraph (a) of this section. Equipment-mounted gauges or meters are acceptable for this purpose, if they are grouped at a central site.

§ 130.470 Fire alarms.

(a) Each fire detector and control unit must be of a type specifically approved by the Commandant (G-MSE).

(b) No fire-alarm circuit for the engine room may contain a fire detector for any other space.

(c) The number and placement of fire detectors must be approved by the cognizant OCMI.

§ 130.480 Test procedure and operations manual.

(a) A procedure for tests to be conducted on automated equipment by the