

§ 116.422

46 CFR Ch. I (10–1–02 Edition)

(2) The space in question is open and unobstructed such that a fire in any part of the space will quickly be discovered.

(3) The area above the ceiling is easily accessible from below for fire fighting purposes.

[CGD 85–080, 61 FR 900, Jan. 10, 1996; 61 FR 20556, May 7, 1996; 61 FR 24464, May 15, 1996, as amended at 62 FR 51348, Sept. 30, 1997; USCG 1998–4442, 63 FR 52191, Sept. 30, 1998]

§ 116.422 Ceilings, linings, trim, interior finish and decorations.

(a) Ceilings, linings, and any furring incidental to their installation in control spaces, passageways, stairways, accommodation spaces and service spaces must be of noncombustible material in accordance with § 164.009 in subchapter Q of this chapter, or other standard specified by the Commandant.

(b) Bulkheads, linings and ceilings may be covered by a combustible interior finish provided that such a finish is:

(1) Approved under § 164.012 in subchapter Q of this chapter, or other standard specified by the Commandant; or

(2) Listed by Underwriters Laboratories, does not exceed 2 millimeters (.075 inches) in thickness, and has a flame spread rating of not more than 20 and a smoke developed rating of not more than 10 when tested in accordance with ASTM E 84 (incorporated by reference, see § 114.600) or UL 723 by an independent laboratory.

(c) Bulkheads, linings, and ceilings in high risk accommodation spaces may have a combustible veneer trim and decorations that do not meet the requirements of paragraph (b) of this section, provided:

(1) The overall thickness of the combustible veneer does not exceed 2 millimeters (.075 inches); and

(2) The total volume of the combustible face trim, moldings, and decorations, including veneers, in any space does not exceed a volume equivalent to a 2.5 millimeter (0.1 inch) veneer on the combined area of the bulkheads and ceiling of the space.

(d) Combustible veneers may not be used in passageways, stairway enclosures or in low risk accommodation spaces. Combustible veneers, trim and

decorations may not be used in or extend into hidden spaces such as behind linings or ceilings.

(e) Partial bulkheads or decks used to subdivide a space for artistic treatment and privacy must meet the requirements of Class C bulkheads.

(f) Nothing in this subpart may be construed as prohibiting the covering of any surface, including the surfaces of corridors, stairway enclosures, and hidden spaces, with a reasonable number of coats of paint or with a marine finish meeting the requirements of § 164.012 in subchapter Q of this chapter or other standard specified by the Commandant.

[CGD 85–080, 61 FR 900, Jan. 10, 1996, as amended at 62 FR 51349, Sept. 30, 1997; USCG–2000–7790, 65 FR 58462, Sept. 29, 2000]

§ 116.423 Furniture and furnishings.

(a) For the purpose of this subpart, rooms containing “fire resistant furnishings” are considered to be those in which:

(1) Furniture such as chairs, sofas, and similar items are tested and meet the requirements in UL 1056 “Fire Test of Upholstered Furniture,” or meet the requirements in § 72.05–55 in subchapter H of this chapter.

(2) Case furniture such as bookshelves, desks, cabinets, counters, beds, or other freestanding furniture are constructed in accordance with the requirements in § 72.05–55 (a)(1) in subchapter H of this chapter.

(3) Draperies, curtains and other similar furnishings and decorations are flame resistant. These materials must be tested in accordance with National Fire Protection Association (NFPA) 701 “Fire Tests for Flame Resistant Textiles and Films,” and must comply with either the small or large scale tests.

(4) Rugs and carpet may be used in addition to deck coverings. Rugs and carpets must be constructed of 100 percent wool or equivalent as determined by a flame spread rating not exceeding 75 and a smoke developed rating not exceeding 100 when tested according to ASTM E 84 (incorporated by reference, see § 114.600) or have a critical radiant flux not less than 0.8 watts per square centimeter (18 BTU’s per hour per square inch) when tested according to

ASTM E 648 (incorporated by reference, see § 114.600) "Critical Radiant Flux of Floor-Covering Systems Using a Radiant Heat Energy Source," and with a specific optical density not to exceed 450 in both flaming and nonflaming modes when tested according to ASTM E 662 (incorporated by reference, see § 114.600) "Specific Optical Density of Smoke generated by Solid Materials." Also:

(i) Rugs and carpets shall not extend up bulkheads or vertical surfaces more than 10 centimeters (4 inches) above the deck.

(ii) Rugs and carpets are not permitted in machinery spaces, high risk service spaces, or areas where the spillage or leakage of flammable or combustible liquids is possible including areas immediately adjacent to bar service areas.

(b) Passageways and stairway enclosures shall contain only fire resistant furnishings. In addition, all upholstered chairs, sofas, etc., in these areas, shall be tested and meet the requirements in UL 1056 or have padding and upholstery of approved fire resistant materials.

[CGD 85-080, 61 FR 900, Jan. 10, 1996, as amended by USCG-2000-7790, 65 FR 58462, Sept. 29, 2000]

§ 116.425 Deck coverings.

(a) Except as provided in this section, deck coverings used for leveling or finishing purposes in control spaces, stairway enclosures, passageways, accommodation spaces and service spaces must be noncombustible.

(1) Materials approved under § 164.006 in subchapter Q of this chapter may be used in thicknesses not to exceed the approved thickness.

(2) Combustible deck leveling and finishing materials which are not approved under § 164.006 in subchapter Q of this chapter may be used in a thickness not to exceed 9.5 millimeters (.375 inches).

(b) [Reserved]

§ 116.427 Fire load of accommodation and service spaces.

(a) Fire load calculations must be submitted by the owner for review to the Marine Safety Center when:

(1) A space is designated as a low risk accommodation space by the owner; or

(2) The cognizant OCMI determines, based on the quantity of combustibles, that the fire load present in a high risk accommodations space may exceed 37.5 kg (7.5 pounds) of combustibles per square meter (square foot) of deck area.

(b) When required under paragraph (a) of this section, fire load calculations must include all combustible construction and outfitting materials in addition to all loose or freestanding combustibles intended for use or stowage in the space. This includes but is not limited to: furniture, furnishings, carpets, rugs, combustible deck coverings, draperies, combustible interior finish, veneers, trim, and decorations, electrical cable insulation, plastic piping, light diffusers, mattresses, bedding, lifesaving equipment, and similar materials. The maximum fire load of a low risk accommodation or low risk service space as determined by fire load calculations must not exceed 15.0 kg (3 pounds) of combustibles per square meter (square foot) of deck area. The maximum fire load of a high risk accommodation space as determined by fire load calculations must not exceed 37.5 kg (7.5 pounds) of combustibles per square meter (square foot) of deck area.

[CGD 85-080, 61 FR 900, Jan. 10, 1996, as amended at 62 FR 51349, Sept. 30, 1997]

§ 116.430 Insulation other than for structural fire protection.

(a) Combustible insulation may be used for pipe and machinery covering or lagging within a machinery space, or used in an individual refrigerator box if the refrigerator box was purchased with the insulation already installed.

(b) Except as allowed by paragraph (a) of this section, any insulation installed for purposes other than structural fire protection and all material incidental to its installation must be noncombustible or approved under § 164.009 in subchapter Q of this chapter. Surfacing material applied to such insulation must be noncombustible or may meet the requirements of § 116.422(c) of this part.