

(a) A shore-power-connection box or receptacle must be permanently installed at a convenient location.

(b) A cable connecting the shore-power-connection box or receptacle to the switchboard or main distribution panel must be permanently installed.

(c) A circuit breaker must be provided at the switchboard or main distribution panel for the shore-power connection.

(d) The circuit breaker, required by paragraph (c) of this section, must be interlocked with the feeder circuit breakers for the vessel's power sources to preclude the vessel's power sources and shore power from energizing the vessel's switchboard simultaneously, except in cases where system devices permit safe momentary paralleling of OSV power with shore power.

§ 129.395 Radio installations.

A separate circuit, with overcurrent protection at the switchboard, must be provided for at least one radio installation. Additional radios, if installed, may be powered from a local lighting power source, such as the pilothouse lighting panel, provided each radio power source has a separate overcurrent protection device.

Subpart D—Lighting Systems

§ 129.410 Lighting fixtures.

(a) Each globe, lens, or diffuser of a lighting fixture must have a high-strength guard or be made of high-strength material, except in accommodations, the pilothouse, the galley, or similar locations where the fixture is not subject to damage.

(b) No lighting fixture may be used as a connection box for a circuit other than the branch circuit supplying the fixture.

(c) Each lighting fixture must be installed as follows:

(1) Each lighting fixture and lampholder must be fixed. No fixture may be supported by the screw shell of a lampholder.

(2) Each pendant-type lighting fixture must be suspended by and supplied through a threaded rigid-conduit stem.

(3) Each tablelamp, desk lamp, floorlamp, or similar equipment must be so secured in place that it cannot be

displaced by the roll, pitch, or heave or by the vibration of the vessel.

(d) Each lighting fixture in an electrical system operating at more than 50 volts must comply with UL 595, "Marine Type Electric Lighting Fixtures." A lighting fixture in an accommodation space, radio room, galley, or similar interior space may comply with UL 57, "Electric Lighting Fixtures," UL 1570, "Fluorescent Lighting Fixtures," UL 1571, "Incandescent Lighting Fixtures," UL 1572, "High Intensity Discharge Lighting Fixtures," UL 1573, "Stage and Studio Lighting Units," or UL 1574, "Track Lighting Systems," as long as the general marine requirements of UL 595 are satisfied.

§ 129.420 Branch circuits for lighting on OSVs of 100 or more gross tons.

On each vessel of 100 or more gross tons, each branch circuit for lighting must comply with § 111.75-5 of this chapter, except that—

(a) Appliance loads, electric-heater loads, and isolated small-motor loads may be connected to a lighting-distribution panelboard; and

(b) Branch circuits, other than for lighting, connected to the lighting-distribution panelboard permitted by paragraph (a) of this section may have fuses or circuit breakers rated at more than 30 amperes.

§ 129.430 Navigational lighting.

(a) Each vessel of less than 100 gross tons and less than 19.8 meters (65 feet) in length must have navigational lighting in compliance with the applicable navigation rules.

(b) Each vessel of 100 or more gross tons, or 19.8 meters (65 feet) or more in length, must have navigational lighting in compliance with the applicable navigation rules and with § 111.75-17(d) of this chapter.

§ 129.440 Emergency lighting.

(a) A vessel of less than 100 gross tons must have adequate emergency lighting fitted along the line of escape to the main deck from accommodations and working (machinery) spaces below the main deck.

(b) The emergency lighting required by paragraph (a) of this section must

§ 129.450

automatically actuate upon failure of the main lighting. Unless a vessel is equipped with a single source of power for emergency lighting, it must have individual battery-powered lighting that is—

- (1) Automatically actuated upon loss of normal power;
- (2) Not readily portable;
- (3) Connected to an automatic battery-charger; and
- (4) Of enough capacity for 6 hours of continuous operation.

§ 129.450 Portable lighting.

Each vessel must be equipped with at least two operable, portable, battery-powered lights. One of these lights must be located in the pilothouse, another at the access to the engine room.

Subpart E—Miscellaneous Electrical Systems

§ 129.510 Lifeboat winches.

Each lifeboat winch operated by electric power must comply with subparts 111.95 and be approved under approval series in subparts 160.015 or 160.115 of this chapter.

§ 129.520 Hazardous areas.

(a) No OSV that carries flammable or combustible liquid with a flashpoint of below 140 °F (60 °C), or carries hazardous cargoes on deck or in integral tanks, or is involved in servicing wells, may have electrical equipment installed in pump rooms, in hose-storage spaces, or within 3 meters (10 feet) of a source of vapor on a weather deck unless the equipment is explosion-proof or intrinsically safe under §111.105-9 or 111.105-11 of this chapter.

(b) No electrical equipment may be installed in any locker used to store paint, oil, turpentine, or other flammable liquid unless the equipment is explosion-proof or intrinsically safe under §111.105-9 or §111.105-11 of this chapter.

(c) Equipment that is explosion-proof and intrinsically safe must comply with subpart 111.105 of this chapter.

46 CFR Ch. I (10-1-02 Edition)

§ 129.530 General alarm.

Each vessel must be fitted with a general alarm that complies with subpart 113.25 of this chapter.

§ 129.540 Remote stopping-systems on OSVs of 100 or more gross tons.

(a) Except as provided by paragraph (b) of this section, each vessel must be fitted with remote stopping-systems that comply with subpart 111.103 of this chapter.

(b) The following remote stopping-systems may substitute for remote stopping-systems that must comply with subpart 111.103 of this chapter:

- (1) For each propulsion unit, in the pilothouse.
- (2) For each discharge pump for bilge slop or dirty oil, at the deck discharge.
- (3) For each powered ventilation system, outside the space ventilated.
- (4) For each fuel-oil pump, outside the space containing the pump.
- (5) For each cargo-transfer pump for combustible and flammable liquid, at each transfer-control station.

(c) Remote stopping-systems required by this section may be combined.

§ 129.550 Power for cooking and heating.

(a) Equipment for cooking and heating must be suitable for marine use. Equipment designed and installed to comply with ABYC Standards A-3 and A-7 or Chapter 6 of NFPA 302 meets this requirement.

(b) The use of gasoline for cooking, heating, or lighting is prohibited.

(c) The use of liquefied petroleum gas for cooking, heating, or other purposes must comply with subpart 58.16 of this chapter.

(d) Each electric space-heater must be provided with a thermal cut-out to prevent overheating.

(e) Each element of an electric space-heater must be enclosed, and the case or jacket of the element made of a corrosion-resistant material.

(f) Each electrical connection for a cooking appliance must be drip-proof.