

March 17, 2009



U.S. Department
of Transportation

East Building, PHH-30
1200 New Jersey Avenue, Southeast
Washington, D.C. 20590

**Pipeline and Hazardous
Materials Safety Administration**

DOT-SP 13325
(FOURTH REVISION)

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: (See individual authorization letter)
2. PURPOSE AND LIMITATION:
 - a. This special permit authorizes the transportation in commerce of the compressed gases described in paragraph 6 below in DOT 3A and 3AA specification cylinders which are equipped with a CG-4 pressure relief device (PRD) set at 3,360 psig. This special permit provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein. The most recent revision supersedes all previous revisions.
 - b. The safety analyses performed in development of this special permit only considered the hazards and risks associated with transportation in commerce. The safety analyses did not consider the hazards and risks associated with consumer use or other uses not associated with transportation in commerce.
 - c. Unless otherwise stated herein, this special permit consists of the special permit authorization letter issued to the grantee together with this document.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR §§ 173.301(f)(3) and 180.205(c)(4) in that the use of a CG-4 pressure relief device with a burst pressure outside of the specified tolerance is not authorized, except as specified herein.
5. BASIS: This special permit is based on the Pipeline and Hazardous Materials Safety Administration's (PHMSA) editorial review under § 107.121 initiated on December 4, 2008.

6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Hazardous Materials Description			
Proper Shipping Name	Hazard Class/ Division	Identification Number	Packing Group
Hydrogen chloride, anhydrous	2.3	UN1050	N/A Hazard Zone C
Hydrogen bromide, anhydrous	2.3	UN1048	N/A Hazard Zone C

7. SAFETY CONTROL MEASURES:

a. PACKAGING - Packaging prescribed are DOT Specification 3A-2265, 3AA-2265, 3A-2400, and 3AA-2400 cylinders with water capacities less than or equal to 1,000 pounds. Each cylinder is equipped with a CG-4 style pressure relief device (PRD) with a burst pressure setting of 3,360 psig.

b. OPERATIONAL CONTROLS -

(1) The maximum permitted fill density of each cylinder is less than or equal to 65 percent for Hydrogen chloride and 154 percent for Hydrogen bromide of the cylinder's water volume at 60°F.

(2) The pressure in the cylinder may not exceed 95 percent of the cylinders test pressure at 65°C (149°F).

(3) The pressure in the cylinder may not exceed 90 percent of the start-to-discharge pressure of the cylinders pressure relief device at 54.4°C (130°F).

(4) Cylinders must be filled by weight. The maximum tolerance of the scale must be +/- 0.5%.

(5) Each cylinder valve and PRD must be replaced in accordance with Air Products "Valve Maintenance Schedule" (000-PKG-221) on file with the Office of Hazardous Materials Special Permits and Approvals and all of the PRDs must be in conformance with the requirements of § 173.301(f)(3) prior to January 1, 2015.

8. SPECIAL PROVISIONS:

a. A person who is not a holder of this special permit who receives a package covered by this special permit may reoffer it for transportation provided no modification or change is made to the cylinder or its content and it is reoffered for transportation in conformance with this special permit and the HMR.

b. A current copy of this special permit must be maintained at each facility where the package is offered or reoffered for transportation.

c. Each cylinder must be plainly and durably marked "DOT-SP 13325" as specified in § 172.301(c).

9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle, rail freight and cargo vessel.

10. MODAL REQUIREMENTS: A current copy of this special permit must be carried aboard each cargo vessel and motor vehicle used to transport packages covered by this special permit.

11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this special permit and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:

o All terms and conditions prescribed in this special permit and the Hazardous Materials Regulations, 49 CFR Parts 171-180.

o Persons operating under the terms of this special permit must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.

o Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this special permit must receive training on the requirements and conditions of this special permit in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this special permit, including display of its number, when this special permit has expired or is otherwise no longer in effect.

Under Title VII of the Safe, Accountable, Flexible, Efficient Transportation Equity Act: A Legacy for Users (SAFETEA-LU)- 'The Hazardous Materials Safety and Security Reauthorization Act of 2005' (Pub. L. 109-59), 119 Stat. 1144 (August 10, 2005), amended the Federal hazardous materials transportation law by changing the term "exemption" to "special permit" and authorizes a special permit to be granted up to two years for new special permits and up to four years for renewals.

12. REPORTING REQUIREMENTS: Shipments or operations conducted under this special permit are subject to the Hazardous Materials Incident Reporting requirements specified in 49 CFR 171.15 - Immediate notice of certain hazardous materials incidents, and 171.16 - Detailed hazardous materials incident reports. In addition, the grantee(s) of this special permit must notify the Associate Administrator for Hazardous Materials Safety, in writing, of any incident involving a package, shipment or operation conducted under terms of this special permit.

Issued in Washington, D.C.:



for Theodore L. Willke
Associate Administrator for Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Pipeline and Hazardous Material Safety Administration, U.S. Department of Transportation, East Building PHH-30, 1200 New Jersey Avenue, Southeast, Washington, D.C. 20590.

Copies of this special permit may be obtained by accessing the Hazardous Materials Safety Homepage at http://hazmat.dot.gov/sp_app/special_permits/spec_perm_index.htm Photo reproductions and legible reductions of this special permit are permitted. Any alteration of this special permit is prohibited.

PO: MMT/am