

February 24, 2009



U.S. Department
of Transportation

East Building, PHH-30
1200 New Jersey Avenue, Southeast
Washington, D.C. 20590

**Pipeline and Hazardous
Materials Safety Administration**

DOT-SP 11579
(FOURTEENTH REVISION)

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: (See individual authorization letter)
2. PURPOSE AND LIMITATION:
 - a. This special permit authorizes the transportation in commerce of certain Division 1.1B, 1.1D, 1.4B, 1.4D and 1.5D explosives, Division 5.1 oxidizers, Class 8 materials and combustible liquids in separate containers secured on the same vehicle frame structure. This special permit provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein. The most recent revision supersedes all previous revisions.
 - b. The safety analyses performed in development of this special permit only considered the hazards and risks associated with transportation in commerce.
 - c. Unless otherwise stated herein, this special permit consists of the special permit authorization letter issued to the grantee together with this document.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR § 177.835(c)(3) in that Division 1.1 explosives may not be loaded into or carried on any vehicle in a combination with a cargo tank containing material required to be placarded under § 177.823 (i.e., Combustible liquid, n.o.s.), except as specified herein; § 177.848(e)(2), in that transportation of Division 1.1, 1.4 and 1.5 explosives with Division 5.1 and/or Class 8 materials on the same motor vehicle is not authorized, except as specified herein; and § 173.848(g)(3) in that detonators and detonator assemblies are not authorized to be transported on the same motor vehicle with other Class 1 explosives, except as specified herein.

February 24, 2009

5. BASIS: This special permit is based on the Pipeline and Hazardous Materials Safety Administration's (PHMSA) editorial review under § 107.121 initiated on December 4, 2008.
6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Hazardous Materials Description			
Proper Shipping Name	Hazard Class/ Division	Identification Number	Packing Group
Acetic acid solution, <i>not less than 50 percent but not more than 80 percent, by mass</i>	8	UN2790	II
Acetic acid solution <i>not less than 10 percent but not more than 50 percent, by mass</i>	8	UN2790	III
Ammonium nitrate	5.1	UN1942	III
Ammonium nitrate based fertilizer	5.1	UN2067	III
Ammonium nitrate emulsion or Ammonium nitrate suspension or Ammonium nitrate gel, <i>intermediate for blasting explosives</i>	5.1	UN3375	II
Ammonium nitrate-fuel oil mixture <i>containing only prilled ammonium nitrate and fuel oil</i>	1.5D	NA0331	II
Articles, explosive, n.o.s.	1.4S	UN0349	II
Boosters, <i>without detonator</i>	1.1D	UN0042	II
Combustible liquid, n.o.s.	Combustible	NA1993	III
Cord, detonating, <i>flexible</i>	1.1D	UN0065	II
Cord, detonating, <i>flexible</i>	1.4D	UN0289	II

February 24, 2009

Hazardous Materials Description			
Proper Shipping Name	Hazard Class/ Division	Identification Number	Packing Group
Corrosive liquid, acidic, organic, n.o.s.	8	UN3265	II
Detonator assemblies, non-electric, <i>for blasting</i>	1.1B 1.4B	UN0360 UN0361	II II
Detonators, electric, <i>for blasting</i>	1.1B 1.4B	UN0030 UN0255	II II
Explosive, blasting, type A	1.1D	UN0081	II
Explosive, blasting, Type B or Agent Blasting, Type B	1.5D	UN0331	II
Explosive, blasting, Type E or Agent Blasting, Type E	1.1D 1.5D	UN0241 UN0332	II
Oxidizing liquid, n.o.s.*	5.1	UN2426	II
Oxidizing liquid, n.o.s.*	5.1	UN3139	III
Oxidizing solid, n.o.s.*	5.1	UN1479	
Nitrites, inorganic, aqueous solution, n.o.s.	5.1	UN3219	II

* These oxidizing substances shall not meet the definition for UN3375 Ammonium nitrate emulsions, suspension or gels as given in 49 CFR Section 172.101(c) Table Special Provision 147.

NOTE: Other blasting explosives and oxidizers must be specifically identified to, and acknowledged in writing, by the Office of Hazardous Materials Special Permits and Approvals (OHMSPA) prior to the first shipment.

February 24, 2009

7. SAFETY CONTROL MEASURES:

a. PACKAGING - Prescribed packagings are as follows:

(1) The following packagings are authorized for the Class 8 and UN3219 hazardous materials:

(i) Non-DOT specification metal containers shown in Dyno Nobel's Drawing Nos. YAT12005B, 321298, 321299 and AYC691 appended to the October 25, 1995 application and Dyno Nobel's Drawing Nos. 310082, 310083 and 310084 appended to the March 20, 2001 application, Tread Corporation Drawing No. P1338T, Rev. B dated December 2, 1996 appended to the March 2001 application for DOT-E 12677, and Tread UniBody Series 3216-US06, Drawing No. UU1001A02 dated August 22, 2003 appended to this application all of which are suitable for the transportation of UN3265 and UN3219, Packing Group II liquids. Drawings are on file with the Office of Hazardous Materials Special Permits and Approvals (OHMSPA).

(ii) Non-DOT specification metal containers of similar design which have been authorized in writing by the Associate Administrator for Hazardous Materials Safety prior to first shipment may also be used.

The metal containers must have a net volumetric capacity of not more than 450 liters (119 gallons) and must be permanently mounted in the motor vehicle cargo area. The container may not have a common wall with other compartments or tanks containing Class 1 explosive materials, combustible liquids, Division 5.1 liquid oxidizing materials, Division 5.1 oxidizing solids.

(2) The following packagings are authorized for the Division 1.5D explosive materials and those Division 5.1 ammonium nitrate emulsions, suspensions or gels which have been specifically authorized by OHMSPA for shipment in bulk under this special permit:

(i) DOT 406, DOT 407, DOT 412, MC 306, MC 307 and MC 312 cargo tank motor vehicles.

February 24, 2009

(ii) UN31A, UN31B or UN31H intermediate bulk containers.

(iii) DOT Specification IM-102 portable tanks and DOT Specification IM 101 portable tanks equipped with relief devices specified for IM-102 portable tanks so that the effective maximum allowable working pressure of the tank will not exceed 1.75 bars (25.4 psig).

(iv) Non-DOT specification compartmented cargo tanks suitable for transportation of UN0332 liquid blasting explosives and UN3139 and UN3375 liquid oxidizers. All non-DOT specification cargo tanks must be equipped with pressure relief systems meeting the requirements of §§ 178.346-3 or 178.347-4.

(3) Combustible liquids (NA1993) must be packaged in DOT Specification cargo tanks, non-DOT specification cargo tanks, or non-pressure capable tanks suitable for liquids (fuel oil) having a capacity not to exceed 350 gallons.

(4) The Division 1.1D and 1.4D, 1.5D, and 1.4S explosives must be packaged as prescribed in the § 173.62(c) Table according to their UN number and overpacked in an IME Safety Library Publication 22 (IME SLP-22) container or compartment.

(5) The Division 1.1B and 1.4B electric detonators and non-electric detonator assemblies must be packaged according to § 173.63(f) or (g) in a separate IME SLP-22 container or compartment.

(6) Division 1.5D Ammonium nitrate-fuel oil mixture (NA0331) as well as Division 5.1 Ammonium nitrate (UN1942), Ammonium nitrate based fertilizer (UN2067) and Oxidizing solid, n.o.s. (UN1479) shall be packaged in sift-proof, non-pressure capable cargo bins suitable for transport of Packing Group II solids.

February 24, 2009

b. TESTING -

(1) All DOT specification bulk packages must be tested and inspected as specified in 49 CFR PART 180, Subparts D, E or G as appropriate.

(2) All non-DOT specification cargo tanks must be tested and inspected in accordance with the requirements for MC 306 cargo tanks in 49 CFR PART 180, Subpart E. A copy of the test results must be carried on the motor vehicle.

(3) Tanks or compartments that are non-pressure capable must be annually leak tested with water or the material to be transported without external pressure. Tanks or compartments must show no signs of leakage at filled volume capacity for at least five minutes. Leakage of any nature requires further inspection and repair before use under the terms of this special permit.

c. OPERATIONAL CONTROLS -

(1) Transportation is limited to private carriage by company owned or leased vehicles, private carriage by wholly-owned subsidiary companies, or contract carriers specifically identified to, and acknowledged in writing by OHMSPA prior to first shipment.

(2) The IME SLP-22 container(s) or compartment(s) must be located either directly behind the cab or under the chassis deck. The IME SLP-22 container(s) or compartment(s) which are transporting Division 1.1B, 1.4B or 1.4S electric or non-electric detonators and/or detonator assemblies must be on the opposite side of the vehicle from the IME SLP-22 container(s) or compartment(s) which are transporting Division 1.1D, 1.4D and 1.5D packaged explosives. An IME SLP-22 container(s) or compartment(s) may not share a common wall or be in direct contact with another IME SLP-22 container or compartment or a cargo tank, container or piping containing a hazardous material, except that IME SLP-22 containers as shown in the appended Tread Corporation Drawings S10150A01, dated August 11, 2005 or similar approved designs by the Associate Administrator for Hazardous Materials Safety.

February 24, 2009

(3) None of the materials in any cargo tank or container on the motor vehicle may be mixed, transferred or circulated while the vehicle is in transit on a public road or highway.

(4) The discharge valve for all tanks containing liquid or emulsion must be closed during transportation.

(5) Augers that are an integral part of the containers identified in 7(a)(6) may remain full of material while in transportation on public road or highway.

(6) NA1993 hazardous materials that are contained in process lines or pumps may be transported on public road or highway.

(7) UN3375, UN3239 and UN0332 hazardous materials that are contained in process lines and pumps that are included in a DOT specification cargo tank Leakage Test, may be transported on public road or highway, provided:

(i) pumps and lines are readily identifiable with a stainless steel tag attached to the pump indicating inspector and date that the pump, suction and discharge line (if applicable) were included in the Leakage Test; and

(ii) a label(s) are placed on the items tested in (i) above.

(8) All other process lines, discharge lines, chutes, surge hoppers, pumps or augers should be appropriately cleaned to minimize residue prior to transport on public roads or highways.

8. SPECIAL PROVISIONS:

a. A current copy of this special permit must be maintained at each facility where the package is offered or reoffered for transportation.

b. The cargo compartment of the motor vehicle must be plainly and durably marked on both sides behind the cab section in letters and numbers at least 5 cm (2 inches) high on a contrasting background "DOT-SP 11579".

February 24, 2009

- c. All Class 1 materials and bulk packages of Division 5.1, Class 8 and Combustible liquids must be multi-placarded as specified in 49 CFR 172.500 or in accordance with the Institute of Manufacturers of Explosives "Bulk Truck Marking and Placarding Guide". All non-bulk packages of Class 8 and Division 5.1 must be marked and labeled as specified in 49 CFR §§ 172.300 and 172.400.
9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle and cargo vessel.
10. MODAL REQUIREMENTS:
- a. A current copy this special permit must be carried aboard each cargo vessel or motor vehicle used to transport the combinations of hazardous materials covered by this special permit.
- b. Drivers must have been instructed as to the necessary safeguards and proper procedures in the event of an unusual delay, fire, explosion or accident involving the hazardous materials covered by this special permit.
11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this special permit and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:
- o All terms and conditions prescribed in this special permit and the Hazardous Materials Regulations, 49 CFR Parts 171-180.
 - o Persons operating under the terms of this special permit must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.
 - o Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this special permit must receive training on the requirements and conditions of this special permit in addition to the training required by §§ 172.700 through 172.704. No person may use or apply this special permit, including display of its number, when this special permit has expired or is otherwise no longer in effect.

February 24, 2009

Under Title VII of the Safe, Accountable, Flexible, Efficient Transportation Equity Act: A Legacy for Users (SAFETEA-LU)- 'The Hazardous Materials Safety and Security Reauthorization Act of 2005' (Pub. L. 109-59), 119 Stat. 1144 (August 10, 2005), amended the Federal hazardous materials transportation law by changing the term "exemption" to "special permit" and authorizes a special permit to be granted up to two years for new special permits and up to four years for renewals.

12. REPORTING REQUIREMENTS: Shipments or operations conducted under this special permit are subject to the Hazardous Materials Incident Reporting requirements specified in 49 CFR §§ 171.15 - Immediate notice of certain hazardous materials incidents, and 171.16 - Detailed hazardous materials incident reports. In addition, the grantee(s) of this special permit must notify the Associate Administrator for Hazardous Materials Safety, in writing, of any incident involving a package, shipment or operation conducted under terms of this special permit.

Issued in Washington, D.C.



for Theodore L. Willke
Associate Administrator for Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Pipeline and Hazardous Materials Safety Administration, Department of Transportation, Washington, D.C. 20590. Attention: PHH-31.

Copies of this special permit may be obtained by accessing the Hazardous Materials Safety Homepage at http://hazmat.dot.gov/sp_app/special_permits/spec_perm_index.htm Photo reproductions and legible reductions of this special permit are permitted. Any alteration of this special permit is prohibited.

PO: SW/SS/CHH/sln