

## Environmental Protection Agency

## § 49.124

Coal and Coke, IBR approved for § 49.123(a).

(vi) ASTM E711-87(Reapproved 2004) Standard Test Method for Gross Calorific Value of Refuse-Derived Fuel by the Bomb Calorimeter, IBR approved for § 49.123(a).

(vii) ASTM D2880-03, Standard Specification for Gas Turbine Fuel Oils, IBR approved for § 49.130(e)(1).

(viii) ASTM D4294-03, Standard Test Method for Sulfur in Petroleum Products by Energy-Dispersive X-ray Fluorescence Spectroscopy, IBR approved for § 49.130(e)(1).

(ix) ASTM D6021-96(Reapproved 2001) <sup>1</sup>, Standard Test Method for Measurement of Total Hydrogen Sulfide in Residual Fuels by Multiple Headspace Extraction and Sulfur Specific Detection, IBR approved for § 49.130(e)(1).

(x) ASTM D3177-02, Standard Test Methods for Total Sulfur in the Analysis Sample of Coal and Coke, IBR approved for § 49.130(e)(2).

(xi) ASTM D4239-04a, Standard Test Methods for Sulfur in the Analysis Sample of Coal and Coke Using High Temperature Tube Furnace Combustion Methods, IBR approved for § 49.130(e)(2).

(xii) ASTM D2492-02, Standard Test Method for Forms of Sulfur in Coal, IBR approved for § 49.130(e)(2).

(xiii) ASTM E775-87(Reapproved 2004), Standard Test Methods for Total Sulfur in the Analysis Sample of Refuse-Derived Fuel, IBR approved for § 49.130(e)(3).

(xiv) ASTM D1072-90(Reapproved 1999), Standard Test Method for Total Sulfur in Fuel Gases, IBR approved for § 49.130(e)(4).

(xv) ASTM D3246-96, Standard Test Method for Sulfur in Petroleum Gas by Oxidative Microcoulometry, IBR approved for § 49.130(e)(4).

(xvi) ASTM D4084-94(Reapproved 1999) Standard Test Method for Analysis of Hydrogen Sulfide in Gaseous Fuels (Lead Acetate Reaction Rate Method), IBR approved for § 49.130(e)(4).

(xvii) ASTM D5504-01, Standard Test Method for Determination of Sulfur Compounds in Natural Gas and Gaseous Fuels by Gas Chromatography and Chemiluminescence, IBR approved for § 49.130(e)(4).

(xviii) ASTM D4468-85(Reapproved 2000), Standard Test Method for Total Sulfur in Gaseous Fuels by Hydrogenolysis and Rateometric Colorimetry, IBR approved for § 49.130(e)(4).

(xix) ASTM D2622-03, Standard Test Method for Sulfur in Petroleum Products by Wavelength Dispersive X-ray Fluorescence Spectrometry, IBR approved for § 49.130(e)(4).

(xx) ASTM D6228-98(Reapproved 2003), Standard Test Method for Determination of Sulfur Compounds in Natural Gas and Gaseous Fuels by Gas Chromatography and Flame Photometric Detection, IBR approved for § 49.130(e)(4).

### § 49.124 Rule for limiting visible emissions.

(a) *What is the purpose of this section?* This section limits the visible emissions of air pollutants from certain air pollution sources operating within the Indian reservation to control emissions of particulate matter to the atmosphere and ground-level concentrations of particulate matter, to detect the violation of other requirements in the "General Rules for Application to Indian Reservations in EPA Region 10", and to indicate whether a source is continuously maintained and properly operated.

(b) *Who is affected by this section?* This section applies to any person who owns or operates an air pollution source that emits, or could emit, particulate matter or other visible air pollutants to the atmosphere, unless exempted in paragraph (c) of this section.

(c) *What is exempted from this section?* This section does not apply to open burning, agricultural activities, forestry and silvicultural activities, non-commercial smoke houses, sweat houses or lodges, smudge pots, furnaces and boilers used exclusively to heat residential buildings with four or fewer dwelling units, fugitive dust from public roads owned or maintained by any Federal, Tribal, State, or local government, and emissions from fuel combustion in mobile sources.

(d) *What are the opacity limits for air pollution sources?* (1) The visible emissions from an air pollution source must not exceed 20% opacity, averaged over any consecutive six-minute period, unless paragraph (d)(2) or (d)(3) of this

section applies to the air pollution source.

(2) The visible emissions from an air pollution source may exceed the 20% opacity limit if the owner or operator of the air pollution source demonstrates to the Regional Administrator's satisfaction that the presence of uncombined water, such as steam, is the only reason for the failure of an air pollution source to meet the 20% opacity limit.

(3) The visible emissions from an oil-fired boiler or solid fuel-fired boiler that continuously measures opacity with a continuous opacity monitoring system (COMS) may exceed the 20% opacity limit during start-up, soot blowing, and grate cleaning for a single period of up to 15 consecutive minutes in any eight consecutive hours, but must not exceed 60% opacity at any time.

(e) *What is the reference method for determining compliance?* (1) The reference method for determining compliance with the opacity limits is EPA Method 9. A complete description of this method is found in appendix A of 40 CFR part 60.

(2) An alternative reference method for determining compliance is a COMS that complies with Performance Specification 1 found in appendix B of 40 CFR part 60.

(f) *Definitions of terms used in this section.* The following terms that are used in this section, are defined in § 49.123 General provisions: Act, agricultural activities, air pollutant, air pollution source, ambient air, coal, continuous opacity monitoring system (COMS), distillate fuel oil, emission, forestry or silvicultural activities, fuel, fuel oil, fugitive dust, gaseous fuel, grate cleaning, marine vessel, mobile sources, motor vehicle, nonroad engine, nonroad vehicle, oil-fired boiler, opacity, open burning, particulate matter, PM10, PM2.5, reference method, refuse, Regional Administrator, residual fuel oil, smudge pot, solid fuel, solid fuel-fired boiler, soot blowing, stack, standard conditions, start-up, stationary source, uncombined water, used oil, visible emissions, and wood.

**§ 49.125 Rule for limiting the emissions of particulate matter.**

(a) *What is the purpose of this section?* This section limits the amount of particulate matter that may be emitted from certain air pollution sources operating within the Indian reservation to control ground-level concentrations of particulate matter.

(b) *Who is affected by this section?* This section applies to any person who owns or operates an air pollution source that emits, or could emit, particulate matter to the atmosphere, unless exempted in paragraph (c) of this section.

(c) *What is exempted from this section?* This section does not apply to woodwaste burners, furnaces and boilers used exclusively for space heating with a rated heat input capacity of less than 400,000 British thermal units (Btu) per hour, non-commercial smoke houses, sweat houses or lodges, open burning, and mobile sources.

(d) *What are the particulate matter limits for air pollution sources?* (1) Particulate matter emissions from a combustion source stack (except for wood-fired boilers) must not exceed an average of 0.23 grams per dry standard cubic meter (0.1 grains per dry standard cubic foot), corrected to seven percent oxygen, during any three-hour period.

(2) Particulate matter emissions from a wood-fired boiler stack must not exceed an average of 0.46 grams per dry standard cubic meter (0.2 grains per dry standard cubic foot), corrected to seven percent oxygen, during any three-hour period.

(3) Particulate matter emissions from a process source stack, or any other stack not subject to paragraph (d)(1) or (d)(2) of this section, must not exceed an average of 0.23 grams per dry standard cubic meter (0.1 grains per dry standard cubic foot) during any three-hour period.

(e) *What is the reference method for determining compliance?* The reference method for determining compliance with the particulate matter limits is EPA Method 5. A complete description of this method is found in appendix A of 40 CFR part 60.

(f) *Definitions of terms used in this section.* The following terms that are used in this section are defined in § 49.123