

Automotive Engineering that we have incorporated by reference. The first column lists the number and name of the material. The second column lists the sections of this part where we reference it. Anyone may purchase copies of these materials from the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096. Table 2 follows:

TABLE 2 OF § 1039.810—SAE MATERIALS

Document number and name	Part 1039 reference
SAE J1930, Electrical/Electronic Systems Diagnostic Terms, Definitions, Abbreviations, and Acronyms, revised May 1998 ...	1039.135

**§ 1039.815 What provisions apply to confidential information?**

(a) Clearly show what you consider confidential by marking, circling, bracketing, stamping, or some other method.

(b) We will store your confidential information as described in 40 CFR part 2. Also, we will disclose it only as specified in 40 CFR part 2. This applies both to any information you send us and to

any information we collect from inspections, audits, or other site visits.

(c) If you send us a second copy without the confidential information, we will assume it contains nothing confidential whenever we need to release information from it.

(d) If you send us information without claiming it is confidential, we may make it available to the public without further notice to you, as described in 40 CFR 2.204.

**§ 1039.820 How do I request a hearing?**

(a) You may request a hearing under certain circumstances, as described elsewhere in this part. To do this, you must file a written request, including a description of your objection and any supporting data, within 30 days after we make a decision.

(b) For a hearing you request under the provisions of this part, we will approve your request if we find that your request raises a substantial factual issue.

(c) If we agree to hold a hearing, we will use the procedures specified in 40 CFR part 1068, subpart G.

APPENDIX I TO PART 1039 [RESERVED]

APPENDIX II TO PART 1039—STEADY-STATE DUTY CYCLES FOR CONSTANT-SPEED ENGINES

(a) The following duty cycle applies for discrete-mode testing of constant-speed engines:

D2 mode number	Engine speed <sup>1</sup>	Torque (percent) <sup>2</sup>	Weighting factors
1	Maximum test speed	100	0.05
2	Maximum test speed	75	0.25
3	Maximum test speed	50	0.30
4	Maximum test speed	25	0.30
5	Maximum test speed	10	0.10

<sup>1</sup> Maximum test speed is defined in 40 CFR part 1065.

<sup>2</sup> Except as noted in § 1039.505, the percent torque is relative to maximum test torque.

(b) The following duty cycle applies for ramped-modal testing of constant-speed engines:

RMC mode	Time in mode (seconds)	Engine speed	Torque (percent) <sup>1,2</sup>
1a Steady-state	53	Engine Governed	100.
1b Transition	20	Engine Governed	Linear transition.
2a Steady-state	101	Engine Governed	10.
2b Transition	20	Engine Governed	Linear transition.
3a Steady-state	277	Engine Governed	75.
3b Transition	20	Engine Governed	Linear transition.
4a Steady-state	339	Engine Governed	25.
4b Transition	20	Engine Governed	Linear transition.
5 Steady-state	350	Engine Governed	50.

<sup>1</sup> The percent torque is relative to maximum test torque.

<sup>2</sup> Advance from one mode to the next within a 20-second transition phase. During the transition phase, command a linear progression from the torque setting of the current mode to the torque setting of the next mode.

APPENDIX III TO PART 1039—STEADY-STATE DUTY CYCLES FOR VARIABLE-SPEED ENGINES WITH MAXIMUM POWER BELOW 19 kW

(a) The following duty cycle applies for discrete-mode testing of variable-speed engines with maximum power below 19 kW:

G2 mode number	Engine speed <sup>1</sup>	Observed torque (percent) <sup>2</sup>	Weighting factors
1 .....	Maximum test speed .....	100	0.09
2 .....	Maximum test speed .....	75	0.20
3 .....	Maximum test speed .....	50	0.29
4 .....	Maximum test speed .....	25	0.30
5 .....	Maximum test speed .....	10	0.07
6 .....	Idle .....	0	0.05

<sup>1</sup> Speed terms are defined in 40 CFR part 1065.

<sup>2</sup> The percent torque is relative to the maximum torque at the commanded test speed.

(b) The following duty cycle applies for ramped-modal testing of variable-speed engines with maximum power below 19 kW:

RMC mode	Time in mode (seconds)	Engine speed <sup>1,3</sup>	Torque (percent) <sup>2,3</sup>
1a Steady-state .....	41	Warm Idle .....	0.
1b Transition .....	20	Linear transition .....	Linear transition.
2a Steady-state .....	135	Maximum Test Speed .....	100.
2b Transition .....	20	Maximum Test Speed .....	Linear transition.
3a Steady-state .....	112	Maximum Test Speed .....	10.
3b Transition .....	20	Maximum Test Speed .....	Linear transition.
4a Steady-state .....	337	Maximum Test Speed .....	75.
4b Transition .....	20	Maximum Test Speed .....	Linear transition.
5a Steady-state .....	518	Maximum Test Speed .....	25.
5b Transition .....	20	Maximum Test Speed .....	Linear transition.
6a Steady-state .....	494	Maximum Test Speed .....	50.
6b Transition .....	20	Linear transition .....	Linear transition.
7 Steady-state .....	43	Warm Idle .....	0.

<sup>1</sup> Speed terms are defined in 40 CFR part 1065.

<sup>2</sup> The percent torque is relative to the maximum torque at the commanded engine speed.

<sup>3</sup> Advance from one mode to the next within a 20-second transition phase. During the transition phase, command a linear progression from the torque setting of the current mode to the torque setting of the next mode, and simultaneously command a similar linear progression for engine speed if there is a change in speed setting.

APPENDIX IV TO PART 1039—STEADY-STATE DUTY CYCLES FOR VARIABLE-SPEED ENGINES WITH MAXIMUM POWER AT OR ABOVE 19 kW

(a) The following duty cycle applies for discrete-mode testing of variable-speed engines with maximum power at or above 19 kW:

C1 mode number	Engine speed <sup>1</sup>	Observed torque (percent) <sup>2</sup>	Weighting factors
1 .....	Maximum test speed .....	100	0.15
2 .....	Maximum test speed .....	75	0.15
3 .....	Maximum test speed .....	50	0.15
4 .....	Maximum test speed .....	10	0.10
5 .....	Intermediate test speed .....	100	0.10
6 .....	Intermediate test speed .....	75	0.10
7 .....	Intermediate test speed .....	50	0.10
8 .....	Idle .....	0	0.15

<sup>1</sup> Speed terms are defined in 40 CFR part 1065.

<sup>2</sup> The percent torque is relative to the maximum torque at the commanded test speed.

(b) The following duty cycle applies for ramped-modal testing of variable-speed engines with maximum power at or above 19 kW:

RMC Mode	Time in mode (seconds)	Engine speed <sup>1,3</sup>	Torque (percent) <sup>2,3</sup>
1a Steady-state .....	126	Warm Idle .....	0.
1b Transition .....	20	Linear Transition <sup>2</sup> .....	Linear Transition.
2a Steady-state .....	159	Intermediate Speed .....	100.
2b Transition .....	20	Intermediate Speed .....	Linear Transition.
3a Steady-state .....	160	Intermediate Speed .....	50.
3b Transition .....	20	Intermediate Speed .....	Linear Transition.
4a Steady-state .....	162	Intermediate Speed .....	75.
4b Transition .....	20	Linear Transition .....	Linear Transition.
5a Steady-state .....	246	Maximum Test Speed .....	100.
5b Transition .....	20	Maximum Test Speed .....	Linear Transition.
6a Steady-state .....	164	Maximum Test Speed .....	10.
6b Transition .....	20	Maximum Test Speed .....	Linear Transition.
7a Steady-state .....	248	Maximum Test Speed .....	75.
7b Transition .....	20	Maximum Test Speed .....	Linear Transition.
8a Steady-state .....	247	Maximum Test Speed .....	50.
8b Transition .....	20	Linear Transition .....	Linear Transition.
9 Steady-state .....	128	Warm Idle .....	0.

<sup>1</sup> Speed terms are defined in 40 CFR part 1065.

<sup>2</sup> The percent torque is relative to the maximum torque at the commanded engine speed.

<sup>3</sup> Advance from one mode to the next within a 20-second transition phase. During the transition phase, command a linear progression from the torque setting of the current mode to the torque setting of the next mode, and simultaneously command a similar linear progression for engine speed if there is a change in speed setting.

APPENDIX V TO PART 1039 [RESERVED]

APPENDIX VI TO PART 1039—NONROAD  
COMPRESSION-IGNITION COMPOSITE  
TRANSIENT CYCLE

Time(s)	Normalized speed (percent)	Normalized torque (percent) <sup>1</sup>
1 .....	0	0
2 .....	0	0
3 .....	0	0
4 .....	0	0
5 .....	0	0
6 .....	0	0
7 .....	0	0
8 .....	0	0
9 .....	0	0
10 .....	0	0
11 .....	0	0
12 .....	0	0
13 .....	0	0
14 .....	0	0
15 .....	0	0
16 .....	0	0
17 .....	0	0
18 .....	0	0
19 .....	0	0
20 .....	0	0
21 .....	0	0
22 .....	0	0
23 .....	0	0
24 .....	1	3
25 .....	1	3
26 .....	1	3
27 .....	1	3
28 .....	1	3
29 .....	1	3
30 .....	1	6
31 .....	1	6
32 .....	2	1
33 .....	4	13
34 .....	7	18
35 .....	9	21
36 .....	17	20
37 .....	33	42

Time(s)	Normalized speed (percent)	Normalized torque (percent) <sup>1</sup>
38 .....	57	46
39 .....	44	33
40 .....	31	0
41 .....	22	27
42 .....	33	43
43 .....	80	49
44 .....	105	47
45 .....	98	70
46 .....	104	36
47 .....	104	65
48 .....	96	71
49 .....	101	62
50 .....	102	51
51 .....	102	50
52 .....	102	46
53 .....	102	41
54 .....	102	31
55 .....	89	2
56 .....	82	0
57 .....	47	1
58 .....	23	1
59 .....	1	3
60 .....	1	8
61 .....	1	3
62 .....	1	5
63 .....	1	6
64 .....	1	4
65 .....	1	4
66 .....	0	6
67 .....	1	4
68 .....	9	21
69 .....	25	56
70 .....	64	26
71 .....	60	31
72 .....	63	20
73 .....	62	24
74 .....	64	8
75 .....	58	44
76 .....	65	10
77 .....	65	12
78 .....	68	23
79 .....	69	30
80 .....	71	30
81 .....	74	15

Time(s)	Normalized speed (percent)	Normalized torque (percent) <sup>1</sup>	Time(s)	Normalized speed (percent)	Normalized torque (percent) <sup>1</sup>
82	71	23	154	15	6
83	73	20	155	39	47
84	73	21	156	39	4
85	73	19	157	35	26
86	70	33	158	27	38
87	70	34	159	43	40
88	65	47	160	14	23
89	66	47	161	10	10
90	64	53	162	15	33
91	65	45	163	35	72
92	66	38	164	60	39
93	67	49	165	55	31
94	69	39	166	47	30
95	69	39	167	16	7
96	66	42	168	0	6
97	71	29	169	0	8
98	75	29	170	0	8
99	72	23	171	0	2
100	74	22	172	2	17
101	75	24	173	10	28
102	73	30	174	28	31
103	74	24	175	33	30
104	77	6	176	36	0
105	76	12	177	19	10
106	74	39	178	1	18
107	72	30	179	0	16
108	75	22	180	1	3
109	78	64	181	1	4
110	102	34	182	1	5
111	103	28	183	1	6
112	103	28	184	1	5
113	103	19	185	1	3
114	103	32	186	1	4
115	104	25	187	1	4
116	103	38	188	1	6
117	103	39	189	8	18
118	103	34	190	20	51
119	102	44	191	49	19
120	103	38	192	41	13
121	102	43	193	31	16
122	103	34	194	28	21
123	102	41	195	21	17
124	103	44	196	31	21
125	103	37	197	21	8
126	103	27	198	0	14
127	104	13	199	0	12
128	104	30	200	3	8
129	104	19	201	3	22
130	103	28	202	12	20
131	104	40	203	14	20
132	104	32	204	16	17
133	101	63	205	20	18
134	102	54	206	27	34
135	102	52	207	32	33
136	102	51	208	41	31
137	103	40	209	43	31
138	104	34	210	37	33
139	102	36	211	26	18
140	104	44	212	18	29
141	103	44	213	14	51
142	104	33	214	13	11
143	102	27	215	12	9
144	103	26	216	15	33
145	79	53	217	20	25
146	51	37	218	25	17
147	24	23	219	31	29
148	13	33	220	36	66
149	19	55	221	66	40
150	45	30	222	50	13
151	34	7	223	16	24
152	14	4	224	26	50
153	8	16	225	64	23

Environmental Protection Agency

Pt. 1039, App. VI

Time(s)	Normalized speed (percent)	Normalized torque (percent) <sup>1</sup>	Time(s)	Normalized speed (percent)	Normalized torque (percent) <sup>1</sup>
226	81	20	298	53	31
227	83	11	299	51	24
228	79	23	300	48	40
229	76	31	301	39	0
230	68	24	302	35	18
231	59	33	303	36	16
232	59	3	304	29	17
233	25	7	305	28	21
234	21	10	306	31	15
235	20	19	307	31	10
236	4	10	308	43	19
237	5	7	309	49	63
238	4	5	310	78	61
239	4	6	311	78	46
240	4	6	312	66	65
241	4	5	313	78	97
242	7	5	314	84	63
243	16	28	315	57	26
244	28	25	316	36	22
245	52	53	317	20	34
246	50	8	318	19	8
247	26	40	319	9	10
248	48	29	320	5	5
249	54	39	321	7	11
250	60	42	322	15	15
251	48	18	323	12	9
252	54	51	324	13	27
253	88	90	325	15	28
254	103	84	326	16	28
255	103	85	327	16	31
256	102	84	328	15	20
257	58	66	329	17	0
258	64	97	330	20	34
259	56	80	331	21	25
260	51	67	332	20	0
261	52	96	333	23	25
262	63	62	334	30	58
263	71	6	335	63	96
264	33	16	336	83	60
265	47	45	337	61	0
266	43	56	338	26	0
267	42	27	339	29	44
268	42	64	340	68	97
269	75	74	341	80	97
270	68	96	342	88	97
271	86	61	343	99	88
272	66	0	344	102	86
273	37	0	345	100	82
274	45	37	346	74	79
275	68	96	347	57	79
276	80	97	348	76	97
277	92	96	349	84	97
278	90	97	350	86	97
279	82	96	351	81	98
280	94	81	352	83	83
281	90	85	353	65	96
282	96	65	354	93	72
283	70	96	355	63	60
284	55	95	356	72	49
285	70	96	357	56	27
286	79	96	358	29	0
287	81	71	359	18	13
288	71	60	360	25	11
289	92	65	361	28	24
290	82	63	362	34	53
291	61	47	363	65	83
292	52	37	364	80	44
293	24	0	365	77	46
294	20	7	366	76	50
295	39	48	367	45	52
296	39	54	368	61	98
297	63	58	369	61	69

Time(s)	Normalized speed (percent)	Normalized torque (percent) <sup>1</sup>	Time(s)	Normalized speed (percent)	Normalized torque (percent) <sup>1</sup>
370	63	49	442	88	72
371	32	0	443	88	72
372	10	8	444	84	72
373	17	7	445	83	73
374	16	13	446	77	73
375	11	6	447	74	73
376	9	5	448	76	72
377	9	12	449	46	77
378	12	46	450	78	62
379	15	30	451	79	35
380	26	28	452	82	38
381	13	9	453	81	41
382	16	21	454	79	37
383	24	4	455	78	35
384	36	43	456	78	38
385	65	85	457	78	46
386	78	66	458	75	49
387	63	39	459	73	50
388	32	34	460	79	58
389	46	55	461	79	71
390	47	42	462	83	44
391	42	39	463	53	48
392	27	0	464	40	48
393	14	5	465	51	75
394	14	14	466	75	72
395	24	54	467	89	67
396	60	90	468	93	60
397	53	66	469	89	73
398	70	48	470	86	73
399	77	93	471	81	73
400	79	67	472	78	73
401	46	65	473	78	73
402	69	98	474	76	73
403	80	97	475	79	73
404	74	97	476	82	73
405	75	98	477	86	73
406	56	61	478	88	72
407	42	0	479	92	71
408	36	32	480	97	54
409	34	43	481	73	43
410	68	83	482	36	64
411	102	48	483	63	31
412	62	0	484	78	1
413	41	39	485	69	27
414	71	86	486	67	28
415	91	52	487	72	9
416	89	55	488	71	9
417	89	56	489	78	36
418	88	58	490	81	56
419	78	69	491	75	53
420	98	39	492	60	45
421	64	61	493	50	37
422	90	34	494	66	41
423	88	38	495	51	61
424	97	62	496	68	47
425	100	53	497	29	42
426	81	58	498	24	73
427	74	51	499	64	71
428	76	57	500	90	71
429	76	72	501	100	61
430	85	72	502	94	73
431	84	60	503	84	73
432	83	72	504	79	73
433	83	72	505	75	72
434	86	72	506	78	73
435	89	72	507	80	73
436	86	72	508	81	73
437	87	72	509	81	73
438	88	72	510	83	73
439	88	71	511	85	73
440	87	72	512	84	73
441	85	71	513	85	73

Environmental Protection Agency

Pt. 1039, App. VI

Time(s)	Normalized speed (percent)	Normalized torque (percent) <sup>1</sup>	Time(s)	Normalized speed (percent)	Normalized torque (percent) <sup>1</sup>
514	86	73	586	77	29
515	85	73	587	81	72
516	85	73	588	89	69
517	85	72	589	49	56
518	85	73	590	79	70
519	83	73	591	104	59
520	79	73	592	103	54
521	78	73	593	102	56
522	81	73	594	102	56
523	82	72	595	103	61
524	94	56	596	102	64
525	66	48	597	103	60
526	35	71	598	93	72
527	51	44	599	86	73
528	60	23	600	76	73
529	64	10	601	59	49
530	63	14	602	46	22
531	70	37	603	40	65
532	76	45	604	72	31
533	78	18	605	72	27
534	76	51	606	67	44
535	75	33	607	68	37
536	81	17	608	67	42
537	76	45	609	68	50
538	76	30	610	77	43
539	80	14	611	58	4
540	71	18	612	22	37
541	71	14	613	57	69
542	71	11	614	68	38
543	65	2	615	73	2
544	31	26	616	40	14
545	24	72	617	42	38
546	64	70	618	64	69
547	77	62	619	64	74
548	80	68	620	67	73
549	83	53	621	65	73
550	83	50	622	68	73
551	83	50	623	65	49
552	85	43	624	81	0
553	86	45	625	37	25
554	89	35	626	24	69
555	82	61	627	68	71
556	87	50	628	70	71
557	85	55	629	76	70
558	89	49	630	71	72
559	87	70	631	73	69
560	91	39	632	76	70
561	72	3	633	77	72
562	43	25	634	77	72
563	30	60	635	77	72
564	40	45	636	77	70
565	37	32	637	76	71
566	37	32	638	76	71
567	43	70	639	77	71
568	70	54	640	77	71
569	77	47	641	78	70
570	79	66	642	77	70
571	85	53	643	77	71
572	83	57	644	79	72
573	86	52	645	78	70
574	85	51	646	80	70
575	70	39	647	82	71
576	50	5	648	84	71
577	38	36	649	83	71
578	30	71	650	83	73
579	75	53	651	81	70
580	84	40	652	80	71
581	85	42	653	78	71
582	86	49	654	76	70
583	86	57	655	76	70
584	89	68	656	76	71
585	99	61	657	79	71

Time(s)	Normalized speed (percent)	Normalized torque (percent) <sup>1</sup>	Time(s)	Normalized speed (percent)	Normalized torque (percent) <sup>1</sup>
658	78	71	730	103	32
659	81	70	731	102	50
660	83	72	732	103	30
661	84	71	733	103	44
662	86	71	734	102	40
663	87	71	735	103	43
664	92	72	736	103	41
665	91	72	737	102	46
666	90	71	738	103	39
667	90	71	739	102	41
668	91	71	740	103	41
669	90	70	741	102	38
670	90	72	742	103	39
671	91	71	743	102	46
672	90	71	744	104	46
673	90	71	745	103	49
674	92	72	746	102	45
675	93	69	747	103	42
676	90	70	748	103	46
677	93	72	749	103	38
678	91	70	750	102	48
679	89	71	751	103	35
680	91	71	752	102	48
681	90	71	753	103	49
682	90	71	754	102	48
683	92	71	755	102	46
684	91	71	756	103	47
685	93	71	757	102	49
686	93	68	758	102	42
687	98	68	759	102	52
688	98	67	760	102	57
689	100	69	761	102	55
690	99	68	762	102	61
691	100	71	763	102	61
692	99	68	764	102	58
693	100	69	765	103	58
694	102	72	766	102	59
695	101	69	767	102	54
696	100	69	768	102	63
697	102	71	769	102	61
698	102	71	770	103	55
699	102	69	771	102	60
700	102	71	772	102	72
701	102	68	773	103	56
702	100	69	774	102	55
703	102	70	775	102	67
704	102	68	776	103	56
705	102	70	777	84	42
706	102	72	778	48	7
707	102	68	779	48	6
708	102	69	780	48	6
709	100	68	781	48	7
710	102	71	782	48	6
711	101	64	783	48	7
712	102	69	784	67	21
713	102	69	785	105	59
714	101	69	786	105	96
715	102	64	787	105	74
716	102	69	788	105	66
717	102	68	789	105	62
718	102	70	790	105	66
719	102	69	791	89	41
720	102	70	792	52	5
721	102	70	793	48	5
722	102	62	794	48	7
723	104	38	795	48	5
724	104	15	796	48	6
725	102	24	797	48	4
726	102	45	798	52	6
727	102	47	799	51	5
728	104	40	800	51	6
729	101	52	801	51	6



Environmental Protection Agency

Pt. 1039, App. VI

Time(s)	Normalized speed (percent)	Normalized torque (percent) <sup>1</sup>	Time(s)	Normalized speed (percent)	Normalized torque (percent) <sup>1</sup>
802	52	5	874	83	6
803	52	5	875	83	6
804	57	44	876	83	6
805	98	90	877	83	6
806	105	94	878	59	4
807	105	100	879	50	5
808	105	98	880	51	5
809	105	95	881	51	5
810	105	96	882	51	5
811	105	92	883	50	5
812	104	97	884	50	5
813	100	85	885	50	5
814	94	74	886	50	5
815	87	62	887	50	5
816	81	50	888	51	5
817	81	46	889	51	5
818	80	39	890	51	5
819	80	32	891	63	50
820	81	28	892	81	34
821	80	26	893	81	25
822	80	23	894	81	29
823	80	23	895	81	23
824	80	20	896	80	24
825	81	19	897	81	24
826	80	18	898	81	28
827	81	17	899	81	27
828	80	20	900	81	22
829	81	24	901	81	19
830	81	21	902	81	17
831	80	26	903	81	17
832	80	24	904	81	17
833	80	23	905	81	15
834	80	22	906	80	15
835	81	21	907	80	28
836	81	24	908	81	22
837	81	24	909	81	24
838	81	22	910	81	19
839	81	22	911	81	21
840	81	21	912	81	20
841	81	31	913	83	26
842	81	27	914	80	63
843	80	26	915	80	59
844	80	26	916	83	100
845	81	25	917	81	73
846	80	21	918	83	53
847	81	20	919	80	76
848	83	21	920	81	61
849	83	15	921	80	50
850	83	12	922	81	37
851	83	9	923	82	49
852	83	8	924	83	37
853	83	7	925	83	25
854	83	6	926	83	17
855	83	6	927	83	13
856	83	6	928	83	10
857	83	6	929	83	8
858	83	6	930	83	7
859	76	5	931	83	7
860	49	8	932	83	6
861	51	7	933	83	6
862	51	20	934	83	6
863	78	52	935	71	5
864	80	38	936	49	24
865	81	33	937	69	64
866	83	29	938	81	50
867	83	22	939	81	43
868	83	16	940	81	42
869	83	12	941	81	31
870	83	9	942	81	30
871	83	8	943	81	35
872	83	7	944	81	28
873	83	6	945	81	27

Pt. 1039, App. VI

40 CFR Ch. I (7-1-07 Edition)

Time(s)	Normalized speed (percent)	Normalized torque (percent) <sup>1</sup>	Time(s)	Normalized speed (percent)	Normalized torque (percent) <sup>1</sup>
946	80	27	1018	80	36
947	81	31	1019	81	26
948	81	41	1020	86	18
949	81	41	1021	82	35
950	81	37	1022	79	53
951	81	43	1023	82	30
952	81	34	1024	83	29
953	81	31	1025	83	32
954	81	26	1026	83	28
955	81	23	1027	76	60
956	81	27	1028	79	51
957	81	38	1029	86	26
958	81	40	1030	82	34
959	81	39	1031	84	25
960	81	27	1032	86	23
961	81	33	1033	85	22
962	80	28	1034	83	26
963	81	34	1035	83	25
964	83	72	1036	83	37
965	81	49	1037	84	14
966	81	51	1038	83	39
967	80	55	1039	76	70
968	81	48	1040	78	81
969	81	36	1041	75	71
970	81	39	1042	86	47
971	81	38	1043	83	35
972	80	41	1044	81	43
973	81	30	1045	81	41
974	81	23	1046	79	46
975	81	19	1047	80	44
976	81	25	1048	84	20
977	81	29	1049	79	31
978	83	47	1050	87	29
979	81	90	1051	82	49
980	81	75	1052	84	21
981	80	60	1053	82	56
982	81	48	1054	81	30
983	81	41	1055	85	21
984	81	30	1056	86	16
985	80	24	1057	79	52
986	81	20	1058	78	60
987	81	21	1059	74	55
988	81	29	1060	78	84
989	81	29	1061	80	54
990	81	27	1062	80	35
991	81	23	1063	82	24
992	81	25	1064	83	43
993	81	26	1065	79	49
994	81	22	1066	83	50
995	81	20	1067	86	12
996	81	17	1068	64	14
997	81	23	1069	24	14
998	83	65	1070	49	21
999	81	54	1071	77	48
1000	81	50	1072	103	11
1001	81	41	1073	98	48
1002	81	35	1074	101	34
1003	81	37	1075	99	39
1004	81	29	1076	103	11
1005	81	28	1077	103	19
1006	81	24	1078	103	7
1007	81	19	1079	103	13
1008	81	16	1080	103	10
1009	80	16	1081	102	13
1010	83	23	1082	101	29
1011	83	17	1083	102	25
1012	83	13	1084	102	20
1013	83	27	1085	96	60
1014	81	58	1086	99	38
1015	81	60	1087	102	24
1016	81	46	1088	100	31
1017	80	41	1089	100	28

Environmental Protection Agency

Pt. 1039, App. VI

Time(s)	Normalized speed (percent)	Normalized torque (percent) <sup>1</sup>	Time(s)	Normalized speed (percent)	Normalized torque (percent) <sup>1</sup>
1090	98	3	1162	71	47
1091	102	26	1163	70	42
1092	95	64	1164	67	34
1093	102	23	1165	74	2
1094	102	25	1166	75	21
1095	98	42	1167	74	15
1096	93	68	1168	75	13
1097	101	25	1169	76	10
1098	95	64	1170	75	13
1099	101	35	1171	75	10
1100	94	59	1172	75	7
1101	97	37	1173	75	13
1102	97	60	1174	76	8
1103	93	98	1175	76	7
1104	98	53	1176	67	45
1105	103	13	1177	75	13
1106	103	11	1178	75	12
1107	103	11	1179	73	21
1108	103	13	1180	68	46
1109	103	10	1181	74	8
1110	103	10	1182	76	11
1111	103	11	1183	76	14
1112	103	10	1184	74	11
1113	103	10	1185	74	18
1114	102	18	1186	73	22
1115	102	31	1187	74	20
1116	101	24	1188	74	19
1117	102	19	1189	70	22
1118	103	10	1190	71	23
1119	102	12	1191	73	19
1120	99	56	1192	73	19
1121	96	59	1193	72	20
1122	74	28	1194	64	60
1123	66	62	1195	70	39
1124	74	29	1196	66	56
1125	64	74	1197	68	64
1126	69	40	1198	30	68
1127	76	2	1199	70	38
1128	72	29	1200	66	47
1129	66	65	1201	76	14
1130	54	69	1202	74	18
1131	69	56	1203	69	46
1132	69	40	1204	68	62
1133	73	54	1205	68	62
1134	63	92	1206	68	62
1135	61	67	1207	68	62
1136	72	42	1208	68	62
1137	78	2	1209	68	62
1138	76	34	1210	54	50
1139	67	80	1211	41	37
1140	70	67	1212	27	25
1141	53	70	1213	14	12
1142	72	65	1214	0	0
1143	60	57	1215	0	0
1144	74	29	1216	0	0
1145	69	31	1217	0	0
1146	76	1	1218	0	0
1147	74	22	1219	0	0
1148	72	52	1220	0	0
1149	62	96	1221	0	0
1150	54	72	1222	0	0
1151	72	28	1223	0	0
1152	72	35	1224	0	0
1153	64	68	1225	0	0
1154	74	27	1226	0	0
1155	76	14	1227	0	0
1156	69	38	1228	0	0
1157	66	59	1229	0	0
1158	64	99	1230	0	0
1159	51	86	1231	0	0
1160	70	53	1232	0	0
1161	72	36	1233	0	0

Time(s)	Normalized speed (percent)	Normalized torque (percent) <sup>1</sup>
1234 .....	0	0
1235 .....	0	0
1236 .....	0	0
1237 .....	0	0
1238 .....	0	0

<sup>1</sup>The percent torque is relative to maximum torque at the commanded engine speed.

[69 FR 39213, June 29, 2004, as amended at 70 FR 40465, July 13, 2005]

**PART 1048—CONTROL OF EMISSIONS FROM NEW, LARGE NONROAD SPARK-IGNITION ENGINES**

**Subpart A—Overview and Applicability**

- Sec.
- 1048.1 Does this part apply to me?
- 1048.5 Which engines are excluded from this part's requirements?
- 1048.10 How is this part organized?
- 1048.15 Do any other regulation parts affect me?
- 1048.20 What requirements from this part apply to excluded stationary engines?

**Subpart B—Emission Standards and Related Requirements**

- 1048.101 What exhaust emission standards must my engines meet?
- 1048.105 What evaporative emissions standards and requirements apply?
- 1048.110 How must my engines diagnose malfunctions?
- 1048.115 What other requirements must my engines meet?
- 1048.120 What warranty requirements apply to me?
- 1048.125 What maintenance instructions must I give to buyers?
- 1048.130 What installation instructions must I give to equipment manufacturers?
- 1048.135 How must I label and identify the engines I produce?
- 1048.140 What are the provisions for certifying Blue Sky Series engines?
- 1048.145 Are there interim provisions that apply only for a limited time?

**Subpart C—Certifying Engine Families**

- 1048.201 What are the general requirements for obtaining a certificate of conformity?
- 1048.205 What must I include in my application?
- 1048.210 May I get preliminary approval before I complete my application?
- 1048.220 How do I amend the maintenance instructions in my application?

- 1048.225 How do I amend my application for certification to include new or modified engines?
- 1048.230 How do I select engine families?
- 1048.235 What emission testing must I perform for my application for a certificate of conformity?
- 1048.240 How do I demonstrate that my engine family complies with exhaust emission standards?
- 1048.245 How do I demonstrate that my engine family complies with evaporative emission standards?
- 1048.250 What records must I keep and make available to EPA?
- 1048.255 When may EPA deny, revoke, or void my certificate of conformity?

**Subpart D—Testing Production-line Engines**

- 1048.301 When must I test my production-line engines?
- 1048.305 How must I prepare and test my production-line engines?
- 1048.310 How must I select engines for production-line testing?
- 1048.315 How do I know when my engine family fails the production-line testing requirements?
- 1048.320 What happens if one of my production-line engines fails to meet emission standards?
- 1048.325 What happens if an engine family fails the production-line requirements?
- 1048.330 May I sell engines from an engine family with a suspended certificate of conformity?
- 1048.335 How do I ask EPA to reinstate my suspended certificate?
- 1048.340 When may EPA revoke my certificate under this subpart and how may I sell these engines again?
- 1048.345 What production-line testing records must I send to EPA?
- 1048.350 What records must I keep?

**Subpart E—Testing In-use Engines**

- 1048.401 What testing requirements apply to my engines that have gone into service?
- 1048.405 How does this program work?
- 1048.410 How must I select, prepare, and test my in-use engines?
- 1048.415 What happens if in-use engines do not meet requirements?
- 1048.420 What in-use testing information must I report to EPA?
- 1048.425 What records must I keep?

**Subpart F—Test Procedures**

- 1048.501 How do I run a valid emission test?
- 1048.505 How do I test engines using steady-state duty cycles, including ramped-modal testing?
- 1048.510 Which duty cycles do I use for transient testing?