

Total resource effectiveness index value or TRE index value means a measure of the supplemental total resource requirement per unit reduction of organic HAP associated with a continuous front-end process vent stream, based on vent stream flow rate, emission rate of organic HAP, net heating value, and corrosion properties (whether or not the continuous front-end process vent stream contains halogenated compounds), as quantified by the equations given under § 63.115, with the exceptions noted in § 63.485.

Vent stream, as used in reference to batch front-end process vents, continuous front-end process vents, and aggregate batch vent streams, means the emissions from one or more process vents.

Waste management unit is defined in § 63.111, except that where the definition in § 63.111 uses the term "chemical manufacturing process unit," the term "EPPU" shall apply for the purposes of this subpart.

Wastewater means water that:

(1) Contains either:

(i) An annual average concentration of organic HAP listed in Table 5 of this subpart of at least 5 parts per million by weight and has an annual average flow rate of 0.02 liter per minute or greater; or

(ii) An annual average concentration of organic HAP listed on Table 5 of this subpart of at least 10,000 parts per million by weight at any flow rate; and

(2) Is discarded from an EPPU that is part of an affected source. Wastewater is process wastewater or maintenance wastewater.

Wastewater stream means a stream that contains wastewater as defined in this section.

[62 FR 46925, Sept. 5, 1996, as amended at 64 FR 11542, Mar. 9, 1999; 65 FR 38044, June 19, 2000; 66 FR 36927, July 16, 2001]

§ 63.483 Emission standards.

(a) Except as allowed under paragraphs (b) through (d) of this section, the owner or operator of an existing or new affected source shall comply with the provisions in:

- (1) Section 63.484 for storage vessels;
- (2) Section 63.485 for continuous front-end process vents;

(3) Sections 63.486 through 63.492 for batch front-end process vents;

(4) Sections 63.493 through 63.500 for back-end process operations;

(5) Section 63.501 for wastewater;

(6) Section 63.502 for equipment leaks;

(7) Section 63.504 for additional test methods and procedures;

(8) Section 63.505 for monitoring levels and excursions; and

(9) Section 63.506 for general reporting and recordkeeping requirements.

(b) When emissions of different kinds (*i.e.*, emissions from continuous front-end process vents, batch front-end process vents, aggregate batch vent streams, storage vessels, process wastewater, and/or in-process equipment subject to § 63.149) are combined, and at least one of the emission streams would be classified as Group 1 in the absence of combination with other emission streams, the owner or operator of an affected source shall comply with the requirements of either paragraph (b)(1) or (b)(2) of this section, as appropriate. For purposes of this paragraph (b), owners or operators of affected sources with combined emission streams containing one or more batch front-end process vents and containing one or more continuous front-end process vents may comply with either paragraph (b)(1) or (b)(2) of this section, as appropriate. For purposes of this paragraph (b), owners or operators of affected sources with combined emission streams containing one or more batch front-end process vents but not containing one or more continuous process vents shall comply with paragraph (b)(3) of this section.

(1) Comply with the applicable requirements of this subpart for each kind of emission in the stream as specified in paragraphs (a)(1) through (a)(6) of this section.

(2) Comply with the first set of requirements, identified in paragraphs (b)(2)(i) through (b)(2)(v) of this section, which applies to any individual emission stream that is included in the combined stream, where either that emission stream would be classified as Group 1 in the absence of combination with other emission streams, or the owner or operator chooses to consider that emission stream to be Group 1 for

purposes of this paragraph. Compliance with the first applicable set of requirements identified in paragraphs (b)(2)(i) through (b)(2)(v) of this section constitutes compliance with all other requirements in paragraphs (b)(2)(i) through (b)(2)(v) of this section applicable to other types of emissions in the combined stream.

(i) The requirements of this subpart for Group 1 continuous front-end process vents, including applicable monitoring, recordkeeping, and reporting;

(ii) The requirements of § 63.119(e), as specified in § 63.484, for control of emissions from Group 1 storage vessels, including applicable monitoring, recordkeeping, and reporting;

(iii) The requirements of § 63.139, as specified in § 63.501, for control devices used to control emissions from waste management units, including applicable monitoring, recordkeeping, and reporting;

(iv) The requirements of § 63.139, as specified in § 63.501, for closed vent systems for control of emissions from in-process equipment subject to § 63.149, as specified in § 63.501, including applicable monitoring, recordkeeping, and reporting; or

(v) The requirements of this subpart for aggregate batch vent streams, including applicable monitoring, recordkeeping, and reporting.

(3) The owner or operator of an affected source with combined emission streams containing one or more batch front-end process vents, but not containing one or more continuous front-end process vents, shall comply with paragraphs (b)(3)(i) and (b)(3)(ii) of this section.

(i) The owner or operator of the affected source shall comply with § 63.486 for the batch front-end process vent stream(s).

(ii) The owner or operator of the affected source shall comply with either paragraph (b)(1) or (b)(2) of this section, as appropriate, for the remaining emission streams.

(c) Instead of complying with §§ 63.484, 63.485, 63.493, and 63.501, the owner or operator of an existing affected source may elect to control any or all of the storage vessels, continuous front-end process vents, batch front-end process vents, aggregate batch

vent streams, back-end process emissions, and wastewater streams and associated waste management units within the affected source, to different levels using an emissions averaging compliance approach that uses the procedures specified in § 63.503. The restrictions concerning which emission points may be included in an emissions average, including how many emission points may be included, are specified in § 63.503(a)(1). An owner or operator electing to use emissions averaging shall still comply with the provisions of §§ 63.484, 63.485, 63.486, 63.493, and 63.501 for affected source emission points not included in the emissions average.

(d) A State may decide not to allow the use of the emissions averaging compliance approach specified in paragraph (c) of this section.

[62 FR 46925, Sept. 5, 1996, as amended at 65 FR 38048, June 19, 2000]

§ 63.484 Storage vessel provisions.

(a) This section applies to each storage vessel that is assigned to an affected source, as determined by § 63.480(g). Except for those storage vessels exempted by paragraph (b) of this section, the owner or operator of affected sources shall comply with the requirements of §§ 63.119 through 63.123 and 63.148, with the differences noted in paragraphs (c) through (s) of this section, for the purposes of this subpart.

(b) Storage vessels described in paragraphs (b)(1) through (b)(7) of this section are exempt from the storage vessel requirements of this section.

(1) Storage vessels containing styrene-butadiene latex;

(2) Storage vessels containing latex products other than styrene-butadiene latex, located downstream of the stripping operations;

(3) Storage vessels containing high conversion latex products;

(4) Storage vessels located downstream of the stripping operations at affected sources subject to the back-end residual organic HAP limitation located in § 63.494, that are complying through the use of stripping technology, as specified in § 63.495;

(5) Storage vessels containing styrene;