

§ 63.545

40 CFR Ch. I (7-1-07 Edition)

§ 63.545 Standards for fugitive dust sources.

(a) Each owner or operator of a secondary lead smelter shall prepare and at all times operate according to a standard operating procedures manual that describes in detail the measures that will be put in place to control fugitive dust emission sources within the areas of the secondary lead smelter listed in paragraphs (a)(1) through (a)(5) of this section.

- (1) Plant roadways;
- (2) Battery breaking area;
- (3) Furnace area;
- (4) Refining and casting area; and
- (5) Materials storage and handling area.

(b) The standard operating procedures manual shall be submitted to the Administrator or delegated authority for review and approval.

(c) The controls specified in the standard operating procedures manual shall at a minimum include the requirements of paragraphs (c)(1) through (c)(5) of this section, unless the owner or operator satisfies the requirements in paragraph (f) of this section.

(1) Plant roadways—paving of all areas subject to vehicle traffic and pavement cleaning twice per day of those areas, except on days when natural precipitation makes cleaning unnecessary or when sand or a similar material has been spread on plant roadways to provide traction on ice or snow.

(2) Battery breaking area—partial enclosure of storage piles, wet suppression applied to storage piles with sufficient frequency and quantity to prevent the formation of dust, and pavement cleaning twice per day; or total enclosure of the battery breaking area.

(3) Furnace area—partial enclosure and pavement cleaning twice per day; or total enclosure and ventilation of the enclosure to a control device.

(4) Refining and casting area—partial enclosure and pavement cleaning twice per day; or total enclosure and ventilation of the enclosure to a control device.

(5) Materials storage and handling area—partial enclosure of storage piles, wet suppression applied to storage piles with sufficient frequency and quantity

to prevent the formation of dust, vehicle wash at each exit from the area, and paving of the area; or total enclosure of the area and ventilation of the enclosure to a control device, and a vehicle wash at each exit.

(d) The standard operating procedures manual shall require that daily records be maintained of all wet suppression, pavement cleaning, and vehicle washing activities performed to control fugitive dust emissions.

(e) No owner or operator of a secondary lead smelter shall discharge or cause to be discharged into the atmosphere from any building or enclosure ventilation system any gases that contain lead compounds in excess of 2.0 milligrams of lead per dry standard cubic meter (0.00087 grains of lead per dry standard cubic foot).

(f) Demonstrate to the Administrator (or delegated State, local, or Tribal authority) that an alternative measure(s) is equivalent or better than a practice(s) described in paragraphs (c)(1) through (c)(5) of this section.

[62 FR 32216, June 13, 1997, as amended at 68 FR 37350, June 23, 2003]

§ 63.546 Compliance dates.

(a) Each owner or operator of an existing secondary lead smelter shall achieve compliance with the requirements of this subpart no later than December 23, 1997. Existing sources wishing to apply for an extension of compliance pursuant to section § 63.6(i) of this part must do so no later than June 23, 1997.

(b) Each owner or operator of a secondary lead smelter that commences construction or reconstruction after June 9, 1994, shall achieve compliance with the requirements of this subpart by June 13, 1997 or upon startup of operations, whichever is later.

[62 FR 32216, June 13, 1997, as amended at 64 FR 4572, Jan. 29, 1999]

§ 63.547 Test methods.

(a) The following test methods in appendix A of part 60 listed in paragraphs (a)(1) through (a)(5) of this section shall be used to determine compliance with the emission standards for lead compounds under §§ 63.543(a), 63.544 (c), and (d), and 63.545(e):