

§ 408.143

| Effluent characteristic | Effluent limitations | |
|-------------------------|-----------------------|---|
| | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Oil and grease | 2.1 | 0.84 |
| pH | (¹) | (¹) |

¹ Within the range 6.0 to 9.0.

[39 FR 23140, June 26, 1974, as amended at 44 FR 45945, Aug. 9, 1979; 60 FR 33943, June 29, 1995]

§ 408.143 [Reserved]

§ 408.144 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| pH | No limitation. |
| BOD5 | Do. |
| Oil and grease | Do. |

[40 FR 6439, Feb. 11, 1975, as amended at 60 FR 33943, June 29, 1995]

§ 408.145 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic | Effluent limitations | |
|-------------------------|----------------------------------|---|
| | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| | Metric units (kg/kkg of seafood) | |
| BOD5 | 20 | 8.1 |
| TSS | 7.5 | 3.0 |
| Oil and grease | 1.9 | 0.76 |
| pH | (¹) | (¹) |

40 CFR Ch. I (7-1-06 Edition)

| Effluent characteristic | Effluent limitations | |
|-------------------------|--|---|
| | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| | English units (lb/1,000 lb of seafood) | |
| BOD5 | 20 | 8.1 |
| TSS | 7.5 | 3.0 |
| Oil and grease | 1.9 | 0.76 |
| pH | (¹) | (¹) |

¹ Within the range 6.0 to 9.0.

§ 408.146 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33943, June 29, 1995]

§ 408.147 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.142 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

Subpart O—Fish Meal Processing Subcategory

SOURCE: 40 FR 55781, Dec. 1, 1975, unless otherwise noted.

§ 408.150 Applicability; description of the fish meal processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing of menhaden on the Gulf and Atlantic Coasts and the processing of anchovy on the West Coast into fish meal, oil and solubles.