Environmental Protection Agency

§ 408.151 Specialized definitions.

For the purpose of this subpart:

- (a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.
- (b) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

§ 408.152 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

(a) Any menhaden or anchovy fish meal reduction facility which utilizes a solubles plant to process stick water or bail water shall meet the following limitations.

	Effluent limitations		
Effluent characteristic	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not ex- ceed—	
	Metric units (kilograms per 1,000 kg of seafood)		
BOD5	7.0	3.9	
TSS	3.7	1.5	
Oil and grease	1.4	0.76	
pH	(1)	(1)	
	English units (pounds per 1,000 lb of seafood)		
BOD5	7.0	3.9	
TSS	3.7	1.5	
Oil and grease	1.4	0.76	
pH	(1)	(1)	

¹ Within the range 6.0 to 9.0.

(b) Any menhaden or anchovy fish meal reduction facility not covered under §408.152(a) shall meet the following limitations:

	Effluent limitations	
Effluent characteristic	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not ex- ceed—
	Metric units (kg/kkg of seafood)	
BOD5	3.5	2.8
TSS	2.6	1.7
Oil and grease	3.2	1.4
pH	(1)	(1)
		nits (lb/1,000 lb of seafood)
BOD5	3.5	2.8
TSS	2.6	1.7
Oil and grease	3.2	1.4
pH	(1)	(1)

¹ Within the range 6.0 to 9.0.

[40 FR 55781, Dec. 1, 1975, as amended at 41 FR 31821, July 30, 1976; 60 FR 33943, June 29, 1995]

§408.153 [Reserved]

§ 408.154 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

Pollutant or pollutant property	Pretreatment standard	
TSS	No limitation.	
pH	Do.	
Oil and grease	Do.	

[40 FR 55781, Dec. 1, 1975, as amended at 60 FR 33943, June 29, 1995]

§ 408.155 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart: