

**§ 408.313**

(b) Any Alaskan herring fillet processing facility not covered under § 408.312(a) shall meet the following limitations: No pollutants may be discharged which exceed 1.27 cm (0.5 inch) in any dimension.

[40 FR 55798, Dec. 1, 1975, as amended at 60 FR 33948, June 29, 1995]

**§ 408.313 [Reserved]**

**§ 408.314 Pretreatment standards for existing sources.**

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55798, Dec. 1, 1975, as amended at 60 FR 33948, June 29, 1995]

**§ 408.315 Standards of performance for new sources.**

(a) The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

(1) Any herring fillet processing facility located in population or processing centers including but not limited to Anchorage, Cordova, Juneau, Ketchikan, Kodiak and Petersburg shall meet the following limitations:

| Effluent characteristic          | Effluent limitations  |   |
|----------------------------------|-----------------------|---|
|                                  | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kkg of seafood) |                       |   |
| TSS .....                        | 23                    | 18  |

**40 CFR Ch. I (7-1-06 Edition)**

| Effluent characteristic                | Effluent limitations  |   |
|--|-----------------------|---|
|  | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Oil and grease .....                   | 20                    | 7.3   |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )  |
| English units (lb/1,000 lb of seafood) |                       |   |
| TSS .....                              | 23                    | 18  |
| Oil and grease .....                   | 20                    | 7.3   |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )  |

<sup>1</sup> Within the range 6.0 to 9.0.

(2) Any Alaskan herring fillet processing facility not covered under § 408.315(a)(1) shall meet the following limitations: No pollutants may be discharged which exceed 1.27 cm (0.5 inch) in any dimension.

(b) [Reserved]

**§ 408.316 Pretreatment standards for new sources.**

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55798, Dec. 1, 1975, as amended at 60 FR 33949, June 29, 1995]

**§ 408.317 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).**

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those

**Environmental Protection Agency**

**§ 408.325**

specified for conventional pollutants (which are defined in § 401.16) in § 408.312 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

**Subpart AF—Non-Alaskan Herring Fillet Processing Subcategory**

SOURCE: 40 FR 55799, Dec. 1, 1975, unless otherwise noted.

**§ 408.320 Applicability; description of the non-Alaskan herring fillet processing subcategory.**

The provisions of this subpart are applicable to discharges resulting from the processing of herring fillets outside of Alaska.

**§ 408.321 Specialized definitions.**

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

**§ 408.322 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.**

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic | Effluent limitations            |   |
|-------------------------|---------------------------------|---|
|                         | Maximum for any 1 day           | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kg of seafood) |   |
| TSS .....               | 32                              | 24  |
| Oil and grease .....    | 27                              | 10  |

| Effluent characteristic | Effluent limitations                   |   |
|-------------------------|--|---|
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )  |
|                         | English units (lb/1,000 lb of seafood) |   |
| TSS .....               | 32                                     | 24  |
| Oil and grease .....    | 27                                     | 10  |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55799, Dec. 1, 1975, as amended at 60 FR 33949, June 29, 1995]

**§ 408.323 [Reserved]**

**§ 408.324 Pretreatment standards for existing sources.**

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55799, Dec. 1, 1975, as amended at 60 FR 33949, June 29, 1995]

**§ 408.325 Standards of performance for new sources.**

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic | Effluent limitations            |   |
|-------------------------|---------------------------------|---|
|                         | Maximum for any 1 day           | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kg of seafood) |   |
| BOD5 .....              | 16                              | 15  |