

Environmental Protection Agency

§ 408.325

specified for conventional pollutants (which are defined in § 401.16) in § 408.312 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

Subpart AF—Non-Alaskan Herring Fillet Processing Subcategory

SOURCE: 40 FR 55799, Dec. 1, 1975, unless otherwise noted.

§ 408.320 Applicability; description of the non-Alaskan herring fillet processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing of herring fillets outside of Alaska.

§ 408.321 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

§ 408.322 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	Metric units (kg/kg of seafood)	
TSS	32	24
Oil and grease	27	10

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
pH	(1)	(1)
	English units (lb/1,000 lb of seafood)	
TSS	32	24
Oil and grease	27	10
pH	(1)	(1)

¹ Within the range 6.0 to 9.0.

[40 FR 55799, Dec. 1, 1975, as amended at 60 FR 33949, June 29, 1995]

§ 408.323 [Reserved]

§ 408.324 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

Pollutant or pollutant property	Pretreatment standard
BOD5	No limitation.
TSS	Do.
pH	Do.
Oil and grease	Do.

[40 FR 55799, Dec. 1, 1975, as amended at 60 FR 33949, June 29, 1995]

§ 408.325 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	Metric units (kg/kg of seafood)	
BOD5	16	15