

§ 405.125

publicly owned treatment works by a point source subject to the provisions of this subpart.

Pollutant or pollutant property	Pretreatment standard
pH	No limitation.
BOD5	Do.
TSS	Do.

[40 FR 6435, Feb. 11, 1975, as amended at 60 FR 33935, June 29, 1995]

§ 405.125 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	Metric units (kilograms per 1,000 kg of BOD5 input)	
BOD5	0.220	0.110
TSS	0.275	.138
pH	(¹)	(¹)
	English units (pounds per 100 lb of BOD5 input)	
BOD5	0.022	0.011
TSS	0.023	.014
pH	(¹)	(¹)

¹ Within the range 6.0 to 9.0.

§ 405.126 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33935, June 29, 1995]

§ 405.127 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollut-

40 CFR Ch. I (7-1-06 Edition)

ant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 405.122 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24996, July 9, 1986]

PART 406—GRAIN MILLS POINT SOURCE CATEGORY

Subpart A—Corn Wet Milling Subcategory

- Sec.
- 406.10 Applicability; description of the corn wet milling subcategory.
- 406.11 Specialized definitions.
- 406.12 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 406.13 [Reserved]
- 406.14 Pretreatment standards for existing sources.
- 406.15 Standards of performance for new sources.
- 406.16 Pretreatment standards for new sources.
- 406.17 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.

Subpart B—Corn Dry Milling Subcategory

- 406.20 Applicability; description of the corn dry milling subcategory.
- 406.21 Specialized definitions.
- 406.22 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 406.23 [Reserved]
- 406.24 Pretreatment standards for existing sources.
- 406.25 Standards of performance for new sources.
- 406.26 Pretreatment standards for new sources.
- 406.27 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Subpart C—Normal Wheat Flour Milling Subcategory

- 406.30 Applicability; description of the normal wheat flour milling subcategory.
- 406.31 Specialized definitions.