

§ 417.164

| Effluent characteristic | Effluent limitations |
|--|------------------------------|
| COD | 0.07. |
| TSS | 0.002. |
| Surfactants | 0.02. |
| Oil and grease | 0.002. |
| pH | Within the range 6.0 to 9.0. |
| English units (pounds per 1,000 lb of anhydrous product) | |
| BOD5 | 0.02. |
| COD | 0.07. |
| TSS | 0.002. |
| Surfactants | 0.02. |
| Oil and grease | 0.002. |
| pH | Within the range 6.0 to 9.0. |

§ 417.164 [Reserved]

§ 417.165 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

(a) For normal liquid detergent operations the following values pertain:

| Effluent characteristic | Effluent limitations | |
|--|-----------------------|---|
| | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kilograms per 1,000 kg of anhydrous product) | | |
| BOD5 | 0.10 | 0.05 |
| COD | 0.44 | .22 |
| TSS | 0.01 | .005 |
| Surfactants | 0.10 | .05 |
| Oil and grease | 0.01 | .005 |
| pH | (¹) | (¹) |
| English units (pounds per 1,000 lb of anhydrous product) | | |
| BOD5 | 0.10 | 0.05 |
| COD | 0.44 | .22 |
| TSS | 0.01 | .005 |
| Surfactants | 0.10 | .05 |
| Oil and grease | 0.01 | .005 |
| pH | (¹) | (¹) |

¹ Within the range 6.0 to 9.0.

(b) For fast turnaround operation of automated fill lines, the following values pertain: The maximum for any one day when the number of turnarounds exceeds eight in any thirty consecutive day period shall be the sum of the appropriate value below and that from paragraph (a) of this section; and the average of daily values for thirty consecutive days shall be the value shown below multiplied by the number of turnarounds in excess of eight and prorated to thirty days plus the appropriate value from paragraph (a) of this section:

40 CFR Ch. I (7-1-06 Edition)

secutive days shall be the value shown below multiplied by the number of turnarounds in excess of eight and prorated to thirty days plus the appropriate value from paragraph (a) of this section:

| Effluent characteristic | Effluent limitations |
|--|------------------------------|
| Metric units (kilograms per 1,000 kg of anhydrous product) | |
| BOD5 | 0.02. |
| COD | 0.07. |
| TSS | 0.002. |
| Surfactants | 0.02. |
| Oil and grease | 0.002. |
| pH | Within the range 6.0 to 9.0. |
| English units (pounds per 1,000 lb of anhydrous product) | |
| BOD5 | 0.02. |
| COD | 0.07. |
| TSS | 0.002. |
| Surfactants | 0.02. |
| Oil and grease | 0.002. |
| pH | Within the range 6.0 to 9.0. |

§ 417.166 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart.

(a) There shall be no discharge of waste water streams in which both the COD/BOD7 ratio exceeds 10.0 and the COD exceeds 1.10 kg/kg of anhydrous product.

(b) For waste streams having either a ratio of COD to BOD7 of 10.0 or less or having a COD content of 1.10 kg/kg of anhydrous product or less the pretreatment standard shall be:

(1) For normal liquid detergent operations the following values pertain:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 | No limitation. |
| COD | Do. |
| TSS | Do. |
| Surfactants | Do. |
| Oil and grease | Do. |
| pH | Do. |

Environmental Protection Agency

§417.173

(2) For fast turnaround operation of automated fill lines, the following values pertain; the maximum for any one day when the number of turnarounds exceeds eight in any thirty consecutive day period shall be the sum of the appropriate value below and that from paragraph (b)(1) of this section; and the average of daily values for thirty consecutive days shall be the value shown below multiplied by the number of turnarounds in excess of eight and prorated to thirty days plus the appropriate value from paragraph (b)(1) of this section:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 | No limitation. |
| COD | Do. |
| TSS | Do. |
| Surfactants | Do. |
| Oil and grease | Do. |
| pH | Do. |

[40 FR 27455, June 30, 1975, as amended at 60 FR 33955, June 29, 1995]

Subpart Q—Manufacture of Detergents by Dry Blending Subcategory

§417.170 Applicability; description of the manufacture of detergents by dry blending subcategory.

The provisions of this subpart are applicable to discharges resulting from the operations associated with the manufacture of detergents by means of the blending of dry ingredients, including, but not limited to, blending and subsequent packaging.

§417.171 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *anhydrous product* shall mean the theoretical product that would result if all water were removed from the actual product.

(c) The term *surfactant* shall mean those methylene blue active substances amenable to measurement by the method described in "Methods for Chemical Analysis of Water and Wastes," 1971, Environmental Protection Agency, Analytical Quality Control Laboratory, page 131.

(d) The term BOD7 shall mean the biochemical oxygen demand as determined by incubation at 20 degrees C for a period of 7 days using an acclimated seed. Agitation employing a magnetic stirrer set at 200 to 500 rpm may be used.

[39 FR 13372, Apr. 12, 1974, as amended at 40 FR 27455, June 30, 1975]

§417.172 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic | Effluent limitations | |
|-------------------------|--|---|
| | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| | Metric units (kilograms per 1,000 kg of anhydrous product) | English units (pounds per 1,000 lb of anhydrous product) |
| BOD5 | 0.03 | 0.01 |
| COD | 0.21 | .07 |
| TSS | 0.03 | .01 |
| Surfactants | 0.03 | .01 |
| Oil and grease | 0.015 | .005 |
| pH | (¹) | (¹) |

¹ Within the range 6.0 to 9.0.

[39 FR 13372, Apr. 12, 1974, as amended at 60 FR 33955, June 29, 1995]

§417.173 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this