

§ 417.196

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	English units (pounds per 1,000 lb of anhydrous product)	
BOD5	0.60	0.30
COD	2.70	1.35
TSS	0.20	.10
Surfactants	0.40	.20
Oil and grease	0.04	.02
pH	(¹)	(¹)

¹ Within the range 6.0 to 9.0.

§ 417.196 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33956, June 29, 1995]

PART 418—FERTILIZER MANUFACTURING POINT SOURCE CATEGORY

Subpart A—Phosphate Subcategory

Sec.

- 418.10 Applicability; description of the phosphate subcategory.
- 418.11 Specialized definitions.
- 418.12 Effluent limitations and guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 418.13 Effluent limitations and guidelines representing the degree of effluent reduction attained by the application of the best available technology economically achievable.
- 418.14 [Reserved]
- 418.15 Standards of performance for new sources.
- 418.16 Pretreatment standards for new sources.
- 418.17 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.

Subpart B—Ammonia Subcategory

- 418.20 Applicability; description of the ammonia subcategory.
- 418.21 Specialized definitions.
- 418.22 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best

40 CFR Ch. I (7–1–06 Edition)

- practicable control technology currently available.
- 418.23 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 418.24 [Reserved]
- 418.25 Standards of performance for new sources.
- 418.26 Pretreatment standards for new sources.
- 418.27 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.

Subpart C—Urea Subcategory

- 418.30 Applicability; description of the urea subcategory.
- 418.31 Specialized definitions.
- 418.32 Effluent limitations and guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 418.33 Effluent limitations and guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 418.34 [Reserved]
- 418.35 Standards of performance for new sources.
- 418.36 Pretreatment standards for new sources.

Subpart D—Ammonium Nitrate Subcategory

- 418.40 Applicability; description of the ammonium nitrate subcategory.
- 418.41 Specialized definitions.
- 418.42 Effluent limitations and guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 418.43 Effluent limitations and guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 418.44 [Reserved]
- 418.45 Standards of performance for new sources.
- 418.46 Pretreatment standards for new sources.

Subpart E—Nitric Acid Subcategory

- 418.50 Applicability; description of the nitric acid subcategory.
- 418.51 Specialized definitions.
- 418.52 Effluent limitations guidelines representing the degree of effluent reduction