Environmental Protection Agency

(d) The term existing indirect dischargers means only those two iron blast furnace operations with discharges to publicly owned treatment works prior to May 27, 1982.

[67 FR 64266, Oct. 17, 2002]

§ 420.32 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

(a) Iron blast furnace.

SUBPART C

	BPT effluen	t limitations
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days
	Kg/kkg (pounds per 1,000 lb) of product	
TSS	0.0782	0.0260
Ammonia-N	0.161	0.0537
Cyanide	0.0234	0.00782
Phenols (4AAP)	0.00626	0.00210
pH	(1)	(1)

¹ Within the range of 6.0 to 9.0.

(b) [Reserved]

[47 FR 23284, May 27, 1982; 47 FR 41739, Sept. 22, 1982, as amended at 67 FR 64266, Oct. 17, 2002]

§ 420.33 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

(a) Iron blast furnace.

SUBPART C

	BAT effluen	BAT effluent limitations	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days	
	Kg/kkg (pounds per 1,000 lb) of product		
Ammonia-N	0.00876 0.00175	0.00292 0.000876	
Phenols (4AAP)	0.0000584	0.000070	
TRC1	0.000146		
Lead	0.000263	0.0000876	
Zinc	0.000394	0.000131	

¹The limitation for TRC shall be applicable only when chlorination of ironmaking wastewaters is practiced.

(b) [Reserved]

 $[47\ {\rm FR}\ 23284,\ {\rm May}\ 27,\ 1982;\ 47\ {\rm FR}\ 41739,\ {\rm Sept}.$ $22,\ 1982,\ {\rm as}\ {\rm amended}\ {\rm at}\ 49\ {\rm FR}\ 21030,\ {\rm May}\ 17,$ $1984;\ 67\ {\rm FR}\ 64266,\ {\rm Oct.}\ 17,\ 2002]$

The discharge of wastewater pollutants from any new source subject to this subpart shall not exceed the standards set forth below.

(a) Iron blast furnace.

SUBPART C

	New source stan	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days
	Kg/kkg (pounds per 1,000 lb) of products	
TSS	0.0117	0.00438
O&G	0.00292	
Ammonia-N	0.00876	0.00292
Cyanide	0.000584	0.000292
Phenols (4AAP)	0.0000584	0.0000292
TRC 1	0.000146	
Lead	0.000263	0.0000876
Zinc	0.000394	0.000131
pH	(2)	(2)

¹The standards for TRC shall be applicable only when chlorination of ironmaking wastewaters is practiced.
² Within the range of 6.0 to 9.0.

(b) [Reserved]

[47 FR 23284, May 27, 1982; 47 FR 41739, Sept. 22, 1982, as amended at 49 FR 21030, May 17, 1984; 67 FR 64266, Oct. 17, 2002]

§ 420.35 Pretreatment standards for existing sources (PSES).

Except as provided in 40 CFR 403.7 and 403.13, any existing source subject