§ 420.73

SUBPART G-Continued

	BPT effluent limitations	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days
pH	(1)	(1)

¹ Within the range of 6.0 to 9.0.

(2) Carbon plate mills.

SUBPART G

	BPT effluent limitations	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days
	Kg/kkg (pounds per 1,000 lb) of product	
TSS	0.227 0.0568 (¹)	0.0851 (¹)

¹ Within the range of 6.0 to 9.0

(3) Specialty plate mills.

SUBPART G

	BPT effluen	BPT effluent limitations	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days	
	Kg/kkg (pounds per 1,000 lb) of product		
TSS	0.100	0.0376	
O&G	0.0250	(1)	
pH	(1)	(1)	

¹ Within the range of 6.0 to 9.0

(d) Pipe and tube mills, carbon and specialty.

SUBPART G

	BPT effluen	t limitations
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days
	Kg/kkg (pounds per 1,000 lb) of product	
TSS	0.212 0.0530	0.0795

¹ Within the range of 6.0 to 9.0

§ 420.73 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

The Agency has determined that there are not significant quantities of toxic pollutants in hot forming wastewaters after compliance with applicable BPT limitations. Accordingly, since the BPT level of treatment provides adequate control, the Agency is not promulgating more stringent BAT limitations.

§ 420.74 New source performance standards (NSPS).

The discharge of wastewater pollutants from any new source subject to this subpart shall not exceed the standards set forth below.

(a) Primary mills, carbon and specialty—(1) Without scarfing.

SUBPART G

	New source perform- ance standards	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days
	Kg/kkg (pounds per 1,000 lb) of product	
TSS	0.0150 0.00373	0.00563
pH	(¹)	(1)

¹ Within the range of 6.0 to 9.0.

(2) With scarfing.

SUBPART G

	New source perform- ance standards	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days
	Kg/kkg (pounds per 1,000 lb) of product	
TSS O&GpH	0.0234 0.00584 (¹)	0.00876

¹ Within the range of 6.0 to 9.0.

(b) Section mills—(1) Carbon.