

**Environmental Protection Agency**

**§ 420.91**

(3) *Batch, pipe and tube.*

SUBPART H		
Pollutant or pollutant property	BCT effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kkg (pounds per 1,000 lb) of product	
TSS .....	0.496	0.213
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 6.0 to 9.0.

(4) *Continuous.*

SUBPART H		
Pollutant or pollutant property	BCT effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kkg (pounds per 1,000 lb) of product	
TSS .....	0.0964	0.0413
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 6.0 to 9.0.

(b) *Salt bath descaling, reducing*—(1) *Batch.*

SUBPART H		
Pollutant or pollutant property	BCT effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kkg (pounds per 1,000 lb) of product	
TSS .....	0.0949	0.0407
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 6.0 to 9.0.

(2) *Continuous.*

SUBPART H

Pollutant or pollutant property	BCT effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kkg (pounds per 1,000 lb) of product	
TSS .....	0.532	0.228
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 6.0 to 9.0.

[47 FR 23284, May 27, 1982; 47 FR 41739, Sept. 22, 1982]

**Subpart I—Acid Pickling Subcategory**

**§ 420.90 Applicability; description of the acid pickling subcategory.**

The provisions of this subpart are applicable to discharges and to the introduction of pollutants into publicly owned treatment works resulting from sulfuric acid, hydrochloric acid, or combination acid pickling operations.

**§ 420.91 Specialized definitions.**

(a) The term *sulfuric acid pickling* means those operations in which steel products are immersed in sulfuric acid solutions to chemically remove oxides and scale, and those rinsing operations associated with such immersions.

(b) The term *hydrochloric acid pickling* means those operations in which steel products are immersed in hydrochloric acid solutions to chemically remove oxides and scale, and those rinsing operations associated with such immersions.

(c) The term *combination acid pickling* means those operations in which steel products are immersed in solutions of more than one acid to chemically remove scale and oxides, and those rinsing steps associated with such immersions.

(d) The term *fume scrubber* means those pollution control devices used to remove and clean fumes originating in pickling operations.

(e) The term *batch* means those pickling operations which process steel products such as coiled wire, rods, and tubes in discrete batches or bundles.