Environmental Protection Agency

- (x) The date of the latest monitoring system certification or audit.
- (xi) A description of any changes in continuous monitoring systems, processes, or controls since the last reporting period.
- (d) If you have obtained a Title V operating permit pursuant to 40 CFR part 70 or 40 CFR part 71 must report all deviations as defined in this subpart in the semiannual monitoring report reguired by 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A). If you submit a compliance report pursuant to paragraph (a) of this section along with, or as part of, the semiannual monitoring required report by 40 CFR 70.6(a)(3)(iii)(A) **CFR** or 71.6(a)(3)(iii)(A), and the compliance report includes all required information concerning deviations from any emission limitation(including any operating limit), or work practice requirement in this subpart, submission of the compliance report is deemed to satisfy any obligation to report the same deviations in the semiannual monitoring report. However, submission of a compliance report does not otherwise affect any obligation you may have to report deviations from permit requirements to the permit authority.

§ 63.1456 What records must I keep and how long must I keep my records?

- (a) You must keep the records listed in paragraphs (a)(1) through (7) of this section.
- (1) A copy of each notification and report that you submitted to comply with this subpart, including all documentation supporting any initial notification or notification of compliance status that you submitted, according to the requirements in §63.10(b)(2)(xiv).
- (2) The records in \$63.6(e)(3)(iii) through (v) related to startup, shutdown, and malfunction.
- (3) Records of performance tests and performance evaluations as required in §63.10(b)(2)(viii).
- (4) For each monitoring system, you must keep the records specified in paragraphs (a)(4)(i) through (iv) of this section.
- $\begin{array}{ccc} \hbox{(i)} & Records & described & in \\ \S 63.10 \hbox{(b)} \hbox{(2)} \hbox{(vi)} & through \hbox{(xi)}. \end{array}$

- (ii) Monitoring data recorded by the monitoring system during a performance evaluation as required in §63.6(h)(7)(i) and (ii).
- (iii) Previous (i.e., superseded) versions of the performance evaluation plan as required in $\S63.8(d)(3)$.
- (iv) Records of the date and time that each deviation started and stopped, and whether the deviation occurred during a period of startup, shutdown, or malfunction or during another period.
- (5) For each performance test you conduct to demonstrate compliance with an opacity limit according to §63.1450(c), you must keep the records specified in paragraphs (a)(5)(i) through (ix) of this section.
- (i) Dates and time intervals of all opacity observation period segments;
- (ii) Description of overall smelter operating conditions during each observation period. Identify, if any, the smelter copper production process equipment that was out-of-service during the performance test and explain why this equipment was not in operation;
- (iii) Name, affiliation, and copy of current visible emission reading certification for each visible emission observer participating in the performance test:
- (iv) Name, title, and affiliation for each indoor process monitor participating in the performance test;
- (v) Copies of all visible emission observer opacity field data sheets;
- (vi) Copies of all indoor process monitor operating log sheets;
- (vii) Copies of all data summary sheets used for data reduction;
- (viii) Copy of calculation sheets of the average opacity value used to demonstrate compliance with the opacity limit; and
- (ix) Documentation according to the requirements in §63.1450(c)(9)(iv) to support your selection of the site-specific capture system operating limits used for each batch copper converter capture system when blowing.
- (6) For each baghouse subject to the operating limit in §63.1444(f) or §63.1446(c), you must keep the records specified in paragraphs (a)(6)(i) and (ii) of this section.
- (i) Records of alarms for each bag leak detection system.

§ 63.1457

- (ii) Description of the corrective actions taken following each bag leak detection alarm.
- (7) For each control device other than a baghouse or venturi wet scrubber subject to site-specific operating limits in §63.144(g) or §63.1446(f), you must keep documentation according to the requirements in §63.1450(a)(5)(iv) to support your selection of the site-specific operating limits for the control device.
- (b) Your records must be in a form suitable and readily available for expeditious review, according to §63.10(b)(1).
- (c) As specified in §63.10(b)(1), you must keep each record for 5 years following the date of each occurrence, measurement, maintenance, corrective action, report, or record.
- (d) You must keep each record on site for at least 2 years after the date of each occurrence, measurement, maintenance, corrective action, report, or record, according to §63.10(b)(1). You can keep the records off site for the remaining 3 years.

OTHER REQUIREMENTS AND INFORMATION

§ 63.1457 What part of the general provisions apply to me?

Table 2 to this subpart shows which parts of the general provisions in $\S\S 63.1$ through 63.15 apply to you.

§ 63.1458 Who implements and enforces this subpart?

(a) This subpart can be implemented and enforced by us, the United States Environmental Protection Agency (U.S. EPA), or a delegated authority such as your State, local, or tribal agency. If the U.S. EPA Administrator has delegated authority to your State, local, or tribal agency, then that agency has the authority to implement and enforce this subpart. You should contact your U.S. EPA Regional Office to find out if this subpart is delegated to your State, local, or tribal agency.

(b) In delegating implementation and enforcement authority of this subpart to a State, local, or tribal agency under 40 CFR part 63, subpart E, the authorities listed in paragraph (c) of this section are retained by the U.S. EPA Administrator and are not trans-

ferred to the State, local, or tribal agency.

(c) The authorities that will not be delegated to State, local, or tribal agencies are as listed in paragraphs (c)(1) through (4) of this section.

- (1) Approval of alternatives to the emission limitations and work practice standards in §§63.1444 through 63.1446 under §63.6(g).
- (2) Approval of major alternatives to test methods under §63.7(f) and as defined in §63.90.
- (3) Approval of major alternatives to monitoring under §63.8(f) and as defined in §63.90.
- (4) Approval of major alternatives to recordkeeping and reporting under §63.10(f) and as defined in §63.90.

§ 63.1459 What definitions apply to this subpart?

Terms used in this subpart are defined in the Clean Air Act, in §63.2, and in this section as follows:

Bag leak detection system means a system that is capable of continuously monitoring relative particulate matter (dust) loadings in the exhaust of a baghouse in order to detect bag leaks and other upset conditions. A bag leak detection system includes, but is not limited to, an instrument that operates on triboelectric, light scattering, transmittance or other effect to continuously monitor relative particulate matter loadings.

Baghouse means a control device that collects particulate matter by filtering the gas stream through bags. A baghouse is also referred to as a "fabric filter."

Batch copper converter means a Pierce-Smith converter or Hoboken converter in which copper matte is oxidized to form blister copper by a process that is performed in discrete batches using a sequence of charging, blowing, skimming, and pouring.

Blowing means the operating mode for a batch copper converter during which air or oxygen-enriched air is injected into the molten converter bath.

Capture system means the collection of components used to capture gases and fumes released from one or more emission points, and to convey the captured gases and fumes to a control device. A capture system may include,