Environmental Protection Agency

(2) If an operating parameter deviates from the operating limit specified in Table 1 to this subpart, then you must assume that the emission capture system and add-on control device were achieving zero efficiency during the time period of the deviation. For the purposes of completing the compliance calculations specified in §63.4961, you must treat the materials used during a deviation on a controlled coating operation as if they were used on an uncontrolled coating operation for the time period of the deviation, as indicated in Equation 1 of §63.4961.

(d) You must meet the requirements for bypass lines in §63.4967(b) for controlled coating operations for which you do not conduct liquid-liquid material balances. If any bypass line is opened and emissions are diverted to the atmosphere when the coating operation is running, this is a deviation that must be reported as specified in §§63.4910(c)(6) and 63.4920(a)(7). For the purposes of completing the compliance calculations in §63.4961, you must treat the materials used during a deviation on a controlled coating operation as if they were used on an uncontrolled coating operation for the time period of the deviation, as indicated in Equation 1 of §63.4961

(e) You must demonstrate continuous compliance with the work practice standards in §63.4893. If you did not develop a work practice plan, or you did not implement the plan, or you did not records required keep the by §63.4930(k)(8), this is a deviation from the work practice standards that must be reported as specified in §§ 63.4910(c)(6) and 63.4920(a)(7).

(f) As part of each semiannual compliance report required in §63.4920, you must identify the coating operation or group of coating operations for which you used the emission rate with add-on controls option. If there were no deviations from the emission limitations, submit an affirmative statement that you were in compliance with the emission limitations during the reporting period because the organic HAP emission rate for each compliance period was less than or equal to the applicable emission limit in §63.4890, and you achieved the operating limits required by §63.4892 and the work practice standards required by §63.4893 during each compliance period.

(g)-(h) [Reserved]

(i) You must maintain records as specified in §§ 63.4930 and 63.4931.

[68 FR 28619, May 23, 2003, as amended at 71 FR 20466, Apr. 20, 2006]

§63.4963 What are the general requirements for performance tests?

(a) You must conduct each performance test required by 63.4960 according to the requirements in 63.7(e)(1) and under the conditions in this section unless you obtain a waiver of the performance test according to the provisions in 63.7(h).

(1) Representative coating operation operating conditions. You must conduct the performance test under representative operating conditions for the coating operation. Operations during periods of startup, shutdown, or malfunction, and during periods of nonoperation do not constitute representative conditions. You must record the process information that is necessary to document operating conditions during the test and explain why the conditions represent normal operation.

(2) Representative emission capture system and add-on control device operating conditions. You must conduct the performance test when the emission capture system and add-on control device are operating at a representative flow rate, and the add-on control device is operating at a representative inlet concentration. You must record information that is necessary to document emission capture system and add-on control device operating conditions during the test and explain why the conditions represent normal operation.

(b) You must conduct each performance test of an emission capture system according to the requirements in $\S63.4964$. You must conduct each performance test of an add-on control device according to the requirements in $\S63.4965$.

(c) The performance test to determine add-on control device organic HAP destruction or removal efficiency must consist of three runs as specified in 63.7(e)(3) and each run must last at least 1 hour.