§63.1313

- (11) PET using a batch dimethyl terephthalate process;
- (12) PET using a batch terephthalic acid process;
- (13) PET using a continuous dimethyl terephthalate process;
- (14) PET using a continuous terephthalic acid process;
- (15) PET using a continuous terephthalic acid high viscosity multiple end finisher process;
- (16) Polystyrene resin using a batch process;
- (17) Polystyrene resin using a continuous process;
 - (18) SAN using a batch process; or
 - (19) SAN using a continuous process.

Thermoplastic product process unit (TPPU) means a collection of equipment assembled and connected by hard-piping or ductwork, used to process raw materials and to manufacture a thermoplastic product as its primary product. This collection of equipment includes unit operations: recovery operations equipment, process vents; equipment identified in §63.149; storage vessels, as determined in §63.1310(g); and the equipment that is subject to the equipment leak provisions as specified in §63.1331. Utilities, lines and equipment not containing process fluids, and other non-process lines, such as heating and cooling systems which do not combine their materials with those in the processes they serve, are not part of the thermoplastic product process unit. A thermoplastic product process unit consists of more than one unit operation.

Total organic compounds (TOC) means those compounds excluding methane and ethane measured according to the procedures of Method 18 or Method 25A, 40 CFR part 60, appendix A.

Total resource effectiveness index value or TRE index value means a measure of the supplemental total resource requirement per unit reduction organic HAP associated with a continuous process vent stream, based on vent stream flow rate, emission rate of organic HAP, net heating value, and corrosion properties (whether or not the continuous process vent stream contains halogenated compounds), as quantified by the equations given under §63.115.

Vent stream, as used in reference to batch process vents, continuous process vents, and aggregate batch vent streams, means the emissions from one or more process vents.

Waste management unit is defined in §63.111, except that where the definition in §63.111 uses the term "chemical manufacturing process unit," the term "TPPU" shall apply for purposes of this subpart.

Wastewater means water that:

- (1) Contains either:
- (i) An annual average concentration of organic HAP listed on Table 6 of this subpart, except for ethylene glycol, of at least 5 parts per million by weight and has an annual average flow rate of 0.02 liter per minute or greater; or
- (ii) An annual average concentration of organic HAP listed on Table 6 of this subpart, except for ethylene glycol, of at least 10,000 parts per million by weight at any flow rate; and
- (2) Is discarded from a TPPU that is part of an affected source. Wastewater is process wastewater or maintenance wastewater.

Wastewater stream means a stream that contains wastewater as defined in this section.

[61 FR 48229, Sept. 12, 1996, as amended at 64 FR 11547, Mar. 9, 1999; 65 FR 38102, June 19, 2000; 66 FR 36937, July 16, 2001]

§63.1313 Emission standards.

- (a) Except as allowed under paragraphs (b) through (d) of this section, the owner or operator of an existing or new affected source shall comply with the provisions in:
 - (1) Section 63.1314 for storage vessels;
- (2) Section 63.1315, or §§ 63.1316 through 63.1320, as appropriate, for continuous process vents;
- (3) Section 63.1321 for batch process vents:
- (4) Section 63.1328 for heat exchange systems;
- (5) Section 63.1329 for process contact cooling towers;
- (6) Section 63.1330 for wastewater;
- (7) Section 63.1331 for equipment leaks;
- (8) Section 63.1333 for additional test methods and procedures;
- (9) Section 63.1334 for parameter monitoring levels and excursions; and

(10) Section 63.1335 for general recordkeeping and reporting requirements.

- (b) When emissions of different kinds (i.e., emissions from continuous process vents subject to either §63.1315 or §§ 63.1316 through 63.1320, batch process vents, aggregate batch vent streams, storage vessels, process wastewater, and/or in-process equipment subject to §63.149) are combined, and at least one of the emission streams would be classified as Group 1 in the absence of combination with other emission streams, the owner or operator shall comply with the requirements of either paragraph (b)(1) or (b)(2) of this section, as appropriate. For purposes of this paragraph (b), combined emission streams containing one or more batch process vents and containing one or more continuous process vents subject to §63.1316(b)(1)(i)(A), § 63, 1315. §63.1316(b)(1)(ii), §63.1316(b)(2)(i), §63.1316(b)(2)(ii), or §63.1316(c)(1), excluding §63.1316(c)(1)(ii), may comply with either paragraph (b)(1) or (b)(2) of this section, as appropriate. For purposes of this paragraph (b), the owner or operator of an affected source with combined emission streams containing one or more batch process vents but not containing one or more continuous process vents subject to §63.1315, §63.1316(b)(1)(i)(A), §63.1316(b)(1)(ii), §63.1316(b)(2)(ii), §63.1316(b)(2)(i), §63.1316(c)(1), excluding §63.1316(c)(1)(ii), shall comply with paragraph (b)(3) of this section.
- (1) Comply with the applicable requirements of this subpart for each kind of emission in the stream as specified in paragraphs (a)(1) through (a)(7) of this section.
- (2) Comply with the first set of requirements, identified in paragraphs (b)(2)(i) through (b)(2)(vi) of this section, which applies to any individual emission stream that is included in the combined stream, where either that emission stream would be classified as Group 1 in the absence of combination with other emission streams, or the owner or operator chooses to consider that emission stream to be Group 1 for purposes of this paragraph. Compliance with the first applicable set of requirements identified in paragraphs (b)(2)(i) through (b)(2)(vi) of this section constitutes compliance with all other re-

- quirements in paragraphs (b)(2)(i) through (b)(2)(vi) of this section applicable to other types of emissions in the combined stream.
- (i) The requirements of this subpart for Group 1 continuous process vents subject to §63.1315, including applicable monitoring, recordkeeping, and reporting;
- (ii) The requirements of $\S63.1316(b)(1)(i)(A)$, $\S63.1316(b)(1)(i)(A)$, $\S63.1316(b)(2)(i)$, or $\S63.1316(c)(1)$, excluding $\S63.1316(c)(1)$, as appropriate, for control of emissions from continuous process vents subject to the control requirements of $\S63.1316$, including applicable monitoring, recordkeeping, and reporting requirements;
- (iii) The requirements of §63.119(e), as specified in §63.1314, for control of emissions from Group 1 storage vessels, including applicable monitoring, recordkeeping, and reporting;
- (iv) The requirements of §63.139, as specified in §63.1330, for control devices used to control emissions from waste management units, including applicable monitoring, recordkeeping, and reporting;
- (v) The requirements of §63.139, as specified in §63.1330, for closed vent systems for control of emissions from in-process equipment subject to §63.149, as specified in §63.1330, including applicable monitoring, recordkeeping, and reporting; or
- (vi) The requirements of this subpart for aggregate batch vent streams subject to §63.1321(c), including applicable monitoring, recordkeeping, and reporting.
- (3) The owner or operator of an affected source with combined emission streams containing one or more batch process vents but not containing one or more continuous process vents subject to §63.1315, §63.1316(b)(1)(i)(A), §63.1316(b)(2)(ii), §63.1316(b)(2)(ii), or §63.1316(c)(1), excluding §63.1316(c)(1)(ii), shall comply with paragraph (b)(3)(i) and (b)(3)(ii) of this section.
- (i) The owner or operator of the affected source shall comply with §63.1321 for the batch process vent(s).
- (ii) The owner or operator of the affected source shall comply with either

§63.1314

paragraph (b)(1) or (b)(2) of this section, as appropriate, for the remaining emission streams.

- Instead of complying §§ 63.1314, 63.1315, 63.1316 through 63.1320, 63.1321, and 63.1330, the owner or operator of an existing affected source may elect to control any or all of the storage vessels, batch process vents, aggregate batch vent streams, continuous process vents, and wastewater streams and associated waste management units within the affected source to different levels using an emissions averaging compliance approach that uses the procedures specified in §63.1332. The restrictions concerning which emission points may be included in an emissions average, including how many emission points may be included, are specified in §63.1332(a)(1). An owner or operator electing to use emissions averaging shall still comply with the provisions of §§ 63.1314, 63.1315, 63.1316 through 63.1320, 63.1321, and 63.1330 for affected source emission points not included in the emissions average.
- (d) A State may decide not to allow the use of the emissions averaging compliance approach specified in paragraph (c) of this section.

[61 FR 48229, Sept. 12, 1996, as amended at 65 FR 38106, June 19, 2000]

§63.1314 Storage vessel provisions.

- (a) This section applies to each storage vessel that is assigned to an affected source, as determined by §63.1310(g). Except as provided in paragraphs (b) through (d) of this section, the owner or operator of an affected source shall comply with the requirements of §§63.119 through 63.123 and 63.148 for those storage vessels, with the differences noted in paragraphs (a)(1) through (a)(17) of this section for the purposes of this subpart.
- (1) When the term "storage vessel" is used in §§ 63.119 through 63.123, the definition of this term in §63.1312 shall apply for the purposes of this subpart.
- (2) When the term "Group 1 storage vessel" is used in §§63.119 through 63.123, the definition of this term in §63.1312 shall apply for the purposes of this subpart.
- (3) When the term "Group 2 storage vessel" is used in §§63.119 through 63.123, the definition of this term in

§63.1312 shall apply for the purposes of this subpart.

- (4) When the emissions averaging provisions of §63.150 are referred to in §§63.119 and 63.123, the emissions averaging provisions contained in §63.1332 shall apply for the purposes of this subpart.
- (5) When December 31, 1992, is referred to in §63.119, March 29, 1995 shall apply instead, for the purposes of this subpart.
- (6) When April 22, 1994, is referred to in §63.119, June 19, 2000 shall apply instead, for the purposes of this subpart.
- (7) Each owner or operator of an affected source shall comply with this paragraph (a)(7)instead $\S63.120(d)(1)(ii)$ for the purposes of this subpart. If the control device used to comply with §63.119(e) is also used to comply with any of the requirements found in §63.1315, §63.1316, §63.1322, or §63.1330, the performance test required in or accepted by the applicable requirements of §§ 63.1315, 63.1316, 63.1322, and 63.1330 is acceptable for demonstrating compliance with §63.119(e) for the purposes of this subpart. The owner or operator is not required to prepare a design evaluation for the device as described control $\S63.120(d)(1)(i)$, if the performance test meets the criteria specified in paragraphs (a)(7)(i) and (a)(7)(ii) of this section.
- (i) The performance test demonstrates that the control device achieves greater than or equal to the required control efficiency specified in §63.119(e)(1) or §63.119(e)(2), as applicable: and
- (ii) The performance test is submitted as part of the Notification of Compliance Status required by §63.1335(e)(5).
- (8) When the term "range" is used in \$\$63.120(d)(3), 63.120(d)(5), and 63.122(g)(2), the term "level" shall apply instead, for the purposes of this subpart.
- (9) For purposes of this subpart, the monitoring plan required by \$63.120(d)(2) shall specify for which control devices the owner or operator has selected to follow the procedures for continuous monitoring specified in \$63.1334. For those control devices for