

§ 431.43

14 CFR Ch. III (1-1-08 Edition)

manner that accurately reflects communications made on individual channels, synchronized time coding, and sequence of communications.

(b) An applicant shall submit procedures to ensure that licensee and reentry site personnel, if any, receive a copy of the communications plan required by this section and that the reentry site operator, if any, concurs with the communications plan.

§ 431.43 Reusable launch vehicle mission operational requirements and restrictions.

(a) An applicant for RLV mission safety approval shall submit procedures—

(1) That ensure RLV mission risks do not exceed the criteria set forth in § 431.35 for nominal and non-nominal operations;

(2) That ensure conformance with the system safety process and associated hazard identification and risk assessment required under § 431.35(c);

(3) That ensure conformance with operational restrictions listed in paragraphs (c) through (e) of this section;

(4) To monitor and verify the status of RLV safety-critical systems sufficiently before enabling both launch and reentry flight to ensure public safety and during mission flight unless technically infeasible; and

(5) For human activation or initiation of a flight safety system that safely aborts the launch of an RLV if the vehicle is not operating within approved mission parameters and the vehicle poses risk to public health and safety and the safety of property in excess of acceptable flight risk as defined in § 431.35.

(b) To satisfy risk criteria set forth in § 431.35(b)(1), an applicant for RLV mission safety approval shall identify suitable and attainable locations for nominal landing and vehicle staging impact or landing, if any. An application shall identify such locations for a contingency abort if necessary to satisfy risk criteria contained in § 431.35(b)(1) during launch of an RLV. A nominal landing, vehicle staging impact and contingency abort location are suitable for launch or reentry if—

(1) For any vehicle or vehicle stage, the area of the predicted three-sigma

dispersion of the vehicle or vehicle stage can be wholly contained within the designated location; and

(2) The location is of sufficient size to contain landing impacts, including debris dispersion upon impact and any toxic release.

(c) For an RLV mission—

(1) A collision avoidance analysis shall be performed in order to maintain at least a 200-kilometer separation from any inhabitable orbiting object during launch and reentry. The analysis shall address:

(i) For launch, closures in a planned launch window for ascent to outer space or, for an orbital RLV, to initial orbit through at least one complete orbit;

(ii) For reentry, the reentry trajectory;

(iii) Expansions of the closure period by subtracting 15 seconds from the closure start-time and adding 15 seconds to the closure end-time for each sequential 90 minutes elapsed time period, or portion thereof, beginning at the time the state vectors of the orbiting objects were determined;

(2) The projected instantaneous impact point (IIP) of the vehicle shall not have substantial dwell time over densely populated areas during any segment of mission flight;

(3) There will be no unplanned physical contact between the vehicle or its components and payload after payload separation and debris generation will not result from conversion of energy sources into energy that fragments the vehicle or its payload. Energy sources include, but are not limited to, chemical, pneumatic, and kinetic energy; and

(4) Vehicle safety operations personnel shall adhere to the following work and rest standards:

(i) A maximum 12-hour work shift with at least 8 hours of rest after 12 hours of work, preceding initiation of an RLV reentry mission or during the conduct of a mission;

(ii) A maximum of 60 hours worked in the 7 days, preceding initiation of an RLV mission;

(iii) A maximum of 14 consecutive work days; and

(iv) A minimum 48-hour rest period after 5 consecutive days of 12-hour shifts.

(d) In addition to requirements of paragraph (c) of this section, any unproven RLV may only be operated so that during any portion of flight—

(1) The projected instantaneous impact point (IIP) of the vehicle does not have substantial dwell time over populated areas; or

(2) The expected average number of casualties to members of the public does not exceed 30×10^{-6} ($E_c \leq 30 \times 10^{-6}$) given a probability of vehicle failure equal to 1 (pf=1) at any time the IIP is over a populated area;

(e) Any RLV that enters Earth orbit may only be operated such that the vehicle operator is able to—

(1) Monitor and verify the status of safety-critical systems before enabling reentry flight to assure the vehicle can reenter safely to Earth; and

(2) Issue a command enabling reentry flight of the vehicle. Reentry flight cannot be initiated autonomously under nominal circumstances without prior enable.

§ 431.45 Mishap investigation plan and emergency response plan.

(a) *Mishap investigation plan and emergency response plan.* An applicant shall submit a mishap investigation plan (MIP) containing the applicant's procedures for reporting and responding to launch and reentry accidents, launch and reentry incidents, or other mishaps, as defined in § 401.5 of this chapter, that occur during the conduct of an RLV mission. An acceptable MIP satisfies the requirements of paragraphs (b)–(d) of this section. An applicant shall also submit an emergency response plan (ERP) that contains procedures for informing the affected public of a planned RLV mission. An acceptable ERP satisfies the requirements of paragraph (e) of this section. The MIP and ERP shall be signed by an individual authorized to sign and certify the application in accordance with § 413.7(c) of this chapter, the person responsible for the conduct of all licensed RLV mission activities designated under § 431.33(b) of this subpart, and the safety official designated under § 431.33(c) of this subpart.

(b) *Report requirements.* A MIP shall provide for—

(1) Immediate notification to the FAA Washington Operations Center in case of a launch or reentry accident, launch or reentry incident, or a mishap that involves a fatality or serious injury (as defined in 49 CFR 830.2);

(2) Notification within 24 hours to the Associate Administrator for Commercial Space Transportation in the event of a mishap that does not involve a fatality or serious injury, as defined in 49 CFR 830.2; and

(3) Submission of a written preliminary report to the FAA Associate Administrator for Commercial Space Transportation in the event of a launch accident or launch incident occurring in the conduct of an RLV mission, or reentry accident or reentry incident, occurring in the conduct of an RLV mission, within 5 days of the event. The report shall identify the event as either a launch or reentry accident or incident and must include the following information:

(i) Date and time of occurrence;

(ii) Description of the event and sequence of events leading to the accident or incident, to the extent known;

(iii) Intended and actual location of launch and reentry or other landing on Earth;

(iv) Identification of the vehicle;

(v) Identification of the payload, if applicable;

(vi) Number and general description of any fatalities and injuries;

(vii) Property damage, if any, and an estimate of its value;

(viii) Identification of hazardous materials, as defined in § 401.5 of this chapter, involved in the event, whether on the vehicle, payload, or on the ground;

(ix) Action taken by any person to contain the consequences of the event;

(x) Weather conditions at the time of the event; and

(xi) Potential consequences for other vehicles or systems of similar type and proposed operations.

(c) *Response plan.* A MIP must contain procedures to—

(1) Ensure the consequences of a launch accident, launch incident, reentry accident, reentry incident, or other mishap occurring in the conduct