

<sup>3</sup>For airplanes that can demonstrate the capability of deriving either the control input on control movement (one from the other) for all modes of operation and flight regimes, the "or" applies. For airplanes with non-mechanical control systems (fly-by-wire) the "and" applies. In airplanes with split surfaces, suitable combination of inputs is acceptable in lieu of recording each surface separately.

<sup>4</sup>This column applies to aircraft manufactured after October 11, 1991.

[Doc. No. 25530, 53 FR 26153, July 11, 1988; 53 FR 30906, Aug. 16, 1988]

APPENDIX E TO PART 135—HELICOPTER FLIGHT RECORDER SPECIFICATIONS

Parameters	Range	Accuracy sensor input to DFDR readout	Sampling interval (per second)	Resolution <sup>2</sup> read out
Time (GMT)	24 Hrs	±0.125% Per Hour	0.25 (1 per 4 seconds).	1 sec
Altitude	− 1,000 ft to max certified altitude of aircraft.	±100 to ±700 ft (See Table 1, TSO-C51a).	1	5' to 30'.
Airspeed	As the installed measuring system.	±3%	1	1 kt
Heading	360°	±2°	1	0.5°.
Normal Acceleration (Vertical)	−3g to +6g	±1% of max range excluding datum error of ±5%.	8	0.01g
Pitch Attitude	±75°	±2°	2	0.5°
Roll Attitude	±180°	±2°	2	0.5°.
Radio Transmitter Keying	On-Off (Discrete)		1	0.25 sec
Power in Each Engine: Free Power Turbine Speed and Engine Torque.	0–130% (power Turbine Speed) Full range (Torque).	±2%	1 speed 1 torque (per engine).	0.2% <sup>1</sup> to 0.4% <sup>1</sup>
Main Rotor Speed	0–130%	±2%	2	0.3% <sup>1</sup>
Altitude Rate	±6,000 ft/min	As installed	2	0.2% <sup>1</sup>
Pilot Input—Primary Controls (Collective, Longitudinal Cyclic, Lateral Cyclic, Pedal).	Full range	±3%	2	0.5% <sup>1</sup>
Flight Control Hydraulic Pressure Low.	Discrete, each circuit		1	
Flight Control Hydraulic Pressure Selector Switch Position, 1st and 2nd stage.	Discrete		1	
AFCS Mode and Engagement Status.	Discrete (5 bits necessary).		1	
Stability Augmentation System Engage.	Discrete		1	
SAS Fault Status	Discrete		0.25	
Main Gearbox Temperature Low.	As installed	As installed	0.25	0.5% <sup>1</sup>
Main Gearbox Temperature High.	As installed	As installed	0.5	0.5% <sup>1</sup>
Controllable Stabilator Position.	Full Range	±3%	2	0.4% <sup>1</sup> .
Longitudinal Acceleration	±1g	±1.5% max range excluding datum error of ±5%.	4	0.01g.
Lateral Acceleration	±1g	±1.5% max range excluding datum of ±5%.	4	0.01g.
Master Warning	Discrete		1	
Nav 1 and 2 Frequency Selection.	Full range	As installed	0.25	
Outside Air Temperature	− 50° C to +90° C	±2° c	0.5	0.3° c

<sup>1</sup>Per cent of full range.

<sup>2</sup>This column applies to aircraft manufactured after October 11, 1991.

[Doc. No. 25530, 53 FR 26154, July 11, 1988; 53 FR 30906, Aug. 16, 1988]

APPENDIX F TO PART 135—AIRPLANE FLIGHT RECORDER SPECIFICATION

The recorded values must meet the designated range, resolution, and accuracy requirements during dynamic and static conditions. All data recorded must be correlated in time to within one second.

Parameters	Range	Accuracy (sensor input)	Seconds per sampling interval	Resolution	Remarks
1. Time or Relative Time Counts <sup>1</sup> .	24 Hrs, 0 to 4095.	±0.125% Per Hour.	4	1 sec	UTC time preferred when available. Counter increments each 4 seconds of system operation.

Pt. 135, App. F

14 CFR Ch. I (1–1–08 Edition)

The recorded values must meet the designated range, resolution, and accuracy requirements during dynamic and static conditions. All data recorded must be correlated in time to within one second.

Parameters	Range	Accuracy (sensor input)	Seconds per sampling interval	Resolution	Remarks
2. Pressure Altitude.	– 1000 ft to max certificated altitude of aircraft, +5000 ft.	±100 to ±700 ft (see table, TSO C124a or TSO C51a).	1	5' to 35"	Data should be obtained from the air data computer when practicable.
3. Indicated air-speed or Calibrated airspeed.	50 KIAS or minimum value to Max $V_{30+}$ and $V_{50}$ to 1.2 $V_D$ .	±5% and ±3%	1	1 kt	Data should be obtained from the air data computer when practicable.
4. Heading (Primary flight crew reference).	0–360° and Discrete "true" or "mag".	±2°	1	0.5°	When true or magnetic heading can be selected as the primary heading reference, a discrete indicating selection must be recorded.
5. Normal Acceleration (Vertical) <sup>9</sup> .	–3g to +6g	±1% of max range excluding datum error of ±5%.	0.125	0.004g	
6. Pitch Attitude	±75°	±2°	1 or 0.25 for airplanes operated under § 135.152(j).	0.5°	A sampling rate of 0.25 is recommended.
7. Roll Attitude <sup>2</sup>	±180°	±2°	1 or 0.5 for airplanes operated under § 135.152(j).	0.5°	A sampling rate of 0.5 is recommended.
8. Manual Radio Transmitter Keying or CVR/DFDR synchronization reference.	On-Off (Discrete) None		1		Preferably each crew member but one discrete acceptable for all transmission provided the CVR/FDR system complies with TSO C124a CVR synchronization requirements (paragraph 4.2.1 ED–55).
9. Thrust/Power on each engine—primary flight crew reference.	Full Range Forward.	±2%	1 (per engine)	0.3% of full range.	Sufficient parameters (e.g. EPR, N1 or Torque, NP) as appropriate to the particular engine being recorded to determine power in forward and reverse thrust, including potential overspeed condition.
10. Autopilot Engagement.	Discrete "on" or "off".		1		
11. Longitudinal Acceleration.	±1g	±1.5% max. range excluding datum error of ±5%.	0.25	0.004g.	
12a. Pitch Control(s) position (non-fly-by-wire systems).	Full Range	±2° Unless Higher Accuracy Uniquely Required.	0.5 or 0.25 for airplanes operated under § 135.152(j).	0.5% of full range.	For airplanes that have a flight control break away capability that allows either pilot to operate the controls independently, record both control inputs. The control inputs may be sampled alternately once per second to produce the sampling interval of 0.5 or 0.25, as applicable.
12b. Pitch Control(s) position (fly-by-wire systems) <sup>3</sup> .	Full Range	±2° Unless Higher Accuracy Uniquely Required.	0.5 or 0.25 for airplanes operated under § 135.152(j).	0.2% of full range	

Federal Aviation Administration, DOT

Pt. 135, App. F

The recorded values must meet the designated range, resolution, and accuracy requirements during dynamic and static conditions. All data recorded must be correlated in time to within one second.

Parameters	Range	Accuracy (sensor input)	Seconds per sampling interval	Resolution	Remarks
13a. Lateral Control position(s) (non-fly-by-wire).	Full Range .....	±2° Unless Higher Accuracy Uniquely Required.	0.5 or 0.25 for airplanes operated under § 135.152(j).	0.2% of full range.	For airplanes that have a flight control break away capability that allows either pilot to operate the controls independently, record both control inputs. The control inputs may be sampled alternately once per second to produce the sampling interval of 0.5 or 0.25, as applicable.
13b. Lateral Control position(s) (fly-by-wire) <sup>4</sup> .	Full Range .....	±2° Unless Higher Accuracy Uniquely Required.	0.5 or 0.25 for airplanes operated under § 135.152(j).		
14a. Yaw Control position(s) (non-fly-by-wire) <sup>5</sup> .	Full Range .....	±2° Unless Higher Accuracy Uniquely Required.	0.5 or 0.25 for airplanes operated under § 135.152(j).	0.3% of full range	For airplanes that have a flight control break away capability that allows either pilot to operate the controls independently, record both control inputs. The control inputs may be sampled alternately once per second to produce the sampling interval of 0.5.
14b. Yaw Control position(s) (fly-by-wire).	Full Range .....	±2° Unless Higher Accuracy Uniquely Required.	0.5 .....	0.2% of full range.	
15. Pitch Control Surface(s) Position <sup>6</sup> .	Full Range .....	±2° Unless Higher Accuracy Uniquely Required.	0.5 or 0.25 for airplanes operated under § 135.152(j).	0.3% of full range.	For airplanes fitted with multiple or split surfaces, a suitable combination of inputs is acceptable in lieu of recording each surface separately. The control surfaces may be sampled alternately to produce the sampling interval of 0.5 or 0.25.
16. Lateral Control Surface(s) Position <sup>7</sup> .	Full Range .....	±2° Unless Higher Accuracy Uniquely Required.	0.5 or 0.25 for airplanes operated under § 135.152(j).	0.2% of full range.	A suitable combination of surface position sensors is acceptable in lieu of recording each surface separately. The control surfaces may be sampled alternately to produce the sampling interval of 0.5 or 0.25.
17. Yaw Control Surface(s) Position <sup>8</sup> .	Full Range .....	±2° Unless Higher Accuracy Uniquely Required.	0.5 .....	0.2% of full range.	For airplanes with multiple or split surfaces, a suitable combination of surface position sensors is acceptable in lieu of recording each surface separately. The control surfaces may be sampled alternately to produce the sampling interval of 0.5.
18. Lateral Acceleration.	±1g .....	±1.5% max. range excluding datum error of ±5%.	0.25 .....	0.004g.	
19. Pitch Trim Surface Position.	Full Range .....	±3° Unless Higher Accuracy Uniquely Required.	1 .....	0.6% of full range	

Pt. 135, App. F

14 CFR Ch. I (1–1–08 Edition)

The recorded values must meet the designated range, resolution, and accuracy requirements during dynamic and static conditions. All data recorded must be correlated in time to within one second.

Parameters	Range	Accuracy (sensor input)	Seconds per sampling interval	Resolution	Remarks
20. Trailing Edge Flap or Cockpit Control Selection <sup>10</sup> .	Full Range or Each Position (discrete).	±3° or as Pilot's Indicator.	2 .....	0.5% of full range.	Flap position and cockpit control may each be sampled alternately at 4 second intervals, to give a data point every 2 seconds.
21. Leading Edge Flap or Cockpit Control Selection <sup>11</sup> .	Full Range or Each Discrete Position.	±3° or as Pilot's Indicator and sufficient to determine each discrete position.	2 .....	0.5% of full range.	Left and right sides, of flap position and cockpit control may each be sampled at 4 second intervals, so as to give a data point to every 2 seconds.
22. Each Thrust reverser Position (or equivalent for propeller airplane).	Stowed, In Transit, and reverse (Discrete).	.....	1 (per engine .....	.....	Turbo-jet—2 discretely enable the 3 states to be determined Turbo-prop—1 discrete
23. Ground Spoiler Position or Speed Brake Selection <sup>12</sup> .	Full Range or Each Position (discrete).	±2° Unless Higher Accuracy Uniquely Required.	1 or 0.5 for airplanes operated under § 135.152(j).	0.5% of full range	
24. Outside Air Temperature or Total Air Temperature <sup>13</sup> .	-50 °C to +90 °C.	±2 °C .....	2 .....	0.3 °C	
25. Autopilot/ Autothrottle/ AFCS Mode and Engagement Status.	A suitable combination of discretely.	.....	1 .....	.....	Discretely should show which systems are engaged and which primary modes are controlling the flight path and speed of the aircraft.
26. Radio Altitude <sup>14</sup> .	-20 ft to 2,500 ft.	±2 ft or ±3% Whichever is Greater Below 500 ft and ±5% Above 500 ft.	1 .....	1 ft +5% above 500 ft.	For autoland/category 3 operations. Each radio altimeter should be recorded, but arranged so that at least one is recorded each second.
27. Localizer Deviation, MLS Azimuth, or GPS Lateral Deviation.	±400 Microamps or available sensor range as installed ±62°.	As installed ±3% recommended..	1 .....	0.3% of full range.	For autoland/category 3 operations. Each system should be recorded but arranged so that at least one is recorded each second. It is not necessary to record ILS and MLS at the same time, only the approach aid in use need be recorded.
28. Glideslope Deviation, MLS Elevation, or GPS Vertical Deviation.	±400 Microamps or available sensor range as installed. 0.9 to + 30° .....	As installed ±3% recommended.	1 .....	0.3% of full range.	For autoland/category 3 operations. Each system should be recorded but arranged so that at least one is recorded each second. It is not necessary to record ILS and MLS at the same time, only the approach aid in use need be recorded.
29. Marker Beacon Passage.	Discrete "on" or "off".	.....	1 .....	.....	A single discrete is acceptable for all markers.
30. Master Warning.	Discrete .....	.....	1 .....	.....	Record the master warning and record each "red" warning that cannot be determined from other parameters or from the cockpit voice recorder.
31. Air/ground sensor (primary airplane system reference nose or main gear).	Discrete "air" or "ground".	.....	1 (0.25 recommended).	.....	

Federal Aviation Administration, DOT

Pt. 135, App. F

The recorded values must meet the designated range, resolution, and accuracy requirements during dynamic and static conditions. All data recorded must be correlated in time to within one second.

Parameters	Range	Accuracy (sensor input)	Seconds per sampling interval	Resolution	Remarks
32. Angle of Attack (If measured directly).	As installed .....	As installed .....	2 or 0.5 for airplanes operated under § 135.152(j).	0.3% of full range.	If left and right sensors are available, each may be recorded at 4 or 1 second intervals, as appropriate, so as to give a data point at 2 seconds or 0.5 second, as required.
33. Hydraulic Pressure Low, Each System.	Discrete or available sensor range, "low" or "normal".	±5% .....	2 .....	0.5% of full range.	
34. Groundspeed	As installed .....	Most Accurate Systems Installed.	1 .....	0.2% of full range.	
35. GPWS (ground proximity warning system).	Discrete "warning" or "off".	.....	1 .....	.....	A suitable combination of discretely unless recorder capacity is limited in which case a single discrete for all modes is acceptable.
36. Landing Gear Position or Landing gear cockpit control selection.	Discrete .....	.....	4 .....	.....	A suitable combination of discretely should be recorded.
37. Drift Angle <sup>15</sup>	As installed .....	As installed .....	4 .....	0.1°	
38. Wind Speed and Direction.	As installed .....	As installed .....	4	1 knot, and 1.0°.	
39. Latitude and Longitude.	As installed .....	As installed .....	4 .....	0.002°, or as installed.	Provided by the Primary Navigation System Reference. Where capacity permits latitude/longitude resolution should be 0.0002°.
40. Stick shaker and pusher activation.	Discrete(s) "on" or "off".	.....	1 .....	.....	A suitable combination of discretely to determine activation.
41. Windshear Detection.	Discrete "warning" or "off".	.....	1.		
42. Throttle/power lever position <sup>16</sup> .	Full Range .....	±2% .....	1 for each lever	2% of full range	For airplanes with non-mechanically linked cockpit engine controls.
43. Additional Engine Parameters.	As installed .....	As installed .....	Each engine each second.	2% of full range	Where capacity permits, the preferred priority is indicated vibration level, N2, EGT, Fuel Flow, Fuel Cut-off lever position and N3, unless engine manufacturer recommends otherwise.
44. Traffic Alert and Collision Avoidance System (TCAS).	Discretely .....	As installed .....	1 .....	.....	A suitable combination of discretely should be recorded to determine the status of—Combined Control, Vertical Control, Up Advisory, and down advisory. (ref. ARINC Characteristic 735 Attachment 6E, TCAS VERTICAL RA DATA OUTPUT WORD.)
45. DME 1 and 2 Distance.	0–200 NM; .....	As installed .....	4 .....	1 NM .....	1 mile.
46. Nav 1 and 2 Selected Frequency.	Full range .....	As installed .....	4 .....	.....	Sufficient to determine selected frequency.
47. Selected barometric setting.	Full Range .....	±5% .....	(1 per 64 sec.) ..	0.2% of full range.	
48. Selected altitude.	Full Range .....	±5% .....	1 .....	100 ft.	
49. Selected speed.	Full Range .....	±5% .....	1 .....	1 knot.	

Pt. 135, App. F

14 CFR Ch. I (1-1-08 Edition)

The recorded values must meet the designated range, resolution, and accuracy requirements during dynamic and static conditions. All data recorded must be correlated in time to within one second.

Parameters	Range	Accuracy (sensor input)	Seconds per sampling interval	Resolution	Remarks
50. Selected Mach.	Full Range .....	±5% .....	1 .....	.01.	
51. Selected vertical speed.	Full Range .....	±5% .....	1 .....	100 ft./min.	
52. Selected heading.	Full Range .....	±5% .....	1 .....	1°.	
53. Selected flight path.	Full Range .....	±5% .....	1 .....	1°.	
54. Selected decision height.	Full Range .....	±5% .....	64 .....	1 ft.	
55. EFIS display format.	Discrete(s) .....	.....	4 .....	.....	Discretes should show the display system status (e.g., off, normal, fail, composite, sector, plan, nav aids, weather radar, range, copy.
56. Multi-function/ Engine Alerts Display format.	Discrete(s) .....	.....	4 .....	.....	Discretes should show the display system status (e.g., off, normal, fail, and the identity of display pages for emergency procedures, need not be recorded.
57. Thrust comand <sup>17</sup> .	Full Range .....	±2% .....	2 .....	2% of full range	
58. Thrust target	Full Range .....	±2% .....	4 .....	2% of full range.	
59. Fuel quantity in CG trim tank.	Full Range .....	±5% .....	(1 per 64 sec.) ..	1% of full range.	
60. Primary Navigation System Reference.	Discrete GPS, INS, VOR/ DME, MLS, Loran C, Omega, Localizer Glidescope.	.....	4 .....	.....	A suitable combination of discretes to determine the Primary Navigation System reference.
61. Ice Detection	Discrete "ice" or "no ice".	.....	4.		
62. Engine warning each engine vibration.	Discrete .....	.....	1.		
63. Engine warning each engine over temp..	Discrete .....	.....	1.		
64. Engine warning each engine oil pressure low.	Discrete .....	.....	1.		
65. Engine warning each engine over speed.	Discrete .....	.....	1.		
66. Yaw Trim Surface Position.	Full Range .....	±3% Unless Higher Accuracy Uniquely Required.	2 .....	0.3% of full range.	
67. Roll Trim Surface Position.	Full Range .....	±3% Unless Higher Accuracy Uniquely Required.	2 .....	0.3% of full range.	
68. Brake Pressure (left and right).	As installed .....	±5% .....	1 .....	.....	To determine braking effort applied by pilots or by autobrakes.
69. Brake Pedal Application (left and right).	Discrete or Analog "applied" or "off".	±5% (Analog) .....	1 .....	.....	To determine braking applied by pilots.
70. Yaw or sideslip angle.	Full Range .....	±5% .....	1 .....	0.5°.	
71. Engine bleed valve position.	Discrete "open" or "closed".	.....	4.		
72. De-icing or anti-icing system selection.	Discrete "on" or "off".	.....	4.		

Federal Aviation Administration, DOT

Pt. 135, App. F

The recorded values must meet the designated range, resolution, and accuracy requirements during dynamic and static conditions. All data recorded must be correlated in time to within one second.

Parameters	Range	Accuracy (sensor input)	Seconds per sampling interval	Resolution	Remarks
73. Computed center of gravity.	Full Range .....	±5% .....	(1 per 64 sec.) ..	1% of full range.	
74. AC electrical bus status.	Discrete "power" or "off".	.....	4 .....	.....	Each bus.
75. DC electrical bus status.	Discrete "power" or "off".	.....	4 .....	.....	Each bus.
76. APU bleed valve position.	Discrete "open" or "closed".	.....	4.		
77. Hydraulic Pressure (each system).	Full range .....	±5% .....	2 .....	100 psi.	
78. Loss of cabin pressure.	Discrete "loss" or "normal".	.....	1.		
79. Computer failure (critical flight and engine control systems).	Discrete "fail" or "normal".	.....	4.		
80. Heads-up display (when an information source is installed).	Discrete(s) "on" or "off".	.....	4.		
81. Para-visual display (when an information source is installed).	Discrete(s) "on" or "off".	.....	1.		
82. Cockpit trim control input position—pitch.	Full Range .....	±5% .....	1 .....	0.2% of full range.	Where mechanical means for control inputs are not available, cockpit display trim positions should be recorded.
83. Cockpit trim control input position—roll.	Full Range .....	±5% .....	1 .....	0.7% of full range.	Where mechanical means for control inputs are not available, cockpit display trim position should be recorded.
84. Cockpit trim control input position—yaw.	Full Range .....	±5% .....	1 .....	0.3% of full range.	Where mechanical means for control input are not available, cockpit display trim positions should be recorded.
85. Trailing edge flap and cockpit flap control position.	Full Range .....	±5% .....	2 .....	0.5% of full range.	Trailing edge flaps and cockpit flap control position may each be sampled alternately at 4 second intervals to provide a sample each 0.5 second.
86. Leading edge flap and cockpit flap control position.	Full Range or Discrete.	±5% .....	1 .....	0.5% of full range.	
87. Ground spoiler position and speed brake selection.	Full Range or Discrete.	±5% .....	0.5 .....	0.3% of full range	

The recorded values must meet the designated range, resolution, and accuracy requirements during dynamic and static conditions. All data recorded must be correlated in time to within one second.

Parameters	Range	Accuracy (sensor input)	Seconds per sampling interval	Resolution	Remarks
88. All cockpit flight control input forces (control wheel, control column, rudder pedal).	Full Range Control Wheel ±70 lbs Control Column ±85 lb Rudder pedal ±165 lbs.	±5%	1	0.3% of full range.	For fly-by-wire flight control systems, where control surface position is a function of the displacement of the control input device only, it is not necessary to record this parameter. For airplanes that have a flight control break away capability that allows either pilot to operate the control independently, record both control force inputs. The control force inputs may be sampled alternately once per 2 seconds to produce the sampling interval of 1.

<sup>1</sup> For A300 B2/B4 airplanes, resolution = 6 seconds.  
<sup>2</sup> For A330/A340 series airplanes, resolution = 0.703°.  
<sup>3</sup> For A318/A319/A320/A321 series airplanes, resolution = 0.275% (0.088°>0.064°). For A330/A340 series airplanes, resolution = 2.20% (0.703°>0.064°).  
<sup>4</sup> For A318/A319/A320/A321 series airplanes, resolution = 0.22% (0.088°>0.080°). For A330/A340 series airplanes, resolution = 1.76% (0.703°>0.080°).  
<sup>5</sup> For A330/A340 series airplanes, resolution = 1.18% (0.703°>0.120°).  
<sup>6</sup> For A330/A340 series airplanes, resolution = 0.783% (0.352°>0.090°).  
<sup>7</sup> For A330/A340 series airplanes, aileron resolution = 0.704% (0.352°>0.100°). For A330/A340 series airplanes, spoiler resolution = 1.406% (0.703°>0.100°).  
<sup>8</sup> For A330/A340 series airplanes, resolution = 0.30% (0.176°>0.12°). For A330/A340 series airplanes, seconds per sampling interval = 1.  
<sup>9</sup> For B-717 series airplanes, resolution = .005g. For Dassault F900C/F900EX airplanes, resolution = .007g.  
<sup>10</sup> For A330/A340 series airplanes, resolution = 1.05% (0.250°>0.120°).  
<sup>11</sup> For A330/A340 series airplanes, resolution = 1.05% (0.250°>0.120°). For A300 B2/B4 series airplanes, resolution = 0.92% (0.230°>0.125°).  
<sup>12</sup> For A330/A340 series airplanes, spoiler resolution = 1.406% (0.703°>0.100°).  
<sup>13</sup> For A330/A340 series airplanes, resolution = 0.5 °C.  
<sup>14</sup> For Dassault F900C/F900EX airplanes, Radio Altitude resolution = 1.25 ft.  
<sup>15</sup> For A330/A340 series airplanes, resolution = 0.352 degrees.  
<sup>16</sup> For A318/A319/A320/A321 series airplanes, resolution = 4.32%. For A330/A340 series airplanes, resolution is 3.27% of full range for throttle lever angle (TLA); for reverse thrust, reverse throttle lever angle (RLA) resolution is nonlinear over the active reverse thrust range, which is 51.54 degrees to 96.14 degrees. The resolved element is 2.8 degrees uniformly over the entire active reverse thrust range, or 2.9% of the full range value of 96.14 degrees.  
<sup>17</sup> For A318/A319/A320/A321 series airplanes, with IAE engines, resolution = 2.58%.

[Doc. No. 28109, 62 FR 38398, July 17, 1997; 62 FR 48135, Sept. 12, 1997; Amdt. 135–85, 67 FR 54323, Aug. 21, 2002; Amdt. 135–89, 68 FR 42939, July 18, 2003; 68 FR 50069, Aug. 20, 2003]

APPENDIX G TO PART 135—EXTENDED OPERATIONS (ETOPS)

G135.1 Definitions.

G135.1.1 *Adequate Airport* means an airport that an airplane operator may list with approval from the FAA because that airport meets the landing limitations of §135.385 or is a military airport that is active and operational.

G135.1.2 *ETOPS Alternate Airport* means an adequate airport that is designated in a dispatch or flight release for use in the event of a diversion during ETOPS. This definition applies to flight planning and does not in any way limit the authority of the pilot in command during flight.

G135.1.3 *ETOPS Entry Point* means the first point on the route of an ETOPS flight, determined using a one-engine inoperative cruise speed under standard conditions in

still air, that is more than 180 minutes from an adequate airport.

G135.1.4 *ETOPS Qualified Person* means a person, performing maintenance for the certificate holder, who has satisfactorily completed the certificate holder's ETOPS training program.

G135.2 Requirements.

G135.2.1 *General*. After February 15, 2008, no certificate holder may operate an airplane, other than an all-cargo airplane with more than two engines, outside the continental United States more than 180 minutes flying time (at the one engine inoperative cruise speed under standard conditions in still air) from an airport described in §135.364 unless—

(a) The certificate holder receives ETOPS approval from the FAA;

(b) The operation is conducted in a multi-engine transport category turbine-powered airplane;