

opening to its terminus and be securely fastened and supported.

(e) A supply duct must be provided with a cowl or scoop having a free area not less than twice the required duct area. When the cowl or scoop is screened, the mouth area must be increased to compensate for the area of the screen wire. A cowl or scoop must be kept open at all times except when the weather is such as to endanger the vessel if the openings are not temporarily closed.

(f) Except as required by §116.610(f) of this chapter, dampers may not be fitted in a supply duct.

(g) A duct opening may not be located where the natural flow of air is unduly obstructed, adjacent to possible sources of vapor ignition, or where exhaust air may be taken into a supply duct.

(h) Provision must be made for closing all supply duct cowls or scoops and exhaust duct discharge openings for a space protected by a fixed gas extinguishing system. All closure devices must be readily available and mounted in the vicinity of the vent.

[CGD 85-080, 61 FR 922, Jan. 10, 1996, as amended at 62 FR 51352, Sept. 30, 1997]

§ 119.470 Ventilation of spaces containing diesel fuel tanks.

(a) Unless provided with ventilation that complies with §119.465 of this part, a space containing a diesel fuel tank and no machinery must meet one of the following requirements:

(1) A space of 14 cubic meters (500 cubic feet) or more in volume must have a gooseneck vent of not less than 65 millimeters (2.5 inches) in diameter; or

(2) A space of less than 14 cubic meters (500 cubic feet) in volume must have a gooseneck vent of not less than 40 millimeters (1.5 inches) in diameter.

(b) Vent openings may not be located adjacent to possible sources of vapor ignition.

Subpart E—Bilge and Ballast Systems

§ 119.500 General.

(a) A vessel must be provided with a satisfactory arrangement for draining

any watertight compartment, other than small buoyancy compartments, under all practicable conditions. Sluice valves are not permitted in watertight bulkheads.

(b) Special consideration may be given to vessels, such as high speed craft, which have a high degree of subdivision and utilize numerous small buoyancy compartments. Where the probability of flooding of the space is limited to external hull damage, compartment drainage may be omitted provided it can be shown by stability calculations, submitted to the cognizant OCMI, that the safety of the vessel will not be impaired.

§ 119.510 Bilge piping system.

A vessel must be provided with a piping system that meets §56.50-50 in subchapter F of this chapter, with the following exceptions:

(a) The space forward of the collision bulkhead need not be fitted with a bilge suction line when the arrangement of the vessel is such that ordinary leakage may be removed from this compartment by the use of a hand portable bilge pump or other equipment, and such equipment is provided; and

(b) The vessel need not comply with §56.50-50(f) in subchapter F of this chapter.

[CGD 85-080, 61 FR 922, Jan. 10, 1996, as amended by CGD 97-057, 62 FR 51047, Sept. 30, 1997]

§ 119.520 Bilge pumps.

(a) Each vessel must be provided with bilge pumps in accordance with §56.50-55 in subchapter F of this chapter, with the following exceptions:

(1) Note 1 in Table 56.50-55(a) is not applicable and should be disregarded; and

(2) A non-self-propelled vessel must comply with §56.50-55(a) in subchapter F of this chapter instead of §56.50-55(b).

(b) In addition to the requirements of paragraph (a) of this section, a vessel of not more than 19.8 meters (65 feet) in length must have a portable hand bilge pump that must be:

(1) Capable of pumping water, but not necessarily simultaneously, from all watertight compartments; and