

Federal Communications Commission

§ 74.794

N-2, N+2, N-3, N+3, N-4, N+4, N-7, N+7, N-8, N+8, N+14, and N+15.

(c) The following D/U signal strength ratios (dB) shall apply to the protection of stations on the first adjacent channel. The D/U ratios for "Digital TV-into-analog TV" shall apply to the protection of TV broadcast, Class A TV, LPTV and TV translator stations. The D/U ratios for "Digital TV-into-digital TV" shall apply to the protection of DTV, digital Class A TV, digital LPTV and digital TV translator stations. The D/U ratios correspond to the digital LPTV or TV translator station's specified out-of-channel emission mask.

	Simple mask	Stringent mask
Digital TV-into-analog TV	10	0
Digital TV-into-digital TV	-7	-12

(d) For analysis of predicted interference from digital low power TV and TV translator stations, the relative field strength values of the assumed antenna vertical radiation pattern in Table 8 in OET Bulletin 69 shall be doubled up to a value of 1.0.

(e) Protection to the authorized facilities of DTV broadcast stations shall be based on not causing predicted interference to the population within the service area defined and described in §73.622(e) of this chapter, except that a digital low power TV or TV translator station must not cause a loss of service to 0.5 percent or more of the population predicted to receive service from the authorized DTV facilities.

(f) Protection to the authorized facilities of TV broadcast stations shall be based on not causing predicted interference to the population within the Grade B field strength contours defined and described in §73.683 of this chapter, except that a digital low power TV or TV translator station must not cause a loss of service to 0.5 percent or more of the population predicted to receive service from the authorized TV broadcast facilities.

(g) Protection to the authorized facilities of Class A and digital Class A TV stations shall be based on not causing predicted interference to the population within the service area defined and described in §73.6010 (a) through (d) of this chapter, respectively, except

that a digital low power TV or TV translator station must not cause a loss of service to 0.5 percent or more of the population predicted to receive service from the authorized Class A TV or digital Class A TV facilities.

(h) Protection to the authorized facilities of low power TV and TV translator stations and digital low power TV and TV translator stations shall be based on not causing predicted interference to the population within the service area defined and described in §§74.707(a) and 74.792, respectively, except that a digital low power TV or TV translator station must not cause a loss of service to 2.0 percent or more of the population predicted to receive service from the authorized low power TV, TV translator, digital low power TV or digital TV translator station.

[69 FR 69335, Nov. 29, 2004]

§ 74.794 Digital emissions.

(a)(1) An applicant for a digital LPTV or TV translator station construction permit shall specify that the station will be constructed to confine out-of-channel emissions within one of the following emission masks: simple or stringent.

(2) The power level of emissions on frequencies outside the authorized channel of operation must be attenuated no less than following amounts below the average transmitted power within the authorized 6 MHz channel. In the mask specifications listed in §74.794(a)(2) and (a)(3), A is the attenuation in dB and Δf is the frequency difference in MHz from the edge of the channel.

(i) *Simple mask.* At the channel edges, emissions must be attenuated no less than 46 dB. More than 6 MHz from the channel edges, emissions must be attenuated no less than 71 dB. At any frequency between 0 and 6 MHz from the channel edges, emissions must be attenuated no less than the value determined by the following formula:

$$A \text{ (dB)} = 46 + (\Delta f^2 / 1.44)$$

(ii) *Stringent mask.* In the first 500 kHz from the channel edges, emissions must be attenuated no less than 47 dB. More than 3 MHz from the channel edges, emissions must be attenuated no

§ 74.795

47 CFR Ch. I (10–1–05 Edition)

less than 76 dB. At any frequency between 0.5 and 3 MHz from the channel edges, emissions must be attenuated no less than the value determined by the following formula:

$$A(\text{dB}) = 47 + 11.5 (\Delta f - 0.5)$$

(3) The attenuation values for the simple and stringent emission masks are based on a measurement bandwidth of 500 kHz. Other measurement bandwidths may be used and converted to the reference 500 kHz value by the following formula:

$$A(\text{dB}) = A_{\text{alternate}} + 10 \log (BW_{\text{alternate}} / 500)$$

where A(dB) is the measured or calculated attenuation value for the reference 500 kHz bandwidth, and A_{alternate} is the measured or calculated attenuation for a bandwidth BW_{alternate}. Emissions include sidebands, spurious emissions and radio harmonics. Attenuation is to be measured at the output terminals of the transmitter (including any filters that may be employed). In the event of interference caused to any service by out-of-channel emissions, greater attenuation may be required.

(b) In addition to meeting the emission attenuation requirements of the simple or stringent mask (including attenuation of radio frequency harmonics), digital low power TV and TV translator stations authorized to operate on TV channels 22–24, (518–536 MHz), 32–36 (578–608 MHz), 38 (614–620 MHz), and 65–69 (776–806 MHz) must provide specific “out of band” protection to Radio Navigation Satellite Services in the bands: L5 (1164–1215 MHz); L2 (1215–1240 MHz) and L1 (1559–1610 MHz).

(1) An FCC-certificated transmitter specifically certified for use on one or more of the above channels must include filtering with an attenuation of not less than 85 dB in the GPS bands, which will have the effect of reducing harmonics in the GPS bands from what is produced by the digital transmitter, and this attenuation must be demonstrated as part of the certification application to the Commission.

(2) For an installation on one of the above channels with a digital transmitter not specifically FCC-certificated for the channel, a low pass filter or equivalent device rated by its manufacturer to have an attenuation of at least 85 dB in the GPS bands, which

will have the effect of reducing harmonics in the GPS bands from what is produced by the digital transmitter, and must be installed in a manner that will prevent the harmonic emission content from reaching the antenna. A description of the low pass filter or equivalent device with the manufacturer’s rating or a report of measurements by a qualified individual shall be retained with the station license. Field measurements of the second or third harmonic output of a transmitter so equipped are not required.

[69 FR 69336, Nov. 29, 2004]

§ 74.795 Digital low power TV and TV translator transmission system facilities.

(a) A digital low power TV or TV translator station shall operate with a transmitter that is either certificated for licensing based on the following provisions or has been modified for digital operation pursuant to § 74.796.

(b) The following requirements must be met before digital low power TV and TV translator transmitter will be certificated by the FCC:

(1) The transmitter shall be designed to produce digital television signals that can be satisfactorily viewed on consumer receiving equipment based on the digital broadcast television transmission standard in § 73.682(d) of this chapter;

(2) Emissions on frequencies outside the authorized channel, measured at the output terminals of the transmitter (including any filters that may be employed), shall meet the requirements of § 74.794, as applicable;

(3) The transmitter shall be equipped to display the digital power output (*i.e.*, average power over a 6 MHz channel) and shall be designed to prevent the power output from exceeding the maximum rated power output under any condition;

(4) When subjected to variations in ambient temperature between 0 and 40 degrees Centigrade and variations in power main voltage between 85% and 115% of the rated power supply voltage, the frequency stability of the local oscillator in the RF channel upconverter shall be maintained within 10 kHz of the nominal value; and