## INSTRUMENT **BEAM LINE**



ATION NEUTRON SOURCE

## HYSPEC - Hybrid Spectrometer

HYSPEC is a high-intensity, direct-geometry instrument optimized for measurement of excitations in small single-crystal specimens. The incident neutron beam is monochromated using a Fermi chopper with short, straight blades and is then focused onto the sample using Bragg scattering optics. Neutrons are detected in a bank of position-sensitive detector tubes that can be positioned over a wide range of scattering angles about the sample axis. This combination of Fermi chopper and Bragg focusing



optics, plus a position-sensitive detector bank, leads to a highly flexible instrument in which the energy and wave vector resolution can be independently varied by nearly an order of magnitude. Either full or partial neutron polarization analysis can be deployed on HYSPEC. This is accomplished by using a Heusler crystal array to polarize the incident beam and either a <sup>3</sup>He spin filter or supermirror wideangle polarization analyzers for the scattered beam.

## SPECIFICATIONS

Moderator	Coupled cryogenic hydrogen
Moderator- to-Fermi chopper distance	37.2 m
Chopper - to-sample distance	3.2 m
Focusing crystals- to-sample distance	1.4–1.8 m
Sample- to-detector distance	4.5 m
Incident energy range	3.6–90 meV
Energy resolution (elastic scattering)	$0.02 < (\Delta E/E_I)$ < 0.2
Scattering- angle range	2° < 2θ <sub>S</sub> < 135°

## APPLICATIONS

HYSPEC is applicable primarily to studies in the following:

- Superconductors
- Strongly correlated electron materials
- Ferroelectrics
- Lattice and magnetic dynamics
- Phase transitions
- Quantum critical points
- Complex phases in intermetallic compounds
- Frustrated magnets
- Low-dimensional magnetic excitations
- Transition metal oxides
- Spin and lattice dynamics in nanostructures

FOR MORE INFORMATION, CONTACT Instrument Scientist: Mark Hagen, hagenme@ornl.gov, 865.241.9782 http://neutrons.ornl.gov/instrument\_systems/hyspec.shtml



To be commissioned in 2011

