

**ADDITIONAL INFORMATION FOR REGISTRATION OF ACCELERATOR(S)**

A Certificate of Registration authorizing operation of an accelerator must be received by your facility **prior to** operation. This includes the initial beam on and commissioning of the accelerator.

Completion of the attached form will assist the Radiation Safety Licensing Branch in evaluating your request for registration of your accelerator. (See 25 Texas Administrative Code(TAC) §289.226 and §289.229)

In addition to this form, the following must be submitted:

- Diagram of floor plan of the accelerator vault and surrounding areas
- Shielding calculations
- Operating and safety procedures
- Supervising Radiation Oncologist-copy of ABR License and curriculum Vitae (not required for industrial accelerator applications)

In order to correctly complete the shielding calculation form, please note the following:

**Workload** - The degree of use of the x-ray unit stated in terms of the weekly exposure of the useful beam at one meter from the source. ( $Rm^2$ )

**Barrier Name** - This should be the name given to the individual barrier. (example: Barrier 1, Barrier A, etc.). Indicate barrier name on copy of room design submitted. Include information for the ceiling and floor as applicable.

**P/S** - Is the barrier a primary (P) or a secondary (S) barrier?

Primary (P) - Is a radiation protective barrier which may be struck by the main or useful beam of radiation.

Secondary(S) - Is a radiation protective barrier which may not be struck by the useful beam of radiation, but only by leakage and/or scattered radiation.

**U/C** - Is the area uncontrolled (U) or controlled (C)?

Controlled (C) - Is an area which requires control of access, occupancy, and working conditions for radiation protection purposes.

Uncontrolled (U) - Is any area which does **not** meet the requirements of a controlled area.

**U** - Use Factor - The expected fraction of the workload during which the appropriate beam of radiation may strike the barrier in question. NOTE: For a secondary barrier (U) is always 1.

**T** - Occupancy Factor - The maximum fraction of time during which the area shielded by the barrier in question may be occupied by any one person.

**Distance - Primary** - The distance in meters from the isocenter to the point of incidence on the primary barrier.

**Distance - Secondary** - The distance in meters from the isocenter to the point of incidence on the secondary barrier.

**Include information for the ceiling and floor.**



Barrier Name: circle - Primary / Secondary  
circle - Controlled / Uncontrolled  
Use Factor \_\_\_\_\_  
Occupancy Factor \_\_\_\_\_  
Distance to Primary Barrier \_\_\_\_\_ meters  
Distance to Secondary Barrier \_\_\_\_\_ meters  
Thickness of Barrier \_\_\_\_\_ cm  
Type of Barrier Material:  
circle - Pb concrete iron \*other(specify) \_\_\_\_\_  
include tenth value layer thickness

---

Barrier Name: circle - Primary / Secondary  
circle - Controlled / Uncontrolled  
Use Factor \_\_\_\_\_  
Occupancy Factor \_\_\_\_\_  
Distance to Primary Barrier \_\_\_\_\_ meters  
Distance to Secondary Barrier \_\_\_\_\_ meters  
Thickness of Barrier \_\_\_\_\_ cm  
Type of Barrier Material:  
circle - Pb concrete iron \*other(specify) \_\_\_\_\_  
include tenth value layer thickness

---

Barrier Name: Ceiling circle - Primary / Secondary  
circle - Controlled / Uncontrolled  
Use Factor \_\_\_\_\_  
Occupancy Factor \_\_\_\_\_  
Distance to Primary Barrier \_\_\_\_\_ meters  
Distance to Secondary Barrier \_\_\_\_\_ meters  
Thickness of Barrier \_\_\_\_\_ cm  
Type of Barrier Material:  
circle - Pb concrete iron \*other(specify) \_\_\_\_\_  
include tenth value layer thickness

---

Barrier Name: Floor (if applicable) circle - Primary / Secondary  
circle - Controlled / Uncontrolled  
Use Factor \_\_\_\_\_  
Occupancy Factor \_\_\_\_\_  
Distance to Primary Barrier \_\_\_\_\_ meters  
Distance to Secondary Barrier \_\_\_\_\_ meters  
Thickness of Barrier \_\_\_\_\_ cm  
Type of Barrier Material:  
circle - Pb concrete iron \*other(specify) \_\_\_\_\_  
include tenth value layer thickness

---