

Table E417.19-1

Command Receiver Decoder Acceptance	Section E417.13	Quantity Tested
Component Examination:	E417.5	
Visual Examination	E417.5(b)	100%
Dimension Measurement	E417.5(c)	100%
Identification Check	E417.5(e)	100%
Performance Verification:	E417.3(d)	
Status-of-health <sup>(1)</sup>	E417.19(b)	100%
Functional Performance <sup>(1)</sup>	E417.19(c)	100%
Radio Frequency Processing <sup>(1)</sup>	E417.19(e)	100%
Inadvertent Command Output	E417.19(f)	
Logic Sequence <sup>(1)</sup>	E417.19(f)(5)	100%
Destruct Sequence <sup>(1)</sup>	E417.19(f)(6)	100%
Receiver Abnormal Logic <sup>(1)</sup>	E417.19(f)(7)	100%
Tone Drop <sup>(1)</sup>	E417.19(f)(9)	100%
AM Rejection <sup>(1)</sup>	E417.19(f)(10)	100%
Decoder Channel Deviation Rejection <sup>(1)</sup>	E417.19(f)(11)	100%
Abbreviated Performance Verification:	E417.3(e)	
Input Current Monitor <sup>(2)</sup>	E417.19(g)	100%
Output Functions <sup>(2)</sup>	E417.19(h)	100%
Radio Frequency Level Monitor <sup>(2)</sup>	E417.19(i)	100%
Thermal Performance <sup>(3)</sup>	E417.19(j)	100%
Operating Environment Tests:	E417.13	