

**U.S. Consumer Product Safety Commission
SAMPLE COLLECTION REPORT**

1. Sample Flag		2. Date Collected 12/4/96	3. Sample Type and Number: 97-830-3080 <input checked="" type="radio"/> Physical <input type="radio"/> Documentary	
4a. Product Name LOCK DE-ICER		4b Model V-500 VICTOR	4c NEISS 0955	5. Assignment Number
6. Complete for Import Samples Port of Entry: _____ Country of Origin: _____ Entry No. and Date: _____ Customs Contact: _____			7. MIS 32626 32567	8. Hours Activity <u> 1 </u> Travel <u> 3 </u>
		9a Home RO FOCR	9b Collecting RO FOCR	
10. Sample Cost	11. Invoice Value of Lot		12. Size of Lot 12	Units unt
13. Manufacturer/Importer # VIC019 VICTOR AUTOMOTIVE PRODUCT 501 S. WOLF RD. DES MOINES, IL 60016 <i>Plains</i>		14. Shipper/Foreign Manufacturer SEE #13		15. Dealer/Import Broker # SEE #13
16. Supporting documents attached: Invoice No. and Date: <u> #13325 </u> <u> 10/4/96 </u> Date Shipped: _____ Shipping Record and Date: _____ Affidavit Signer's name, title and date: <u> SIGNED BY TONI COCCONE, OFC. MGR, 12/04/96. </u>				
17. Product Identification: Product is described as a .625 fluid ounce pressurized container of Victor brand model #V-500 lock de-icer. Container has black and yellow label, red injector tip, white cap, all enclosed in a blister				
18. Reason for collection/analysis needed: <input checked="" type="radio"/> FHSA <input type="radio"/> CPSA <input type="radio"/> FFA <input type="radio"/> PPPA <input type="radio"/> RSA F/U to FOCR KAN-RP surveillance- suspect labeling violations.				
19. Summary of Field Screening: Product container and accompanying packaging both have several labeling violations, see attached narrative report for details. LSHL- please conduct analysis to confirm percentage of hazardous				
20. Sample size/Method of Collection: Sample was collected during inspection conducted on 12/04/96. Sample was collected at random from stock on hand in firm's warehouse; current inventory number unavailable. Sample remained in my custody or				
21. Identification on sample: 97-830-3080 DRB 12/4/96		22. Identification on seal and date: 97-830-3080 Dennis Blasius 12/4/96		
23a. Sample delivered to: SAMPLE CUST VIA RPS		23b Date 12/10/96	24. Report/Record Sent to: FOCR	
25. Laboratory/Office: LSHL <u> X </u> LSEL <u> </u> CRM <u> </u> CCA <u> </u> Other <u> </u>				
26. Remarks: Copy of narrative report, MSDS, invoicing, affidavit and original inspection request included with sample.				
27. Related Samples: 97-830-3201 thru 3204.				
28a Collector's name/title: Dennis Blasius Resident Investigator		28b Collector's signature/date: <i>Dennis R. Blasius</i> 12/9/96		
29a Reviewer's name/title: <i>John R. Vace, SSSP</i>		29b Reviewer's signature/date: <i>John R. Vace</i> 12/12/96		

122

MATERIAL SAFETY
DATA SHEET



Subsidiary of Ashland Oil Inc
P.O. BOX 2219
COLUMBUS, OHIO 43216
(614) 889-3333

Emergency
Telephone
1(800) 274-5263 or
1(800) ASHLAND

RECEIVED FEB 06 1995

Page: 1

002732

TECTYL 482

THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (THE HAZARD

Exhibit "D"

Victor Automotive

12/04/96 inspection

Q22

Product Name: TECTYL 482

ULTRAMOTIVE CORP
PO BOX 58
BETHEL

VT 05032

05 50 074 9199410-

PRODUCT: 7432486
INVOICE: 128145
INVOICE DATE: 01/22/95
TO: ULTRAMOTIVE CORP
CUSHING BLVD
BETHEL

Date Sheet No: 0223E08-007.008
Prepared: 01/18/95
Supersedes: 11/21/94
Print Date: 01/28/95

ATTN: PLANT MGR./SAFETY DIR.

VT 05032

SECTION I PRODUCT IDENTIFICATION

General or Generic ID: PETROLEUM BASED RUST PREVENTATIVE

SECTION II COMPONENTS

THE COMPOSITION OF THIS PRODUCT IS BEING WITHHELD AS A TRADE SECRET.

IF PRESENT, IARC, NTP AND OSHA CARCINOGENS AND CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III SECTION 313 ARE IDENTIFIED IN THIS SECTION. SEE DEFINITION PAGE FOR CLARIFICATION

INGREDIENT	Percent	PEL	TLV	Note
CORROSION INHIBITOR	10-25	5 MG/M3	5 MG/M3	(1)
ANTI-WEAR ADDITIVE	1-5			(2)
DISPERSANT SPIKE ADDITIVE	1-5			(3)
ALIPHATIC HYDROCARBON MIXTURE CAS #: 64742-83-8	55-70	5 MG/M3	5 MG/M3	(4)
ETHYLENE GLYCOL MONOBUTYL ETHER CAS #: 111-76-2	5-10	25 PPM - SKIN	25 PPM - SKIN	(5)

Notes:

- (1) PEL/TLV IS FOR OIL MIST. ACGIH SHORT TERM EXPOSURE LIMIT (STEL) FOR OIL MIST IS 10 MG/CLM.
THIS PROPRIETARY MATERIAL CONTAINS A METAL SULFONATE. RECENT INFORMATION INDICATES THAT SUCH SULFONATES HAVE THE POTENTIAL TO CAUSE ALLERGIC SKIN REACTIONS.
- (2) PEL/TLV NOT ESTABLISHED FOR THIS MATERIAL
THIS PRODUCT CONTAINS 80-90% ZINC C1-C16 ALKYL DITHIOPHOSPHATE (CAS #68648-42-3). ZINC COMPOUNDS ARE REPORTABLE UNDER SECTION 313 OF SARA TITLE III.
- (3) PEL/TLV NOT ESTABLISHED FOR THIS MATERIAL
THIS PRODUCT CONTAINS 50% ANTIMONY DIALKYL DITHIOCARBAMATE. ANTIMONY COMPOUNDS ARE REPORTABLE UNDER SECTION 313 OF SARA TITLE III.
- (4) PEL/TLV IS FOR OIL MIST. ACGIH SHORT TERM EXPOSURE LIMIT (STEL) FOR OIL MIST IS 10 MG/CUM.
- (5) SKIN ABSORPTION MAY CONTRIBUTE TO THE OVERALL ABSORPTION OF THIS MATERIAL. APPROPRIATE MEASURES SHOULD BE TAKEN TO PREVENT ABSORPTION SO THAT THE TLV AND/OR PEL ARE NOT INVALIDATED. SEE SECTION V.
THIS CHEMICAL IS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF SARA TITLE III.
NIOSH RECOMMENDS A LIMIT OF 5 PPM TWA FOR A 10 HOUR WORKDAY AND 40 HOUR WORKWEEK.

SECTION III PHYSICAL DATA

Boiling Point	for COMPONENT(9-10%)	338.00 Deg F 168.88 Deg C 760.00 mm Hg
Vapor Pressure	for COMPONENT(5-10%)	0.88 mm Hg 77.00 Deg F 25.00 Deg C
Specific Vapor Density	AIR = 1	> 1.00
Specific Gravity		77.00 Deg F 25.00 Deg C
Percent Volatiles		1-10%
Evaporation Rate		SLOWER THAN ETHER
Appearance		NOT SPECIFIED
State		LIQUID
Form		METER SOLN

CONTINUED ON PAGE: 2

129

253
02

MATERIAL SAFETY
DATA SHEET



ASHLAND CHEMICAL, INC.

Subsidiary Of Ashland Oil, Inc

P.O. BOX 2219

COLUMBUS, OHIO 43216

(614) 889-3333

24-HOUR
Emergency
Telephone

1 (800) 274-5263

1 (800) ASHLAND

002732

TECTYL 482

Page:

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED;

SMALL SPILL: ABSORB LIQUID ON VERMICULITE, FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL.

LARGE SPILL: ELIMINATE ALL IGNITION SOURCES (FLARES, FLAMES INCLUDING PILOT LIGHTS, ELECTRICAL SPARKS), PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN-UP HAS BEEN COMPLETED. STOP SPILL AT SOURCE; PREVENT FROM ENTERING DRAINS, SEWERS, STREAMS OR OTHER BODIES OF WATER. PREVENT FROM SPREADING. IF RUNOFF OCCURS, NOTIFY AUTHORITIES AS REQUIRED. PUMP OR VACUUM TRANSFER SPILLED PRODUCT TO CLEAN CONTAINERS FOR RECOVERY. ABSORB UNRECOVERABLE PRODUCT. TRANSFER CONTAMINATED ABSORBENT, SOIL AND OTHER MATERIALS TO CONTAINERS FOR DISPOSAL.

PREVENT RUN-OFF TO SEWERS, STREAMS OR OTHER BODIES OF WATER. IF RUN-OFF OCCURS, NOTIFY PROPER AUTHORITIES AS REQUIRED, THAT A SPILL HAS OCCURRED.

WASTE DISPOSAL METHOD:

SMALL SPILL: DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

LARGE SPILL: DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

SECTION VIII PROTECTIVE EQUIPMENT TO BE USED

RESPIRATORY PROTECTION: IF WORKPLACE EXPOSURE LIMIT(S) OF PRODUCT OR ANY COMPONENT IS EXCEEDED (SEE SECTION II) A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. OSHA REGULATIONS ALSO PERMIT OTHER NIOSH/MSHA RESPIRATORS (NEGATIVE PRESSURE TYPE) UNDER SPECIFIED CONDITIONS (SEE YOUR INDUSTRIAL HYGIENIST). ENGINEERING OR ADMINISTRATIVE CONTROLS SHOULD BE IMPLEMENTED TO REDUCE EXPOSURE.

VENTILATION: PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

PROTECTIVE GLOVES: WEAR RESISTANT GLOVES SUCH AS: NEOPRENE, NITRILE RUBBER

EYE PROTECTION: CHEMICAL SPLASH GOGGLES IN COMPLIANCE WITH OSHA REGULATIONS ARE ADVISED; HOWEVER, OSHA REGULATIONS ALSO PERMIT OTHER TYPE SAFETY GLASSES. CONSULT YOUR SAFETY REPRESENTATIVE.

OTHER PROTECTIVE EQUIPMENT: TO PREVENT REPEATED OR PROLONGED SKIN CONTACT, WEAR IMPERVIOUS CLOTHING AND BOOTS.

SECTION IX SPECIAL PRECAUTIONS OR OTHER COMMENTS

CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED, SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID), ALL HAZARD PRECAUTIONS GIVEN IN THIS DATASHEET MUST BE OBSERVED.

THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

SECTION X LABEL INFORMATION

WARNING:

COMBUSTIBLE LIQUID AND VAPOR

MAY CAUSE EYE AND SKIN IRRITATION.

COMPONENT(S) MAY BE ABSORBED THROUGH SKIN IN TOXIC AMOUNTS.

INHALATION OF VAPOR MAY CAUSE IRRITATION OF NASAL AND RESPIRATORY PASSAGES.

SWALLOWING MAY CAUSE IRRITATION OF MOUTH, ESOPHAGUS, AND GASTROINTESTINAL SYSTEM AND MAY BE FATAL.

HANDLING & STORAGE:

KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. USE OR STORE ONLY WITH ADEQUATE VENTILATION. AVOID CONTACT WITH EYES AND SKIN. WEAR SAFETY GLASSES OR GOGGLES, RESISTANT GLOVES, AND OTHER APPROPRIATE PROTECTIVE EQUIPMENT ESSENTIAL FOR YOUR OPERATION. MINIMIZE EXPOSURE THROUGH GOOD HYGIENIC PRACTICES. DO NOT TRANSFER TO UNLABELED CONTAINER. DO NOT USE CUTTING OR WELDING TORCH ON THIS CONTAINER (EVEN EMPTY). FOR INDUSTRIAL USE ONLY.

FIRST AID:

EYES: FLUSH THOROUGHLY WITH WATER. GET MEDICAL ATTENTION IMMEDIATELY.

SKIN: WASH THOROUGHLY WITH SOAP AND WATER.

INHALATION: IF AFFECTED, REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, GET MEDICAL ATTENTION.

INGESTION: DO NOT INDUCE VOMITING. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

CHRONIC INFORMATION:

CONTAINS MATERIAL(S) WHICH MAY CAUSE BLOOD ABNORMALITIES, CENTRAL NERVOUS SYSTEM DEPRESSION, RESPIRATORY SYSTEM, EYE, KIDNEY AND/OR LIVER DAMAGE. CONTAINS: PETROLEUM OIL AND ETHYLENE GLYCOL MONOBUTYL ETHER(EGMBE).

*** COMPONENTS APPEAR IN SECTION II ***

124



002732

TECTYL 482

Page: 2

SECTION IV - FIRE AND EXPLOSION INFORMATION

FLASH POINT(PMCC) 180.0 - 170.0 Deg F (71.1 - 76.7 Deg C)
EXPLOSIVE LIMIT (LOWEST VALUE OF COMPONENT) LOWER - 1.1%
EXTINGUISHING MEDIA: REGULAR FOAM OR CARBON DIOXIDE OR DRY CHEMICAL
HAZARDOUS DECOMPOSITION PRODUCTS: MAY FORM TOXIC MATERIALS: CARBON DIOXIDE AND CARBON MONOXIDE, VARIOUS HYDROCARBONS, ETC., SULFUR COMPOUNDS, CALCIUM OXIDE
FIREFIGHTING PROCEDURES: WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE WHEN FIGHTING FIRES.
SPECIAL FIRE & EXPLOSION HAZARDS: NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.
VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR BE MOVED BY VENTILATION AND IGNITED BY HEAT, PILOT LIGHTS, OTHER FLAMES AND IGNITION SOURCES AT LOCATIONS DISTANT FROM MATERIAL HANDLING POINT.
ALL FIVE GALLON PAILS AND LARGER METAL CONTAINERS INCLUDING TANK CARS AND TANK TRUCKS SHOULD BE GROUNDED AND/OR BONDED WHEN MATERIAL IS TRANSFERRED.
HPPA CODES: HEALTH- 1 FLAMMABILITY- 2 REACTIVITY- 0

SECTION V - HEALTH HAZARD DATA

PERMISSIBLE EXPOSURE LEVEL: NOT ESTABLISHED FOR PRODUCT. SEE SECTION 11.
EFFECTS OF ACUTE OVEREXPOSURE:
EYES - EXPOSURE CAUSES EYE IRRITATION. SYMPTOMS MAY INCLUDE STINGING, TEARING, REDNESS, AND SWELLING.
SKIN - EXPOSURE CAUSES SKIN IRRITATION. PROLONGED OR REPEATED EXPOSURE MAY DRY THE SKIN. SYMPTOMS MAY INCLUDE REDNESS, BURNING, DRYING AND CRACKING, SKIN BURNS AND SKIN DAMAGE. PRE-EXISTING SKIN DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS MATERIAL.
SKIN ABSORPTION IS POSSIBLE, AND MAY CONTRIBUTE TO SYMPTOMS OF TOXICITY FROM OTHER ROUTES OF EXPOSURE.
BREATHING - EXPOSURE TO VAPOR OR MIST IS POSSIBLE.
SHORT-TERM INHALATION TOXICITY IS LOW. BREATHING SMALL AMOUNTS DURING NORMAL HANDLING IS NOT LIKELY TO CAUSE HARMFUL EFFECTS; BREATHING LARGE AMOUNTS MAY BE HARMFUL.
SYMPTOMS MAY INCLUDE:
-IRRITATION (NOSE, THROAT, RESPIRATORY TRACT)- PRE-EXISTING LUNG DISORDERS, E.G. ASTHMA-LIKE CONDITIONS, MAY BE AGGRAVATED BY EXPOSURE TO THIS MATERIAL.
-CENTRAL NERVOUS SYSTEM DEPRESSION (DIZZINESS, DROWSINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUSNESS)-
-AND DEATH
SWALLOWING - SINGLE DOSE ORAL TOXICITY IS LOW. SWALLOWING SMALL AMOUNTS DURING NORMAL HANDLING IS NOT LIKELY TO CAUSE HARMFUL EFFECTS; SWALLOWING LARGE AMOUNTS MAY BE HARMFUL.
SYMPTOMS MAY INCLUDE:
-GASTROINTESTINAL IRRITATION (NAUSEA, VOMITING, DIARRHEA)-
THIS MATERIAL CAN ENTER THE LUNGS DURING SWALLOWING OR VOMITING AND CAUSE LUNG INFLAMMATION AND/OR DAMAGE.
FIRST AID:
IF ON SKIN: REMOVE CONTAMINATED CLOTHING. WASH EXPOSED AREA WITH SOAP AND WATER. IF SYMPTOMS PERSIST, SEEK MEDICAL ATTENTION. LAUNDRY CLOTHING BEFORE REUSE.
IF IN EYES: IF SYMPTOMS DEVELOP, MOVE INDIVIDUAL AWAY FROM EXPOSURE AND INTO FRESH AIR. FLUSH EYES GENTLY WITH WATER WHILE HOLDING EYELIDS APART. IF SYMPTOMS PERSIST OR THERE IS ANY VISUAL DIFFICULTY, SEEK MEDICAL ATTENTION.
IF SWALLOWED: DO NOT INDUCE VOMITING, KEEP PERSON WARM AND QUIET, AND GET MEDICAL ATTENTION.
IF BREATHED: IF SYMPTOMS DEVELOP, IMMEDIATELY MOVE INDIVIDUAL AWAY FROM EXPOSURE AND INTO FRESH AIR. SEEK IMMEDIATE MEDICAL ATTENTION; KEEP PERSON WARM AND QUIET. IF PERSON IS NOT BREATHING, BEGIN ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN.

PRIMARY ROUTE(S) OF ENTRY:

INHALATION, SKIN CONTACT, SKIN ABSORPTION

EFFECTS OF CHRONIC OVEREXPOSURE:

ETHYLENE GLYCOL MONOBUTYL ETHER (GLYCOL ETHER EB) CAUSES HARM TO THE FETUS IN LABORATORY ANIMAL STUDIES. HARM TO THE FETUS OCCURS ONLY AT EXPOSURE LEVELS THAT HARM THE PREGNANT ANIMAL. THE RELEVANCE OF THESE FINDINGS TO HUMANS IS UNCERTAIN.
OVEREXPOSURE TO THIS MATERIAL (OR ITS COMPONENTS) HAS BEEN SUGGESTED AS A CAUSE OF THE FOLLOWING EFFECTS IN LABORATORY ANIMALS, AND MAY AGGRAVATE PRE-EXISTING DISORDERS OF THESE ORGANS IN HUMANS: ANEMIA, LIVER ABNORMALITIES, KIDNEY DAMAGE, LUNG DAMAGE, BLOOD ABNORMALITIES, TESTIS DAMAGE, SPLEEN DAMAGE
OVEREXPOSURE TO THIS MATERIAL (OR ITS COMPONENTS) HAS BEEN SUGGESTED AS A CAUSE OF THE FOLLOWING EFFECTS IN HUMANS, AND MAY AGGRAVATE PRE-EXISTING DISORDERS OF THESE ORGANS: CENTRAL NERVOUS SYSTEM EFFECTS

SECTION VI - REACTIVITY DATA

HAZARDOUS POLYMERIZATION: CANNOT OCCUR
STABILITY: STABLE
INCOMPATIBILITY: AVOID CONTACT WITH: STRONG OXIDIZING AGENTS

victor automotive
12/04/96 inspection

093

ULTRAM

ULTRAMOTIVE CORP.

P. O. BOX 58
BETHEL, VT 05032
(802) 234-9901 • FAX (802) 234-9904


INVOICE

13325

Victor Automotive Products
501 South Wolf Road
Des Plaines, IL 60016

SHIPPED TO

same

INVOICE DATE	DATE SHIPPED	OUR ORDER NO.	YOUR ORDER NO.	TERMS	F.O.B.	SALESPERSON	SHIPPED VIA
10/04/96	10/04/96	671	9225	2% 10, N30	Bethel, VT		Yellow
QUANTITY	DESCRIPTION					PRICE	AMOUNT
100,440	units, V-500 Lock Deicer 360 cases @ 279					\$0.08	\$8,035.20
This is a partial shipment agianst the above order.							
12/4/96 TC 							

84144, RAPIDFORMS INC. TO REGISTER CALL 800 257 6754

THANK YOU

Agent or Cashier

THE CERTIFICATION This is to certify that the above named materials are properly
test, described, packaged, marked and labeled, and are in proper condition for trans-
portation according to the applicable regulations of the Department of Transportation

1 C.C.D. TO: (ADDRESS)

C.O.D. AMOUNT

\$


TITLE

C.O.D. CHARGE TO BE PAID BY SHIPPER CONSIGNEE

Per

(The signature here acknowledges only the amount prepaid.)

Charges Advanced,



and labeled, and are in proper condition for transportation according to the applicable regulations of the Department of Transportation
All of labeling shall state whether it is "carrier's or shipper's weight"

in writing the agreed or declared value of the property,
the amount, and all other requirements of Rule 41 of the Uniform Freight Classification and Rule 5 of the National Motor Freight Classification.

declared value of the
property specifically stated
or to be not exceeding

per

\$

ULTRAMOTIVE CORPORATION
501 South Wolf Road • Bethel, VT 05032

Shipper _____

Agent VFS 10/4/96 (4)

Per _____

Per SPH 12/4/96

victor automotive
12/04/96 inspection
(093)

CPSC Surveillance Report

1. Reporting Office FOCR	2. Home Office FOCR	3. Date 8/14/96	4. Product Code 1133
5a. Product Name LOCK DE-ICER		5b. Model VICTOR #V-500 AMOUNT UNK	
5c. Product Description & Identification LOCK DE-ICER, UNDER PRESSURE, SMALL METAL TUBE IN BLISTER PACKAGE.			
Attachment: () Label () Photo () Literature () Other _____			
5d. Manufacturer/Importer - Name and Address VICTOR AUTOMOTIVE PRODUCT INC. DES PLAINES, IL. 60016			
6a. Suspected Problem/Violation <input checked="" type="checkbox"/> FHSA - Labeling, Banned <input type="checkbox"/> PPPA - No CRP, Ineffective CRP, Labeling <input type="checkbox"/> FFA - Labeling, Fails Std., Cert. <input type="checkbox"/> CPSA - Possible Sec. 15, Fails Std., Cert. <input type="checkbox"/> RSA - Noncompliance <input type="checkbox"/> Other - Refer to other Federal or State Agency		6b Describe NO WARNING ON FRONT DISPLAY PANEL. TUBE WAS TURNED IN PACKAGE, NO WARNING COULD BE READ, CONTENTS UNDER PRESSURE, FLAMMABLE?	
7. Establishment Where Encountered - Name and Address WESTLAKE ACE HARDWARE 15225 87TH ST. LENEXA, KS. 66219			
8. Reported by (Type Name & Title) ROBERT B. WADSWORTH JR. INVESTIGATOR	9. Employee No. 8158	10. Signature 8/16/96 <i>Robert B. Wadsworth</i>	
11. Reporting Office Action <input checked="" type="checkbox"/> Referred to Home Office <input type="checkbox"/> Referred to HO () <input type="checkbox"/> Official Sample Collected (Sample # _____) <input type="checkbox"/> EI at Dealer <input type="checkbox"/> Other <input type="checkbox"/> None; if none, why:	12. Reviewing Official		14. Signature <i>[Signature]</i>
	13. Title <i>SPSE</i>	15. Date <i>9/6/96</i>	
	16. Distribution: <i>0: FOCR Compli</i>		

127

PRODUCT IDENTIFICATION

packaging.

FIELD SUMMARY

flashpoint.

METHOD OF COLLECTION

in the locked CPSC office from time of collection until later shipment to the Sample Custodian on 12/10/96. Samples were labeled as ID'd in #21, and shipped in a box sealed as ID'd in #22.

129

MATERIAL SAFETY
DATA SHEET



ASHLAND CHEMICAL, INC.
Subsidiary of Ashland Oil Inc
P.O. BOX 2219
COLUMBUS, OHIO 43216
(614) 889-3333

24-HOUR
Emergency
Telephone
1(800) 274-5263 or
1(800) ASHLAND

RECEIVED FEB 06 1995

002732

TECTYL 482

Page:

THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (THE HAZARD COMMUNICATIONS)

Exhibit "D"

Victor Automotive

12/14/96 inspection

003

1500

Product Name: TECTYL 482

ULTRAMOTIVE CORP
PO BOX 58
BETHEL

VT 05032

05 50 074 9199410-

PRODUCT: 7432486
INVOICE: 128145
INVOICE DATE: 01/22/95
TO: ULTRAMOTIVE CORP
CUSHING BLVD
BETHEL

Date Sheet No: 0223808-007.005
Prepared: 01/18/95
Supersedes: 11/21/94
Print Date: 01/28/95

ATTN: PLANT MGR./SAFETY DIR.

VT 05032

SECTION I - PRODUCT IDENTIFICATION

General or Generic ID: PETROLEUM BASED RUST PREVENTATIVE

SECTION II - COMPONENTS

THE COMPOSITION OF THIS PRODUCT IS BEING WITHHELD AS A TRADE SECRET.

IF PRESENT, IARC, NTP AND OSHA CARCINOGENS AND CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III SECTION 313 ARE IDENTIFIED IN THIS SECTION. SEE DEFINITION PAGE FOR CLARIFICATION

INGREDIENT	Percent	PEL	TLV	Note
CORROSION INHIBITOR	10-25	5 MG/M3	5 MG/M3	(1)
ANTI-WEAR ADDITIVE	1-5			(2)
DISPERSANT SPIKE ADDITIVE	1-5			(3)
ALIPHATIC HYDROCARBON MIXTURE CAS #: 64742-83-8	55-70	5 MG/M3	5 MG/M3	(4)
ETHYLENE GLYCOL MONOBUTYL ETHER CAS #: 111-78-2	5-10	25 PPM - SKIN	25 PPM - SKIN	(5)

Notes:

- (1) PEL/TLV IS FOR OIL MIST. ACGIH SHORT TERM EXPOSURE LIMIT (STEL) FOR OIL MIST IS 10 MG/CUM.
THIS PROPRIETARY MATERIAL CONTAINS A METAL SULFONATE. RECENT INFORMATION INDICATES THAT SUCH SULFONATES HAVE THE POTENTIAL TO CAUSE ALLERGIC SKIN REACTIONS.
- (2) PEL/TLV NOT ESTABLISHED FOR THIS MATERIAL
THIS PRODUCT CONTAINS 50-80% ZINC C1-C18 ALKYL-DITHIOMPHOSPHATE (CAS #68648-42-3). ZINC COMPOUNDS ARE REPORTABLE UNDER SECTION 313 OF SARA TITLE III.
- (3) PEL/TLV NOT ESTABLISHED FOR THIS MATERIAL
THIS PRODUCT CONTAINS 50% ANTIMONY DIALKYLDITHIOCARBAMATE. ANTIMONY COMPOUNDS ARE REPORTABLE UNDER SECTION 313 OF SARA TITLE III.
- (4) PEL/TLV IS FOR OIL MIST. ACGIH SHORT TERM EXPOSURE LIMIT (STEL) FOR OIL MIST IS 10 MG/CUM.
- (5) SKIN ABSORPTION MAY CONTRIBUTE TO THE OVERALL ABSORPTION OF THIS MATERIAL. APPROPRIATE MEASURES SHOULD BE TAKEN TO PREVENT ABSORPTION SO THAT THE TLV AND/OR PEL ARE NOT INVALIDATED. SEE SECTION V.
THIS CHEMICAL IS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF SARA TITLE III.
NIOSH RECOMMENDS A LIMIT OF 5 PPM TWA FOR A 10 HOUR WORKDAY AND 40 HOUR WORKWEEK.

SECTION III - PHYSICAL DATA

Boiling Point	for COMPONENT(5-10%)	335.00 Deg F 168.00 Deg C 760.00 mm Hg
Vapor Pressure	for COMPONENT(5-10%)	0.88 mm Hg 77.00 Deg F 25.00 Deg C
Specific Vapor Density	AIR = 1	> 1.00
Specific Gravity		77.00 Deg F 25.00 Deg C
Percent Volatiles		1-10%
Evaporation Rate		SLOWER THAN ETHER
Appearance		NOT SPECIFIED
State		LIQUID
Form		HETER SOLN

CONTINUED ON PAGE: 2

120

263 of
MATERIAL SAFETY
DATA SHEET



ASHLAND CHEMICAL, INC.
Subsidiary Of Ashland Oil, Inc.
P.O. BOX 2219
COLUMBUS, OHIO 43216
(614) 889-3333

24-HOUR
Emergency
Telephone
1 (800) 274-5263
1 (800) ASHLAND

002732

TECTYL 482

Page:

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED;

SMALL SPILL: ABSORB LIQUID ON VERMICULITE, FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL.

LARGE SPILL: ELIMINATE ALL IGNITION SOURCES (FLARES, FLAMES INCLUDING PILOT LIGHTS, ELECTRICAL SPARKS). PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN-UP HAS BEEN COMPLETED. STOP SPILL AT SOURCE. PREVENT FROM ENTERING DRAINS, SEWERS, STREAMS OR OTHER BODIES OF WATER. PREVENT FROM SPREADING. IF RUNOFF OCCURS, NOTIFY AUTHORITIES AS REQUIRED. PUMP OR VACUUM TRANSFER SPILLED PRODUCT TO CLEAN CONTAINERS FOR RECOVERY. ABSORB UNRECOVERABLE PRODUCT. TRANSFER CONTAMINATED ABSORBENT, SOIL AND OTHER MATERIALS TO CONTAINERS FOR DISPOSAL.

PREVENT RUN-OFF TO SEWERS, STREAMS OR OTHER BODIES OF WATER. IF RUN-OFF OCCURS, NOTIFY PROPER AUTHORITIES AS REQUIRED, THAT A SPILL HAS OCCURRED.

WASTE DISPOSAL METHOD:

SMALL SPILL: DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

LARGE SPILL: DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

SECTION VIII - PROTECTIVE EQUIPMENT TO BE USED

RESPIRATORY PROTECTION: IF WORKPLACE EXPOSURE LIMIT(S) OF PRODUCT OR ANY COMPONENT IS EXCEEDED (SEE SECTION II), A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. OSHA REGULATIONS ALSO PERMIT OTHER NIOSH/MSHA RESPIRATORS (NEGATIVE PRESSURE TYPE) UNDER SPECIFIED CONDITIONS (SEE YOUR INDUSTRIAL HYGIENIST). ENGINEERING OR ADMINISTRATIVE CONTROLS SHOULD BE IMPLEMENTED TO REDUCE EXPOSURE.

VENTILATION: PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

PROTECTIVE GLOVES: WEAR RESISTANT GLOVES SUCH AS: NEOPRENE, NITRILE RUBBER

EYE PROTECTION: CHEMICAL SPLASH GOGGLES IN COMPLIANCE WITH OSHA REGULATIONS ARE ADVISED. HOWEVER, OSHA REGULATIONS ALSO PERMIT OTHER TYPE SAFETY GLASSES. CONSULT YOUR SAFETY REPRESENTATIVE.

OTHER PROTECTIVE EQUIPMENT: TO PREVENT REPEATED OR PROLONGED SKIN CONTACT, WEAR IMPERVIOUS CLOTHING AND BOOTS.

SECTION IX - SPECIAL PRECAUTIONS OR OTHER COMMENTS

CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED, SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID), ALL HAZARD PRECAUTIONS GIVEN IN THIS DATASHEET MUST BE OBSERVED.

THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

SECTION X - LABEL INFORMATION

WARNING:

COMBUSTIBLE LIQUID AND VAPOR

MAY CAUSE EYE AND SKIN IRRITATION.

COMPONENT(S) MAY BE ABSORBED THROUGH SKIN IN TOXIC AMOUNTS.

INHALATION OF VAPOR MAY CAUSE IRRITATION OF NASAL AND RESPIRATORY PASSAGES.

SWALLOWING MAY CAUSE IRRITATION OF MOUTH, ESOPHAGUS, AND GASTROINTESTINAL SYSTEM AND MAY BE FATAL.

HANDLING & STORAGE:

KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. USE OR STORE ONLY WITH ADEQUATE VENTILATION. AVOID CONTACT WITH EYES AND SKIN. WEAR SAFETY GLASSES OR GOGGLES, RESISTANT GLOVES AND OTHER APPROPRIATE PROTECTIVE EQUIPMENT ESSENTIAL FOR YOUR OPERATION. MINIMIZE EXPOSURE THROUGH GOOD HYGIENIC PRACTICES. DO NOT TRANSFER TO UNLABELED CONTAINER. DO NOT USE CUTTING OR WELDING TORCH ON THIS CONTAINER (EVEN EMPTY). FOR INDUSTRIAL USE ONLY.

FIRST AID:

EYES: FLUSH THOROUGHLY WITH WATER. GET MEDICAL ATTENTION IMMEDIATELY.

SKIN: WASH THOROUGHLY WITH SOAP AND WATER.

INHALATION: IF AFFECTED, REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, GET MEDICAL ATTENTION.

INGESTION: DO NOT INDUCE VOMITING. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

CHRONIC INFORMATION:

CONTAINS MATERIAL(S) WHICH MAY CAUSE BLOOD ABNORMALITIES, CENTRAL NERVOUS SYSTEM DEPRESSION, RESPIRATORY SYSTEM, EYE, KIDNEY AND/OR LIVER DAMAGE. CONTAINS: PETROLEUM OIL AND ETHYLENE GLYCOL MONOBUTYL ETHER(EGMBE).

*** COMPONENTS APPEAR IN SECTION II ***



002732

TECTYL 482

Page: 2

SECTION IV - FIRE AND EXPLOSION INFORMATION

FLASH POINT(MWCC) 180.0 - 170.0 Deg F (71.1 - 76.7 Deg C)
EXPLOSIVE LIMIT (LOWEST VALUE OF COMPONENT) LOWER - 1.1%
EXTINGUISHING MEDIA: REGULAR FOAM OR CARBON DIOXIDE OR DRY CHEMICAL
HAZARDOUS DECOMPOSITION PRODUCTS: MAY FORM TOXIC MATERIALS; CARBON DIOXIDE AND CARBON MONOXIDE, VARIOUS HYDROCARBONS, ETC., SULFUR COMPOUNDS, CALCIUM OXIDE
FIREFIGHTING PROCEDURES: WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE WHEN FIGHTING FIRES.
SPECIAL FIRE & EXPLOSION HAZARDS: NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.
VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR BE MOVED BY VENTILATION AND IGNITED BY HEAT, PILOT LIGHTS, OTHER FLAMES AND IGNITION SOURCES AT LOCATIONS DISTANT FROM MATERIAL HANDLING POINT.
ALL FIVE GALLON PAILS AND LARGER METAL CONTAINERS INCLUDING TANK CARS AND TANK TRUCKS SHOULD BE GROUNDED AND/OR BONDED WHEN MATERIAL IS TRANSFERRED.
NFPA CODES: HEALTH- 1 FLAMMABILITY- 2 REACTIVITY- 0

SECTION V - HEALTH HAZARD DATA

PERMISSIBLE EXPOSURE LEVEL: NOT ESTABLISHED FOR PRODUCT. SEE SECTION II.
EFFECTS OF ACUTE OVEREXPOSURE:
YES - EXPOSURE CAUSES EYE IRRITATION. SYMPTOMS MAY INCLUDE STINGING, TEARING, REDNESS, AND SWELLING.
SKIN - EXPOSURE CAUSES SKIN IRRITATION. PROLONGED OR REPEATED EXPOSURE MAY DRY THE SKIN. SYMPTOMS MAY INCLUDE REDNESS, BURNING, DRYING AND CRACKING. SKIN BURNS AND SKIN DAMAGE. PRE-EXISTING SKIN DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS MATERIAL.
SKIN ABSORPTION IS POSSIBLE AND MAY CONTRIBUTE TO SYMPTOMS OF TOXICITY FROM OTHER ROUTES OF EXPOSURE.
BREATHING - EXPOSURE TO VAPOR OR MIST IS POSSIBLE.
SHORT-TERM INHALATION TOXICITY IS LOW. BREATHING SMALL AMOUNTS DURING NORMAL HANDLING IS NOT LIKELY TO CAUSE HARMFUL EFFECTS; BREATHING LARGE AMOUNTS MAY BE HARMFUL.
SYMPTOMS MAY INCLUDE:
-IRRITATION (NOSE, THROAT, RESPIRATORY TRACT)- PRE-EXISTING LUNG DISORDERS, E.G. ASTHMA-LIKE CONDITIONS, MAY BE AGGRAVATED BY EXPOSURE TO THIS MATERIAL.
-CENTRAL NERVOUS SYSTEM DEPRESSION (DIZZINESS, DROWSINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUSNESS)-
-AND DEATH
SWALLOWING - SINGLE DOSE ORAL TOXICITY IS LOW. SWALLOWING SMALL AMOUNTS DURING NORMAL HANDLING IS NOT LIKELY TO CAUSE HARMFUL EFFECTS; SWALLOWING LARGE AMOUNTS MAY BE HARMFUL.
SYMPTOMS MAY INCLUDE:
-GASTROINTESTINAL IRRITATION (NAUSEA, VOMITING, DIARRHEA)-
THIS MATERIAL CAN ENTER THE LUNGS DURING SWALLOWING OR VOMITING AND CAUSE LUNG INFLAMMATION AND/OR DAMAGE.
FIRST AID:
IF ON SKIN: REMOVE CONTAMINATED CLOTHING. WASH EXPOSED AREA WITH SOAP AND WATER. IF SYMPTOMS PERSIST, SEEK MEDICAL ATTENTION. LAUNDRY CLOTHING BEFORE REUSE.
IF IN EYES: IF SYMPTOMS DEVELOP, MOVE INDIVIDUAL AWAY FROM EXPOSURE AND INTO FRESH AIR. FLUSH EYES GENTLY WITH WATER WHILE HOLDING EYELIDS APART. IF SYMPTOMS PERSIST OR THERE IS ANY VISUAL DIFFICULTY, SEEK MEDICAL ATTENTION.
IF SWALLOWED: DO NOT INDUCE VOMITING. KEEP PERSON WARM AND QUIET. AND GET MEDICAL ATTENTION.
IF BREATHED: IF SYMPTOMS DEVELOP, IMMEDIATELY MOVE INDIVIDUAL AWAY FROM EXPOSURE AND INTO FRESH AIR. SEEK IMMEDIATE MEDICAL ATTENTION. KEEP PERSON WARM AND QUIET. IF PERSON IS NOT BREATHING, BEGIN ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN.

PRIMARY ROUTE(S) OF ENTRY:

INHALATION, SKIN CONTACT, SKIN ABSORPTION

EFFECTS OF CHRONIC OVEREXPOSURE:

ETHYLENE GLYCOL MONOBUTYL ETHER (GLYCOL ETHER EB) CAUSES HARM TO THE FETUS IN LABORATORY ANIMAL STUDIES. HARM TO THE FETUS OCCURS ONLY AT EXPOSURE LEVELS THAT HARM THE PREGNANT ANIMAL. THE RELEVANCE OF THESE FINDINGS TO HUMANS IS UNCERTAIN.
OVEREXPOSURE TO THIS MATERIAL (OR ITS COMPONENTS) HAS BEEN SUGGESTED AS A CAUSE OF THE FOLLOWING EFFECTS IN LABORATORY ANIMALS, AND MAY AGGRAVATE PRE-EXISTING DISORDERS OF THESE ORGANS IN HUMANS: ANEMIA, LIVER ABNORMALITIES, KIDNEY DAMAGE, LUNG DAMAGE, BLOOD ABNORMALITIES, TESTIS DAMAGE, SPLEEN DAMAGE
OVEREXPOSURE TO THIS MATERIAL (OR ITS COMPONENTS) HAS BEEN SUGGESTED AS A CAUSE OF THE FOLLOWING EFFECTS IN HUMANS, AND MAY AGGRAVATE PRE-EXISTING DISORDERS OF THESE ORGANS: CENTRAL NERVOUS SYSTEM EFFECTS

SECTION VI - PHYSICAL AND CHEMICAL DATA

HAZARDOUS POLYMERIZATION: CANNOT OCCUR
STABILITY: STABLE
INCOMPATIBILITY: AVOID CONTACT WITH: STRONG OXIDIZING AGENTS

132

subject to the classifier.

VICTOR
Victor Automotive
12/4/96 Inspection

Q43

ULTRAM

ULTRAMOTIVE CORP.

P. O. BOX 58
BETHEL, VT 05032
(802) 234-9901 • FAX (802) 234-9904


INVOICE

13325

Victor Automotive Products
501 South Wolf Road
Des Plaines, IL 60016

SHIPPED TO

same

INVOICE DATE	DATE SHIPPED	OUR ORDER NO.	YOUR ORDER NO.	TERMS	F.O.B.	SALESPERSON	SHIPPED VIA
10/04/96	10/04/96	671	9225	2% 10, N30	Bethel, VT		Yellow
QUANTITY	DESCRIPTION					PRICE	AMOUNT
100,440	units, V-500 Lock Deicer 360 cases @ 279					\$0.08	\$8,035.20
This is a partial shipment against the above order.							
12/4/96 TC 							

84144, RAPID-ORDER, INC. TO REORDER CALL 800 757 8354

THANK YOU

FR190

Agent or Cashier

THIS CERTIFICATION is to certify that the above-named materials are property not described, packaged, marked and labeled, and are in proper condition for transportation according to the applicable regulations of the Department of Transportation.

SIGNATURE

TITLE


Per

T.C.D. TO: (ADDRESS)

C.O.D. AMOUNT

C.O.D. CHARGE TO BE PAID BY SHIPPER CONSIGNEE

(The signature here acknowledges only the amount prepaid.)



and labeled, and are in proper condition for transportation according to the applicable regulations of the Department of Transportation. All of labeling shall state whether it is "consignee's or shipper's weight".

By signing this agreed or declared value of the property, the Shipper, and all other requirements of Rule 41 of the Uniform Freight Classification and Rule 1 of the National Motor Freight Classification.

Declared value of the property specifically stated or to be not exceeding

per

Charges Advanced

\$

ULTRAMOTIVE CORPORATION
Shipping Blvd. • Bethel, VT 05032

Shipper

Agent

VFS 10/4/96 (4)
SPOTter 45012

Per

1

Exhibit 6
Victor Automotive

003

U.S. CONSUMER PRODUCT SAFETY COMMISSION		1. AREA O 12/14/96 Inspection CPSC - Milwaukee - 111 West Post Victor North Wisconsin Ave. Inc. Waukesha WI 53188	
2. NAME OF INDIVIDUAL Tom Cronk	3. TITLE OF INDIVIDUAL vice manager	4. DATE 12/14/96	
5. FIRM NAME Victor Automotive Products, Inc		6. SAMPLE NUMBER	
7. NUMBER AND STREET 5015 Grand	8. CITY AND STATE (Include Zip Code) Dunellen, IL 60016		
9. SAMPLES COLLECTED (Describe fully. List lot, serial, model numbers and other positive identification)			
<p>The following samples were collected by the Consumer Product Safety Commission pursuant to Section 27(f) of the Consumer Product Safety Act (15 U.S.C. 2070(f) and/or Section 11(b) of the Federal Hazardous Substances Act (15 U.S.C. 1270(b) and/or Sections 5(c) and (d) of the Flammable Fabrics Act (15 U.S.C. 1194(c) and (d) and/or Section 704(c) of the Federal Food Drug and Cosmetic Act (21 U.S.C. 374(c)) [Authority for sample collections made in connection with the Poison Prevention Packaging Act of 1970 (15 U.S.C. 1471 et seq.)], and receipt for said samples is hereby acknowledged. Sections cited are quoted on the reverse side of this form.</p> <p><u>97-830-3202</u> → 12 - Victor Grand # V-500 Electric Tire Emergency Repair, 4oz. "oil"</p> <p>→ 12 - Victor Grand # V-500 Pressurized Lock De-Icer and Lubricant, <u>97-830-3080</u> 6.15 fl oz. container</p> <p>→ 4 - Victor Grand # V-301 Vinyl Adhesive 1.5 fl oz. 5.2c <u>97-830-3203</u></p> <p>→ 4 - Victor Grand # V-104 Floor Cement; 3.15 fl oz. Tube 5.2c <u>97-830-3204</u></p> <p>→ 12 - Victor Grand # V-502 Pressurized Lock De-Icer and Lubricant, <u>97-830-3201</u> 1.25 fl oz container</p>			
10. SAMPLES		11. SAMPLES WERE	
a. AMOUNT RECEIVED FOR SAMPLE		<input checked="" type="checkbox"/> PURCHASED	
b. SIGNATURE (Person from whom sample received) Tom Cronk		<input type="checkbox"/> BORROWED (To be returned)	
		12. COLLECTOR	
		a. NAME (Print or type) Dennis C. Elias	
		b. SIGNATURE Dennis C. Elias	

VICTOR AUTOMOTIVE
12/04/96 INSPECTION

093

CPSC Surveillance Report

1. Reporting Office FOCR		2. Home Office FOCR		3. Date 8/14/96		4. Product Code 1133			
5a. Product Name LOCK DE-ICER				5b. Model VICTOR #V-500 AMOUNT UNK					
5c. Product Description & Identification LOCK DE-ICER, UNDER PRESSURE, SMALL METAL TUBE IN BLISTER PACKAGE.									
Attachment: () Label () Photo () Literature () Other _____									
5d. Manufacturer/Importer - Name and Address VICTOR AUTOMOTIVE PRODUCT INC. DES PLAINES, IL. 60016									
6a. Suspected Problem/Violation <input checked="" type="checkbox"/> FHSA - Labeling, Banned <input type="checkbox"/> PPPA - No CRP, Ineffective CRP, Labeling <input type="checkbox"/> FFA - Labeling, Fails Std., Cert. <input type="checkbox"/> CPSA - Possible Sec. 15, Fails Std., Cert. <input type="checkbox"/> RSA - Noncompliance <input type="checkbox"/> Other - Refer to other Federal or State Agency				6b. Describe NO WARNING ON FRONT DISPLAY PANEL. TUBE WAS TURNED IN PACKAGE, NO WARNING COULD BE READ. CONTENTS UNDER PRESSURE, FLAMMABLE?					
7. Establishment Where Encountered - Name and Address WESTLAKE ACE HARDWARE 15225 87TH ST. LENEXA, KS. 66219									
8. Reported by (Type Name & Title) ROBERT B. WADSWORTH JR. INVESTIGATOR			9. Employee No. 8158		10. Signature 8/16/96 <i>Robert B. Wadsworth</i>				
11. Reporting Office Action <input checked="" type="checkbox"/> Referred to Home Office <input type="checkbox"/> Referred to HO () <input type="checkbox"/> Official Sample Collected (Sample # _____) <input type="checkbox"/> EI at Dealer <input type="checkbox"/> Other <input type="checkbox"/> None; if none, why:			12. Reviewing Official			13. Title SPSE		14. Signature <i>W J...</i>	
			15. Date 9/6/96			16. Distribution: 0: FOCR Compli			

39

PRODUCT IDENTIFICATION

in blister packaging. UPC #7723100058.

FIELD SUMMARY

flashpoint.

METHOD OF COLLECTION

in the locked CPSC office from time of collection until later shipment to the Sample Custodian on 12/10/96. Samples were labeled as ID'd in #21, and shipped in a box sealed as ID'd in #22.

12/20

003

EXHIBIT B
Victor Automotive

U.S. CONSUMER PRODUCT SAFETY COMMISSION		1. AREA OF INTEREST: <i>12/14/96 Inspection</i> <i>CPSC - MEMPHIS - 1100 SOUTH POST</i> <i>11376 NORTH WINDSORBOYE LN.</i> <i>MEMPHIS, TN 38118</i>			
2. NAME OF INDIVIDUAL <i>Terry Crank</i>	3. TITLE OF INDIVIDUAL <i>vice manager</i>	4. DATE <i>12/14/96</i>			
5. FIRM NAME <i>Victor Automotive Products, Inc.</i>			6. SAMPLE NUMBER		
7. NUMBER AND STREET <i>501 S. Union St</i>	8. CITY AND STATE (Include Zip Code) <i>Donna, TN 37016</i>				
9. SAMPLES COLLECTED (Describe fully. List lot, serial, model numbers and other positive identification) <p>The following samples were collected by the Consumer Product Safety Commission pursuant to Section 27(f) of the Consumer Product Safety Act (15 U.S.C. 2078(f) and/or Section 11(b) of the Federal Hazardous Substances Act (15 U.S.C. 1270(b) and/or Sections 5(c) and (d) of the Flammable Fabrics Act (15 U.S.C. 1194(c) and (d) and/or Section 704(c) of the Federal Food Drug and Cosmetic Act (21 U.S.C. 374(c)) [Authority for sample collections made in connection with the Poison Prevention Packaging Act of 1970 (15 U.S.C. 1471 et seq.)], and receipt for said samples is hereby acknowledged. Sections cited are quoted on the reverse side of this form.</p> <p><u>97-830-3202</u> ↳ 12 - Victor Brand # VB-50 Electric Fire Resistance Paper, 4oz. Act.</p> <p>↳ 12 - Victor Brand # V-500 Precision Lock De-Icer and Lubricant. <u>97-830-3080</u> 615 fl oz. container</p> <p>↳ 4 - Victor Brand # V-301 Vinyl Adhesive 1.5 fl oz. size.</p> <p><u>97-830-3203</u></p> <p>↳ 4 - Victor Brand # V-104 Floor Cement; 3 1/2 fl. oz. tube size</p> <p><u>97-830-3204</u></p> <p>↳ 12 - Victor Brand # V-502 Precision Lock De-Icer and Lubricant, <u>97-830-3201</u> 125 fl oz container</p>					
10. SAMPLES a. AMOUNT RECEIVED FOR SAMPLE <hr/> b. SIGNATURE (Person from whom sample received) <i>[Signature]</i>		11. SAMPLES WERE <input checked="" type="checkbox"/> PURCHASED <input type="checkbox"/> BORROWED (To be returned)		12. COLLECTOR a. NAME (Print or type) <i>[Name]</i> b. SIGNATURE <i>[Signature]</i>	

SNAP PRODUCTS, INC.
501 SOUTH BASINGER ROAD, PANDORA, OH 45877 • (419) 384-3241

VB-58
2/1

MATERIAL SAFETY DATA SHEET

Exhibit "G"
Victor Automotive
12/04/96 Inspection

003

PRODUCT NAME : SNAP FIX-A-FLAT
PRODUCT NUMBER : S 277, S 455, S 457
FIRE - 0 HEALTH - 2 REACTIVITY - 0

EMERGENCY PHONE NUMBER : (919) 286-4446

1. HAZARDOUS INGREDIENTS

MATERIAL	CAS REG. NO.	TLV / UNITS	SOURCE	%
PERCENE	127-18-4	25 PPM	NIOSH / OSHA	N/A
CHLORODIFLUOROMETHANE	75-45-6	1000 PPM	ACGIH	N/A

2. PHYSICAL PROPERTIES

APPEARANCE AND ODOR :	NO DISTINGUISHING PATTERN AND TYPICAL ODOR		
SPECIFIC GRAVITY (H ₂ O = 1):	1.555	SOLUBILITY IN H ₂ O :	TRACE
BOILING POINT F (C):	N/A	VAPOR PRESSURE :	APP. 165 PSIG (MAX. @ 130 F)
FREEZING POINT F (C):	N/A	% VOLATILES BY VOLUME :	N/A
EVAPORATION RATE : (BUTYL ACETATE = 1)	>1.0	VISCOSITY Cps @ 100 F :	N/A
PHAS IS :	NONE	VAPOR DENSITY (AIR = 1):	HEAVIER

3. FIRE AND EXPLOSIVE HAZARDS

FLASH POINT : NONE METHOD USED : N/A	FLAMMABLE LIMITS :	LEL / UEL - N/A
EXTINGUISHING MEDIA :	CARBON DIOXIDE, FOAM, WATER FOG.	
SPECIAL FIREFIGHTING PROCEDURES :	KEEP CONTAINER COOL. USE EQUIPMENT OR SHIELDING TO PROTECT PERSONNEL AGAINST BURSTING, RUPTURING OR VENTING CONTAINERS. USE SELF CONTAINED BREATHING APPARATUS.	
UNUSUAL FIRE AND EXPLOSION HAZARDS :	AEROSOL CANS MAY RUPTURE OR BURST ABOVE 130 F.	
FIRE NFPA CODE :	0	
OTHER SPECIAL HAZARDS :	NONE	
DOT FLAME EXTENSION :	NON-FLAMMABLE	

40

SNAP PRODUCTS, INC.
MATERIAL SAFETY DATA SHEET

PRODUCT NAME : SNAP FIX-A-FLAT

PRODUCT NUMBER : S 277, S453, S457

7. SPECIAL PROTECTION INFORMATION

GENERAL VENTILATION :	SUFFICIENT	LOCAL EXHAUST :	RECOMMENDED
RESPIRATION PROTECTION : TYPE	IF TLV IS EXCEEDED, USE NIOSH / OSHA APPROVED RESPIRATOR WITH CARTRIDGES FOR ORGANIC VAPORS.		
MECHANICAL :	N / A		
GLOVES :	NONE IN NORMAL USE. MAY USE NEOPRENE, VITON, OR POLYVINYL COATED GLOVES OR EQUIVALENT.		
EYE PROTECTION :	NONE IN NORMAL USE. MAY USE SAFETY GLASSES OR GOGGLES.		
OTHER :	DO NOT INTENTIONALLY INHALE FUMES. READ AND FOLLOW THE DIRECTIONS ON THE PRODUCT LABEL. THEY ARE BEST GUIDE FOR USAGE IN MOST EFFECTIVE WAY. TAKE NECESSARY SAFETY PRECAUTIONS.		

8. SPILL OR LEAK PROCEDURES

CONTAINMENT PROCEDURES : VENTILATE. AVOID BREATHING VAPORS. CONTAIN SPILL.

PROTECTIVE CLOTHING : CHEMICAL RESISTANT BOOTS AND AN APRON IF SPLASHING IS A PROBLEM.

WASTE DISPOSAL PROCEDURES : DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

9. STORAGE AND HANDLING REQUIREMENTS

HANDLING PROCEDURES : AVOID CONTACT WITH SKIN AND AVOID BREATHING VAPORS. PIPE VENTS OUTDOORS. STORE IN A COOL DRY, VENTILATED AREA. VAPORS ARE HEAVIER THAN AIR AND WILL COLLECT IN LOW AREAS.

SNAP PRODUCTS, INC.
MATERIAL SAFETY DATA SHEET

PRODUCT NAME : SNAP FDI-A-FLAT PRODUCT NUMBER : 5 277, 5451, 8 457

10. DOT SHIPPING INFORMATION - NOT TO BE USED AS TRANSPORTATION DOCUMENT

PROPER SHIPPING NAME : ORM-D

DOMESTIC HAZARD CLASS : 70

DOT LABEL : NON-FLAMMABLE GAS, AEROSOLS.

DOT CLASS OR DIVISION : 2.2

UN / NA NUMBER : UN 1950

ERG GUIDE NUMBER : 12

INTERNATIONAL HAZARD CLASS : 2.2. CLASS 9, IF CERTIFIED FOR INTERNATIONAL SHIPPING AND IMDG CODE IN ACCORDANCE WITH 49 CFR 171.12.

IMDG PACKAGING GROUP : II

VESSEL STORAGE CATEGORY : A

IMDG CODE PAGE : SEE 9022

IMO LABEL : NON-FLAMMABLE GAS, IF CERTIFIED FOR INTERNATIONAL SHIPPING AND IMDG CODES IN ACCORDANCE WITH 49 CFR 171.12. NO LABELS REQUIRED. PACKAGES SHOULD BE MARKED "AEROSOLS".

SHIPPING LIMIT : 125 KG PER WOOD BOX / 55KG PER FIBERBOARD BOX (GROSS WEIGHT).

ADDITIONAL INFORMATION : IMO PSN : AEROSOL DISPENSERS UN 1950.

11. REGULATORY INFORMATION

SPECIFY THE FOLLOWING :

OSHA - WHICH CHEMICAL(S) APPEAR ON HAZARDOUS SUBSTANCE LIST : PERCLEN.

RCRA HAZARDOUS WASTE CODE U210.

RCRA REPORTABLE QUANTITIES AS A HAZARDOUS WASTE : NOT APPLICABLE

SARA REPORTING REQUIREMENTS : THIS PRODUCT CONTAINS PERCLEN, CAS 127-18-4, A CHEMICAL SUBJECT TO SARA TITLE III REPORTING.

TSCA (PCBS, ASBESTOS, NEW CHEMICALS) STATUS : NONE

NOTE : THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING ACCURACY OF THE DATA OR RESULTS TO BE OBTAINED FROM THE USE THEREOF. IT IS USER'S OBLIGATION TO DETERMINE CONDITIONS OF SAFE USE OF THE PRODUCT AND WE ASSUME NO RESPONSIBILITY FOR ITS USE.

MANUFACTURER'S CONTACT / REVISED BY : DINESH J. PAREKH

REVISION DATE : 10 - 12 - 93

END MSDS.

116-00141-09125

PAGE 3 OF 4

5 277, 5451, 8 457

RECOMMENDED

STOR WITH

UV COATED

TONER ON
B-WAY


142

Victor Automotive
12/04/96 inspection

(023)

Technical Chemical Company
Telephone 214-556-1421, FAX 214-506-7493
800-527-0885
Vernon, CA.

REMIT TO
XXXXXXXXXXXXXXXXXX
P.O. BOX 910142
XXXXXXXXXXXXXXXXXX



A MEMBER

PLEASE REMIT TO:
P. O. 910142
DALLAS, TX 75391-0142

67076 67001

67076

VICTOR AUTOMOTIVE PRODUCTS
501 SOUTH WOLF ROAD

VICTOR AUTOMOTIVE PRODUCTS
501 SOUTH WOLF ROAD

DES PLAINES IL 60016

DES PLAINES IL 60016

PART NO.	PART NUMBER DESCRIPTION	QTY. SHIPPED	UNIT PRICE	EXTENSION
56	VICTOR 4 OZ. TIRE SEAL W/CONE *	1319	12.96	17,094.24

12.96 / 24 = .54

12/4/96 TC

Q

*Indicates Partial Shipment

SEE TERMS & CONDITIONS ON REVERSE SIDE PLEASE ATTACH COPY OF INVOICE WITH PAYMENT

Inc. Total 17094.24	Shipping Charges .00	Tax .00	Terms NET 60 DAYS	17,094.24	
Date	Customer Order No.	Shipped Via RECT UAY	Invoice No. 167421	Packing List No. 69142	FOR DESTINATION

victor automotive
12/04/96 inspection

(43)

CPSC Surveillance Report

1. Reporting Office FOCR	2. Home Office FOCR	3. Date 8/14/96	4. Product Code 1133
5a. Product Name LOCK DE-ICER		5b. Model VICTOR #V-500 AMOUNT UNK	

5c. Product Description & Identification LOCK DE-ICER, UNDER PRESSURE, SMALL METAL TUBE IN BLISTER PACKAGE.

Attachment: () Label () Photo () Literature () Other _____

5d. Manufacturer/Importer - Name and Address
VICTOR AUTOMOTIVE PRODUCT INC.
 DES PLAINES, IL. 60016

6a. <u>Suspected Problem/Violation</u> <input checked="" type="checkbox"/> FHSA - Labeling, Banned <input type="checkbox"/> PPPA - No CRP, Ineffective CRP, Labeling <input type="checkbox"/> FFA - Labeling, Fails Std., Cert. <input type="checkbox"/> CPSA - Possible Sec. 15, Fails Std., Cert. <input type="checkbox"/> RSA - Noncompliance <input type="checkbox"/> Other - Refer to other Federal or State Agency	6b. <u>Describe</u> NO WARNING ON FRONT DISPLAY PANEL. TUBE WAS TURNED IN PACKAGE, NO WARNING COULD BE READ, CONTENTS UNDER PRESSURE, FLAMMABLE?
--	--

7. Establishment Where Encountered - Name and Address
WESTLAKE ACE HARDWARE
 15225 87TH ST.
 LENEXA, KS. 66219

8. Reported by (Type Name & Title) ROBERT B. WADSWORTH JR. INVESTIGATOR	9. Employee No. 8158	10. Signature 8/16/96 <i>Robert B Wadsworth Jr</i>
--	----------------------	--

11. Reporting Office Action <input checked="" type="checkbox"/> Referred to Home Office <input type="checkbox"/> Referred to HO () <input type="checkbox"/> Official Sample Collected (Sample # _____) <input type="checkbox"/> EI at Dealer <input type="checkbox"/> Other <input type="checkbox"/> None; if none, why:	12. Reviewing Official	
	13. Title <i>SPSE</i>	14. Signature <i>W J...</i>
	15. Date <i>9/6/96</i>	16. Distribution: <i>0: FOCR copy</i>

(45)

FIELD SUMMARY

flashpoint.

METHOD OF COLLECTION

in the locked CPSC office from time of collection until later shipment to the Sample Custodian on 12/10/96. Samples were labeled as ID'd in #21, and shipped in a box sealed as ID'd in #22.

V301 - VINYL ADHESIVE



GREAT NORTHERN RESEARCH, INC. • (612) 379-9248
2901 S.E. 4th St • Minneapolis, Minnesota 55414

EXHIBIT J
Victor Automotive
12/04/96 Inspection

000

MATERIAL SAFETY DATA

I. Product Information

Date May 9, 1991

EMERGENCY ASSISTANCE

612-379-9248 OR
612-755-3861

Tradename VA-1 Vinyl Adhesive

Chemical Name and Synonyms
N/A

Chemical Family
N/A

CAS Registry No. See below

HMIS Hazard Rating

Least	0	(0) Health	2
Slight	1	(1) Flammable	3
Moderate	2	(2) Reactivity	0
High	3		
Extreme	4		

II Hazardous Ingredients

Principal Hazardous Components (Chemical And Common Names)

	CAS REG. NO.	%/WT APPROX.	TLV OSHA
Synthetic Resins	N/A	19 - 20%	N/A
Acetone	67 - 64 - 1	48 - 50%	1000 ppm
Methyl Ethyl Ketone	78 - 93 - 3	28 - 30%	200 ppm
Cyclohexanone	108 - 94 - 1	3 - 4%	200 ppm

III Physical Data

Softening Point, R & B (°F/C) N/A	Percent Volatile (by Volume) 80%
Specific Gravity (H ₂ O = 1) 0.89	Evaporation Rate (N-Butyl Ac-1) 7.7
Boiling Point (°F/C) 135° F. - 175° F.	Vapor Pressure (mm Hg.) 82 - 186 mm Hg @ 25° F.
Solubility in Water Miscible	Vapor Density (Air = 1) 2.4
Appearance and Odor Clear viscous liquid Ether like odor	

IV Fire and Explosion Hazard Data

Flash Point, -4° TOC F.	Flammable Limits Lel 2.8 Uel 13.2
Extinguishing Media dry chem., CO ₂ , Foam	Autoignition Temperature 400° F. +
Special Fire Fighting Procedures Do not enter confined fire space without proper protective equipment including a NIOSH approved SCBA. Use water spray to cool fire exposed surfaces and to protect personnel.	
Unusual Fire and Explosion Hazards	

RESPIRATORY PROTECTION REQUIRED FOR FIRE FIGHTING PERSONNEL

NA = Not Applicable
NDA = No Data Available

(Continued on Reverse Side)

Handwritten signature

V. Health Hazard

Threshold Limit Value 200 ppm Methyl Ethyl Ketone, Cyclohexanone, 1000 ppm Acetone

Signs and Symptoms of Exposure:

1. Acute Overexposure Irritation of eyes, nose, throat. Liquid may damage eye tissue.
2. Chronic Overexposure headache, dizziness, skin dermatitis, anesthetic nature, vomiting.

Adverse Conditions Generally Apperceived by Exposure N/A

Primary Routes of Entry:

1. Oral LD₅₀ 7 gm/kg (rat)
2. Dermal LD₅₀ 4 gms/kg (rabbit)
3. Inhalation LD₅₀ N/A
4. Eye Irritation irritant
5. Skin Irritation irritant

Chemical Listed as Carcinogen or Potential Carcinogen

National Toxicology Program Yes No I.A.R.C. Monographs Yes No OSHA Yes No

OSHA Permissible Exposure Limit 200 PPM TWA

ACGIH Threshold Limit Value 200 ppm

Other Exposure Limit Used N/A

Emergency and First Aid Procedures:

1. Inhalation Remove victim to fresh air and provide oxygen if breathing is difficult.
2. Eyes Flush eyes with copious quantities of water while holding eye lids open. If irritation persists, consult a physician.
3. Skin Wash skin with soap and water. Use emollient skin creams. If irritation persists, consult a physician.
4. Ingestion Do not induce vomiting. Get medical attention.

Stability — Unstable Stable
Conditions to Avoid

Hazardous Polymerization — May Occur Will Not Occur

Incompatibility (Materials to Avoid)

Strong acids, bases or oxidizers

Hazardous Decomposition Products

Steps to be Taken in Case Material is Released or Spilled

Stay upwind and away from spill. Keep away from fire and flame. Universal type foam will suppress vapors. Use Sand on small spills. Flush with water, use absorbent pads. Ventilate if indoors.

Waste Disposal

Dispose of in accordance with Local, County, State and Federal regulations

Respiratory Protection Use NIOSH Approved gas mask or respirator if above exposure limits. Use approved ventilation to maintain below established exposure limits. Use approved equipment if it is expected skin contact is probable. Chemical gloves

Other Protective Equipment it is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn if needed.

Use and store with adequate ventilation. Do not pressurize, cut, weld, or in any other manner expose container to heat, sparks, flame, etc.
Other Precautions All handling equipment should be electrically grounded.

Walter Gorbunow
Great Northern Research, Inc.

TOTAL P.03

149

VICTOR

VICTOR AUTOMOTIVE PRODUCTS, INC.

501 S. Wolf Rd. Des Plaines, Illinois 60018 (708) 296-5570

EXHIBIT A
Victor Automotive
12/4/96 Inspection
Show this purchase Order Number
on all correspondence, invoices,
shipping papers and packages.

Q23

010142

TO ENVIRO PAC INTERNATIONAL
6 CAROL DRIVE
LINCOLN, R.I. 02865

DATE OF ORDER 5-22-96	REQ. NO.
SHIP TO ABOVE	

WHEN SHIP		SHIP VIA	F.O.B. POINT	TERMS	
ASAP RUSH PLEASE				2730DAYS	
QTY. ORDERED	QTY. RECEIVED	STOCK NUMBER/DESCRIPTION		UNIT PRICE	TOTAL
1 20M		#V301 VINYL ADHESIVE		\$.2380 EA.	
2					
3					
4					
5					
6					
7					
8					
CONFIRMATION					

1. Please send _____ copies of your invoice.
2. Order is to be entered in accordance with prices, delivery and specifications shown above.
3. Notify us immediately if you are unable to ship as specified.

[Signature]
Authorized by

order form #F453 Grayarc, P.O. Box 2944, Hartford, CT 06104 2944
©EG 1982, Printed in U.S.A.

DUPLICATE

12/4/96 TC

150

EXHIBIT 6
Victor Automotive

022

U.S. CONSUMER PRODUCT SAFETY COMMISSION		1. AREA OF INTEREST 12/14/96 Inspection CPSC - MEMPHIS 11276 NATL HIGHWAY CN. MEMPHIS TN 38188	
		2. NAME OF INDIVIDUAL Toni Crane	3. TITLE OF INDIVIDUAL Office Manager
5. FIRM NAME Victor Automotive Products, Inc.		4. DATE 12/14/96	
7. NUMBER AND STREET 515 1st St		8. CITY AND STATE (Include Zip Code) Memphis, TN 38116	

9. SAMPLES COLLECTED (Describe fully. List lot, serial, model numbers and other positive identification)

The following samples were collected by the Consumer Product Safety Commission pursuant to Section 27(f) of the Consumer Product Safety Act (15 U.S.C. 2076(f) and/or Section 11(b) of the Federal Hazardous Substances Act (15 U.S.C. 1270(b) and/or Sections 5(c) and (d) of the Flammable Fabrics Act (15 U.S.C. 1194(c) and (d) and/or Section 704(c) of the Federal Food Drug and Cosmetic Act (21 U.S.C. 374(c)) [Authority for sample collections made in connection with the Poison Prevention Packaging Act of 1970 (15 U.S.C. 1471 et seq.)], and receipt for said samples is hereby acknowledged. Sections cited are quoted on the reverse side of this form.

97-830-3202

→ 12 - Victor brand # VB-58 Electric fire emergency spark, 4oz.

→ 12 - Victor brand # V-500 pressurized lock de-icer and lubricant.

97-830-3080

615 fl oz. container

→ 4 - Victor brand # V-301 vinyl adhesive 1.5 fl oz. size.

97-830-3203

→ 1 - Victor brand # V-104 adhesive; 1.5 fl oz. size.

97-830-3204

→ 12 - Victor brand # V-502 pressurized lock de-icer and lubricant,

97-830-3201

125 fl oz container

10. SAMPLES	11. SAMPLES WERE	12. COLLECTOR
a. AMOUNT RECEIVED FOR SAMPLE	<input checked="" type="checkbox"/> PURCHASED	a. NAME (Print or type) Dennis C. Blain
b. SIGNATURE (Person from whom sample received) Toni Crane	<input type="checkbox"/> BORROWED (To be returned)	b. SIGNATURE D.C. Blain

victor automotive
12/04/96 inspection 003

CPSC Surveillance Report

1. Reporting Office FOCR	2. Home Office FOCR	3. Date 8/14/96	4. Product Code 1133
5a. Product Name LOCK DE-ICER		5b. Model VICTOR #V-500 AMOUNT UNK	
5c. Product Description & Identification LOCK DE-ICER, UNDER PRESSURE, SMALL METAL TUBE IN BLISTER PACKAGE.			
Attachment: () Label () Photo () Literature () Other _____			
5d. Manufacturer/Importer - Name and Address VICTOR AUTOMOTIVE PRODUCT INC. DES PLAINES, IL. 60016			
6a. Suspected Problem/Violation <input checked="" type="checkbox"/> FHSA - Labeling, Banned <input type="checkbox"/> PPPA - No CRP, Ineffective CRP, Labeling <input type="checkbox"/> FFA - Labeling, Fails Std., Cert. <input type="checkbox"/> CPSA - Possible Sec. 15, Fails Std., Cert. <input type="checkbox"/> RSA - Noncompliance <input type="checkbox"/> Other - Refer to other Federal or State Agency		6b Describe NO WARNING ON FRONT DISPLAY PANEL. TUBE WAS TURNED IN PACKAGE, NO WARNING COULD BE READ, CONTENTS UNDER PRESSURE, FLAMMABLE?	
7. Establishment Where Encountered - Name and Address WESTLAKE ACE HARDWARE 15225 87TH ST. LENEXA, KS. 66219			
8. Reported by (Type Name & Title) ROBERT B. WADSWORTH JR. INVESTIGATOR		9. Employee No. 8158	10. Signature 8/16/96 <i>Robert B. Wadsworth</i>
11. Reporting Office Action <input checked="" type="checkbox"/> Referred to Home Office <input type="checkbox"/> Referred to HO () <input type="checkbox"/> Official Sample Collected (Sample # _____) <input type="checkbox"/> EI at Dealer <input type="checkbox"/> Other <input type="checkbox"/> None; if none, why:		12. Reviewing Official	
		13. Title SPSE	14. Signature <i>W J Gandy</i>
		15. Date 9/6/96	16. Distribution: 0: FOCR Compli

**U.S. Consumer Product Safety Commission
SAMPLE COLLECTION REPORT**

1. Sample Flag		2. Date Collected 12/4/96	3. Sample Type and Number: 97-830-3204 <input checked="" type="radio"/> Physical <input type="radio"/> Documentary	
4a. Product Name RUBBER CEMENT		4b Model VICTOR	4c NEISS 0909	5. Assignment Number
6. Complete for Import Samples		7. MIS 32006 33567		8. Hours Activity Travel <u>1</u>
Port of Entry: _____ Country of Origin: _____ Entry No. and Date: _____ Customs Contact: _____		9a Home RO FOCR	9b Collecting RO FOCR	
10. Sample Cost		11. Invoice Value of Lot		12. Size of Lot Units 4 unt
13. Manufacturer/Importer # VIC019 VICTOR AUTOMOTIVE PRODUCT 501 S. WOLF RD. DES MOINES, IL 60016 <i>None</i>		14. Shipper/Foreign Manufacturer SEE #13		15. Dealer/Import Broker # SEE #13
16. Supporting documents attached: Invoice No. and Date: <u>#610059-00</u> <u>10/8/96</u> Date Shipped: _____ Shipping Record and Date: _____ Affidavit Signer's name, title and date: <u>SIGNED BY TONI COCCONE, OFC. MGR, 12/04/96.</u>				
17. Product Identification: Product is described as a 3/8 fluid ounce tube of rubber cement, Victor brand. Tube is green, white and yellow with black lettering. Tube has warning on front stating "Danger: Extremely harmful or fatal"				
18. Reason for collection/analysis needed: <input checked="" type="radio"/> FHSA <input type="radio"/> CPSA <input type="radio"/> FFA <input type="radio"/> PPPA <input type="radio"/> RSA F/U to FOCR KAN-RP surveillance- suspect labeling violations.				
19. Summary of Field Screening: Product container and accompanying packaging both have several labeling violations, see narrative report for details. LSHL- please conduct analysis to confirm percentage of hazardous ingredients and				
20. Sample size/Method of Collection: Sample was collected during inspection conducted on 12/04/96. Sample was collected at random from stock on hand in firm's warehouse; current inventory number unavailable. Sample remained in my custody or				
21. Identification on sample: " 97-830-3204 DRB 12/4/96 "		22. Identification on seal and date: " 97-830-3204 Dennis Blasius 12/4/96 "		
23a. Sample delivered to: SAMPLE CUST VIA RPS		23b Date 12/10/96	24. Report/Record Sent to: FOCR	
25. Laboratory/Office: LSHL <u>X</u> LSEL _____ CRM _____ CCA _____ Other _____				
26. Remarks: Copy of narrative report, MSDS, invoicing, affidavit and original inspection request included with sample.				
27. Related Samples: 97-830-3080; 3201, 3202 and 3203.				
28a Collector's name/title: Dennis Blasius Resident Investigator		28b Collector's signature/date: <i>Dennis R. Blasius</i> 12/9/96		
29a Reviewer's name/title: <i>John R. Ucko SP5</i>		29b Reviewer's signature/date: <i>John R. Ucko</i> 12/12/96		

154

PRODUCT IDENTIFICATION

if swallowd, vapors harmful. See back panel." Back of tube has use instructions and Victor Automotive Products name, address.

FIELD SUMMARY

flashpoint.

METHOD OF COLLECTION

in the locked CPSC office from time of collection until later shipment to the Sample Custodian on 12/10/96. Samples were labeled as ID'd in #21, and shipped in a box sealed as ID'd in #22.

55

HENKEL Adhesive m
Victor Automotive
12/04/96 Inspection

022

HENKEL ADHESIVES CORP/EL
740 TOLLGATE ROAD
ELGIN IL 60123
708-931-9980

~~6000~~ RUBBER CEMENT

VICTOR AUTOMOTIVE
501 S. WOLF RD.
DES PLAINES IL 60016

INVOICE#:
DATE: 07/19/96
PAGE: 1

24-HOUR EMERGENCY PHONE NO: CHEMTREC, 800/424-9300

MATERIAL SAFETY DATA SHEET

CHEMICAL NAME:
NONE

TRADE NAME: HENKEL# RC-7818

CHEMICAL FAMILY:
POLYMER SOLUTION (FLAMMABLE)

FORMULA:
MIXTURE

HAZARD CLASS:

U.N. NUMBER:
1133

PACKING GROUP:

***** HAZARDOUS COMPONENTS *****

NAME: HEPTANE

CAS NUMBER:

‡ BY WEIGHT:

92.00

142-82-5

ACGIH TLV: 400 PPM

OSHA PEL: 500 PPM

OSHA STEL: 500 PPM

NAME: ETHYL ALCOHOL

CAS NUMBER:

‡ BY WEIGHT:

1.00

74-17-5

ACGIH TLV: 1000 PPM

OSHA PEL: 1000 PPM

OSHA STEL:

***** PHYSICAL PROPERTIES DATA *****

BOILING POINT: 200 F

SPECIFIC GRAVITY: 0.7

VAPOR PRESSURE (mm HG AT 20 DEG C): 76

154

INVOICE#:
DATE: 07/19/96
PAGE: 3

MATERIAL SAFETY DATA SHEET

(HENKEL #: RC-7818)

CONDITIONS TO AVOID: OPEN FLAME AND EXCESSIVE HEAT
INCOMPATIBILITY: STRONG OXIDIZING AGENTS
HAZARDOUS DECOMPOSITION PRODUCTS:
CARBON MONOXIDE, CARBON DIOXIDE, HYDROCARBONS
AND OTHER ACRID PRODUCTS OF COMBUSTION.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
CONDITIONS TO AVOID:

***** SPILL AND DISPOSAL PROCEDURES *****

SPILL PROCEDURES: EXTINGUISH ALL SOURCES OF IGNITION. COLLECT ON
SAFETY ABSORBENTS AND DISPOSE OF PROPERTY.
DISPOSAL PROCEDURES:
TREAT AS A FLAMMABLE WASTE IN COMPLIANCE WITH
THE EPA REGULATIONS. DISPOSE OF IN ACCORDANCE
WITH LOCAL, STATE AND FEDERAL REGULATIONS.

***** PROTECTIVE EQUIPMENT *****

VENTILATION: RECOMMENDED
RESPIRATORY PROTECTION: CHEMICAL FILTER MASK CARTRIDGE TYPE
IS REQUIRED IF TLV IS EXCEEDED.
PROTECTIVE CLOTHING:
CHEMICALLY RESISTANT GLOVES SUCH AS NEOPRENE RUBBER.
EYE PROTECTION: OSHA APPROVED FULL FACE MASK.

***** SPECIAL PRECAUTIONS *****

HANDLING & STORAGE PRECAUTIONS:
TREAT AS A FLAMMABLE LIQUID. STORE IN ACCORDANCE WITH FEDERAL,
STATE, LOCAL AND INSURANCE REGULATIONS AS PRESCRIBED
CLASS I/GROUP D FLAMMABLE LIQUIDS. KEEP AWAY FROM SOURCES OF
HEAT SUCH AS DIRECT SUN, BOILERS ETC.
AVOID SPARKS AND OPEN FLAMES.
SPECIAL COMMENTS:
NON-HAZARDOUS INGREDIENTS WITHHELD UNDER PA TRADE SECRET STATUS.

EPA SARA TITLE III HAZARD CLASS:
FLAMMABLE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO THE REPORTING
REQUIREMENTS OF EPA SARA TITLE III SECTION 313 (40CFR372):

Table with 3 columns: CHEMICAL, CAS NUMBER, WEIGHT PERCENT. Row 1: NONE

Handwritten number 157

INVOICE#:
DATE: 07/19/96
PAGE: 2

MATERIAL SAFETY DATA SHEET

(HENKEL #: RC-7818)

PERCENT VOLATILE: 89%
VAPOR DENSITY: 3.5
EVAPORATION RATE: 5.6
SOLUBILITY IN WATER: NIL
PH: N/A
APPEARANCE AND ODOR: LIGHT YELLOW LIQUID WITH SOLVENT ODOR.

***** FIRE AND EXPLOSION HAZARD DATA *****

FLASH POINT & METHOD: 25 F
FLAMMABLE LIMITS: N/A
LEL: 1.2
UEL: 7.5
EXTINGUISHING MEDIA: CARBON DIOXIDE, DRY CHEMICAL, FOAM.
SPECIAL FIRE FIGHTING PROCEDURES:
WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACE MASK.
UNUSUAL FIRE & EXPLOSION HAZARDS:
VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND.
THIS COULD CAUSE IGNITION BY PILOT LIGHT, SPARKS, HEATERS,
SMOKING, ELECTRIC MOTOR, STATIC DISCHARGE OR OTHER IGNITION
SOURCES. NEVER WELD OR CUT EMPTY DRUMS.

***** HEALTH HAZARD INFORMATION *****

THRESHOLD LIMIT VALUE: NOT KNOWN
PRIMARY ROUTES OF EXPOSURE:
EYE CONTACT: TEARING, BLURRED VISION
SKIN CONTACT: DRIED SKIN, IRRITATION POSSIBLE
INHALATION: HEADACHE, NAUSEA, VOMITING, NARCOSIS
INGESTION: NAUSEA
CHRONIC EFFECTS OF EXPOSURE:
ANEMIA, LIVER ABNORMALITIES, KIDNEY DAMAGE, LUNG DAMAGE

***** FIRST AID *****

EYE FIRST AID:
FLUSH WITH WATER FOR 15 MINUTES. SEEK MEDICAL ATTENTION.
SKIN FIRST AID: WASH THOROUGHLY WITH SOAP AND WATER.
IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION.
INHALATION FIRST AID: REMOVE TO FRESH AIR. IF BREATHING IS
DIFFICULT, SEEK MEDICAL ATTENTION.
INGESTION FIRST AID:
IF CONSCIOUS, INDUCE VOMITING - SEEK MEDICAL ATTENTION.

***** REACTIVITY DATA *****

STABLE OR UNSTABLE: STABLE

Handwritten signature or initials '158'

U.S. CONSUMER PRODUCT SAFETY COMMISSION

1 AREA 0 *Victor Automotive*
 CPSC - MEMPHIS
 12/14/96 Inspection
 CPSC - MEMPHIS
 12/14/96 Inspection
 CPSC - MEMPHIS

009

2. NAME OF INDIVIDUAL *Toni Curione* 3. TITLE OF INDIVIDUAL *Office Manager* 4. DATE *12/14/96*

5. FIRM NAME *Victor Automotive Products, Inc.* 6. SAMPLE NUMBER

7. NUMBER AND STREET *5015 ...* 8. CITY AND STATE (Include Zip Code) *Dallas, TX 75216*

9. SAMPLES COLLECTED (Describe fully. List lot, serial, model numbers and other positive identification)

The following samples were collected by the Consumer Product Safety Commission pursuant to Section 27(f) of the Consumer Product Safety Act (15 U.S.C. 2076(f) and/or Section 11(b) of the Federal Hazardous Substances Act (15 U.S.C. 1270(b) and/or Sections 5(c) and (d) of the Flammable Fabrics Act (15 U.S.C. 1194(c) and (d) and/or Section 704(c) of the Federal Food Drug and Cosmetic Act (21 U.S.C. 374(c)) [Authority for sample collections made in connection with the Poison Prevention Packaging Act of 1970 (15 U.S.C. 1471 et seq.)], and receipt for said samples is hereby acknowledged. Sections cited are quoted on the reverse side of this form.

97-830-3202

→ 12 - Victor brand # VB-58 Bicycle Tire Repair Kit, 4oz.

→ 12 - Victor brand # V-500 Professional Lock De-Icer and Lubricant.

97-830-3080 6.25 fl oz. container

→ 4 - Victor brand # V-301 Vinyl Adhesive 1.5 fl oz. size

97-830-3203

→ 4 - Victor brand # V-104 Suction Mat; 18 fl. oz. tube size

97-830-3204

→ 12 - Victor brand # V-502 Professional Lock De-Icer and Lubricant,

97-830-3201 1.25 fl oz container

10. SAMPLES		11. SAMPLES WERE		12. COLLECTOR	
a. AMOUNT RECEIVED FOR SAMPLE		<input checked="" type="checkbox"/> PURCHASED		b. NAME (Print or type) <i>Dennis C. Blasco</i>	
c. SIGNATURE (Person from whom sample received) <i>Toni Curione</i>		<input type="checkbox"/> BORROWED (To be returned)		d. SIGNATURE <i>Dennis C. Blasco</i>	

160

VICTOR AUTOMOTIVE
12/04/96 inspection

002

CPSC Surveillance Report

1. Reporting Office FOCR	2. Home Office FOCR	3. Date 8/14/96	4. Product Code 1133
5a. Product Name LOCK DE-ICER		5b. Model VICTOR #V-500 AMOUNT UNK	
5c. Product Description & Identification LOCK DE-ICER, UNDER PRESSURE, SMALL METAL TUBE IN BLISTER PACKAGE.			

Attachment: () Label () Photo () Literature () Other _____

5d. Manufacturer/Importer - Name and Address
VICTOR AUTOMOTIVE PRODUCT INC.
 DES PLAINES, IL. 60016

6a. Suspected Problem/Violation <input checked="" type="checkbox"/> FHSA - Labeling, Banned <input type="checkbox"/> PPPA - No CRP, Ineffective CRP, Labeling <input type="checkbox"/> FFA - Labeling, Fails Std., Cert. <input type="checkbox"/> CPSA - Possible Sec. 15, Fails Std., Cert. <input type="checkbox"/> RSA - Noncompliance <input type="checkbox"/> Other - Refer to other Federal or State Agency	6b Describe NO WARNING ON FRONT DISPLAY PANEL. TUBE WAS TURNED IN PACKAGE, NO WARNING COULD BE READ, CONTENTS UNDER PRESSURE, FLAMMABLE?
---	--

7. Establishment Where Encountered - Name and Address
WESTLAKE ACE HARDWARE
 15225 87TH ST.
 LENEXA, KS. 66219

B. Reported by (Type Name & Title) ROBERT B. WADSWORTH JR. INVESTIGATOR	9. Employee No. 8158	10. Signature 8/16/96 <i>Robert B. Wadsworth Jr.</i>
11. Reporting Office Action <input checked="" type="checkbox"/> Referred to Home Office <input type="checkbox"/> Referred to HO () <input type="checkbox"/> Official Sample Collected (Sample # _____) <input type="checkbox"/> EI at Dealer <input type="checkbox"/> Other <input type="checkbox"/> None; if none, why:	12. Reviewing Official	
	13. Title SPSE	14. Signature <i>[Signature]</i>
	15. Date 9/4/96	16. Distribution: 0: FOCR Compli

162



DEPARTMENT FOR HEALTH SERVICES

CABINET FOR HUMAN RESOURCES
COMMONWEALTH OF KENTUCKY
FRANKFORT 40621-0001

File
EIF

August 22, 1990

Mr. Bert Braverman, President
Victor Automotive Products
501 S. Wolf Road
Des Plaines, IL 60016

(708) 298-8870

Dear Sir:

The review for labeling compliance of hazardous substance products, both interstate and intrastate, on retail shelves in the State of Kentucky is an ongoing activity carried out by this regulatory agency. The labeling is reviewed for compliance with the Kentucky Hazardous Substances Labeling Act (KRS 217.650 to 217.710 and 217.993), the Federal Hazardous Substances Act and Regulations. In addition if applicable the products are reviewed for compliance with the Federal Poison Prevention Packaging Act and Regulations. (copies attached)

Investigators of this agency recently collected samples of products, with your firm identified on the label, due to labeling discrepancies and/or violations. This correspondence is to bring to your attention the discrepancies. If applicable, you should take appropriate action and/or make corrections on the next printing of the labels.

Although the exact product formulation is unknown, by review of similar products of other firms and previous experience with label reviews, certain deductions were made. The product and labeling evaluation is identified on product review sheets (copies attached) and is also summarized as follows:

Victor Wiper Blade
Renewer Kit 2 fl. oz.
Plastic Bottle (V-506)

Lacks common or usual name of hazardous ingredient(s).
Lacks appropriate signal word, DANGER (POISON used?) on front panel. Likely requires other statement(s) of hazard. Lacks precautionary labeling required on accompanying literature CFR 1500.121 (c) (iii) (6). Also improper first aid treatment, "give a tablespoonful of salt in a glass of warm water" CFR 1500.134. If hazardous ingredient is methyl alcohol, may require a child-resistant closure and Skull-and-Cross bones symbol.

163

Victor Automotive
Page 2
August 22, 1990

Victor Instant Electro
Start Battery Additive
4 oz. Bottle (V-614)

Statement(s) of hazard are not in
capital letters. Lacks
precautionary labeling required on
accompanying literature CFR
1500.121 (c) (iii) (6).

The agency is not aware of all of the products, bearing your name on the label, that you may be manufacturing, repacking or that may be supplied to you by another firm. We do not know the date of manufacture of the products and/or if they are old labels, which may now be revised, however, it is apparent that there is some confusion as to the appropriate labeling of your product. Your product is either in violation or is over-labeled.

As the Kentucky Hazardous Substances Act is comparable to the Federal Hazardous Substance Act, compliance can be obtained by following labeling advice for either state or federal officials. If you wish to contact Consumer Product Safety Commission (CPSC) compliance officer, the appropriate Consumer Product Safety Regional Center is:

Central Regional Center
230 South Dearborn Street, Room 2944
Chicago, Illinois 60604
(312) 353-8260

This agency plans on continuing the review of products sold in this State, if additional products under your firm's name are found with labeling discrepancies, that information will also be provided to you.

Should you have comments or questions and/or wish to contact me, my phone number is (502) 564-4537. If you wish to fax this agency changes in labeling, etc., my fax number is (502) 564-6533.

Sincerely,


Terry M. Wescott, Manager
Product Safety Branch

cc: L.R. Mays
Steve Mays
CPSC: CRC

124

PRODUCT REVIEW FORM
SURVEILLANCE OF PRODUCTS REQUIRING CAUTIONARY LABELING
AND CHILD RESISTANT PACKAGING

INSPECTOR NUMBER: 3 DATE: 5-9-90 Prod.#: V-506

Dealer and address: Nationwide Auto Parts, 2809 Veach Rd., Owensboro, Ky 42301

Manufacturer and address: Victor Automotive Products, Inc., Chicago, IL 60641

Brand and Product: Victor Wiper Blade Renewer Kit

Container (size, type)*: 2 fl. oz. plastic bottle on blister pack

Label type (paper, embossed, etc.): Paper Mfg Code: _____

Hazardous ingredient(s): (not stated)

Labeling appears to be in compliance with FHSA: (yes) (no)

Safety closure present: (yes) (no) CRC determined effective? (yes) (no)

NON-COMPLIANCE CRC: _____

NON-COMPLIANCE LABELING: _____ (check appropriate items below):

Lacks FHSA precautionary labeling:

- (X) Common or usual name of hazardous substance(s).
- (X) Signal word: DANGER
- (X) Statement of hazard(s): ?
- () Instruction to read other panels
- () Precautionary measures describing actions to be followed or avoided.
- () First aid treatment when necessary or appropriate.
- () "KEEP OUT OF THE REACH OF CHILDREN" or equivalent.
- () Name and address of manufacturer, packer distributor, or seller.

Placement and contrast of SIGNAL WORD, STATEMENT OF HAZARD(S):

- () Must appear on main label in contrast and apart from other labeling.
- () Signal word in capital letters
- () Statement of Hazard(s) in capital letters

- (X) Precautionary labeling required on accompanying literature (blister pack)

Lacks Other specific labeling:

- (?) Highly toxic labeling includes "POISON" with skull and crossbones symbol.
- () "POISON" instead of signal word as per CFR 1500.129.
- () Petroleum Distillates specific labeling.
- () Methyl Alcohol specific labeling.
- () Turpentine specific labeling.

SAMPLE COLLECTED: (yes) (no) If yes sample number: LRM-ASA-465

if other sizes of the same product are available in identical packaging enter other sizes here: _____

If however in non-compliance additional forms should be completed for each size.

169


VICTOR

280K-4154-465

Wiper Blade Renewer Kit

063 14 59
VBR 506
0170457

\$1.29



CONTENTS:
2 FL. OZ.

V-506

**VICTOR
WIPER
BLADE
RENEWER
KIT**

NET 2 FL. OZ.

DIRECTIONS:
• WIPER TO BASE
• APPLY WITH APPLICATION
• APPLY RENEWER AGAIN



WIPER BLADE RENEWER KIT

30

INSTRUCTIONS:

1. APPLY SMALL AMOUNT OF RENEWER TO WIPER BLADES.
2. BUFF WITH SPECIAL APPLICATOR.
3. APPLY SMALL AMOUNT AGAIN ... WAIT A FEW SECONDS AND WIPE WITH CLEAN CLOTH ... THIS SHOULD GIVE YOU MONTHS OF GOOD SAFE VISION ... REPEAT AGAIN FIRST SIGN OF STREAKING.

INSTRUCCIONES:

1. APLIQUE UNA PEQUEÑA CANTIDAD DE RENOVADOR A LA HOJA DEL WIPER.
2. PULIR CON UN APLICADOR ESPECIAL.
3. APLIQUE UNA PEQUEÑA CANTIDAD NUEVAMENTE ... ESPERE UNOS SEGUNDOS Y LIMPIE CON UN PAÑO LIMPIO ... ESTO LE DARÁ MESES DE BUENA VISION ... REPITA DE NUEVO, EN EL PRIMER SIGNO DE RAYADO O LINEAS.



7

VICTOR A

AGO, IL 60641

VICTOR AUTOMOTIVE PRODUCTS, INC., CHICAGO, IL 60641

PRODUCT REVIEW FORM
SURVEILLANCE OF PRODUCTS REQUIRING CAUTIONARY LABELING
AND CHILD RESISTANT PACKAGING

INSPECTOR NUMBER: 10 DATE: 5-1-90 Prod.#: _____

Dealer and address: H&S^{Ace} Hardware, 5416 Proctor Hwy, Louisville 40213

Manufacturer and address: Victor Automotive Products Inc., ^{Chicago} Des Plaines, IL 60016

Brand and Product: Victor Instant Electro Start Battery Additive

Container (size, type)*: 4 fl. oz. - plastic bottle

Label type (paper, embossed, etc.): paper Mfg Code: V-614

Hazardous ingredient(s): cadmium sulphate - ~~cadmium sulphate~~

Labeling appears to be in compliance with FHSA: (yes) (no)

Safety closure present: (yes) (no) CRC determined effective? (yes) (no)

NON-COMPLIANCE CRC: _____

NON-COMPLIANCE LABELING: (check appropriate items below):

Lacks FHSA precautionary labeling:

- Common or usual name of hazardous substance(s).
- Signal word: ~~Caution~~
- Statement of hazard(s): _____
- Instruction to read other panels
- Precautionary measures describing actions to be followed or avoided.
- First aid treatment when necessary or appropriate.
- "KEEP OUT OF THE REACH OF CHILDREN" or equivalent.
- Name and address of manufacturer, packer distributor, or seller.

Label Placement and contrast of SIGNAL WORD, STATEMENT OF HAZARD(S):

- Must appear on main label in contrast and apart from other labeling.
- Signal word in capital letters
- Statement of Hazard(s) in capital letters

Lacks Other specific labeling:

- Highly toxic labeling includes "POISON" with skull and crossbones symbol.
- "POISON" instead of signal word as per CFR 1500.129.
- Petroleum Distillates specific labeling.
- Methyl Alcohol specific labeling.
- Turpentine specific labeling.

\$1.29

SAMPLE COLLECTED: (yes) (no) If yes sample number: HS-SLM-H30


*If other sizes of the same product are available in identical packaging enter other sizes here: _____

If however in non-compliance additional forms should be completed for each size.

167

INSTANT ElectroStart

83652
 1129



VICTOR
INSTANT ELECTRO START BATTERY ADDITIVE

WARNING: Harmful Swallowed Eye Irritant
 See Caution Side Of Label
NET 4L. OZS.

CAUTION: Contains Cadmium Sulphate. In case of eye contact flush thoroughly with water. If swallowed, induce vomiting and call a physician.
KEEP OUT OF THE REACH OF CHILDREN

VICTOR AUTOMOTIVE PRODUCTS INC.
 CHICAGO, IL 60641

59

BATTERY ADDITIVE For Weak Batteries

WARNING

READ BACK OF CARD BEFORE USING

CONTENTS:
 1 - 4 oz. Bottle

V-614
 DES PLAINES, IL 60016

INSTANT ELECTRO START Battery Additive

DIRECTIONS

1. Remove battery caps.
2. Using scale at edge of label, pour 1/4 of contents into each cell of a 12 volt battery, or 1/8 contents into each cell of a 6 volt battery.
3. After adding Electro Start, very weak batteries must be fully charged at slow rate. Normal driving will charge serviceable batteries. Electro Start makes batteries charge easier, work better and last longer.

INSTRUCCIONES


Remueva las tapas de la batería.

Usando la escala de medidas al final de la etiqueta, vierta 1/4 del contenido en cada célula de una batería de 12 voltios, o 1/8 del contenido en cada célula de una batería de 6 voltios.

Después de haber añadido el Empezador Electro, Baterías que están muy débiles deberán de ser cargadas lentamente. El manejo normal cargará las baterías que son servibles. El Empezador Electro hace que las baterías se cargan más simplemente, trabajan mejor y duran más.

WARNING!


- DO NOT JUMP BATTERY FOR 1 HOUR AFTER USING ELECTRO START
- DO NOT SMOKE OR USE OPEN FLAME NEAR BATTERY
- STAND AWAY FROM BATTERY WHEN USING BOOSTER CABLES
- DO NOT ATTACH BOOSTER CABLES WITH ENGINE RUNNING
- DO NOT POUR IN ELECTRO START WITH ENGINE RUNNING
- ADD ELECTRO START TO BATTERY IN A WELL VENTILATED AREA
- CLOSE HOOD OF CAR BEFORE STARTING ENGINE
- DO NOT JUMP BATTERIES THAT MAY BE FROZEN
- WHEN USING A BATTERY CHARGER, CHARGE AT A SLOW RATE




CAUTION: Contains Cadmium Sulphate. In case of eye contact flush thoroughly with water and call physician. If swallowed, induce vomiting and call physician. **KEEP OUT OF REACH OF CHILDREN.**

89

Victor Automotive Products, Inc.



269



EBA

FILE: *E/F*

OFFICE OF CONSUMER PROTECTION & CITIZEN ADVOCACY • P.O. BOX 7856 • MADISON, WI 53707-7856 • 608-266-1852

C 890113-0386

JAN 26 1989

TO: KOTTMER MAX D

Date

3530 CROWN BOULEVARD
LA CROSSE WI 54601

RE: R 890113-0386
VICTOR AUTOMOTIVE PRODUCTS INC

NOT AVAILABLE
CHICAGO IL 60641

Dear Consumer:

We have received your complaint. The number assigned to your file is printed on the top line of your Name/Address label.

We have reviewed your inquiry and have determined that it would be more appropriately handled by the agency listed below. Therefore, we have taken the liberty of forwarding your correspondence to that office requesting their assistance and consideration. Please address further inquiries to the office listed below.

Thank you for bringing this matter to our attention.

Sincerely,

Connie M. Eberhardt
Consumer Specialist

4/CME:fg

cc/enc: Department of Agriculture, Trade
and Consumer Protection
801 West Badger Road
Post Office Box 8911
Madison, WI 53708
Telephone Number: 266-2225

170

Mr. Max D. Kottmer
January 24, 1989
Page 2

cc/enc: National Highway Traffic Safety
Administration
Consumer Services
U.S. Department of Transportation
400 Seventh Street Southwest
Washington, DC 20590
Telephone Number: 800-424-9393

✓ U.S. Consumer Product Safety
Commission
517 East Wisconsin Avenue
Milwaukee, WI 53202

171

FIELD ACTIVITY COVERSHEET

1. REGION/STATE FOCR	2. OPERATION (Check One) <input checked="" type="checkbox"/> Inspection <input type="checkbox"/> Establishment Visit <input type="checkbox"/> Telephone Contact <input type="checkbox"/> Investigation <input type="checkbox"/> Other _____	3. DATE 5-23-88 4. NUMBER (For FO Use)
------------------------------------	---	---

5. ESTABLISHMENT
 Name Victor Automotive Products, Inc.
 Address 501 N. Wolf St.
 City Des Plaines State IL Zip 60016 Telephone No. (312) 290-8870

6. RELATED FIRM Parent Headquarters Subsidiary Other
 Name _____ City _____ State _____

7. PRODUCTS COVERED <u>Automotive Chemical Products</u>	8. OTHER CONSUMER PRODUCTS <u>Auto Accessories</u>
---	--

9. ESTABLISHMENT TYPE <input type="checkbox"/> Manufacturer <input type="checkbox"/> Importer <input type="checkbox"/> Wholesaler <input checked="" type="checkbox"/> Own Label Distributor <input type="checkbox"/> Retailer <input checked="" type="checkbox"/> Repackager <input type="checkbox"/> Other _____	10. ANNUAL PRODUCTION Products Covered \$ _____ Units _____ Other Products \$ _____ Units _____
--	--

11. L.S. BUSINESS % Received <u>30</u> % Shipped <u>70</u>	12. SAMPLES COLLECTED <u>None</u>	13. MIS CODE <u>33567</u>	14. HOURS Activity <u>20</u> Travel <u>1</u>
---	---	-------------------------------------	---

15. REASON FOR ACTIVITY (Assignment Reference)
FOCR Work Plans, FPC 88003

16. ANNOUNCED Rationale for Announced Inspection
UNANNOUNCED

17. EMPLOYEE'S NAME Robert B. Johnston	TITLE Investigator	SIGNATURE <i>Robert B. Johnston</i>
--	------------------------------	---

18. ENDORSEMENT REMARKS SUMMARY OTHER _____

This firm was inspected as part of the FPC 88-003, Household Chemicals Compliance Program and as follow-up to a State of Wisconsin report of an ingestion of their Lock Heat lock de-icer which was investigated as IDI (880126CEN0504).

The inspection revealed that the firm is a repacker and own-label distributor of automotive products. Mr. Bert Braverman, Owner and President, supplied information concerning the labeling and formulations for the products. Review of the labeling for the firm's products found that warnings on tube type products were at the bottom end of the tube, instead of at the top end of the tube, wrong ingredients were listed on the Vinyl Adhesive, typesize and placement of the warnings were not always correct. The previous inspection of this firm found similar problems, but because of the size of the products, seizures were not accomplished. At that time CARM advised that an injunction should be considered, so that the firm would have to make the necessary corrections.

F/U: Pending CARM review and comment.

19. REVIEWER'S NAME James A. Miersch	TITLE SPSI	SIGNATURE <i>James A. Miersch</i>
--	----------------------	---

20. REVIEW DATE 6-28-88	21. DISTRIBUTION <input checked="" type="checkbox"/> =FOCR thru Complince Branch cc=CARM, C. Jacobson
-----------------------------------	--

184