

Sediment Tracer Study

at the Mouth of the Columbia River

***An Investigation to Determine the FATE of Dredged Sediment
Placed at the Shallow Water Site (SWS)***

THE TRACER TEAM

Russ Boudreau @ Moffatt & Nichol Engineers- Project Engineer: CA

Trap Puckette @ Evans Hamilton, Inc - Principal Investigator: SC

Jonathan Marsh @ Environmental Tracing Systems – CoPI: UK

Kevin Redman @ Evans Hamilton – Tool Pusher, Inc: WA

Kevin Smith @ Evans Hamilton, Inc: WA

Gene Bock @ MERTS/Clatsop Community College – Captain of the Boat: OR

***R/V Forerunner* @ MERTS/Clatsop Community College**

Hans R. Moritz and Doris J. McKillip
U.S. Army Corps of Engineers, Portland District

Overview

- MCR Dredging & Disposal - Motivation
- Sediment Tracer at MCR
 - Tracer Execution
 - Tracer Results to Date
 - Future Studies
- Relevance & Benefits


Columbia River Estuary



MCR Channel (RM -3to 3): Annual O&M Dredging (4 miles) = 1 MCY/mile per year

Mouth of the Columbia River

“CONSTRUCTED” 1885-1917



Pile Dikes

Jetty “A”

North Jetty

**MCR
Navigation
Channel**

Clatsop Spit

South Jetty


*Peacock
Spit*

6 miles long
2,640 ft wide
55/48 ft deep

Pacific Ocean

Bathymetry Showing Location of Shoals & Jetties

Excessive Erosion of Shoals Can Lead to Loss of Jetty Foundation = Loss of Jetty





Hopper Dredges working at MCR

Essayons

Sugar Island

3-5 Million cy of Sand Dredged from MCR Each Year

**MCR Maintenance Dredging is Performed during June-Sept
Work is split between a GOVT and PRVT IND hopper dredge**

Mouth of the Columbia River - Bathymetry and 2006 Dredged Material Placement Sites




Figure 1

DWS= Deep Water Site, 102 MPRSA NJ Site = North Jetty disposal site, 404 CWA
 SWS= Shallow Water Site, 102 MPRSA (formally Site E, 103 MPRSA)

SJ Res. Site = South Jetty research site, restricted use by EPA permit

View to the Northwest

Peacock

Spit

Benson Beach

NORTH JETTY

SWS ODMDS MPRSA 102

MCR Channel

Clatsop


ebb

flood

Spit

SOUTH JETTY


Distance from tip of south jetty to tip of north jetty is 2 miles



Opportunity for Intervention

- **Benefits-** Sustain sediment budget on north side of MCR Inlet.
 - *Defer north jetty repair, stabilize inlet, reduce shoreline erosion north of MCR
- **Risks -** Dredged material does not “behave” as intended = Unintended consequences
 - * Moves back into MCR Channel or AWAY from intended direction of transport

Use the SWS to feed material onto *Peacock Spit* and Sustain the sediment budget north of MCR (place 1.5-2.5 Mcy/yr):




- * Reduce the rate of erosion affecting the north jetty
- * Reduce shoreline erosion along areas north of MCR

Table A1. Summary of SWS ODMDS utilization and dispersive properties of site.

YEAR	VOLUME PLACED IN SWS ODMDS % of MCR dredging	SPECIFICIED PLACEMENT METHOD ^ C=contractor G=government	MAXIMUM MOUND HEIGHT @ END OF DREDGING SEASON *	EFFECTIVENESS OF USING ENTIRE SW SITE TO DISPERSE DREDGED MATERIAL	TRANSPORT DURING DREDGING SEASON (CY) **	TRANSPORT DURING WINTER (CY) **	NET ANNUAL TRANSPORT OF SEDIMENT OUT OF SW SITE (CY) **
1997	1.0 MCY 68%	None (C)	2-3 ft peak = 5 ft	20% of the Site Was Used	-400,000 (40%)	+614,000 60%	+214,000 20% accumulated
1998	3.5 MCY 81%	Grid Cells (C) Uniformly (G)	5-6 ft peak = 6 ft	70% of the Site Was Used	-2,100,000 (60%)	-1,216,000 (35%)	-3,315,000 (95% eroded)
1999	3.8 MCY 74%	Grid Cells(C) Uniformly(G)	6-7 ft Peak = 7 ft	80% of the Site Was Used	-1,520,000 (40%)	-1,091,000 (30%)	-2,611,000 (70% eroded)
2000	2.9 MCY 75%	Grid Cells(C) Uniformly(G)	6-8 ft Peak = 8 ft	60% of the Site Was Used	-1,160,000 (40%)	-739,000 (25%)	-1,899,000 (65% eroded)
2001	2.2 MCY 54%	Disposal Lanes(C) Uniformly(G)	6-7 ft Peak = 9 ft	70% of the Site Was Used	-1,200,000 (50%)	-1,752,000 (73%)	-2,952,000 (123% eroded)
2002	1.5 MCY 32%	Disposal Lanes(C)	6-7 ft Peak = 8 ft	50% of the Site Was Used	-300,000 (20%)	-1,710,000 (113%)	-2,010,000 (134% eroded)
2003	2.8 MCY 86%	Grid Cells (C) Grid Cells (G)	2-4 ft Peak = 5 ft	>90% of the Site Was Used	-900,000 (32%)	-575,000 (21%)	-1,475,000 (52% eroded)
2004	2.9 MCY 57%	Grid Cells (C) Grid Cells (G)	2-5 ft Peak = 5 ft	>90% of the Site Was Used	-1,000,000 (34%)	-1,000,000 (34%)	-2,000,000 (68% eroded)
2005	2.6 MCY 67%	Grid Cells (C) Grid Cells (G)	2-6 ft Peak = 7 ft	>90% of the Site Was Used	-900,000 (35%)	-1,900,000 (73%)	-2,800,000 (107% eroded)
2006	1.8 MCY 53%	Grid Cells (C) Grid Cells (G)	2-6 ft Peak = 6 ft	>75% of the Site Was Used	-680,000 (37%)	-600,000++ (33%)	-1,280,000++ (67% eroded)
	2.8 MCY 64%	AVERAGE VALUES	5-6 ft Peak = 9 ft	68%	39%	49%	88%

Mouth of the Columbia River - Bathymetry



DWS= Deep Water Site, 102 MPRSA NJ Site = North Jetty disposal site, 404 CWA
SWS= Shallow Water Site, 102 MPRSA (formally Site E, 103 MPRSA)

SJ Res. Site = South Jetty research site, restricted use by EPA permit

MCR Bathymetry Difference: 1997 - 2006





Figure 20



1958 to 2003 Bathymetric Change

Use of the SWS has reduced the rate of erosion affecting Peacock Spit.


Sustain the Peacock Spit, and it will protect the north jetty and inlet.

**Mouth of the Columbia River
Shallow Water Site
(SWS ODMDS)**


Figure 8

BASELINE CONDITION


BASELINE CONDITION



SWS Bottom Change During 2006 Dredged Material Disposal



Mouth of the Columbia River
Shallow Water Site
AUG 2005







Figure 34

1973-1997: 50 M cy of dredged sand placed in SWS


1997-2006: 25 M cy has been placed ---- 3 M cy remain within SWS

Recent results

DELFT 3-D Model USGS



Initial distribution of "SWS" sand (and fixed layer) in the top 5cm of bed



"Final" distribution of site E disposal sand in the top 5cm of bed at the end of February 2004

Tracer Study Objectives

Study designed to assess seabed mobility and the fate of dredge material once on the seabed;

No dispersion associated with the initial placement of the dredged sediments.


The sediment tracer was to be placed on the seabed rather than introducing the tracer in the dredge hopper and releasing it as part of the dredged dumping operations.

The sediment tracer must ‘behave’ in the same way (in terms of sediment transport) as the dredged sediment placed in the disposal site. The tracer would be moved (or become suspended) by waves and currents along with the dredged material.


Verify if dredged sediment placed in nearshore disposal sites (<60 feet depth), becomes part of the littoral budget and provide direct measurement of the transport pathways.

- a) Does MCR dredged material placed at the SWS move northward onto Peacock Spit and ultimately onto Benson Beach, offshore toward deeper water, southward toward the MCR navigation channel, or inshore toward the interior of the MCR inlet?**
- b) What is the rate that dredged material is transported out of the SWS for each of the above pathway scenarios?**

TRACER EXECUTION




Mouth of the Columbia River - Bathymetry and 2006 Dredged Material Placement Sites





DWS= Deep Water Site, 102 MPRSA NJ Site = North Jetty disposal site, 404 CWA
 SWS= Shallow Water Site, 102 MPRSA (formally Site E, 103 MPRSA)


SJ Res. Site = South Jetty research site, restricted use by EPA permit





Mouth of the Columbia River
Shallow Water Site
AUG 2005












Cross-section Along SWS Seabed
Section A-A'

A

A'






**Cross-section Along SWS Seabed
Section B-B'**

B

B'






Figure 3.6: Background grab sampling sites, 21 & 22 September 2006



Figure 3.5: Tracer:sediment being transferred from the storage box into the hopper prior to being placed into the dissolving bags.





50 meter radius “release circle”




Figure 3.4: Map showing locations of sediment deployments relative to the main tracer release area and individual tracer placements.



Figure 3.3: Deployment of the sediment traps, 1 October 2006




Figure 3.1: Shipek grab



Figure 3.2: Shipek grab being deployed at MCR




Figure 4.3: Day 2 grab samples and sediment traps 3rd October

Table 6: Mass budget analysis summary Day 2

	Area 1 (0–100 m radius)	Area 2 (100–300 m annulus)	Total
Area	31,416 m ²	251,327 m ²	282,743 m ²
Depth of sediment sampled	0.05 m	0.05 m	
Volume of sediment	1,571 m ³	12,566 m ³	14,137 m ³
Mass of dry sediment in volume	8.2×10^6	3.7×10^7	4.5×10^7
Total tracer particles measured in grabs in Area	1.38×10^{11}	1.70×10^{10}	1.55×10^{11}
Total tracer particles released			1.5×10^{11}
Percentage accounted for in Area	92%	11%	103%

Based on the relatively recent disposal 2 days prior, it is estimated that minimal burial of the tracer had taken place.

ARGUS Cameras

http://zuma.nwra.com/north_head/




Tracer Release Zone



View from North Head ARGUS Station

ALL WAS CALM on 1 NOV 2006



BUT Times were a Changing.




Figure 4.1: Significant wave height data from 1st October to 5th December 2006














Tracer particle in native sand
white light only, no
fluorescence illumination.

Tracer particle in native sand
White light and fluorescence
illumination

Tracer particle in native sand
No white light, fluorescence
illumination only.

Figure 2.5: Fluorescence micrographs of an MCR tracer particle




Figure 4.4: Tracer concentrations measured in grab samples collected Day 61–63 (around the tracer release area)




Figure 4.5: Tracer concentrations measured in grab samples collected Day 61–63 including Benson Beach

Table 7: Mass budget analysis summary Day 61–63

	Area 1 (0–100m radius)	Area 2 (100–300m annulus)	Area 3 (Outwith 300m radius)	Total
Area	31,416 m ²	251,327 m ²	1.12×10 ⁷ m ²	1.16×10 ⁷ m ²
Depth of sediment sampled	0.05 m	0.05 m	0.05 m	0.05 m
Volume of sediment	1,571 m ³	12,566 m ³	560,200 m ³	582,300 m ³
Mass of dry sediment in volume	8.2 × 10 ⁶	3.7 × 10 ⁷	1.33 × 10 ⁹	1.38 × 10 ⁹
Total tracer particles measured in grabs in Area	7.96 × 10 ⁸	1.42× 10 ⁹	9.34×10 ⁹	1.16 × 10 ¹⁰
Total tracer particles released				1.5 × 10 ¹¹
Percentage accounted for in Area	0.53%	0.95%	6.3%	7.7%

Interim Conclusions

Did the tracer 'behave' in the same way as dredged sediment in SWS disposal site

The tracer particles had a density, particle size D50 and range, and fall velocity very similar to the natural sediment.

The Study Team concluded that the tracer did have the same physical characteristics as the natural sediment.

Interim Conclusions

Does dredged sediment disposed in nearshore shallow water areas become part of the littoral budget?

Based on the Day 61–63 grab sample data, there is strong and consistent evidence that the tracer was mobile and transported in a north or northwest direction in line with longshore transport at SWS. These data indicate that the material did become part of the littoral budget.

Caveat

The data indicates that a significant proportion of the tracer has not moved very far from the original release area.

One uncertainty surrounding the pattern of deposition is the fact that samples were collected using a grab sampler in an area with active sand waves, consequently, a significant amount of the tracer may be at a depth greater than that sampled.

Interim Conclusions

Does sediment from SWS move northward onto Peacock Spit and ultimately Benson Beach?

The tracer results directly show that the tracer particles released in SWS did move north onto Peacock Spit and as far as Benson Beach within 2 months, with both very fine and fine sand tracer particles detected.

The fact the tracer was detected in one Benson Beach sample relatively quickly is very interesting and supports CENWP's inferred sediment transport

.....that dredged sediment from SWS is likely to nourish the beaches to the north along the Washington coastline. The sediment tracers proved the existence of a pathway.

Continued sampling would help to understand the significance and volume of movement.




Figure 1



1939

As Peacock Spit Erodes, The MCR North Jetty is subjected to scour and wave attack



North Head

Shoreline 1913

Benson Beach has receded
2,000 ft since 1939

North Jetty

2002

South Jetty

North Jetty, 25 ft high

Benson Beach

Low Tide


25 ft wave



Storm Tide

Cameras Located within North Head Lighthouse

Keep an EYE on Things at MCR – Public Access to Website



2 miles; 3.22 km


ARGUS Cameras


http://zuma.nwra.com/north_head/






Panoramic to Plan Views – 26 Sept 04


 670m




Thu. Mar. 03. 18.20.00. GMT. 2005




Sat. Apr. 16. 18.20.00. GMT. 2005



Mon. May. 16. 23. 20. 00. GMT. 2005




Why are the waves breaking there: Sediment Moving out of SWS?



October 2005 – end of SWS material placement

26 MAY 2006 ARGUS Beach Monitoring System at North Head cameras 5 & 6

Additional Erosion (cutting) of Beach Scarp during winter '05-'06



Sand from “Sand Bars” being transported onshore

Note lighter color of sand migrating shoreward from sand bars covering darker sands

The darker color sands contain hematite and other heavy minerals. The darker sands are more dense and less mobile than the lighter color sands, and tend to stay on the beach during the winter wave season. The dredged sediment placed at the SWS has likely contributed to the sand supply of Peacock Spit. The lighter color sands may come from the dredged sand placed at the SWS.