



UNITED STATES DEPARTMENT OF COMMERCE
National Oceanic and Atmospheric Administration

National Marine Fisheries Service

P.O. Box 21668

Juneau, Alaska 99802-1668

November 4, 2008

Colonel Kevin J. Wilson
District Engineer
U.S. Army Corps of Engineers
P.O. Box 6898
Anchorage, Alaska 99506-0898

Re: POA-1980-74
Portland Canal

Attn: Roberta Budnik

Dear Colonel Wilson:

The National Marine Fisheries Service (NMFS) has reviewed the above referenced application by the Alaska Department of Transportation and Public Facilities to make repairs and upgrades to the Hyder Harbor. Specifically, the work would include repairing timber floats, installation of a new floating log breakwater, and possibly replacing existing wood piles depending on their condition. The project is located in Hyder, Alaska (55.9084 N, -130.0237 W).

Section 305(b) of the Magnuson-Stevens Fishery Conservation and Management Act requires federal agencies to consult with NMFS on all actions that may adversely affect Essential Fish Habitat (EFH). NMFS is required to make EFH Conservation Recommendations, which may include measures to avoid, minimize, mitigate or otherwise offset adverse effects. The Alaska Department of Fish and Game's Anadromous Waters Catalog identifies numerous anadromous streams in the vicinity of the proposed project. These streams support runs of pink, chum, and coho salmon. Juvenile salmon use nearshore habitat during spring and early summer for feeding and predator avoidance prior to migration out to sea.

In accordance with Section 305(b)(4)(A) of the Magnuson-Stevens Act, NMFS makes the following EFH Conservation Recommendations:

1. No in-water work should be permitted from April 1 through June 15 of any year to protect out-migrating salmon.
2. All intertidal work below the high tide line should occur when tidelands are not submerged to reduce turbidity.
3. No docks, ramps, or other structures that block sunlight should be placed in or over eelgrass beds.
4. The use of any wood that has been surface or pressure-treated with creosote or treated with pentachlorophenol should be prohibited. If treated wood must be used, any wood that comes in contact with water should be treated with waterborne preservatives



approved for use in aquatic and/or marine environments. These include, but are not limited to: Chromated Copper Arsenic (CCA) Type C, Ammoniacal Copper Zinc Arsenate (ACZA), Alkaline Copper Quat (ACQ), Copper Boron Azole (CBA) or Copper Azole (CA). Use wood treated with waterborne preservatives in accordance with Best Management Practices developed by the Western Wood Preservers Institute. Treated wood should be inspected before installation to ensure that no superficial deposits of preservative material remain on the wood.

5. Piles should be driven with a vibratory hammer to the extent practicable. Pile driving can generate intense underwater sound pressure waves that can disrupt migration and injure or kill fish. Vibratory hammers produce less intense sounds than impact hammers (NMFS 2005). Fish have been observed to avoid sounds similar to those produced by vibratory hammers and to remain within the field of harmful sound associated with an impact hammer (Dolat 1997). If an impact hammer is required because of substrate type or the need for seismic stability, piles should be driven as deep as possible with a vibratory hammer before the impact hammer is used.

Under section 305(b)(4)(B) of the Magnuson-Stevens Act the Corps is required to respond to NMFS EFH Conservation Recommendations in writing within 30 days. If the Corps will not make a decision within 30 days the Corps should provide NMFS with a letter within 30 days to that effect and indicate when a full response will be provided.

If you have any questions regarding our recommendations for this project, please contact John Hudson at 907-586-7643 or john.hudson@noaa.gov.

Sincerely,



Robert D. Mecum
Acting Administrator, Alaska Region

cc: Applicant
EPA Juneau, Chris Meade*
ADNR, Mark Minnillo*
USFWS Juneau, Richard Enriquez*
ADEC Juneau, Brenda Krauss*
OHMP, Erin Allee*

* e-mail PDF

Literature cited

Dolat, S.W. 1997. Acoustic measurements during the Baldwin Bridge Demolition (final, dated March 14, 1997). Prepared for White Oak Construction by Sonalysts, Inc., Waterford, CT. 34 pp plus appendices.

National Marine Fisheries Service. 2005. Final Environmental Impact Statement, Essential Fish Habitat Identification and Conservation in Alaska, Vol. 2, Appendix G; National Marine Fisheries Service, Department of Commerce. April, 2005.