

UNITED STATES DEPARTMENT OF COMMERCE National Oceanic and Atmospheric Administration

National Marine Fisheries Service P.O. Box 21668 Juneau, Alaska 99802-1668

September 17, 2008

Colonel Kevin J. Wilson District Engineer U.S. Army Corps of Engineers P.O. Box 6898 Anchorage, Alaska 99506-0898

Re: POA-2008-659 Naukati Bay

Attn: Joseph Connor

Dear Colonel Wilson:

The National Marine Fisheries Service (NMFS) has reviewed the above referenced application from Kathy Sheets of Ketchikan, Alaska to construct a personal use dock in Naukati Bay, Prince of Wales Island. The proposed work includes construction of a 100-foot by 8-foot pier supported by pressure treated pilings, a 55-foot by 6-foot ramp, and a 50-foot by 20-foot floating dock. The pilings will be placed on solid rock and anchored with rock gabions. The dock will be secured by two galvanized pilings and will not ground at any tidal stage.

Section 305(b) of the Magnuson-Stevens Fishery Conservation and Management Act requires federal agencies to consult with NMFS on all actions that may adversely affect Essential Fish Habitat (EFH). NMFS is required to make EFH Conservation Recommendations, which may include measures to avoid, minimize, mitigate or otherwise offset adverse effects. The Alaska Department of Fish and Game's Anadromous Streams Catalog indicates that Naukati Bay provides important habitat for chum, coho, and pink salmon.

In accordance with Section 305(b)(4)(A) of the Magnuson-Stevens Act, NMFS makes the following EFH Conservation Recommendations:

- 1. No in-water work should be permitted from April 1 through June 15 of any year to protect out-migrating salmon.
- 2. No docks, ramps, or other structures that block sunlight should be placed in or over eelgrass beds.
- 3. The use of any wood that has been surface or pressure-treated with pentachlorophenol should be prohibited. Treated wood that comes in contact with water should be treated with waterborne preservatives approved for use in aquatic and/or marine environments. These include, but are not limited to: Chromated Copper Arsenic (CCA) Type C, Ammoniacal Copper Zinc Arsenate (ACZA), Alkaline Copper Quat (ACQ), Copper Boron Azole (CBA) or Copper Azole (CA). Use wood treated with waterborne



preservatives in accordance with Best Management Practices developed by the Western Wood Preservers Institute.

- 4. Drive piles with a vibratory hammer. Pile driving can generate intense underwater sound pressure waves that can injure or kill fish (Longmuir and Lively 2001, Stotz and Colby 2001). Vibratory hammers produce less intense sounds than impact hammers (NMFS 2005). Fish have been observed to avoid sounds similar to those produced by vibratory hammers and to remain within the field of harmful sound associated with an impact hammer (Dolat 1997). If an impact hammer is required because of substrate type or the need for seismic stability, piles should be driven as deep as possible with a vibratory hammer before the impact hammer is used.
- 5. Drive piles during low tide when they are located in intertidal areas. Potentially harmful sound pressure waves are attenuated more rapidly in shallow water than in deep water (Rogers and Cox 1988).

Additionally, to reduce the possibility for harassment or injury to marine mammals, pile driving should not occur if any marine mammals are observed within 200 meters of the platform. The operator should scan the area for the presence of marine mammals. If marine mammals are sighted within 200 meters of the sound source or are observed to be disturbed by the activity at any distance, pile driving should cease until the animals leave the immediate area.

Under section 305(b)(4) of the Magnuson-Stevens Act, the Corps is required to respond to NMFS EFH Conservation Recommendations in writing within 30 days. If the Corps will not make a decision within 30 days of receiving NMFS EFH Conservation Recommendations, the Corps should provide NMFS with a letter within 30 days to that effect, and indicate when a full response will be provided.

If you have any questions regarding our recommendations for this project, please contact John Hudson at 907-586-7643 or john.hudson@noaa.gov.

Sincerely,

Robert D. Mecum

Acting Administrator, Alaska Region

cc: Applicant

EPA Juneau, Chris Meade* ADNR, Mark Minnillo* USFWS Juneau, Richard Enriquez* ADEC Juneau, Brenda Krauss* OHMP, Erin Allee*

* e-mail PDF

Literature cited

Dolat, S.W. 1997. Acoustic measurements during the Baldwin Bridge Demolition (final, dated March 14, 1997). Prepared for White Oak Construction by Sonalysts, Inc., Waterford, CT/34 pp + appendices.

Longmuir, C. and T. Lively. 2001. Bubble curtain systems for use during marine pile driving. Report by Fraser River Pile & Dredge Ltd., New Westminster, British.Columbia. 9 pp.

National Marine Fisheries Service. 2005. Final Environmental Impact Statement, Essential Fish Habitat Identification and Conservation in Alaska, Vol. 2, Appendix G; National Marine Fisheries Service, Department of Commerce. April, 2005.

Rogers, P.H. and M. Cox. 1988. Underwater sound as a biological stimulus. pp. 131-149. *In* Sensory biology of aquatic animals. Atema, J, R.R. Fay, A.N. Popper, and W.N. Tavolga, eds. Springer-Verlag. New York.

Stotz, T. and J. Colby. 2001. January 2001 dive report for Mukilteo wingwall replacement project. Washington State Ferries Memorandum. 5 pp. + appendices.

G:\AGENCY FOLDERS\COE\2008 - MASTER FILE\Naukati Bay POA-2008-659 Sheets dock jph Sept 08.doc