

U. S. DEPARTMENT OF COMMERCE
NATIONAL BUREAU OF STANDARDS
WASHINGTON, D. C. 20234

PROVISIONAL CERTIFICATE
STANDARD SAMPLE 1061a
MAGNESIUM CYCLOHEXANEBUTYRATE

(Standard for Determination of Magnesium in Petroleum Products)

This compound was prepared to insure material that is essentially free from other metals and has suitable solubility, compatibility, and uniformity for use in the preparation of a standard of magnesium in lubricating oils. The compound is being certified provisionally to one part per hundred of magnesium, pending further studies of analytical procedures, of loss of weight on drying, and of changes in weight when exposed to air. Every effort should be made to maintain a uniform procedure, by following the directions in this certificate.

CHEMICAL AND SPECTROGRAPHIC ANALYSES
Procedure and Results of Chemical Analysis

Magnesium, percent-----6.8

Magnesium was determined by wet-ashing a 1-g sample (dried for 48 hours over phosphorus pentoxide) with sulfuric and nitric acids, precipitating twice as magnesium ammonium phosphate, and weighing the $Mg_2P_2O_7$ after ignition at 1000°C. Analyst, B. B. Bendigo.

Procedure and Results of Spectrographic Analysis

The compound was examined spectrographically for metallic impurities. A 5-mg sample of the compound was excited in a direct-current arc and the photographed spectrum was examined for the characteristic lines of 50 elements. Several impurities were found, but none is considered to be present in sufficient concentration to interfere with the intended use. The impurities were each estimated to be less than 0.01 percent. Analyst, Elizabeth K. Hubbard.

STABILITY. - Tests show that standard lubricating-oil solutions of this compound with concentrations of magnesium up to 500 ppm are stable for several weeks when prepared by the directions given below.

COMPATIBILITY. - Lubricating-oil solutions of this compound have been found to be compatible with lubricating-oil solutions of the other compounds in this series. Blends of several different compounds have been prepared by the procedures given in the provisional certificates for the other compounds. (Tests have not been carried out to insure compatibility with the various additives that may be in the oils to be analyzed.)

DIRECTIONS FOR PREPARING LUBRICATING-OIL SOLUTIONS OF
MAGNESIUM CYCLOHEXANEBUTYRATE

Transfer approximately 1.0 g of this compound from the bottle to a small beaker and dry over fresh phosphorus pentoxide in a desiccator for 48 hours. (Tightly close the bottle containing the remainder of the compound.) Quickly and accurately transfer 0.735 g of this dried salt to a weighed 200-ml flask. (This weight of salt is equivalent to 50 mg of magnesium.) Add 3 ml of xylene and 5 ml of 2-ethylhexanoic acid and heat the flask on a hot plate, with swirling and without charring, until a clear solution forms. Add to the hot solution 80 to 90 ml of lubricating oil and gently shake the flask to mix the contents. Allow the flask to cool to room temperature and add enough lubricating oil to bring the total weight of the contents of the flask to 100 ± 0.5 g. Stopper the flask and shake gently to insure a homogeneous solution. The concentration of magnesium in this solution is 500 ppm.



MERRILL B. WALLENSTEIN, Chief
Division of Physical Chemistry

November 15, 1963
Washington, D. C. 20234

USCOMM-NBS-DC