



Toolbox of Countermeasures and Their Potential Effectiveness for Intersection Crashes

Introduction

This issue brief documents estimates of the crash reduction that might be expected if a specific countermeasure or group of countermeasures is implemented with respect to intersection crashes. The crash reduction estimates are presented as Crash Reduction Factors (CRFs).

Traffic engineers and other transportation professionals can use the information contained in this issue brief when asking the following types of question: Which countermeasures might be considered at the signalized intersection of Maple and Elm streets, an intersection experiencing a high number of total crashes and left-turn crashes? What change in the number of total crashes and left-turn crashes can be expected with the implementation of the various countermeasures?

Crash Reduction Factors

A CRF is the percentage crash reduction that might be expected after implementing a given countermeasure. In some cases, the CRF is negative, i.e. the implementation of a countermeasure is expected to lead to a percentage increase in crashes.

One CRF estimate is provided for each countermeasure. Where multiple CRF estimates were available from the literature, selection criteria were used to choose which CRFs to include in the issue brief:

- Firstly, CRFs from studies that took into account regression to the mean and changes in traffic volume were preferred over studies that did not.
- Secondly, CRFs from studies that provided additional information about the conditions under which the countermeasure was applied (e.g. road type, area type) were preferred over studies that did not.

Where these criteria could not be met, a CRF may still be provided. In these cases, it is recognized that the reliability of the estimate of the CRF is low, but the estimate is the best available at this time. The CRFs in this issue brief may be periodically updated as new information becomes available.

The Desktop Reference for Countermeasures lists all of the CRFs included in this issue brief, and adds many other CRFs available in the literature. A few CRFs found in the literature were not included in the *Desktop Reference*. These CRFs were considered to have too large a range or too large a standard error to be meaningful, or the original research did not provide sufficient detail for the CRF to be useful.

A CRF should be regarded as a generic estimate of the effectiveness of a countermeasure. The estimate is a useful guide, but it remains necessary to apply engineering judgment and to consider site-specific environmental, traffic volume, traffic mix, geometric, and operational conditions which



U.S. Department of Transportation
Federal Highway Administration



Institute of Transportation Engineers

will affect the safety impact of a countermeasure. The user must ensure that a countermeasure applies to the particular conditions being considered. The reader is also encouraged to obtain and review the original source documents for more detailed information, and to search databases such as the National Transportation Library (ntlsearch.bts.gov) for information that becomes available after the publication of this issue brief.

Presentation of the Crash Reduction Factors

In the Tables presented in this issue brief, the crash reduction estimates are provided in the following format:

$$\text{CRF}(\text{standard error})^{\text{REF}}$$

The CRF is the value selected from the literature.

The standard error is given where available. The standard error is the standard deviation of the error in the estimate of the CRF. The true value of the CRF is unknown. The standard error provides a measure of the precision of the estimate of the true value of the CRF. A relatively small standard error indicates that a CRF is relatively precisely known. A relatively large standard error indicates that a CRF is not precisely known. The standard error may be used to estimate a confidence interval of the true value of the CRF. (An example of a confidence interval calculation is given below.)

The REF is the reference number for the source information.

As an example, the CRF for the countermeasure *install cameras to detect red-light running* for right-angle fatal/injury crashes is:

$$\mathbf{16(6)^{27}}$$

The following points should be noted:

- The CRF of 16 means that a 16% reduction in right-angle fatal/injury crashes is expected after the installation of red-light running cameras.
- This CRF is bolded which means that a) a rigorous study methodology was used to estimate the CRF, and b) the standard error is relatively small. A CRF which is not bolded indicates that a less rigorous methodology (e.g. a simple before-after study) was used to estimate the CRF and/or the standard error is large compared with the CRF.
- The standard error for this CRF is 6. Using the standard error, it is possible to calculate the 95% confidence interval for the potential crash reduction that might be achieved by implementing the countermeasure. The 95% confidence interval is ± 2 standard errors from the CRF. Therefore, the 95% confidence interval for the installation of red-light running cameras for right-angle fatal/injury crashes is between 4% and 28% ($16 - 2 \times 6 = 4\%$, and $16 + 2 \times 6 = 28\%$).
- The reference number is 27 (Persaud et al., as listed in the References at the end of this issue brief).

Using the Tables

The CRFs for intersection crashes are presented in three tables which summarize the available information. The Tables are:

Table 1: Signalization Countermeasures, which includes signal operations countermeasures, signal hardware countermeasures, and combination signal and other countermeasures

Table 2: Geometric Countermeasures, which includes left turn countermeasures, right turn countermeasures, and other geometric countermeasures

Table 3: Signs/Markings/Operational Countermeasures, which includes signs, pavement markings modifications, regulatory, lighting, and operational countermeasures

Readers familiar with the previous edition of this issue brief will notice the following changes:

- Countermeasure cost estimates of low, medium, high are no longer provided as most agencies have readily available cost estimate information with actual dollar amounts.
- Countermeasures that do not have an estimate of crash reduction effectiveness are no longer included.

The following points should be noted:

- Where available, separate CRFs are provided for different crash severities. The crash severities are: all, fatal/injury, fatal, injury, or property damage only (PDO).
- Where available, existing traffic control information is provided (i.e. the conditions existing before implementation of a countermeasure). The control information may be no signal, signal, stop, or stop/yield. "Undefined" is used when a publication does not provide more specific information such as no signal, signal, stop, or yield controlled.
- Where available, the Tables provide daily traffic volume(vehicles/day) information for the major and minor roads of the intersection where the potential effectiveness of the countermeasure was measured. Where only one volume is provided, this volume refers to the traffic volume on the major road, unless otherwise specified.
- Blank cells mean that no information is reported in the source document.
- For additional information, please visit the FHWA Office of Safety website (safety.fhwa.dot.gov).

Legend

CRF(standard error)^{REF}

CRF is a crash reduction factor, which is an estimate of the percentage reduction that might be expected after implementing a given countermeasure. A number in bold indicates a rigorous study methodology and a small standard error in the value of the CRF. Standard error, where available, is the standard deviation of the error in the estimate of the CRF. REF is the reference number for the source information.

Additional crash types identified in the *Other Crashes* column:

a: Head-on b: Run-off-road c: Overturn d: Night e: Day f: Multiple-vehicle g: Fixed-object h: Older-driver i: Younger-driver
j: Right-turn k: Speed-related l: Speed related/day m: Speed related/night n: Speed related/dry o: Speed related/wet
p: Wet q: Night/wet r: Pedestrian s: All turns t: Bicycle u: Emergency vehicle

Table 1: Signalization Countermeasures

Countermeasure(s)	Crash Severity	Control	Area Type	Configuration	All Crashes	Left-turn Crashes	Rt-angle Crashes	Rear-end Crashes	Sideswipe Crashes	Other Crashes	Major/Minor Daily Traffic Volume (vehicles/day)
SIGNAL OPERATIONS COUNTERMEASURES											
Add all-red clearance interval (from 0 to 1 second)	All	Signal	Urban				0(44) ²⁸				
Add exclusive pedestrian phasing	All	Signal								r 34 ¹⁶	
Convert exclusive leading protected to exclusive lagging protected	All	Signal			-15(19) ¹⁵	-49(54) ¹⁵					
Convert permissive or permissive/protected to protected only left-turn phasing	All					99 ⁴¹					
Convert permissive to permissive/protected left-turn phasing	All					16 ⁴¹					
Convert protected left-turn phase to protected/permissive	All	Signal			-20(17) ¹⁵	-65(71) ¹⁵		4(22) ¹⁵			
	Fatal/Injury	Signal			-10(25) ¹⁵						
Convert protected/permissive left-turn phase to permissive/protected	All	Signal			13(19) ¹⁷	33(22) ¹⁷					
Improve signal timing [to intervals specified by the ITE <i>Determining Vehicle Change Intervals: A Proposed Recommended Practice (1985)</i>]	All	Signal		4-Leg	8(9)³⁰		4(18) ³⁰	-12(16) ³⁰		h 42 ²⁵	
	All	Signal	All							f 5 ¹¹	
	All	Signal				75 ⁹					
	Fatal/Injury	Signal				55 ⁹	30 ⁹			a 75 ⁹	
	Fatal/Injury	Signal								b 62 ⁹	
	Fatal/Injury	Signal		4-Leg	12(9) ³⁰		-6(22) ³⁰	-8(17) ³⁰			
	Fatal/Injury	Signal	All							f 9 ¹¹	
	Fatal/Injury	Signal								r 37 ³⁰	
	PDO	Signal				63 ⁹	46 ⁹	17 ⁹		b 28 ⁹	
Increase yellow change interval	All	Signal			15 ⁹		30 ⁹				
Install emergency vehicle pre-emption systems	All	Signal								u 70 ³¹	
Modify signal phasing (implement a leading pedestrian interval)	All	Signal								r 5 ¹⁶	
Provide actuated signals	All	Signal				80 ⁹	10 ⁹				
Provide Advanced Dilemma Zone Detection for rural high speed approaches	Fatal/Injury	Signal	Rural	4-Leg (1 app)	39 ⁴⁰						
Provide protected left-turn phase	Fatal/Injury	Signal	Urban			16(2)¹⁹	19(2)¹⁹				
	All	Signal			30 ⁹	41 ⁹	54 ⁹	27 ⁹		c 27 ⁹	<5,000/lane (Total)
	All	Signal			36 ⁹	46 ⁹	56 ⁹	35 ⁹		c 35 ⁹	>5,000/lane (Total)
	All	Signal			27 ⁹	48 ⁹	63 ⁹	31 ⁹		c 31 ⁹	
Provide protected/permissive left-turn phase (leading flashing green) (Request MUTCD Experimentation)	Fatal/Injury	Signal	Urban			16(4)¹⁹	12(4)¹⁹				
Provide protected/permissive left-turn phase (leading green arrow)	Fatal/Injury	Signal	Urban			17(2)¹⁹	25(2)¹⁹				
Provide signal coordination	All	Signal					32 ¹⁶				
Provide split phases	All	Signal			25 ¹⁶						

Table 1 (continued on page 5)

Table 1 (continued) Signalization Countermeasures

Countermeasure(s)	Crash Severity	Control	Area Type	Configuration	All Crashes	Left-turn Crashes	Rt-angle Crashes	Rear-end Crashes	Sideswipe Crashes	Other Crashes	Major/Minor Daily Traffic Volume (vehicles/day)
SIGNAL OPERATIONS COUNTERMEASURES (CONTINUED)											
Remove flash mode (late night/early morning)	All	Signal			29 ¹⁶		75(19) ²⁸				
Replace existing WALK / DON'T WALK signals with pedestrian count down signal heads	All	Signal	Urban							r	25 ²⁰
SIGNAL HARDWARE COUNTERMEASURES											
Add 3-inch yellow retroreflective sheeting to signal backplates	All	Signal	Urban		15(51) ³³						
Add additional signal and upgrade to 12-inch lenses	All	Signal		4-Leg						h	31 ²⁵
	All	Signal		4-Leg						i	17 ²⁵
Add signal (additional primary head)	All	Signal	Urban	4-Leg	28 ⁷		35 ⁷	28 ⁷			
	Fatal/Injury	Signal	Urban	4-Leg	17 ⁷						
	PDO	Signal	Urban	4-Leg	31 ⁷						
Convert signal from pedestal-mounted to mast arm	All	Signal			49 ³¹	12 ³¹	74 ³¹	41 ³¹			
	Fatal/Injury	Signal			44 ³¹						
	PDO	Signal			51 ³¹						
Improve visibility of signal heads (increase signal lens size, install new backboards, add reflective tape to existing backboards, and/or install additional signal heads)	All	Signal	Urban		7 ³⁵					d	6 ³⁵
	All	Signal	Urban							e	6 ³⁵
	Fatal/Injury	Signal	Urban		3 ³⁵						
	PDO	Signal	Urban		9 ³⁵						
Improve visibility of signal heads (install two red displays in each head)	All	Signal			9 ¹⁶		36 ¹⁶				
Install larger signal lenses (12 inch)	All	Signal			11 ¹⁶		46 ²⁸				
	All	Signal	Urban		24 ³³						
	Fatal/Injury	Signal	Urban		16 ³³						
Install signal backplates only	All	Signal			13 ¹⁶		50 ¹⁶				
Install signal backplates (or visors)	All	Signal					20 ⁹				
Install signals	All	No Signal			33 ¹⁶	38 ²⁶				j	50 ²⁶
	All	No Signal			38 ⁹		74 ⁹	22 ⁹		c	22 ⁹
	All	No Signal			20 ⁹		43 ⁹	20 ⁹		c	20 ⁹
	All	No Signal	Rural		15 ²⁶						
	Fatal	No Signal			38 ²⁶						
	Fatal/Injury	Stop	Urban	3-Leg	14(32) ²¹		34(45) ²¹	-50(51) ²¹			11,750-42,000 / 900-4,000
	Fatal/Injury	Stop	Urban	4-Leg	23(22) ²¹		67(20) ²¹	-38(39) ²¹			12,650-22,400 / 2,400-3,625
	PDO	No Signal			-15 ²⁶						
Install signals (temporary)	Fatal/Injury	No Signal					39 ⁹		50 ⁹		
	PDO	No Signal				11 ⁹	73 ⁹			a	83 ⁹
Install signals (to have one over each approach lane)	All	Undefined	All				46 ⁸				
Remove unwarranted signals	All	Signal	Urban		24 ¹¹		24 ¹¹	29 ¹¹		d	30 ¹¹
	All	Signal	Urban							e	22 ¹¹
	All	Signal	Urban							g	31 ¹¹
	Fatal/Injury	Signal	Urban		53 ¹¹						
	PDO	Signal	Urban		24 ¹¹						
Replace signal lenses with optical lenses	All	Signal			17 ¹⁶	10 ⁹	10 ⁹	10 ⁹		a	20 ⁹
COMBINATION SIGNAL AND OTHER COUNTERMEASURES											
Install left-turn lane and add turn phase	All	Signal			58 ¹⁶						
Install signals and add channelization	PDO	No Signal				24 ⁹	63 ⁹			a	27 ⁹
	Fatal/Injury	No Signal					67 ⁹		54 ⁹	b	35 ⁹

Table 1 (continued on page 6)

Table 2: Geometric Countermeasures

Countermeasure(s)	Crash Severity	Control	Area Type	Configuration	All Crashes	Left-turn Crashes	Rt-angle Crashes	Rear-end Crashes	Sideswipe Crashes	Other Crashes	Major/Minor Daily Traffic Volume (vehicles/day)
LEFT TURN COUNTERMEASURES											
Add indirect left-turn treatments to minimize conflicts	All	Stop			18(8) ³⁸						>34,000
	All	Stop			-24(35) ³⁸						>34,000/4 lanes
	All	Stop			26(8) ³⁸						>34,000/6 lanes
	All	Stop			24(63) ³⁸						>34,000/8 lanes
	Fatal/Injury	Stop			27(12) ³⁸						>34,000
	PDO	Stop			6(11) ³⁸						>34,000
Create directional median openings to allow left-turns and u-turns	All	Signal			51 ³¹						
Install left-turn lane	All	Signal	Rural	3-Leg	15 ¹⁴						4,200-26,000/ 1,300-11,400
	All	Signal	Rural	4-Leg (1 app)	18 ¹⁴						4,200-26,000/ 1,300-11,400
	All	Signal	Urban	3-Leg	7 ¹⁴						4,600-55,100/ 100-26,000
	All	Signal	Urban	4-Leg (1 app)	10(10) ¹⁴	13 ¹¹					4,600-55,100/ 100-26,000
	All	Signal	Urban	4-Leg (2 apps)	19(13) ¹⁴	24 ¹¹					4,600-55,100/ 100-26,000
	All	Stop	Rural	3-Leg	44(6) ¹⁴	62 ¹¹					1,100-32,400/ 25-11,800
	All	Stop	Rural	4-Leg (1 app)	28(3) ¹⁴	37 ¹¹					1,100-32,400/ 25-11,800
	All	Stop	Rural	4-Leg (2 apps)	48(3) ¹⁴	60 ¹¹					1,100-32,400/ 25-11,800
	All	Stop	Urban	3-Leg	33(12) ¹⁴						1,520-40,600/ 80-8,000
	All	Stop	Urban	4-Leg (1 app)	27(3) ¹⁴	26 ¹¹					1,520-40,600/ 80-8,000
	All	Stop	Urban	4-Leg (2 apps)	47(4) ¹⁴	45 ¹¹					1,520-40,600/ 80-8,000
	Fatal/Injury	Signal	Urban	4-Leg (1 app)	9(1) ¹⁴						4,600-55,100/ 100-26,000
	Fatal/Injury	Signal	Urban	4-Leg (2 apps)	17(2) ¹⁴						4,600-55,100/ 100-26,000
	Fatal/Injury	Stop	Rural	3-Leg	55(8) ¹⁴						1,100-32,400/ 25-11,800
	Fatal/Injury	Stop	Rural	4-Leg (1 app)	35(3) ¹⁴						1,100-32,400/ 25-11,800
	Fatal/Injury	Stop	Rural	4-Leg (2 apps)	58(4) ¹⁴						1,100-32,400/ 25-11,800
	Fatal/Injury	Stop	Urban	4-Leg (1 app)	29(4) ¹⁴						1,520-40,600/ 80-8,000
	Fatal/Injury	Stop	Urban	4-Leg (2 apps)	50(6) ¹⁴						1,520-40,600/ 80-8,000
Install left-turn lane (double)	Fatal/Injury	Undefined				47 ⁹	20 ⁹	29 ⁹	50 ⁹	a 75 ⁹	
	PDO	Undefined				71 ⁹	8 ⁹	32 ⁹		b 13 ⁹	
Install left-turn lane (painted separation)	All	Undefined			50 ⁹	57 ⁹	62 ⁹	54 ⁹		c 54 ⁹	<5,000/lane (Total)
	All	Undefined				35 ⁹	49 ⁹	39 ⁹		c 39 ⁹	>5,000/lane (Total)
	Fatal/Injury	Undefined	Mostly rural	3-Leg	22(14) ⁶						5,000-15,000
	Fatal/Injury	Undefined	Mostly rural	4-Leg	-28(27) ⁶						5,000-15,000
	PDO	Undefined	Mostly rural	3-Leg	20(19) ⁶						5,000-15,000
	PDO	Undefined	Mostly rural	4-Leg	26(12) ⁶						5,000-15,000
Install left-turn lane (physical channelization)	All	No Signal		4-Leg (2 apps)	42 ¹⁶						
	All	No Signal	Rural	3-Leg	44 ¹⁶						

Table 2 (continued on page 7)

Table 2 (continued)
Geometric Countermeasures

Countermeasure(s)	Crash Severity	Control	Area Type	Configuration	All Crashes	Left-turn Crashes	Rt-angle Crashes	Rear-end Crashes	Sideswipe Crashes	Other Crashes	Major/Minor Daily Traffic Volume (vehicles/day)	
LEFT TURN COUNTERMEASURES (CONTINUED)												
Install left-turn lane (physical channelization)	All	No Signal	Rural	4-Leg (1 app)	28 ¹⁶							
	All	No Signal	Urban	3-Leg	33 ¹⁶							
	All	No Signal	Urban	4-Leg (1 app)	27 ¹⁶							
	All	Undefined			51 ⁹	24 ⁹	68 ⁹	50 ⁹		c 50 ⁹	<5,000/lane (Total)	
	All	Undefined			19 ⁹	24 ⁹	55 ⁹	28 ⁹		c 28 ⁹	>5,000/lane (Total)	
	Fatal/Injury	Undefined				50 ⁹	58 ⁹	11 ⁹				
	Fatal/Injury	Undefined	Rural	3-Leg	27(13) ⁶							5,000-15,000
	Fatal/Injury	Undefined	Rural	4-Leg	4(12) ⁶							5,000-15,000
	PDO	Undefined					54 ⁹	56 ⁹		b 50 ⁹		
	PDO	Undefined	Rural	3-Leg	-20(23) ⁶							5,000-15,000
PDO	Undefined	Rural	4-Leg	16(22) ⁶							5,000-15,000	
Install left-turn lane (signal has left-turn phase)	All	Signal			31 ¹⁶	44 ¹⁶						
	All	Signal		4-Leg						h 73 ²⁵		
	All	Signal		4-Leg						i 66 ²⁵		
Install left-turn lane (signal has no turn phase)	All	Signal			23 ¹⁶	50 ¹⁶						
Install left-turn lane (with channelization and existing left-turn phase)	All	Signal			35 ⁹							
Install left-turn lane (with channelization and no left-turn phase)	All	Undefined			15 ⁹							
Install left-turn lane (within existing curbs)	All	Signal			26 ¹⁶	66 ¹⁶						
Install left-turn refuge within flush median	All	Undefined			24 ⁹			44 ⁹		c 44 ⁹	<5,000/lane (Total)	
	All	Undefined			44 ⁹	77 ⁹		40 ⁹	52 ⁹	a 52 ⁹	>5,000/lane (Total)	
	All	Undefined								c 40 ⁹	>5,000/lane (Total)	
Remove left-turn lane	All	Signal	Rural	3-Leg	-18 ³							
	All	Signal	Rural	4-Leg (1 app)	-22 ³							
	All	Signal	Rural	4-Leg (2 apps)	-49 ³							
	All	Signal	Urban	3-Leg	-8 ³							
	All	Signal	Urban	4-Leg (1 app)	-11 ³							
	All	Signal	Urban	4-Leg (2 apps)	-23 ³							
	All	Stop	Urban	3-Leg	-49 ³							
	All	Stop	Urban	4-Leg (1 app)	-37 ³							
	All	Stop	Urban	4-Leg (2 apps)	-88 ³							
	Fatal/Injury	Signal	Rural	3-Leg	-16 ³							
	Fatal/Injury	Signal	Rural	4-Leg (1 app)	-21 ³							
	Fatal/Injury	Signal	Rural	4-Leg (2 apps)	-45 ³							
	Fatal/Injury	Signal	Urban	3-Leg	-6 ³							
	Fatal/Injury	Signal	Urban	4-Leg (1 app)	-10 ³							
	Fatal/Injury	Signal	Urban	4-Leg (2 apps)	-21 ³							
	Fatal/Injury	Stop	Urban	3-Leg	-53 ³							
	Fatal/Injury	Stop	Urban	4-Leg (1 app)	-41 ³							
	Fatal/Injury	Stop	Urban	4-Leg (2 apps)	-98 ³							
RIGHT TURN COUNTERMEASURES												
Increase length of right-turn lane	Fatal/Injury	All	All	All	15 ³⁷							
Install right-turn lane	All	Signal	All	4-Leg (1 app)	4(2) ¹⁴						4,200-55,100 / 100-26,000	

Table 2 (continued on page 8)

Table 2 (continued)
Geometric Countermeasures

Countermeasure(s)	Crash Severity	Control	Area Type	Configuration	All Crashes	Left-turn Crashes	Rt-angle Crashes	Rear-end Crashes	Sideswipe Crashes	Other Crashes	Major/Minor Daily Traffic Volume (vehicles/day)
RIGHT TURN COUNTERMEASURES (CONTINUED)											
Install right-turn lane	All	Stop	All	4-Leg (1 app)	14(5) ¹⁴						1,100-40,600 / 25-11,800
	All	Signal	All	4-Leg (2 apps)	8(3) ¹⁴						4,200-55,100 / 100-26,000
	All	Stop	All	4-Leg (2 apps)	26(7) ¹⁴						1,100-40,600 / 25-11,800
	Fatal/Injury	Signal	All	4-Leg (1 app)	9(3) ¹⁴						4,200-55,100 / 100-26,000
	Fatal/Injury	Stop	All	4-Leg (1 app)	23(7) ¹⁴						1,100-40,600 / 25-11,800
	All	Undefined					50 ⁹	65 ⁹	20 ⁹	j	53 ⁹
Install right-turn lane (painted separation)	Fatal/Injury	All	All	All	30 ³⁷						
Install left-turn lane (physical channelization)	Fatal/Injury	All	All	All	35 ³⁷						
OTHER GEOMETRIC COUNTERMEASURES											
Convert four-leg to two T-intersections	Fatal/Injury	Undefined	Urban	4-Leg	33(6) ⁶						<70%/>30%
	Fatal/Injury	Undefined	Urban	4-Leg	-35(15) ⁶						>85%/<15%
	Fatal/Injury	Undefined	Urban	4-Leg	25(5) ⁶						70-85%/15-30%
	PDO	Undefined	Urban	4-Leg	10(5) ⁶						<70%/>30%
	PDO	Undefined	Urban	4-Leg	-15(6) ⁶						>85%/<15%
Convert intersection to roundabout	All	All	All		35(3) ³²						
	All	Signal	All		48(5) ³²						
	All	Stop (2-way)	All		44(4) ³²						
	All	Stop (4-way)	All		-3(15) ³²						
	All	Stop (2-way)	Rural	1-Lane	72(4) ³²						
	All	Signal	Urban		1(12) ³²						
	All	Stop (2-way)	Urban		31(6) ³²						
	All	Stop (2-way)	Urban	1-Lane	56(6) ³²						
	All	Signal	Urban	2-Lanes	67(4) ³²						
	All	Stop (2-way)	Urban	2-Lanes	18(8) ³²						
	Fatal/Injury	All	All		76(3) ³²						
	Fatal/Injury	Signal	All		78(6) ³²						
	Fatal/Injury	Stop (2-way)	All		82(3) ³²						
	Fatal/Injury	Stop (4-way)	All		-28(41) ³²						
	Fatal/Injury	Stop (2-way)	Rural	1-Lane	87(3) ³²						
Fatal/Injury	Signal	Urban		60(12) ³²							
Fatal/Injury	Stop (2-way)	Urban		74(6) ³²							
Fatal/Injury	Stop (2-way)	Urban	1-Lane	78(7) ³²							
Fatal/Injury	Stop (2-way)	Urban	2-Lanes	72(9) ³²							
Improve sight distance in 1 quadrant	All	Stop/Yield (2-way)	Rural	4-Leg	5 ¹³						
Improve sight distance in 2 quadrants	All	Stop/Yield (2-way)	Rural	4-Leg	9 ¹³						
Improve sight distance in 3 quadrants	All	Stop/Yield (2-way)	Rural	4-Leg	13 ¹³						
Improve sight distance in 4 quadrants	All	Stop/Yield (2-way)	Rural	4-Leg	17 ¹³						
	All	Signal	Rural	4-Leg	0 ¹³						
Increase median width by 3 ft	All	Stop	Rural	4-Leg						f	4(1) ¹²
	All	Stop	Urban	3-Leg						f	-3(1) ¹²
	All	Signal	Urban	4-Leg						f	-3(1) ¹²

Table 2 (continued on page 9)

Table 2 (continued)
Geometric Countermeasures

Countermeasure(s)	Crash Severity	Control	Area Type	Configuration	All Crashes	Left-turn Crashes	Rt-angle Crashes	Rear-end Crashes	Sideswipe Crashes	Other Crashes	Major/Minor Daily Traffic Volume (vehicles/day)
OTHER GEOMETRIC COUNTERMEASURES (CONTINUED)											
Increase median width by 3 ft	All	Stop	Urban	4-Leg						f	-6(1) ¹²
	Fatal/Injury	Stop	Rural	4-Leg						f	4(1) ¹²
	Fatal/Injury	Signal	Urban	4-Leg						f	-3(1) ¹²
	Fatal/Injury	Stop	Urban	4-Leg						f	-5(1) ¹²
Increase pedestrian storage area at corner	Fatal/Injury	Undefined			-12(126) ²						
Install median	All	Stop	Rural		27 ³						
Install median islands (painted) on major road approaches	Fatal/Injury	All	All	All	15 ³⁷						
Install median islands (physical) on major road approaches	Fatal/Injury	All	All	All	25 ³⁷						
Install raised median	All	No Signal			25 ¹⁶						
Install raised median (marked crosswalk)	All	No Signal								r	46 ³⁸
Install raised median (unmarked crosswalk)	All	No Signal								r	39 ³⁸
Install refuge islands	All	Undefined								r	56 ¹⁶
Install splitter islands on minor road approaches	Fatal/Injury	All	All	3-Leg	45 ³⁷						
	Fatal/Injury	All	All	4-Leg	40 ³⁷						
	Fatal/Injury	All	All	All	40 ³⁷						
	Fatal/Injury	All	Rural	All	35 ³⁷						
	Fatal/Injury	All	Urban	All	40 ³⁷						
Install turn and bypass lanes	All	Stop	Rural		5(10) ²⁹						
	Injury	Undefined		3-Leg		36 ⁹	24 ⁹	18 ⁹			
	PDO	Undefined		3-Leg		28 ⁹	53 ⁹	21 ⁹	30 ⁹	a	13 ⁹
	PDO	Undefined		3-Leg						b	40 ⁹

Table 3: Signs/Markings/Operational Countermeasures

Countermeasure(s)	Crash Severity	Control	Area Type	Configuration	All Crashes	Left-turn Crashes	Rt-angle Crashes	Rear-end Crashes	Sideswipe Crashes	Other Crashes	Major/Minor Daily Traffic Volume (vehicles/day)
SIGNS											
Install double stop signs	All	No Signal			11 ¹⁶		55(52) ²⁸				
Install flashing beacons as advance warning	All	Undefined		3-Leg	70 ⁹						
	All	Undefined		4-Leg	39 ⁹						
	All	Signal			27 ¹⁶						
	Fatal/Injury	Undefined				67 ⁹	73 ⁹				
	PDO	Undefined				79 ⁹	62 ⁹				
	All	Signal		4-Leg			62 ²⁵	36 ²⁵			
Install larger stop signs	All	Stop			19 ⁹						>5,000/lane (Total)
Install pedestrian signing	All	Undefined			4 ⁹						
	All	Undefined								r	15 ⁹
Install advance warning signs (positive guidance)	All	Signal			22 ¹⁶		35(1) ²⁸				
	All	Undefined	Urban		30 ⁹						
	All	Undefined	Rural		40 ⁹						
Provide overhead lane-use signs	All	Undefined			10 ³¹						
	All	Undefined			20 ³¹						

Table 3 (continued on page 10)

Table 3 (continued)
Signs/Markings/Operational Countermeasures

Countermeasure(s)	Crash Severity	Control	Area Type	Configuration	All Crashes	Left-turn Crashes	Rt-angle Crashes	Rear-end Crashes	Sideswipe Crashes	Other Crashes	Major/Minor Daily Traffic Volume (vehicles/day)
PAVEMENT MARKINGS/MODIFICATIONS											
Add centerline and move STOP bar to extended curb lines	All	No Signal			29 ¹⁶		24 ¹⁶				
Add centerline and move STOP bar to extended curb lines, double stop signs	All	No Signal			9 ¹⁶		0 ¹⁶				
Add centerline and STOP bar, replace 24-inch with 30-inch stop signs	All	No Signal					67(11) ²⁸				
Improve pavement friction (groove)	All	Undefined			25 ¹⁶					p 59 ¹⁶	
Improve/install pedestrian crossing	All	Undefined								r 25 ⁹	
Install pedestrian crossing	Fatal/Injury	Undefined	Rural							r 60 ²⁴	
Install pedestrian crossing (raised)	All	Undefined			30(67) ²						
	Fatal/Injury	Undefined			36(54) ²						
Install raised intersection	Fatal/Injury	Undefined		4-Leg	-5 ⁶						
	PDO	Undefined		4-Leg	-13 ⁶						
Install raised pavement markers	All	Undefined			10 ¹⁶					p 25 ¹⁶	
	All	Undefined								q 33 ¹⁶	
Install STOP bars (pedestrian crosswalk)	All	Signal			18 ¹⁶						
Install STOP bars (STOP bar on minor road approaches, with short segments of centerline)	All	Undefined			19 ¹⁶						
	All	Undefined					47 ¹⁶				
Install transverse pavement markings	All	Undefined			18 ⁹						
	Fatal/Injury	Stop								k 57(8) ¹⁰	
	Serious Injury	Stop								k 74(13) ¹⁰	
	Slight Injury	Stop								k 52(11) ¹⁰	
	All	Stop								l 66(8) ¹⁰	
	All	Stop								k 48(14) ¹⁰	
	All	Stop								n 45(15) ¹⁰ o 68(11) ¹⁰	
Install transverse rumble strips on approaches	All	Stop			28 ⁹						
	All	Undefined						90 ⁹			
	All	No Signal	Rural		35 ¹⁶						
Mark pavement with supplementary warning messages	All	No Signal			6 ¹⁶						
	Stop	Urban					30(66) ²⁸				
Provide bicycle box (advance stop bar to leave dedicated space for cyclists)	All	Signal								t 35 ³¹	
Provide bicycle lanes	All	Undefined								t 36 ³¹	
Resurface pavement	All	Undefined			33 ¹⁶					p 47 ¹⁶	
REGULATORY											
Convert STOP control to Yield control	All	Stop	Urban	4-Leg	-127(70) ²²						
	All	Stop	All		-137 ¹¹						
Convert to all-way STOP control (from 2-way control)	Fatal/Injury	Stop	Urban		71(6) ¹⁸						
	All	Stop	Urban			20(52) ¹⁸	72(3) ¹⁸	13(13) ¹⁸			
Convert two-way to one-way roadway	All	Undefined			26 ⁹						
Convert Yield control to STOP control	All	No Signal			29 ¹⁶		9 ¹⁶				

Table 3 (continued on page 11)

Table 3 (continued)
Signs/Markings/Operational Countermeasures

Countermeasure(s)	Crash Severity	Control	Area Type	Configuration	All Crashes	Left-turn Crashes	Rt-angle Crashes	Rear-end Crashes	Sideswipe Crashes	Other Crashes	Major/Minor Daily Traffic Volume (vehicles/day)
REGULATORY (CONTINUED)											
Install no left-turn and no u-turn signs	All	Undefined	Urban		62(6) ⁴	59(5) ⁴					19,435-42,000 (Total)
Permit right-turn-on-red	All	Signal			-7(1) ²					r -43(24) ²	
	Fatal/Injury	Signal								j -60(5) ⁶	
	PDO	Signal								j -10(1) ⁶	
Prohibit left turns	All	Undefined			45 ⁹	90 ⁹		30 ⁹		r 10 ⁹	
Prohibit right-turn-on-red	All	Signal			3 ⁴¹		30 ⁹	20 ⁹	20 ⁹	b 30 ⁹	
Prohibit turns	All	Undefined	All							s 45 ¹	
Restrict parking near intersections (to off-street)	All	Undefined			49 ¹⁶					r 30 ⁹	
LIGHTING											
Install lighting	All	Signal			30 ³¹					d 50 ³¹	
	Fatal/Injury	Signal			17 ³¹						
	All	No Signal			47 ¹⁶						
OPERATIONAL											
Convert STOP control (2-way) to signal contro	All	Stop			28 ⁹		74 ⁹				
	Injury	Stop			43 ⁹						
Convert STOP control (2-way) to signal control and install left-turn lane	All	Stop			36 ⁹		74 ⁹	8 ⁹			
	Injury	Stop			53 ⁹						
Increase enforcement related to motorist yielding in marked crosswalks combined with a public education campaign	All	Undefined								r 23 ⁴²	
Install angled median crosswalk	All	Undefined			12 ¹⁶						
Install beacon (flashing) at intersection	All	Undefined	All		30 ¹						
Install cameras to detect red-light running	All	Signal					25(3) ²⁷	-15(3) ²⁷			52,625-109,067/ 12,562-33,679
	All	Signal			-12(5) ²³						17,000-78,000
	All	Signal	Urban			45(6) ³⁶					17,000-78,000
	Fatal/Injury	Signal			-14(9) ²³						52,625-109,067/ 12,562-33,679
Install flashing red/yellow signal (MUTCD: intersection control beacon)	All	No Signal			25 ⁹		35 ⁹				<5,000/lane (Total)
	All	No Signal			26 ⁹		36 ⁹				>5,000/lane (Total)
	All	No Signal								a 50 ⁹	
	Fatal/Injury	No Signal			50 ⁹						
Install pedestrian crossing (signed and marked with curb ramps and extensions)	All	No Signal			37 ¹⁶						
Install pedestrian overpass/ underpass	All	No Signal								r 13 ¹⁶	
Install stop signs at alternate intersections in residential areas	All	Stop	Urban		50 ³⁴						
	Fatal/Injury	Stop	Urban		67 ³⁴						

References

1. [Agent, K. R., Stamatiadis, N., and Jones, S., "Development of Accident Reduction Factors." KTC-96-13, Kentucky Transportation Cabinet, \(1996\)](#)
2. [Bahar, G., Parkhill, M., Hauer, E., Council, F., Persaud, B., Zegeer, C., Elvik, R., Smiley, A., and Scott, B. "Prepare Parts I and II of a Highway Safety Manual: Knowledge Base for Part II". Unpublished material from NCHRP Project 17-27, \(May 2007\)](#)
3. [Bonneson, J., Zimmerman, K., and Fitzpatrick, K., "Roadway Safety Design Synthesis." Texas Transportation Institute for Texas DOT, \(2005\)](#)
4. [Brich, S. C. and Cottrell Jr, B. H., "Guidelines for the Use of No U-Turn and No-Left Turn Signs." VTRC 95-R5, Richmond, Virginia Department of Transportation, \(1994\)](#)
5. [De Brabander, B. and Vereeck, L., "Safety Effects of Roundabouts in Flanders: Signal type, speed limits and vulnerable road users." AAP-1407, Elsevier Science, \(2006\)](#)
6. [Elvik, R. and Vaa, T., "Handbook of Road Safety Measures." Oxford, United Kingdom, Elsevier, \(2004\)](#)
7. [Felipe, E., Mitic, D., and Zein, S. R., "Safety Benefits of Additional Primary Signal Heads." Vancouver, B.C., Insurance Corporation of British Columbia; G.D. Hamilton Associates, \(1998\)](#)
8. [FHWA and Institute of Transportation Engineers, "Making Intersections Safer: A Toolbox of Engineering Countermeasures to Reduce Red-Light Running." FHWA/TX-03/4027-2, Texas Transportation Institute, \(2002\)](#)
9. [Gan, A., Shen, J., and Rodriguez, A., "Update of Florida Crash Reduction Factors and Countermeasures to Improve the Development of District Safety Improvement Projects." Florida Department of Transportation, \(2005\)](#)
10. [Griffin, L. I. and Reinhardt, R. N., "A Review of Two Innovative Pavement Patterns that Have Been Developed to Reduce Traffic Speeds and Crashes." Washington, D.C., AAA Foundation for Traffic Safety, \(1996\)](#)
11. [Harkey, D., Srinivasan, R., Zegeer, C., Persaud, B., Lyon, C., Eccles, K., Council, F. M., and McGee, H., "Crash Reduction Factors for Traffic Engineering and Intelligent Transportation System \(ITS\) Improvements: State of Knowledge Report." Research Results Digest, Vol. 299, Transportation Research Board of the National Academies, \(2005\)](#)
12. [Harwood, D. W., Pietrucha, M. T., Wooldridge, M. D., Brydia, R. E., and Fitzpatrick, K., "NCHRP Report 375: Median Intersection Design." Washington, D.C., Transportation Research Board, National Research Council, \(1995\)](#)
13. [Harwood, D. W., Council, F. M., Hauer, E., Hughes, W. E., and Vogt, A., "Prediction of the Expected Safety Performance of Rural Two-Lane Highways." FHWA-RD-99-207, McLean, Va., Federal Highway Administration, \(2000\)](#)
14. [Harwood, D. W., Bauer, K. M., Potts, I. B., Torbic, D. J., Richard, K. R., Kohlman Rabbani, E. R., Hauer, E., and Elefteriadou, L., "Safety Effectiveness of Intersection Left- and Right-Turn Lanes." FHWA-RD-02-089, McLean, Va., Federal Highway Administration, \(2002\)](#)
15. [Hauer, E., "Left Turn Protection, Safety, Delay and Guidelines: A Literature Review." www.roadsafetyresearch.com, \(2004\)](#)
16. [Institute of Transportation Engineers, "Toolbox of Countermeasures and Their Potential Effectiveness to Make Intersections Safer." Briefing Sheet 8, ITE, FHWA, \(2004\)](#)
17. [Lee, J. C., Wortman, R. H., Hook, D. J., and Poppe, M. J., "Comparative Analysis of Leading and Lagging Left Turns." Phoenix, Arizona Department of Transportation, \(1991\)](#)
18. [Lovell, J. and Hauer, E., "The Safety Effect of Conversion to All-Way Stop Control." Transportation Research Record 1068, Washington, D.C., Transportation Research Board, National Research Council, \(1986\) pp. 103-107.](#)
19. [Lyon, C., Hag, A., Persaud, B. N., and Kodama, S. T., "Development of Safety Performance Functions for Signalized Intersections in a Large Urban Area and Application to Evaluation of Left Turn Priority Treatment." 2005 TRB 84th Annual Meeting: Compendium of Papers CD-ROM, Vol. TRB#05-2192, Washington, D.C., \(2005\)](#)
20. [Markowitz, F., Sciortino, S., Fleck, J.L., and Yee, B.M., "Pedestrian Countdown Signals: Experience with an Extensive Pilot Installation." Institute of Transportation Engineers Journal, January 2006, pp. 43-48. Updated by Memorandum, Olea, R., "Collision changes 2002-2004 and countdown signals." \(February 7th, 2006\)](#)
21. [McGee, H., Taori, S., and Persaud, B. N., "NCHRP Report 491: Crash Experience Warrant for Traffic Signals." Washington, D.C., Transportation Research Board, National Research Council, \(2003\)](#)
22. [McGee, H. W. and Blankenship, M. R., "NCHRP Report 320: Guidelines for Converting Stop to Yield Control at Intersections." Washington, D.C., Transportation Research Board, National Research Council, \(1989\)](#)
23. [Miller, J. S., Khandelwal, R. and Garber, N. J., "Safety Impacts of Photo-Red Enforcement at Suburban Signalized Intersections: An Empirical Bayes Approach." Transportation Research Record, No. 1969, Washington, D.C., Transportation Research Board, National Research Council, \(2006\), pp. 27-34.](#)
24. [Montella, A., "Safety Reviews of Existing Roads: a Quantitative Safety Assessment Methodology." 2005 TRB 84th Annual Meeting: Compendium of Papers CD-ROM, Vol. TRB#05-1295, Washington, D.C., \(2005\)](#)
25. [Morena, D. A., Wainwright, W. S., and Ranck, F., "Older Drivers at a Crossroads." Public Roads, Vol. 70, No. 4, Washington, D.C., FHWA, \(2007\) pp. 6-15.](#)
26. [Pernia, J.C., Lu, J.J., Weng, M.X., Xie, X., and Yu, Z., "Development of Models to Quantify the Impacts of Signalization on Intersection Crashes." Florida Department of Transportation, \(2002\).](#)
27. [Persaud, B., Council, F. M., Lyon, C., Eccles, K., and Griffith, M., "Multi-Jurisdictional Safety Evaluation of Red Light Cameras." Transportation Research Record, No. 1922, Washington, D.C., Transportation Research Board, National Research Council, \(2005\) pp. 29 - 37.](#)
28. [Polanis, S. F., "Low-Cost Safety Improvements. Chapter 27, The Traffic Safety Toolbox: A Primer on Traffic Safety", Washington, D.C., Institution of Transportation Engineers \(1999\) pp. 265-272](#)
29. [Preston, H. and Schoenecker, T., "Bypass Lane Safety, Operations, and Design Study." MN/RC-2000-14, St. Paul, Minnesota Department of Transportation, \(1999\)](#)
30. [Retting, R. A., Chapline, J. F. and Williams, A. F., "Changes in Crash Risk Following Re-timing of Traffic Signal Change Intervals." Accident Analysis and Prevention, Vol. 34, No. 2, Oxford, N.Y., Pergamon Press, \(2002\) pp. 215-220.](#)
31. [Rodegerdts, L. A., Nevers, B., and Robinson, B., "Signalized Intersections: Informational Guide." FHWA-HRT-04-091, \(2004\)](#)
32. [Rodegerdts, L. A., Blogg, M., Wemple, E., Myers, E., Kyte, M., Dixon, M., List, G., Flannery, A., Troutbeck, R., Brilon, W., Wu, N., Persaud, B., Lyon, C., Harkey, D., and Carter, E. C., "Roundabouts in the United States." NCHRP Report 572, Washington, D.C., Transportation Research Board of the National Academies, \(2007\)](#)
33. [Sayed, T., Leur, P., and Pump, J., "Safety Impact of Increased Traffic Signal Backboards Conspicuity." 2005 TRB 84th Annual Meeting: Compendium of Papers CD-ROM, Vol. TRB#05-16, Washington, D.C., \(2005\)](#)

References (continued)

34. [Sayed, T., El-Basyouny, K., and Pump, J., "Safety Evaluation of Stop Sign In-Fill Program." Transportation Research Record 1953, Washington, D.C., Transportation Research Board, National Research Council, \(2006\) pp. 201-210.](#)
35. [Sayed, T., El Esawey, M., and Pump, J., "Evaluating the Safety Impacts of Improving Signal Visibility at Urban Signalized Intersections." 2007 TRB 86th Annual Meeting: Compendium of Papers CD-ROM, Vol. TRB#07-135, Washington, D.C., \(2007\)](#)
36. [Shin, K. and Washington, S., "The Impact of Red Light Cameras on Safety in Arizona." 2006 TRB 85th Annual Meeting: Compendium of Papers CD-ROM, Vol. TRB#06-1514, Washington, D.C., \(2006\)](#)
37. [Turner, B., "Crash reduction estimates for road safety treatments," Vermont, Australia, ARRB Group, \(2007\)](#)
38. [Xu, L., "Right Turns Followed by U-Turns Versus Direct Left Turns: A Comparison of Safety Issues." ITE Journal, Vol. 71, No. 11, Washington, D.C., Institute of Transportation Engineers, \(2001\) pp. 36-43.](#)
39. [Zegeer, C., Stewart, R., Huang, H., and Lagerwey, P., "Safety Effects of Marked vs. Unmarked Crosswalks at Uncontrolled Locations: Executive Summary and Recommended Guidelines" FHWA-RD-01-075, \(March 2002\)](#)
40. [Zimmerman, K. and Bonneson, J., "In-Service Evaluation of the Detection-Control System for Isolated High-Speed Intersections." 2006 TRB 85th Annual Meeting: Compendium of Papers CD-ROM, Vol. TRB#06-1252, Washington, D.C., \(2006\)](#)

===== ❖❖❖❖ *Updated August 2008* ❖❖❖❖ =====

41. [Harkey, D., Srinivasan, R., Baek, J., Council, F. M., Eccles, K., Lefler, N., Gross, F., Persaud, B., Lyon, C., Hauer, E., and Bonneson, J. A., "Crash Reduction Factors for Traffic Engineering and ITS Improvements," NCHRP Report No. 617, \(2008\)](#)
42. [Van Houten, R. and Malenfant, J. E., "Effects of a Driver Enforcement Program on Yielding to Pedestrians," Journal of Applied Behavioral Analysis, No. 37, \(2004\) pp. 351 - 363.](#)

