

Air Emissions from the Treatment of Soils Contaminated
with Petroleum Fuels and Other Substances
EPA-600/R-97-116, October 1997

This report updates a 1992 report that summarizes available information on air emissions from the treatment of soils contaminated with fuels. Soils contaminated by leaks or spills of fuel products, such as gasoline and jet fuel, are a nationwide concern. Air emissions during remediation are a potential problem because of the volatile nature of many of the fuel components and the remediation processes themselves, which may promote or result in contaminant transfer to the vapor phase. Limited information also is included on air emissions from the treatment of soils contaminated with hazardous wastes.

The report will allow staff from state and local regulatory agencies, as well as staff from EPA regional offices, to assess the different options for cleaning up soil contaminated with fuels. Seven general remediation approaches are addressed in this report. For each approach, information is presented about the remediation process, the typical air emission species of concern and their release points, and the available air emissions data. Control technologies for each remediation approach are identified and their reported efficiencies are summarized. Cost data are given for each remediation approach and for its associated control technologies. Emission estimation methods (EEMs) for each remediation approach are presented along with a brief case study. An uncertainty and sensitivity analysis was also prepared for each EEM.

A 1992 report was initially revised in 1995 in fulfillment of EPA Contract No. 68-D2-0160, Work Assignment 62, by Radian Corporation. The 1992 report also was prepared by Radian Corporation.

This second revision to the 1992 report was prepared in 1996 in fulfillment of EPA Contract No. 68-D3-0035, Work Assignment II-92, by E.H. Pechan & Associates, Inc., 2880 Sunrise Boulevard, Suite 220, Rancho Cordova, CA 95742.

The electronic version of this report does not include the figures or appendices listed below. To obtain copies of these pages, please contact Susan Thorneloe of the U.S. Environmental Protection Agency by phone (919-541-2709), fax (919-541-7885), or e-mail (Thorneloe.Susan@epamail.epa.gov).

Figure	Page
1-1 Relative Frequency of Use of Remediation Technologies at UST Sites	1-3

1-2	Relative Frequency of Use at UST Sites by Specific Technology	1-4
1-3	Alternative Treatment Technologies Specified in Superfund Remedial Action RODs from FY 1982 Through FY 1992	1-6
3-1	Summary of Air Emission Points for Excavation and Removal	3-3
4-1	Soil Treatment Temperature Guide	4-3
4-2	Generalized Process Diagram for Thermal Screw-Based Thermal Desorption . . .	4-6
5-1	Simplified Guide to Applicability of Soil Vapor Extraction	5-2
5-2	Generalized Process Flow Diagram for Soil Vapor Extraction	5-4
Figure (cont.)		Page
5-3	Process Flow Diagram for Terra Vac In-Situ Vacuum Extraction System	5-19
6-1	Flow Diagram for Off-Gas Treatment System for In-Situ Biodegradation	6-2
7-1	Slurry Biodegradation Process Flow Diagram	7-3
8-1	Process Flow Diagram for Commercial Rotary Kiln Incinerator	8-2
9-1	Schematic Diagram of Aqueous Soil Washing Process	9-3
9-2	Schematic Diagram of Solvent Extraction Process	9-5
9-3	Generalized Soil Flushing Process Flow Diagram	9-8

Appendix

B	State Cleanup Requirements	B-1
E	Engineering Bulletins for Treatment Processes	E-1
F	Article on Soil Vapor Extraction	F-1
G	Article on Incineration	G-1